

WGS
Asst

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces
Lease No. 032511 (b)
Unit P.J. Langlie "B"

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 28, 1952

Well No. 1 is located 1980 ft. from N line and 1980 ft. from W line of sec. 15
SE/4 NW/4 Sec 15 25-S 37-E N.M.P.
(4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Langlie-Mattix Lea New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3109 ft. DF

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

The above well was drilled in 1936 to a total depth of 3413' PBTD 3409'. Production declined steadily from the initial potential of 50 BOPD. In March, 1937 this well was shot with 120 quarts SNG and cleaned out. Production stabilized at approximately 14 BOPD for one year then declined to nothing. The above well has been shut in since December 1942. We propose to plug and abandon P. J. Langlie "B" #1 as follows:

Shoot off and pull approximately 2100' 7" casing. Spot 20 sack cement plugs at the following depths: 3409' (PBTD); 3140' (Base of 7" csg); 2100' (Top of 7" stub); 504' (Base of Surface Pipe); and at surface. The above intervals are to be filled with a heavy mud. A 4" pipe abandonment marker will be erected and the location leveled to conform with existing regulations.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Stanolind Oil and Gas Company
 Address Box 68
Hobbs, New Mexico
 By Reynold Pennington
 Title Field Superintendent