Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

DIL CONS. COMMISSION P.O. BOX 1980 FORM APPROVED HOBBS, NEW MEXICO. 88249

Expires: March 31, 1993 5. Lease Designation and Serial No. SUNDRY NOTICES AND REPORTS ON WELLS LC032650B Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. 6. If Indian, Alottee or Tribe Name Use "APPLICATION FOR PERMIT -- " for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE OIL WELL GAS 8. Well Name and Number 1. Type of Well: LJ OTHER WELL COATES, A. B. -C-2. Name of Operator TEXACO EXPLORATION & PRODUCTION INC. 22 3. Address and Telephone No. 205 E. Bender, HOBBS, NM 88240 9. API Well No. 397-0432 30 025 11744 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 10. Field and Pool, Exploaratory Area Unit Letter : 660 Feet From The NORTH Line and 2310 Feet From The JUSTIS MONTOYA 11. County or Parish, State __ Line EAST Township 25S Range 37E Section 24 LEA , NEW MEXICO 12. Check Appropriate Box(s) To Indicate Nature of Notice, Report, or Other Data TYPE OF SUBMISSION TYPE OF ACTION Abandonment Change of Plans Recompletion **New Construction** Notice of Intent Plugging Back Non-Routine Fracturing Subsequent Report Casing Repair Water Shut-Off Atlering Casing Conversion to Injection Final Abandonment Notice OTHER: **ACIDIZE** Dispose Water (Note: Report results of multiple co-13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work,)*. 1. 1-22-96-MIRU, PULL RODS & PUMP. 2. 1-23-96-KILL WELL, RIG UP TUBOSCOPE. HEAVY BUILDUP, HOT H20 WELL WITH 75 BBLS. POH CHECK TBG. WELL CAME IN KILL WELL W/1/2&1/2. WELL KICKED. RAN OUT OF H20. OPEN DOWN FLOW LINE.CLOSE BOP SDON. 3. 1-24-96-KILL WELL, POH REST OF TBG. PACKER IN HOLE AND SET @ 6600'. SDON. 4. 1-25-96-MIRU DOWELL, LEAD WITH 500 GALS XYLENE AND FLUSH TO PERFS W/BRINE. ACIDIZE PERFS W/3000 GALS 15% NEFE ACID IN 3 EQUAL STAGES W/1000# ROCK SALT BLOCKS BETWEEN STAGES. MIN PSI 0, MAX 480 PSI. ISIP VAC. RELEASE PACKER AND POH. IN HOLE W/3.5X40 MHMA ON TBG. TAG FILL 40' HIGH. SDON. 5. 1-26-96-POH W/TBG, RAN TBG. OPEN ENDED & TAG FILL. PUMP 60 BBLS FRESH H20 & DISSOLVE SALT TO TD. IN HOLE WITH MHMA & TBG. REMOVE BOP. SDON. 6. 1-27-96-RAN 1.75 BORE INSERT PUMP. SEAT PUMP. SET STROKE, SDFWE. 7. 1-29-96- CHANGE OUT POLISH ROD. RIG DOWN. NO TEST. 8. 1-30-96 THRU 2-19-96 TESTING. 9. 2-20-96 24 HR TEST 14 BO, 105 BW, 90 MCF, 1.75 BORE PUMP, 76" STROKE, 7.5 SPM, PRODUCING FROM 7" CASING PERFS, (6747'-6773'), SOUTH JUSTIS MONTOYA POOL. Engineering Assistant DATE 5/8/96 TYPE OR PRINT NAME Paula S. Ives (This space for Federal or State office use **APPROVED BY** TITLE CONDITIONS OF APPROVAL, IF ANY:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or

representations as to any matter within its jurisdiction