

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐
well well other

2. NAME OF OPERATOR **ARCO Oil and Gas Company**
Division of Atlantic Richfield Company

3. ADDRESS OF OPERATOR
Box 1710, Hobbs, New Mexico 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 660' FNL & 2310' FEL
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: as above

15. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other)		Commingle Downhole	

5. LEASE
LC-032511 (d)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Jal

9. WELL NO.
2

10. FIELD OR WILDCAT NAME
Justis-Bly/Tubb Drinkard

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
11-25S-37E

12. COUNTY OR PARISH
Lea

13. STATE
N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3121' GR

(NOTE: Report results of multiple completion or zone change on Form 9-33C.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

RU 2/11/80. Killed well, inst BOP. POH w/dual compl assy. Drld Model D pkr @ 5650'. RIH w/2-3/8" OD tbg, MA w/BP, SN. Set tbg @ 6129'. Ran rods & 2" x 1 1/2" x 12' x 16' pump. Returned to production with Justis Blinebry and Justis Tubb Drkd zones commingled downhole on 2/23/80. Final Report.

RECEIVED

MAR 28 1980

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Dist. Drlg. Supt. DATE 3/26/80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

A. S. CROWLEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side

RECEIVED
APR 8 1980
OIL CONSERVATION DIV.

RECEIVED

APR 8 1980

OIL CONSERVATION DIV.