

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

Form C-105
Revised 1-1-65

NEW MEXICO OIL CONSERVATION COMMISSION
WELL COMPLETION OR RECOMPLETION REPORT AND LOG

5a. Indicate Type of Lease	
State ☐	Fee ☒
5. State Oil & Gas Lease No.	

1a. TYPE OF WELL						7. Unit Agreement Name									
b. TYPE OF COMPLETION OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐ NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ OTHER ☐						8. Farm or Lease Name Hodges B									
2. Name of Operator Cities Service Oil Company						9. Well No. 6									
3. Address of Operator Box 1919 - Midland, Texas 79701						10. Field and Pool, or Wildcat Justis Blinebry									
4. Location of Well UNIT LETTER <u>N</u> LOCATED <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>1650</u> FEET FROM <u>West</u> LINE OF SEC. <u>1</u> TWP. <u>25S</u> RGE. <u>37E</u> NMPM						12. County Lea									
15. Date Spudded 3-18-75		16. Date T.D. Reached 4-13-75		17. Date Compl. (Ready to Prod.) 5-12-75		18. Elevations (DF, RKB, RT, GR, etc.) 3107' GR		19. Elev. Casinghead 3107'							
20. Total Depth 6300'		21. Plug Back T.D. 6260'		22. If Multiple Compl., How Many		23. Intervals Drilled By Rotary Tools Cable Tools 0' - T.D. 6300'									
24. Producing Interval(s), of this completion - Top, Bottom, Name 5175' - 5576' - Blinebry								25. Was Directional Survey Made No							
26. Type Electric and Other Logs Run log, Deviation Tests Compensated Neutron-Formation Density, Dual Latero-								27. Was Well Cored No							
28. CASING RECORD (Report all strings set in well)															
CASING SIZE		WEIGHT LB./FT.		DEPTH SET		HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED					
8-5/8"		24#		967'		12-1/4"		450 sacks		Circulated					
5-1/2"		(1263.08' - 15.5#)		6300'		7-7/8"		1350 sacks		Circulated					
29. LINER RECORD										30. TUBING RECORD					
SIZE		TOP		BOTTOM		SACKS CEMENT		SCREEN		SIZE		DEPTH SET		PACKER SET	
										2-3/8"		5134'		5134'	
31. Perforation Record (Interval, size and number) 2-0.43" holes each @ 5175', 5191', 5199', 5213', 5218', 5239', 5249', 5255', 5302', 5311', 5321', 5334', 5396', 5412', 5418', 5422', 5431', 5436', 5440', 5445', 5449', 5453', 5457', 5464', 5476', 5524' and 5576'.										32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.					
										DEPTH INTERVAL		AMOUNT AND KIND MATERIAL USED			
										5175' - 5334'		1500 gals 15% IST HCl acid.			
										5396' - 5476'		2000 gals 15% IST HCl acid.			
										5175' - 5576'		60,000 gals gelled 9.0#/gal BW, 73,500# 20/40 sand, 600#			
33. PRODUCTION Benzoic acid flakes and 800# rock salt.															
Date First Production 5-5-75		Production Method (Flowing, gas lift, pumping - Size and type pump) Flowing								Well Status (Prod. or Shut-in) Producing					
Date of Test 5-12-75		Hours Tested 24 hrs.		Choke Size 28/64"		Prod'n. For Test Period		Oil - Bbl. 110		Gas - MCF 110		Water - Bbl. ---		Gas-Oil Ratio 1000	
Flow Tubing Press. 50#		Casing Pressure ---		Calculated 24-Hour Rate		Oil - Bbl.		Gas - MCF		Water - Bbl.		Oil Gravity - API (Corr.) 36.7°			
34. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold										Test Witnessed By E. R. Gobble					
35. List of Attachments Deviation Tests															
36. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief.															
SIGNED <u>E. R. Gobble</u>										TITLE <u>Region Operation Manager</u> DATE <u>May 14, 1975</u>					

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy <u>985'</u>	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates <u>2508'</u>	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen <u>3155'</u>	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres <u>3730'</u>	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta <u>4832'</u>	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinberry <u>5000'</u>	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb <u>5690'</u>	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard <u>6095'</u>	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo _____	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. _____	T. Chinle _____	T. _____
T. Penn. _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0'	633'	633'	Sand & Red Bed				
633'	785'	152'	Red Bed				
785'	910'	125'	Anhydrite				
910'	967'	57'	Red Bed				
967'	2401'	1434'	Anhydrite & Salt				
2401'	3561'	1160'	Anhydrite				
3561'	3616'	55'	Anhydrite & Lime				
3616'	3710'	94'	Lime & Dolomite				
3710'	4605'	895'	Dolomite				
4605'	4685'	80'	Dolomite & Lime				
4685'	5349'	664'	Dolomite				
5349'	5392'	43'	Dolomite & Shale				
5392'	5757'	365'	Dolomite				
5757'	5900'	143'	Dolomite, Shale & Lime				
5900'	5955'	55'	Dolomite				
5955'	5995'	40'	Dolomite, Shale & Lime				
5995'	6039'	44'	Dolomite				
6039'	6082'	43'	Dolomite, Lime & Shale				
6082'	6144'	62'	Dolomite				
6144'	6164'	20'	Dolomite & Lime				
6164'	6300'	136'	Dolomite				
			T.D. 6300'				

NO CORES OR DST'S WERE TAKEN