

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-79

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
B-9613

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Water injection well	7. Unit Agreement Name West Dollarhide Queen Sand Unit
2. Name of Operator Sirgo-Collier, Inc.	8. Farm or Lease Name
3. Address of Operator P. O. Box 3531, Midland, Texas 79702	9. Well No. 109
4. Location of Well UNIT LETTER <u>D</u> <u>750</u> FEET FROM THE <u>North</u> LINE AND <u>500</u> FEET FROM THE <u>West</u> LINE, SECTION <u>32</u> TOWNSHIP <u>24S</u> RANGE <u>38E</u> NMPM.	10. Field and Pool, or Wildcat Dollarhide Queen
15. Elevation (Show whether DF, RT, GR, etc.) 3164' GR	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER Spud, cement surface & injection csg. <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2-4-88 Spudded with 12-1/4" bit to TD of 400'. Ran 10 joints 8-5/8" 24# casing to 397'. Cemented with 280 sx Class "C" with 2% CaCl2. Circulated 25 sx.

2-5-88 Tested BOP and 8-5/8" casing to 600# for 30 minutes. Tested okay.

2-11-88 TD 3990'

2-12-88 Ran 115 joints of 5-1/2" 15.5 & 17# casing to 3990'. Cemented with 920 sx Halliburton Light, 15# salt, 1/4# flocele and tailed with 200 sx Class "C", 2% CaCl2. Circulated 110 sx.

2-13-88

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Amy L. Whitley TITLE Agent DATE March 3, 1988

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE MAR 7 - 1988

CONDITIONS OF APPROVAL, IF ANY:

REC-113

MAR 4 - 1993

HOBBY OFFICE