

**PANTECHS LABORATORIES, INC.**

Leaders in Petroleum Analytical Services
www.pantechs.com

Analytical Report

3/24/2022

Customer:	Occidental Permian Ltd.	Order:	300-3024
Location:	North Hobbs RCF	Received:	3/21/2022
Description:	Monthly Collection	Primary Contact:	Richard Sanders

REPORT DISTRIBUTION:

Brian Carlisle , Casey Morris , Chauncia Farayola , Chip Mitchell , Chris Frei , Dillon Hart , Erica Zuniga , Greg Vencil , James King , Jason Sisson , Jimmy Dobson , John Dorow , Judy Rich , Justin Saxon , Kenley Powell , Kevin Mulkern , Richard Sanders

All data reported in this Analytical Report is in compliance with the test method(s) performed as of the date noted above. The validity and integrity of this report will remain intact as long as it is accompanied by this page and reproduced in full. Any datafile (e.g. txt, csv, etc.) produced which is associated with the results in this report shall be considered for convenience only and does not supersede this report as the official test results. We reserve the right to return to you any unused samples received if we consider so necessary (e.g. samples identified as hazardous waste).

We appreciate you choosing Pantechs Laboratories. If you have any questions concerning this report, please feel free to contact us at any time.

Pantechs Laboratories, Inc.**Order: 300-3024 Order Date: 3/21/2022****Order Description: North Hobbs RCF, Monthly Collection****Sample List**

Fluid	Operator	Location	Site	Sample Point	Date	Time
CO2	Occidental Permian Ltd.	North Hobbs RCF	2098	CO2 Discharge	3/21/2022	12:58 PM
CO2	Occidental Permian Ltd.	North Hobbs RCF	2099	CO2 Discharge	3/21/2022	12:48 PM
Gas	Occidental Permian Ltd.	North Hobbs RCF	1013	#1 Slug Catcher Inlet	3/21/2022	1:30 PM
Gas	Occidental Permian Ltd.	North Hobbs RCF	10002	NGL Plant Inlet	3/21/2022	1:13 PM
Gas	Occidental Permian Ltd.	North Hobbs RCF	21013	#2 Slug Catcher Inlet		
Gas	Occidental Permian Ltd.	North Hobbs RCF	21023	#3 Slug Catcher Inlet	3/21/2022	1:34 PM
Gas	Occidental Permian Ltd.	North Hobbs RCF	DEX PRO	Inlet	3/21/2022	1:23 PM
Gas	Occidental Permian Ltd.	North Hobbs RCF	DEX PRO	Outlet		
Gas	Occidental Permian Ltd.	North Hobbs RCF	Reflux Stabilizer	Sample Valve	3/21/2022	1:07 PM
Gas	Occidental Permian Ltd.	North Hobbs RCF	Surge Tank	Propane Vapor	3/21/2022	1:38 PM
Liquid	Occidental Permian Ltd.	North Hobbs RCF	DEX PRO	Gasoline		
Liquid	Occidental Permian Ltd.	North Hobbs RCF	NGL Storage	NGL	3/21/2022	1:03 PM
Liquid	Occidental Permian Ltd.	North Hobbs RCF	Stabilizer	Bottoms	3/21/2022	1:09 PM
Liquid	Occidental Permian Ltd.	North Hobbs RCF	Surge Tank	Propane Liquid	3/21/2022	1:42 PM

No Sample List

Operator	Location	Site	Sample Point	Comment
Occidental Permian Ltd.	North Hobbs RCF	21013	#2 Slug Catcher Inlet	No Flow at Sample Point
Occidental Permian Ltd.	North Hobbs RCF	DEX PRO	Gasoline	Sample Point All Water
Occidental Permian Ltd.	North Hobbs RCF	DEX PRO	Outlet	Sample Point Inaccessible

Pantechs Laboratories, Inc. - Order: 300-3024 - Order Date: 3/21/2022

Order Description: North Hobbs RCF, Monthly Collection

SAMPLE ID		COLLECTION DATA	
Operator	Occidental Permian Ltd.	Pressure	1623 psig
Location	North Hobbs RCF	Sample Temp	N/A
Site	2098	Atm Temp	62 F
Site Type	Meter	Collection Date	03/21/2022
Sample Point	CO2 Discharge	Collection Time	12:58 PM
Spot/Comp	Spot	Collection By	Cody Carson
Meter ID	2098	Pressure Base	14.650 psi
Purchaser		Temperature Base	60 F
Fluid	CO2	Container(s)	YZ28194

GPA 2177 CO2 Fractional Analysis

COMPOUND	FORMULA	MOL%	VOL%	WT%
NITROGEN	N2	1.897	1.205	1.262
CARBON DIOXIDE	CO2	88.646	87.500	92.676
HYDROGEN SULFIDE	H2S	0.662	0.516	0.536
METHANE	C1	5.873	5.765	2.238
ETHANE	C2	0.868	1.344	0.620
PROPANE	C3	1.114	1.778	1.167
I-BUTANE	iC4	0.174	0.330	0.240
N-BUTANE	nC4	0.365	0.666	0.504
I-PENTANE	iC5	0.132	0.280	0.226
N-PENTANE	nC5	0.109	0.229	0.187
HEXANES PLUS	C6+	0.160	0.388	0.344
TOTALS:		100.000	100.000	100.000

Value of "0.000" in fractional interpreted as below detectable limit.

If Onsite H2S testing is performed, its resulting value is used in fractional table

Liquid Phase Properties

SCF/Gal (Ideal)	SCF/Gal (Real)	Mol Weight	Relative Density (60/60)	Vapor Pressure 100F, psia
58.229	57.904	42.096	0.772	1,463.1

Vapor Phase Properties

ITEM	BTU/CF	Specific Gr.	Z Factor
DRY	142.42	1.461	0.994
WATER SATURATED	140.88	1.447	0.994

Onsite Testing by Stain Tube

METHOD	TYPE	MOL%	GRAINS/100	PPMV
GPA2377	H2S	0.6621	420.42	6,684.7

Pantechs Laboratories, Inc. - Order: 300-3024 - Order Date: 3/21/2022

Order Description: North Hobbs RCF, Monthly Collection

SAMPLE ID		COLLECTION DATA	
Operator	Occidental Permian Ltd.	Pressure	1627 psig
Location	North Hobbs RCF	Sample Temp	N/A
Site	2099	Atm Temp	63 F
Site Type	Meter	Collection Date	03/21/2022
Sample Point	CO2 Discharge	Collection Time	12:48 PM
Spot/Comp	Spot	Collection By	Cody Carson
Meter ID	2099	Pressure Base	14.650 psi
Purchaser		Temperature Base	60 F
Fluid	CO2	Container(s)	YZ12639

GPA 2177 CO2 Fractional Analysis

COMPOUND	FORMULA	MOL%	VOL%	WT%
NITROGEN	N2	1.678	1.073	1.129
CARBON DIOXIDE	CO2	87.219	86.668	92.210
HYDROGEN SULFIDE	H2S	1.880	1.477	1.539
METHANE	C1	6.693	6.614	2.579
ETHANE	C2	1.001	1.561	0.723
PROPANE	C3	1.132	1.819	1.199
I-BUTANE	iC4	0.106	0.202	0.148
N-BUTANE	nC4	0.164	0.301	0.229
I-PENTANE	iC5	0.041	0.088	0.071
N-PENTANE	nC5	0.033	0.070	0.057
HEXANES PLUS	C6+	0.053	0.129	0.116
TOTALS:		100.000	100.000	100.000

Value of "0.000" in fractional interpreted as below detectable limit.

If Onsite H2S testing is performed, its resulting value is used in fractional table

Liquid Phase Properties

SCF/Gal (Ideal)	SCF/Gal (Real)	Mol Weight	Relative Density (60/60)	Vapor Pressure 100F, psia
58.620	58.298	41.628	0.769	1,481.5

Vapor Phase Properties

ITEM	BTU/CF	Specific Gr.	Z Factor
DRY	140.51	1.445	0.995
WATER SATURATED	138.99	1.431	0.994

Onsite Testing by Stain Tube

METHOD	TYPE	MOL%	GRAINS/100	PPMV
GPA2377	H2S	1.8795	1,193.48	18,976.3

Pantechs Laboratories, Inc. - Order: 300-3024 - Order Date: 3/21/2022

Order Description: North Hobbs RCF, Monthly Collection

SAMPLE ID		COLLECTION DATA	
Operator	Occidental Permian Ltd.	Pressure	299 psig
Location	North Hobbs RCF	Sample Temp	N/A
Site	1013	Atm Temp	62 F
Site Type	Meter	Collection Date	03/21/2022
Sample Point	#1 Slug Catcher Inlet	Collection Time	1:30 PM
Spot/Comp	Spot	Collection By	Cody Carson
Meter ID	1013	Pressure Base	14.650 psi
Purchaser		Temperature Base	60 F
Fluid	Gas	Container(s)	PL1954

GPA 2261 Gas Fractional Analysis

COMPOUND	FORMULA	MOL%	WT%	GPM
NITROGEN	N2	1.576	1.049	0.173
CARBON DIOXIDE	CO2	87.314	91.310	14.886
HYDROGEN SULFIDE	H2S	0.784	0.635	0.106
METHANE	C1	6.495	2.476	1.101
ETHANE	C2	1.005	0.718	0.269
PROPANE	C3	1.443	1.512	0.398
I-BUTANE	iC4	0.227	0.314	0.074
N-BUTANE	nC4	0.494	0.682	0.156
I-PENTANE	iC5	0.196	0.336	0.072
N-PENTANE	nC5	0.165	0.283	0.060
HEXANES PLUS	C6+	0.301	0.685	0.129
TOTALS:		100.000	100.000	17.424

Value of "0.000" in fractional interpreted as below detectable limit.

If Onsite H2S testing is performed, its resulting value is used in fractional table

LIQUID YIELD	C2+	C3+	C4+	C5+	26# Liquid	10# Liquid
GAL/MSCF (GPM)	1.158	0.889	0.491	0.261	0.401	0.245

CALCULATED PROPERTIES	BTU/CF	Specific Gr.	Z Factor	Mol Weight	Wobbe IDX
DRY	178.86	1.461	0.994	42.084	147.98
WATER SATURATED	176.70	1.447	0.994	41.349	

Onsite Testing by Stain Tube

METHOD	TYPE	MOL%	GRAINS/100	PPMV
GPA2377	H2S	0.7835	497.50	7,910.3

Pantechs Laboratories, Inc. - Order: 300-3024 - Order Date: 3/21/2022

Order Description: North Hobbs RCF, Monthly Collection

SAMPLE ID		COLLECTION DATA	
Operator	Occidental Permian Ltd.	Pressure	293 psig
Location	North Hobbs RCF	Sample Temp	N/A
Site	10002	Atm Temp	62 F
Site Type	Meter	Collection Date	03/21/2022
Sample Point	NGL Plant Inlet	Collection Time	1:13 PM
Spot/Comp	Spot	Collection By	Cody Carson
Meter ID	10002	Pressure Base	14.650 psi
Purchaser		Temperature Base	60 F
Fluid	Gas	Container(s)	PL1904

GPA 2261 Gas Fractional Analysis

COMPOUND	FORMULA	MOL%	WT%	GPM
NITROGEN	N2	1.752	1.167	0.192
CARBON DIOXIDE	CO2	87.424	91.518	14.904
HYDROGEN SULFIDE	H2S	0.662	0.537	0.089
METHANE	C1	6.581	2.511	1.116
ETHANE	C2	0.944	0.675	0.253
PROPANE	C3	1.277	1.339	0.352
I-BUTANE	iC4	0.227	0.314	0.074
N-BUTANE	nC4	0.492	0.680	0.155
I-PENTANE	iC5	0.194	0.333	0.071
N-PENTANE	nC5	0.164	0.281	0.059
HEXANES PLUS	C6+	0.283	0.645	0.122
TOTALS:		100.000	100.000	17.387

Value of "0.000" in fractional interpreted as below detectable limit.

If Onsite H2S testing is performed, its resulting value is used in fractional table

LIQUID YIELD	C2+	C3+	C4+	C5+	26# Liquid	10# Liquid
GAL/MSCF (GPM)	1.086	0.833	0.481	0.252	0.386	0.232

CALCULATED PROPERTIES	BTU/CF	Specific Gr.	Z Factor	Mol Weight	Wobbe IDX
DRY	172.55	1.459	0.994	42.042	142.83
WATER SATURATED	170.49	1.445	0.994	41.307	

Onsite Testing by Stain Tube

METHOD	TYPE	MOL%	GRAINS/100	PPMV
GPA2377	H2S	0.6621	420.42	6,684.7

Pantechs Laboratories, Inc. - Order: 300-3024 - Order Date: 3/21/2022

Order Description: North Hobbs RCF, Monthly Collection

SAMPLE ID		COLLECTION DATA	
Operator	Occidental Permian Ltd.	Pressure	N/A
Location	North Hobbs RCF	Sample Temp	N/A
Site	21013	Atm Temp	N/A
Site Type	Meter	Collection Date	
Sample Point	#2 Slug Catcher Inlet	Collection Time	
Spot/Comp	Spot	Collection By	
Meter ID	21013	Pressure Base	14.650 psi
Purchaser		Temperature Base	60 F
Fluid	Gas	Container(s)	

No Sample

Employee	Comment
Cody Carson	No Flow at Sample Point

Pantechs Laboratories, Inc. - Order: 300-3024 - Order Date: 3/21/2022

Order Description: North Hobbs RCF, Monthly Collection

SAMPLE ID		COLLECTION DATA	
Operator	Occidental Permian Ltd.	Pressure	299 psig
Location	North Hobbs RCF	Sample Temp	N/A
Site	21023	Atm Temp	62 F
Site Type	Meter	Collection Date	03/21/2022
Sample Point	#3 Slug Catcher Inlet	Collection Time	1:34 PM
Spot/Comp	Spot	Collection By	Cody Carson
Meter ID	21023	Pressure Base	14.650 psi
Purchaser		Temperature Base	60 F
Fluid	Gas	Container(s)	PL1037

GPA 2261 Gas Fractional Analysis

COMPOUND	FORMULA	MOL%	WT%	GPM
NITROGEN	N2	1.772	1.164	0.194
CARBON DIOXIDE	CO2	90.387	93.241	15.410
HYDROGEN SULFIDE	H2S	0.552	0.441	0.074
METHANE	C1	4.411	1.659	0.748
ETHANE	C2	0.692	0.488	0.185
PROPANE	C3	0.984	1.017	0.271
I-BUTANE	iC4	0.194	0.264	0.063
N-BUTANE	nC4	0.424	0.578	0.134
I-PENTANE	iC5	0.160	0.271	0.059
N-PENTANE	nC5	0.136	0.230	0.049
HEXANES PLUS	C6+	0.288	0.647	0.124
TOTALS:		100.000	100.000	17.311

Value of "0.000" in fractional interpreted as below detectable limit.

If Onsite H2S testing is performed, its resulting value is used in fractional table

LIQUID YIELD	C2+	C3+	C4+	C5+	26# Liquid	10# Liquid
GAL/MSCF (GPM)	0.885	0.700	0.429	0.232	0.360	0.231

CALCULATED PROPERTIES	BTU/CF	Specific Gr.	Z Factor	Mol Weight	Wobbe IDX
DRY	132.49	1.481	0.994	42.662	108.87
WATER SATURATED	131.11	1.467	0.994	41.917	

Onsite Testing by Stain Tube

METHOD	TYPE	MOL%	GRAINS/100	PPMV
GPA2377	H2S	0.5517	350.35	5,570.6

Pantechs Laboratories, Inc. - Order: 300-3024 - Order Date: 3/21/2022

Order Description: North Hobbs RCF, Monthly Collection

SAMPLE ID		COLLECTION DATA	
Operator	Occidental Permian Ltd.	Pressure	296 psig
Location	North Hobbs RCF	Sample Temp	N/A
Site	DEX PRO	Atm Temp	62 F
Site Type	Station	Collection Date	03/21/2022
Sample Point	Inlet	Collection Time	1:23 PM
Spot/Comp	Spot	Collection By	Cody Carson
Meter ID		Pressure Base	14.650 psi
Purchaser		Temperature Base	60 F
Fluid	Gas	Container(s)	PL2106

GPA 2261 Gas Fractional Analysis

COMPOUND	FORMULA	MOL%	WT%	GPM
NITROGEN	N2	1.596	1.051	0.175
CARBON DIOXIDE	CO2	89.906	93.000	15.328
HYDROGEN SULFIDE	H2S	0.552	0.442	0.074
METHANE	C1	4.900	1.848	0.831
ETHANE	C2	0.751	0.531	0.201
PROPANE	C3	1.058	1.097	0.292
I-BUTANE	iC4	0.204	0.279	0.067
N-BUTANE	nC4	0.447	0.611	0.141
I-PENTANE	iC5	0.173	0.293	0.063
N-PENTANE	nC5	0.147	0.249	0.053
HEXANES PLUS	C6+	0.266	0.599	0.114
TOTALS:		100.000	100.000	17.339

Value of "0.000" in fractional interpreted as below detectable limit.

If Onsite H2S testing is performed, its resulting value is used in fractional table

LIQUID YIELD	C2+	C3+	C4+	C5+	26# Liquid	10# Liquid
GAL/MSCF (GPM)	0.931	0.730	0.438	0.230	0.354	0.216

CALCULATED PROPERTIES	BTU/CF	Specific Gr.	Z Factor	Mol Weight	Wobbe IDX
DRY	141.24	1.477	0.994	42.546	116.22
WATER SATURATED	139.71	1.463	0.994	41.802	

Onsite Testing by Stain Tube

METHOD	TYPE	MOL%	GRAINS/100	PPMV
GPA2377	H2S	0.5517	350.35	5,570.6

Pantechs Laboratories, Inc. - Order: 300-3024 - Order Date: 3/21/2022

Order Description: North Hobbs RCF, Monthly Collection

SAMPLE ID		COLLECTION DATA	
Operator	Occidental Permian Ltd.	Pressure	N/A
Location	North Hobbs RCF	Sample Temp	N/A
Site	DEX PRO	Atm Temp	N/A
Site Type	Station	Collection Date	
Sample Point	Outlet	Collection Time	
Spot/Comp	Spot	Collection By	
Meter ID		Pressure Base	14.650 psi
Purchaser		Temperature Base	60 F
Fluid	Gas	Container(s)	

No Sample

Employee	Comment
Cody Carson	Sample Point Inaccessible

Pantechs Laboratories, Inc. - Order: 300-3024 - Order Date: 3/21/2022

Order Description: North Hobbs RCF, Monthly Collection

SAMPLE ID		COLLECTION DATA	
Operator	Occidental Permian Ltd.	Pressure	238 psig
Location	North Hobbs RCF	Sample Temp	N/A
Site	Reflux Stabilizer	Atm Temp	64 F
Site Type	Station	Collection Date	03/21/2022
Sample Point	Sample Valve	Collection Time	1:07 PM
Spot/Comp	Spot	Collection By	Cody Carson
Meter ID		Pressure Base	14.650 psi
Purchaser		Temperature Base	60 F
Fluid	Gas	Container(s)	PL1921

GPA 2261 Gas Fractional Analysis

COMPOUND	FORMULA	MOL%	WT%	GPM
NITROGEN	N2	1.773	1.191	0.194
CARBON DIOXIDE	CO2	89.236	94.144	15.208
HYDROGEN SULFIDE	H2S	0.000	0.000	0.000
METHANE	C1	6.797	2.614	1.152
ETHANE	C2	0.974	0.702	0.260
PROPANE	C3	1.051	1.111	0.290
I-BUTANE	iC4	0.085	0.118	0.028
N-BUTANE	nC4	0.080	0.111	0.025
I-PENTANE	iC5	0.000	0.000	0.000
N-PENTANE	nC5	0.000	0.000	0.000
HEXANES PLUS	C6+	0.004	0.009	0.002
TOTALS:		100.000	100.000	17.159

Value of "0.000" in fractional interpreted as below detectable limit.

If Onsite H2S testing is performed, its resulting value is used in fractional table

LIQUID YIELD	C2+	C3+	C4+	C5+	26# Liquid	10# Liquid
GAL/MSCF (GPM)	0.605	0.345	0.055	0.002	0.003	0.002

CALCULATED PROPERTIES	BTU/CF	Specific Gr.	Z Factor	Mol Weight	Wobbe IDX
DRY	118.18	1.448	0.995	41.716	98.22
WATER SATURATED	117.05	1.434	0.994	40.987	

Pantechs Laboratories, Inc. - Order: 300-3024 - Order Date: 3/21/2022

Order Description: North Hobbs RCF, Monthly Collection

SAMPLE ID		COLLECTION DATA	
Operator	Occidental Permian Ltd.	Pressure	175 psig
Location	North Hobbs RCF	Sample Temp	N/A
Site	Surge Tank	Atm Temp	62 F
Site Type	Tank	Collection Date	03/21/2022
Sample Point	Propane Vapor	Collection Time	1:38 PM
Spot/Comp	Spot	Collection By	Cody Carson
Meter ID		Pressure Base	14.650 psi
Purchaser		Temperature Base	60 F
Fluid	Gas	Container(s)	PL2227

GPA 2261 Gas Fractional Analysis

COMPOUND	FORMULA	MOL%	WT%	GPM
NITROGEN	N2	9.123	6.641	1.007
CARBON DIOXIDE	CO2	0.804	0.919	0.138
HYDROGEN SULFIDE	H2S	0.000	0.000	0.000
METHANE	C1	1.253	0.522	0.214
ETHANE	C2	27.084	21.164	7.291
PROPANE	C3	61.716	70.722	17.116
I-BUTANE	iC4	0.016	0.024	0.005
N-BUTANE	nC4	0.002	0.003	0.001
I-PENTANE	iC5	0.000	0.000	0.000
N-PENTANE	nC5	0.000	0.000	0.000
HEXANES PLUS	C6+	0.002	0.005	0.001
TOTALS:		100.000	100.000	25.773

Value of "0.000" in fractional interpreted as below detectable limit.

If Onsite H2S testing is performed, its resulting value is used in fractional table

LIQUID YIELD	C2+	C3+	C4+	C5+	26# Liquid	10# Liquid
GAL/MSCF (GPM)	24.414	17.123	0.007	0.001	0.002	0.001

CALCULATED PROPERTIES	BTU/CF	Specific Gr.	Z Factor	Mol Weight	Wobbe IDX
DRY	2,063.47	1.344	0.988	38.482	1,779.84
WATER SATURATED	2,029.28	1.332	0.988	37.810	

Pantechs Laboratories, Inc. - Order: 300-3024 - Order Date: 3/21/2022

Order Description: North Hobbs RCF, Monthly Collection

SAMPLE ID		COLLECTION DATA	
Operator	Occidental Permian Ltd.	Pressure	N/A
Location	North Hobbs RCF	Sample Temp	N/A
Site	DEX PRO	Atm Temp	N/A
Site Type	Station	Collection Date	
Sample Point	Gasoline	Collection Time	
Spot/Comp	Spot	Collection By	
Meter ID		Pressure Base	14.650 psi
Purchaser		Temperature Base	60 F
Fluid	Liquid	Container(s)	

No Sample

Employee	Comment
Cody Carson	Sample Point All Water

Pantechs Laboratories, Inc. - Order: 300-3024 - Order Date: 3/21/2022

Order Description: North Hobbs RCF, Monthly Collection

SAMPLE ID		COLLECTION DATA	
Operator	Occidental Permian Ltd.	Pressure	30 psig
Location	North Hobbs RCF	Sample Temp	N/A
Site	NGL Storage	Atm Temp	62 F
Site Type	Vessel	Collection Date	03/21/2022
Sample Point	NGL	Collection Time	1:03 PM
Spot/Comp	Spot	Collection By	Cody Carson
Meter ID		Pressure Base	14.650 psi
Purchaser		Temperature Base	60 F
Fluid	Liquid	Container(s)	PL2506

GPA 2177 Liquid Fractional Analysis

COMPOUND	FORMULA	MOL%	VOL%	WT%
NITROGEN	N2	0.022	0.007	0.009
CARBON DIOXIDE	CO2	0.010	0.005	0.007
HYDROGEN SULFIDE	H2S	0.000	0.000	0.000
METHANE	C1	0.000	0.000	0.000
ETHANE	C2	0.000	0.000	0.000
PROPANE	C3	16.966	13.632	11.353
I-BUTANE	iC4	10.216	9.745	9.010
N-BUTANE	nC4	27.876	25.626	24.585
I-PENTANE	iC5	13.225	14.116	14.479
N-PENTANE	nC5	11.196	11.824	12.258
HEXANES PLUS	C6+	20.489	25.045	28.299
TOTALS:		100.000	100.000	100.000

Value of "0.000" in fractional interpreted as below detectable limit.

Calculated Properties

SCF/Gal (Ideal)	SCF/Gal (Real)	Mol Weight	Relative Density (60/60)	Vapor Pressure 100F, psia	Reid VP Equivalent, psi
29.321	27.986	65.901	0.609	60.5	57.4

Pantechs Laboratories, Inc. - Order: 300-3024 - Order Date: 3/21/2022

Order Description: North Hobbs RCF, Monthly Collection

SAMPLE ID		COLLECTION DATA	
Operator	Occidental Permian Ltd.	Pressure	280 psig
Location	North Hobbs RCF	Sample Temp	N/A
Site	Stabilizer	Atm Temp	64 F
Site Type	Vessel	Collection Date	03/21/2022
Sample Point	Bottoms	Collection Time	1:09 PM
Spot/Comp	Spot	Collection By	Cody Carson
Meter ID		Pressure Base	14.650 psi
Purchaser		Temperature Base	60 F
Fluid	Liquid	Container(s)	PL2290

GPA 2177 Liquid Fractional Analysis

COMPOUND	FORMULA	MOL%	VOL%	WT%
NITROGEN	N2	0.011	0.004	0.005
CARBON DIOXIDE	CO2	0.002	0.001	0.002
HYDROGEN SULFIDE	H2S	0.000	0.000	0.000
METHANE	C1	0.000	0.000	0.000
ETHANE	C2	0.000	0.000	0.000
PROPANE	C3	41.764	36.579	32.516
I-BUTANE	iC4	11.666	12.131	11.972
N-BUTANE	nC4	25.162	25.216	25.822
I-PENTANE	iC5	7.761	9.031	9.887
N-PENTANE	nC5	6.022	6.933	7.671
HEXANES PLUS	C6+	7.612	10.105	12.125
TOTALS:		100.000	100.000	100.000

Value of "0.000" in fractional interpreted as below detectable limit.

Calculated Properties

SCF/Gal (Ideal)	SCF/Gal (Real)	Mol Weight	Relative Density (60/60)	Vapor Pressure 100F, psia	Reid VP Equivalent, psi
31.961	30.955	56.638	0.570	103.7	98.9

Pantechs Laboratories, Inc. - Order: 300-3024 - Order Date: 3/21/2022

Order Description: North Hobbs RCF, Monthly Collection

SAMPLE ID		COLLECTION DATA	
Operator	Occidental Permian Ltd.	Pressure	175 psig
Location	North Hobbs RCF	Sample Temp	N/A
Site	Surge Tank	Atm Temp	62 F
Site Type	Tank	Collection Date	03/21/2022
Sample Point	Propane Liquid	Collection Time	1:42 PM
Spot/Comp	Spot	Collection By	Cody Carson
Meter ID		Pressure Base	14.650 psi
Purchaser		Temperature Base	60 F
Fluid	Liquid	Container(s)	PL1629

GPA 2177 Liquid Fractional Analysis

COMPOUND	FORMULA	MOL%	VOL%	WT%
NITROGEN	N2	0.025	0.010	0.016
CARBON DIOXIDE	CO2	0.003	0.002	0.003
HYDROGEN SULFIDE	H2S	0.000	0.000	0.000
METHANE	C1	0.003	0.002	0.001
ETHANE	C2	0.739	0.717	0.504
PROPANE	C3	98.582	98.490	98.595
I-BUTANE	iC4	0.596	0.707	0.786
N-BUTANE	nC4	0.017	0.019	0.022
I-PENTANE	iC5	0.004	0.005	0.007
N-PENTANE	nC5	0.003	0.004	0.005
HEXANES PLUS	C6+	0.028	0.044	0.061
TOTALS:		100.000	100.000	100.000

Value of "0.000" in fractional interpreted as below detectable limit.

Calculated Properties

SCF/Gal (Ideal)	SCF/Gal (Real)	Mol Weight	Relative Density (60/60)	Vapor Pressure 100F, psia	Reid VP Equivalent, psi
36.455	35.823	44.091	0.506	192.7	184.1

THIS PAGE IS INTENTIONALLY LEFT BLANK

EVENT SPECIFIC JUSTIFICATIONS FORM**Facility:** North Hobbs Plant**Start Date:** 07/15/2022 @ 03:19 PM**End Date:** 07/15/2022 @ 03:52 PM**Cause:** THE NORTH PLANT FLARED WHEN "A", "D", "E", "F", and "H" TRAINS SHUT DOWN DUE TO LOW INLET RATES.**Duration of event:** 0:33 hours

Flared MCF: 512

Method of Flared Gas Measurement: Flare Meter

1. Reason why this event was beyond Operator's control:

The emissions event was caused by the unforeseen, unexpected, sudden, and unavoidable breakdown of equipment or process that was beyond the owner/operator's control, and did not stem from activity that could have been foreseen and avoided, and could not have been avoided by good design, operation, and preventative maintenance practices. It is OXY's policy to route all stranded sales gas to a flare during an unforeseen and unavoidable emergency or malfunction, in order to minimize emissions as much as possible. The flare is regularly monitored to ensure flame is lit and meeting opacity requirements.

This event was a sudden and unforeseeable gas release to the flare due to the shutdown of the compressor units. Oxy operators shut down "A", "D", "E", "F", and "H" train compressors due to low inlet rates and the compressors were not needed. OXY operators assisted with shutting down the units, and this shut down of the compressor units triggered a flaring event. The compressors will be shut down until inlet gas rates are higher and the need for the compressors is available.

Notwithstanding proper gas compressor design and operation, various forms of mechanical or technical issues can be sudden, reasonably unforeseeable and unexpected which can cause compressor unit malfunctions to occur without warning or advance notice. OXY made every effort to control and minimize emissions as much as possible during this event.

2. Steps Taken to limit duration and magnitude of venting or flaring:

The emissions event was caused by the unforeseen, unexpected, sudden, and unavoidable breakdown of equipment or process that was beyond the owner/operator's control, and did not stem from activity that could have been foreseen and avoided, and could not have been avoided by good design, operation, and preventative maintenance practices. It is OXY's policy to route all stranded sales gas to a flare during an unforeseen and unavoidable emergency or malfunction, in order to minimize emissions as much as possible. The flare is regularly monitored to ensure flame is lit and meeting opacity requirements.

In this case, the steps taken to limit duration and magnitude of flaring was for Oxy operators to quickly respond to the compression equipment and get it blown down, OXY routed all the stranded sales gas to a flare with a 98% combustion efficiency in order to lessen emissions as much as possible. The flare is regularly monitored to ensure the flame is lit and meeting opacity requirements. After thoroughly inspecting the compressor units that were taken down, they will later be brought back to normal working service when inlet gas rates are higher.

Notwithstanding proper gas compressor design and operation, various forms of mechanical or technical issues can be sudden, reasonably unforeseeable and unexpected which can cause compressor unit malfunctions to occur without warning or advance notice. OXY made every effort to control and minimize emissions as much as possible during this event.

3. Corrective Actions taken to eliminate the cause and reoccurrence of venting or flaring:

The emissions event was caused by the unforeseen, unexpected, sudden, and unavoidable breakdown of equipment or process that was beyond the owner/operator's control, and did not stem from activity that could have been foreseen and avoided, and could not have been avoided by good design, operation, and preventative maintenance practices. It is OXY's policy to route all stranded sales gas to a flare during an unforeseen and unavoidable emergency or malfunction, in order to minimize emissions as much as possible. The flare is regularly monitored to ensure the flame is lit and meeting opacity requirements.

Oxy cannot take any corrective actions to eliminate the cause and potential reoccurrence of compressor malfunctions as notwithstanding proper gas compressor design and operation, various forms of mechanical or technical issues can be sudden, reasonably unforeseeable and unexpected which can cause compressor units malfunctions to occur without warning or advance notice. Oxy continually strives to maintain and operate its facility equipment in a manner consistent with good practices for minimizing emissions and reducing the number of emission events "A", "D", "E", "F", and "H" trains were working as designed and operated normally prior to the sudden and without warning send of gas to the flare from the compressor units. Oxy has a strong and positive compression equipment preventative maintenance program in place. This incident was completely out of OXY's control to prevent from happening as it was determined the flaring was due to blowing down the compressors and sending gas to the flare due to low inlet rates and the compressors not being needed. OXY made every effort to control and minimize emissions as much as possible during this event. The only actions that Oxy can take and handle that is within its control, is to keep continue with its compression equipment preventative maintenance program for these units.

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

DEFINITIONS

Action 127388

DEFINITIONS

Operator: OCCIDENTAL PERMIAN LTD P.O. Box 4294 Houston, TX 772104294	OGRID: 157984
	Action Number: 127388
	Action Type: [C-129] Amend Venting and/or Flaring (C-129A)

DEFINITIONS

For the sake of brevity and completeness, please allow for the following in all groups of questions and for the rest of this application:

- this application's operator, hereinafter "this operator";
- venting and/or flaring, hereinafter "vent or flare";
- any notification or report(s) of the C-129 form family, hereinafter "any C-129 forms";
- the statements in (and/or attached to) this, hereinafter "the statements in this";
- and the past tense will be used in lieu of mixed past/present tense questions and statements.

District I

1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

QUESTIONS

Action 127388

QUESTIONS

Operator: OCCIDENTAL PERMIAN LTD P.O. Box 4294 Houston, TX 772104294	OGRID: 157984
	Action Number: 127388
	Action Type: [C-129] Amend Venting and/or Flaring (C-129A)

QUESTIONS**Prerequisites**

Any messages presented in this section, will prevent submission of this application. Please resolve these issues before continuing with the rest of the questions.

Incident Operator	[157984] OCCIDENTAL PERMIAN LTD
Incident Type	Flare
Incident Status	Closure Not Approved
Incident Well	Not answered.
Incident Facility	[FKJ1517634129] NORTH HOBBS UNIT RCF/WIB

Only valid Vent, Flare or Vent with Flaring incidents (selected above in the Application Details section) that are assigned to your current operator can be amended with this C-129A application.

Determination of Reporting Requirements

Answer all questions that apply. The Reason(s) statements are calculated based on your answers and may provide additional guidance.

Was this vent or flare caused by an emergency or malfunction	Yes
Did this vent or flare last eight hours or more cumulatively within any 24-hour period from a single event	No
Is this considered a submission for a vent or flare event	Yes, major venting and/or flaring of natural gas.

An operator shall file a form C-141 instead of a form C-129 for a release that, includes liquid during venting and/or flaring that is or may be a major or minor release under 19.15.29.7 NMAC.

Was there at least 50 MCF of natural gas vented and/or flared during this event	Yes
Did this vent or flare result in the release of ANY liquids (not fully and/or completely flared) that reached (or has a chance of reaching) the ground, a surface, a watercourse, or otherwise, with reasonable probability, endanger public health, the environment or fresh water	No
Was the vent or flare within an incorporated municipal boundary or within 300 feet from an occupied permanent residence, school, hospital, institution or church in existence	No

Equipment Involved

Primary Equipment Involved	Other (Specify)
Additional details for Equipment Involved. Please specify	Emergency Flare>Low Inlet Rates

Representative Compositional Analysis of Vented or Flared Natural Gas

Please provide the mole percent for the percentage questions in this group.

Methane (CH4) percentage	6
Nitrogen (N2) percentage, if greater than one percent	2
Hydrogen Sulfide (H2S) PPM, rounded up	7,840
Carbon Dioxide (CO2) percentage, if greater than one percent	87
Oxygen (O2) percentage, if greater than one percent	0

If you are venting and/or flaring because of Pipeline Specification, please provide the required specifications for each gas.

Methane (CH4) percentage quality requirement	Not answered.
Nitrogen (N2) percentage quality requirement	Not answered.
Hydrogen Sulfide (H2S) PPM quality requirement	Not answered.
Carbon Dioxide (CO2) percentage quality requirement	Not answered.
Oxygen (O2) percentage quality requirement	Not answered.

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720

District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720

District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico

Energy, Minerals and Natural Resources

Oil Conservation Division

1220 S. St Francis Dr.

Santa Fe, NM 87505

QUESTIONS, Page 2

Action 127388

QUESTIONS (continued)

Operator: OCCIDENTAL PERMIAN LTD P.O. Box 4294 Houston, TX 772104294	OGRID: 157984
	Action Number: 127388
	Action Type: [C-129] Amend Venting and/or Flaring (C-129A)

QUESTIONS

Date(s) and Time(s)	
Date vent or flare was discovered or commenced	07/15/2022
Time vent or flare was discovered or commenced	03:19 PM
Time vent or flare was terminated	03:52 PM
Cumulative hours during this event	0

Measured or Estimated Volume of Vented or Flared Natural Gas	
Natural Gas Vented (Mcf) Details	Not answered.
Natural Gas Flared (Mcf) Details	Cause: Other Other (Specify) Natural Gas Flared Released: 512 Mcf Recovered: 0 Mcf Lost: 512 Mcf]
Other Released Details	Not answered.
Additional details for Measured or Estimated Volume(s). Please specify	Not answered.
Is this a gas only submission (i.e. only significant Mcf values reported)	Yes, according to supplied volumes this appears to be a "gas only" report.

Venting or Flaring Resulting from Downstream Activity	
Was this vent or flare a result of downstream activity	No
Was notification of downstream activity received by this operator	Not answered.
Downstream OGRID that should have notified this operator	Not answered.
Date notified of downstream activity requiring this vent or flare	Not answered.
Time notified of downstream activity requiring this vent or flare	Not answered.

Steps and Actions to Prevent Waste	
For this event, this operator could not have reasonably anticipated the current event and it was beyond this operator's control	True
Please explain reason for why this event was beyond this operator's control	The emissions event was caused by the unforeseen, unexpected, sudden, and unavoidable breakdown of equipment or process that was beyond the owner/operator's control, and did not stem from activity that could have been foreseen and avoided, and could not have been avoided by good design, operation, and preventative maintenance practices. It is OXY's policy to route all stranded sales gas to a flare during an unforeseen and unavoidable emergency or malfunction, in order to minimize emissions as much as possible. The flare is regularly monitored to the ensure flame is lit and meeting opacity requirements.
Steps taken to limit the duration and magnitude of vent or flare	The emissions event was caused by the unforeseen, unexpected, sudden, and unavoidable breakdown of equipment or process that was beyond the owner/operator's control, and did not stem from activity that could have been foreseen and avoided, and could not have been avoided by good design, operation, and preventative maintenance practices. It is OXY's policy to route all stranded sales gas to a flare during an unforeseen and unavoidable emergency or malfunction, in order to minimize emissions as much as possible. The flare is regularly monitored to the ensure flame is lit and meeting opacity requirements.
Corrective actions taken to eliminate the cause and reoccurrence of vent or flare	The emissions event was caused by the unforeseen, unexpected, sudden, and unavoidable breakdown of equipment or process that was beyond the owner/operator's control, and did not stem from activity that could have been foreseen and avoided, and could not have been avoided by good design, operation, and preventative maintenance practices. It is OXY's policy to route all stranded sales gas to a flare during an unforeseen and unavoidable emergency or malfunction, in order to minimize emissions as much as possible. The flare is regularly monitored to the ensure flame is lit and meeting opacity requirements.

District I

1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

ACKNOWLEDGMENTS

Action 127388

ACKNOWLEDGMENTS

Operator: OCCIDENTAL PERMIAN LTD P.O. Box 4294 Houston, TX 772104294	OGRID: 157984
	Action Number: 127388
	Action Type: [C-129] Amend Venting and/or Flaring (C-129A)

ACKNOWLEDGMENTS

☒	I acknowledge that with this application I will be amending an existing incident file (assigned to this operator) for a vent or flare event, pursuant to 19.15.27 and 19.15.28 NMAC.
☒	I acknowledge that amending an incident file does not replace original submitted application(s) or information and understand that any C-129 forms submitted to the OCD will be logged and stored as public record.
☒	I hereby certify the statements in this amending report are true and correct to the best of my knowledge and acknowledge that any false statement may be subject to civil and criminal penalties under the Oil and Gas Act.
☒	I acknowledge that the acceptance of any C-129 forms by the OCD does not relieve this operator of liability should their operations have failed to adequately investigate, report, and remediate contamination that poses a threat to groundwater, surface water, human health, or the environment.
☒	I acknowledge that OCD acceptance of any C-129 forms does not relieve this operator of responsibility for compliance with any other applicable federal, state, or local laws and/or regulations.

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 127388

CONDITIONS

Operator: OCCIDENTAL PERMIAN LTD P.O. Box 4294 Houston, TX 772104294	OGRID: 157984
	Action Number: 127388
	Action Type: [C-129] Amend Venting and/or Flaring (C-129A)

CONDITIONS

Created By	Condition	Condition Date
ralvarado	If the information provided in this report requires further amendment(s), submit a [C-129] Amend Venting and/or Flaring Incident (C-129A), utilizing your incident number from this event.	7/20/2022