Submit 3 Copies To Appropriate District Form C-103 Office Revised March 25, 1999 District I WELL API NO. 1625 N. French Dr., Hobbs, NM 87240 APR 12 2004 OIL CONSERVATION DIVISION District II 30-007-20493 811 South First, Artesia, NM 87210 5. Indicate Type of Lease 1200 South St. Franciscon District III STATE \square 1000 Rio Brazos Rd., Aztec, NM 87410 Shara Frank Francis Drive District IV 6. State Oil & Gas Lease No. Santa Fe, NM 87505 1220 South St Francis, Santa Fe, NM 87505 SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name: (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A QIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH. VPR D PROPOSALS.) 1. Type of Well: Oil Well 🗀 Gas Well Other COALBED METHANE Name of Operator 127 8. Well No. EL PASO ENERGY RATON, L.L.C. 9. Pool name or Wildcat Address of Operator P.O. BOX 190 RATON, NM 87740 Well Location Unit Letter O: 948 feet from the South line and 1444 feet from the East line NMPM COLFAX Section Township 30N Range 18E County 10. Elevation (Show whether DR, RKB, RT, GR, etc.) 7,705' (GR) 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WORK ALTERING CASING 🗀 COMMENCE DRILLING OPNS. TEMPORARILY ABANDON ☐ CHANGE PLANS PLUG AND **ABANDONMENT PULL OR ALTER CASING** ☐ MULTIPLE CASING TEST AND \Box **CEMENT JOB** COMPLETION COMPLETION OTHER: OTHER: 12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation. 01/28/04 HES ran Cement Bond Log. Estimated Cement Top at surface. 03/25/04 HES perf'd 1st stage: 1454'- 1457' 9 Holes HES frac'd 1st stage: Pumped fracture treatment with 30,010 lbs of 16/30 Brady sand, Avg Pres 1140 psi, Avg Rate 16.8 bbl/min. HES perf'd 2nd stage: HES frac'd 2nd stage: 1378'- 1381', 1393'- 1395' 15 Holes Pumped fracture treatment with 41,500 lbs of 16/30 Brady sand, Avg Pres 2035 psi, Avg Rate 8.3 bbl/min. HES perf'd 3nd stage: HES frac'd 3nd stage: 1214'- 1218' 12 Holes Pumped fracture treatment with 15,200 lbs of 16/30 Brady sand, Avg Pres 2485 psi, Avg Rate 13.1 bbl/min. 03/26/04 Installed rods, tubing, and pump. Well is ready to be tested and put on production. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE Shirly Mitchell TITLE_ 04/07/04 Regulatory Analyst DATE Telephone No.: (505) 445-6785 Shirley A. Mitchel Type or print name: (This space for State use) TITLE DISTRICT SUPERVISOR DATE 4/13/04

APPPROVED BY

Conditions of approval, if any