

Submit 3 Copies To Appropriate District Office  
District I  
1625 N. French Dr., Hobbs, NM 87240  
District II  
811 South First, Artesia, NM 87210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 South St. Frances, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised March 25, 1999

OIL CONSERVATION DIVISION

1220 South St. Frances  
Santa Fe, NM 87505

WELL API NO.

30-007-20503

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

VPR D

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☐ Other ☒ Coalbed Methane

2. Name of Operator

EL PASO ENERGY RATON, L.L.C.

3. Address of Operator

P.O. Box 190, Raton, NM 87740

4. Well Location

Unit Letter O : 426 feet from the South line and 1555 feet from the East line

Section 9 Township 30N Range 17E NMPM COLFAX County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

9101' (GL)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

05/31/04 Spud @ 13:15. Drill 11" surface hole to 350'. Run 8 jts. of 8 5/8", J-55, 23 ppf ST&C casing to 344'. Halliburton mixed and pumped 28 bbls water, 100 sx Midcon II, 14 ppg, yield 1.66 at 4 bpm with 70 psi with 6 % salt, 5#/sx gilsonite, .3% versaset, .25 #/sk flocele. Circulated 9 bbls of cement to surface. WOC 8 hrs. Test surface casing to 500 psi for 30 minutes.

06/01/04 Drill 7 7/8" hole from 350' - 2935'. Reached TD 2935' at 4:15 p.m. MIRU Schlumberger & log well. Loggers TD at 2898'. Ran 69 jts. of 5 1/2", M-50, 15.5 ppf LT&C casing to 2876'. Halliburton mix and pump 75 bbls water, 50 bbls gel pre flush. Pumped 531 sx Midcon II PP, 13 ppg, yield 2.04 at 4 bpm. with 6 % salt, 2 lb/sx Granulite, 5 lb/sx Gilsonite, .3% Versaset, and .1% Super CBL. Landed plug. Released pressure. Float held. No cement to surface. Well shut in.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Shirley Mitchell TITLE Regulatory Analyst DATE 06/07/04  
Type or print name Shirley A. Mitchell Telephone No. (505) 445-6785

(This space for State use)

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 6/14/04  
Conditions of approval, if any: