Office	State of the	ew Mexico	Form C-103
District I	Energy, Minerals and Natural Resources		Revised March 25, 1999
1625 N. French Dr., Hobbs, NM 87240 District II			WELL API NO. 30-007-20437
811 South First, Artesia, NM 87210	OIL CONSERVA		5. Indicate Type of Lease
District III	1220 South	1 St Francis	STATE FEE
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, 1	NM 87505	6. State Oil & Gas Lease No.
1220 South Pacheco, Santa Fe, NM 87505	CDC AND DEDORGO ONL		
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A			7. Lease Name or Unit Agreement Name:
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			VPR A
PROPOSALS.) 1. Type of Well:			VIKA
Oil Well Gas Well Other COALBED METHANE			
2. Name of Operator			8. Well No. 127
EL PASO ENERGY RATON, L.L.C.			o. Well ivo.
3. Address of Operator			9. Pool name or Wildcat
P.O. BOX 190 RATON, NM 87740			
4. Well Location Unit Letter P: 990 feet from the South line and 1137 feet from the East line			
Omi Letter r : 990	_teet from the <u>South</u>	inne and <u>1157</u> leet	from the <u>East</u> line
Section 22 Towns	hip 32N Range	19E NMPM	COLFAX County
	Market Control of the	ether DR, RKB, RT, GR, et	c.)
8265' (GR)			
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF IN			SEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON L	REMEDIAL WOR	K ☐ ALTERING CASING ☐
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DR	ILLING OPNS. PLUG AND ABANDONMENT
PULL OR ALTER CASING	MULTIPLE [COMPLETION	CASING TEST AI CEMENT JOB	
OTHER:	Г	OTHER:	COMPLETION
12. Describe proposed or completed opera	tions. (Clearly state all pertinent d		cluding estimated date of starting any proposed work).
SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.			
03/12/04 HES ran cement bond log. Cement Top estimated at 178'.			
05/24/04 HES perf'd 1st stage: 2359'-2361', 2410'-2412', 2438'-2442' 32 Holes			
HES perf'd 2 nd stage 2190' - 2194', 2226' - 2228', 2257' - 2260' 36 Holes			
HES frac'd 2 nd stage: Pumped fracture treatment with 64,843 lbs of 16/30 brown sand at 22.3 bpm, ATP 880 psi, Final ISIP 222 psi.			
HES frac'd 3rd stage: Pumped fracture treatment with 25,747 lbs of 16/30 brown sand at 19.1 bpm, ATP 2098 psi, Final ISIP 1812 psi.			
HES perf'd 4 th stage: 1221'-1223', 1256'-1260', 1266'-1269' 36 Holes HES frac'd 4 th stage: Pumped fracture treatment with 36,948 lbs of 16/30 brown sand at 22.6 bpm, ATP 501 psi, Final ISIP 457 psi.			
HES frac'd 4th stage: Pumped fracture treatment with 36,948 lbs of 16/30 brown sand at 22.6 bpm, ATP 501 psi, Final ISIP 457 psi. HES perf'd 5th stage: 934'-936', 962'-964', 1048'-1050', 1106'-1110' 40 Holes			
HES frac'd 5th stage: Pumped	fracture treatment with 46,320 lbs	s of 16/30 brown sand at 22 9 1	opm, ATP 1176 psi, Final ISIP 572 psi.
05/28/04 Installed rods, tubing, and pump. Well is ready to be tested and placed on production.			
I hereby certify that the information above is true and complete to the best of my knowledge and belief.			
SIGNATURE Shuffy Trut Title Regulatory Analyst DATE 06/28/04			
Type or print name: Shirtey A Mitchell Telephone No.: (505) 445-6785			
APPPROVED BY TITLE DISTRICT SUPERVISOR DATE 7/7/04			
Conditions of approval, if an ∤ :	//		• •
i	/		