	State of New Mex		Form C-103
Office  District I  Leas N French Dr. Hobbs NW 98240 FF J J J J J J J J J J J J J J J J J J		May 27, 2004	
1625 N. French Dr., Hobbs, NM 88240 WELL API NO. 30-007-20472 District II			
1301 W. Grand Ave., Artesia, NM 88210 OIL CONSERVATION DIVISION		5. Indicate Type of Lease	
District III 1000 Rio Brazos Rd., Aztec, NM 82410 2 7 2004 1220 South St. Francis Dr. South Fo. NIM 87505		STATE FEE 🖂	
District IV Santa Fe, NW 6/303		6. State Oil & Gas Lease No.	
1220 S. St. Francis Dr., Santa Fill MONSERVATION 87505			
SUNDRY NOTICES AND REPORTS ON WELLS			7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			*****
PROPOSALS.)  1. Type of Well: Oil Well Gas Well Other Coalbed Methane			VPR A 8. Well Number 177
2. Name of Operator			
EL PASO ENERGY RATON, L.L.C.			9. OGRID Number 180514
3. Address of Operator			10. Pool name or Wildcat
PO BOX 190, RATON, NM 87740			Stubblefield Canyon – Vermejo Gas
4. Well Location			
Unit Letter A: 1146 feet from the North line and 989 feet from the East line			
Section 5 Township 31N Range 21E NMPM Colfax County			
	11. Elevation (Show whether DR,		
Pit or Below-grade Tank Application  or 0	7980' (GL)		China Carlotta Carlot
Pit typeDepth to GroundwaterDistance from nearest fresh water well Distance from nearest surface water			
Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF INT	ENTION TO:	SUBS	SEQUENT REPORT OF:
<del></del>	PLUG AND ABANDON	REMEDIAL WORK	
TEMPORARILY ABANDON		<del>-</del>	
PULL OR ALTER CASING	MULTIPLE COMPL	CASING/CEMENT	JOB
OTHER:		OTHER:	Completion 🖂
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date			
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion			
or recompletion.			
or recompletion.			
-	t Bond Log. TOC at surface.		
08/20/04 Patterson ran Acoustic Cement 08/26/04 Patterson perf'd 1st stage -	2057'- 2064' 28 Holes		
08/20/04 Patterson ran Acoustic Cement 08/26/04 Patterson perf'd 1 <sup>st</sup> stage - HES frac'd 1 <sup>st</sup> stage - Pumped	2057'- 2064' 28 Holes  Delta Frac fluid at 19.5 bpm with 38		sand, ATP 2705 psi, ISIP 2596 psi,
08/20/04 Patterson ran Acoustic Cement 08/26/04 Patterson perf'd 1 <sup>st</sup> stage - HES frac'd 1 <sup>st</sup> stage - Pumped Patterson perf'd 2 <sup>nd</sup> stage - HES frac'd 2 <sup>nd</sup> stage - Pumped	2057'- 2064' 28 Holes  Delta Frac fluid at 19.5 bpm with 38 1899'- 1901', 1988'- 1990', 1996'-  Delta Frac fluid at 16.9 bpm with 2	1998' 24 Holes 4,904 lbs of 16/30 br	ady sand, ATP 2483 psi, ISIP 406 psi.
08/20/04 Patterson ran Acoustic Cement 08/26/04 Patterson perf'd 1 <sup>st</sup> stage - HES frac'd 1 <sup>st</sup> stage - Pumped Patterson perf'd 2 <sup>nd</sup> stage - HES frac'd 2 <sup>nd</sup> stage - Pumped Patterson perf'd 3 <sup>rd</sup> stage -	2057'- 2064' 28 Holes  Delta Frac fluid at 19.5 bpm with 38 1899'- 1901', 1988'- 1990', 1996'-  Delta Frac fluid at 16.9 bpm with 2- 1276'- 1278', 1285'- 1288', 1327'-	1998' 24 Holes 4,904 lbs of 16/30 br 1330', 1336'- 1338'	ady sand, ATP 2483 psi, ISIP 406 psi. 40 Holes
08/20/04 Patterson ran Acoustic Cement 08/26/04 Patterson perf'd 1 <sup>st</sup> stage - HES frac'd 1 <sup>st</sup> stage - Pumped Patterson perf'd 2 <sup>nd</sup> stage - HES frac'd 2 <sup>nd</sup> stage - Pumped Patterson perf'd 3 <sup>rd</sup> stage - HES frac'd 3 <sup>rd</sup> stage - Pumped	2057'- 2064' 28 Holes Delta Frac fluid at 19.5 bpm with 38 1899'- 1901', 1988'- 1990', 1996'- Delta Frac fluid at 16.9 bpm with 2 1276'- 1278', 1285'- 1288', 1327'- Delta Frac fluid at 20.0 bpm with 40	1998' 24 Holes 4,904 lbs of 16/30 br 1330', 1336'- 1338' ,358 lbs of 16/30 brad	ady sand, ATP 2483 psi, ISIP 406 psi. 40 Holes
08/20/04 Patterson ran Acoustic Cement 08/26/04 Patterson perf'd 1 <sup>st</sup> stage - HES frac'd 1 <sup>st</sup> stage - Pumped Patterson perf'd 2 <sup>nd</sup> stage - HES frac'd 2 <sup>nd</sup> stage - Pumped Patterson perf'd 3 <sup>rd</sup> stage - HES frac'd 3 <sup>rd</sup> stage - Pumped Patterson perf'd 4 <sup>th</sup> stage - HES frac'd 4 <sup>th</sup> stage - Pumped	2057'- 2064' 28 Holes Delta Frac fluid at 19.5 bpm with 38 1899'- 1901', 1988'- 1990', 1996'- Delta Frac fluid at 16.9 bpm with 2- 1276'- 1278', 1285'- 1288', 1327'- Delta Frac fluid at 20.0 bpm with 40 1151'- 1154', 1192'- 1194' 20 Holes Frac fluid at 17.8 bpm with 32	1998' 24 Holes 4,904 lbs of 16/30 br 1330', 1336'- 1338' ,358 lbs of 16/30 brad oles ,478 lbs of 16/30 brad	ady sand, ATP 2483 psi, ISIP 406 psi. 40 Holes dy sand, ATP 972 psi, ISIP 700 psi.
08/20/04 Patterson ran Acoustic Cement 08/26/04 Patterson perf'd 1 <sup>st</sup> stage - HES frac'd 1 <sup>st</sup> stage - Pumped Patterson perf'd 2 <sup>nd</sup> stage - HES frac'd 2 <sup>nd</sup> stage - Pumped Patterson perf'd 3 <sup>rd</sup> stage - HES frac'd 3 <sup>rd</sup> stage - Pumped Patterson perf'd 4 <sup>th</sup> stage -	2057'- 2064' 28 Holes Delta Frac fluid at 19.5 bpm with 38 1899'- 1901', 1988'- 1990', 1996'- Delta Frac fluid at 16.9 bpm with 2- 1276'- 1278', 1285'- 1288', 1327'- Delta Frac fluid at 20.0 bpm with 40 1151'- 1154', 1192'- 1194' 20 Holes Frac fluid at 17.8 bpm with 32	1998' 24 Holes 4,904 lbs of 16/30 br 1330', 1336'- 1338' ,358 lbs of 16/30 brad oles ,478 lbs of 16/30 brad	ady sand, ATP 2483 psi, ISIP 406 psi. 40 Holes dy sand, ATP 972 psi, ISIP 700 psi.
08/20/04 Patterson ran Acoustic Cement 08/26/04 Patterson perf'd 1 <sup>st</sup> stage - HES frac'd 1 <sup>st</sup> stage - Pumped Patterson perf'd 2 <sup>nd</sup> stage - HES frac'd 2 <sup>nd</sup> stage - Pumped Patterson perf'd 3 <sup>rd</sup> stage - HES frac'd 3 <sup>rd</sup> stage - Pumped Patterson perf'd 4 <sup>th</sup> stage - HES frac'd 4 <sup>th</sup> stage - Pumped	2057'- 2064' 28 Holes Delta Frac fluid at 19.5 bpm with 38 1899'- 1901', 1988'- 1990', 1996'- Delta Frac fluid at 16.9 bpm with 2- 1276'- 1278', 1285'- 1288', 1327'- Delta Frac fluid at 20.0 bpm with 40 1151'- 1154', 1192'- 1194' 20 Holes Frac fluid at 17.8 bpm with 32	1998' 24 Holes 4,904 lbs of 16/30 br 1330', 1336'- 1338' ,358 lbs of 16/30 brad oles ,478 lbs of 16/30 brad	ady sand, ATP 2483 psi, ISIP 406 psi. 40 Holes dy sand, ATP 972 psi, ISIP 700 psi.
08/20/04 Patterson ran Acoustic Cement 08/26/04 Patterson perf'd 1 <sup>st</sup> stage - HES frac'd 1 <sup>st</sup> stage - Pumped Patterson perf'd 2 <sup>nd</sup> stage - HES frac'd 2 <sup>nd</sup> stage - Pumped Patterson perf'd 3 <sup>rd</sup> stage - HES frac'd 3 <sup>rd</sup> stage - Pumped Patterson perf'd 4 <sup>th</sup> stage - HES frac'd 4 <sup>th</sup> stage - Pumped	2057'- 2064' 28 Holes Delta Frac fluid at 19.5 bpm with 38 1899'- 1901', 1988'- 1990', 1996'- Delta Frac fluid at 16.9 bpm with 2- 1276'- 1278', 1285'- 1288', 1327'- Delta Frac fluid at 20.0 bpm with 40 1151'- 1154', 1192'- 1194' 20 Holes Frac fluid at 17.8 bpm with 32	1998' 24 Holes 4,904 lbs of 16/30 br 1330', 1336'- 1338' ,358 lbs of 16/30 brad oles ,478 lbs of 16/30 brad	ady sand, ATP 2483 psi, ISIP 406 psi. 40 Holes dy sand, ATP 972 psi, ISIP 700 psi.
08/20/04 Patterson ran Acoustic Cement 08/26/04 Patterson perf'd 1 <sup>st</sup> stage - HES frac'd 1 <sup>st</sup> stage - Pumped Patterson perf'd 2 <sup>nd</sup> stage - HES frac'd 2 <sup>nd</sup> stage - Pumped Patterson perf'd 3 <sup>rd</sup> stage - HES frac'd 3 <sup>rd</sup> stage - Pumped Patterson perf'd 4 <sup>th</sup> stage - HES frac'd 4 <sup>th</sup> stage - Pumped	2057'- 2064' 28 Holes Delta Frac fluid at 19.5 bpm with 38 1899'- 1901', 1988'- 1990', 1996'- Delta Frac fluid at 16.9 bpm with 2- 1276'- 1278', 1285'- 1288', 1327'- Delta Frac fluid at 20.0 bpm with 40 1151'- 1154', 1192'- 1194' 20 Holes Frac fluid at 17.8 bpm with 32	1998' 24 Holes 4,904 lbs of 16/30 br 1330', 1336'- 1338' ,358 lbs of 16/30 brad oles ,478 lbs of 16/30 brad	ady sand, ATP 2483 psi, ISIP 406 psi. 40 Holes dy sand, ATP 972 psi, ISIP 700 psi.
08/20/04 Patterson ran Acoustic Cement 08/26/04 Patterson perf'd 1st stage - HES frac'd 1st stage - Pumped Patterson perf'd 2nd stage - HES frac'd 2nd stage - Pumped Patterson perf'd 3rd stage - HES frac'd 3rd stage - HES frac'd 3rd stage - Pumped Patterson perf'd 4th stage - HES frac'd 4th stage - HES frac'd 4th stage - Pumped 08/29/04 RIH tubing, rods and pump.	2057'- 2064' 28 Holes Delta Frac fluid at 19.5 bpm with 38 1899'- 1901', 1988'- 1990', 1996'- Delta Frac fluid at 16.9 bpm with 2- 1276'- 1278', 1285'- 1288', 1327'- Delta Frac fluid at 20.0 bpm with 40 1151'- 1154', 1192'- 1194' 20 H Delta Frac fluid at 17.8 bpm with 32 Well is ready to be tested and pu	1998' 24 Holes 4,904 lbs of 16/30 br 1330', 1336'- 1338' ,358 lbs of 16/30 brac oles ,478 lbs of 16/30 brad t on production.	ady sand, ATP 2483 psi, ISIP 406 psi. 40 Holes dy sand, ATP 972 psi, ISIP 700 psi. y sand, ATP 876 psi, ISIP 316 psi.
08/20/04 Patterson ran Acoustic Cement 08/26/04 Patterson perf'd 1st stage - HES frac'd 1st stage - Pumped Patterson perf'd 2nd stage - HES frac'd 2nd stage - Pumped Patterson perf'd 3rd stage - HES frac'd 3rd stage - HES frac'd 3rd stage - Pumped Patterson perf'd 4th stage - HES frac'd 4th stage - Pumped Patterson perf'd 4th stage - Pumped 08/29/04 RIH tubing, rods and pump.	2057'- 2064' 28 Holes Delta Frac fluid at 19.5 bpm with 38 1899'- 1901', 1988'- 1990', 1996'- Delta Frac fluid at 16.9 bpm with 2- 1276'- 1278', 1285'- 1288', 1327'- Delta Frac fluid at 20.0 bpm with 40 1151'- 1154', 1192'- 1194' 20 H I Delta Frac fluid at 17.8 bpm with 32 Well is ready to be tested and pure over is true and complete to the beserver.	1998' 24 Holes 4,904 lbs of 16/30 br 1330', 1336'- 1338' ,358 lbs of 16/30 brad oles ,478 lbs of 16/30 brad t on production.	ady sand, ATP 2483 psi, ISIP 406 psi. 40 Holes dy sand, ATP 972 psi, ISIP 700 psi.
08/20/04 Patterson ran Acoustic Cement 08/26/04 Patterson perf'd 1st stage - HES frac'd 1st stage - Pumped Patterson perf'd 2nd stage - HES frac'd 2nd stage - Pumped Patterson perf'd 3rd stage - HES frac'd 3rd stage - HES frac'd 3rd stage - Pumped Patterson perf'd 4th stage - HES frac'd 4th stage - Pumped 08/29/04 RIH tubing, rods and pump.	2057'- 2064' 28 Holes Delta Frac fluid at 19.5 bpm with 38 1899'- 1901', 1988'- 1990', 1996'- Delta Frac fluid at 16.9 bpm with 2- 1276'- 1278', 1285'- 1288', 1327'- Delta Frac fluid at 20.0 bpm with 40 1151'- 1154', 1192'- 1194' 20 H  Delta Frac fluid at 17.8 bpm with 32 Well is ready to be tested and pure over is true and complete to the best osed according to NMOCD guidelines	1998' 24 Holes 4,904 lbs of 16/30 br 1330', 1336'- 1338' ,358 lbs of 16/30 brace oles ,478 lbs of 16/30 brace t on production.  st of my knowledge  , a general permit □ o	ady sand, ATP 2483 psi, ISIP 406 psi. 40 Holes dy sand, ATP 972 psi, ISIP 700 psi.  y sand, ATP 876 psi, ISIP 316 psi.  and belief. I further certify that any pit or belowran (attached) alternative OCD-approved plan .
08/20/04 Patterson ran Acoustic Cement 08/26/04 Patterson perf'd 1st stage - HES frac'd 1st stage - Pumped Patterson perf'd 2nd stage - HES frac'd 2nd stage - Pumped Patterson perf'd 3rd stage - HES frac'd 3rd stage - HES frac'd 3rd stage - Pumped Patterson perf'd 4th stage - HES frac'd 4th stage - Pumped Patterson perf'd 4th stage - Pumped 08/29/04 RIH tubing, rods and pump.	2057'- 2064' 28 Holes Delta Frac fluid at 19.5 bpm with 38 1899'- 1901', 1988'- 1990', 1996'- Delta Frac fluid at 16.9 bpm with 2- 1276'- 1278', 1285'- 1288', 1327'- Delta Frac fluid at 20.0 bpm with 40 1151'- 1154', 1192'- 1194' 20 H I Delta Frac fluid at 17.8 bpm with 32 Well is ready to be tested and pure over is true and complete to the beserver.	1998' 24 Holes 4,904 lbs of 16/30 br 1330', 1336'- 1338' ,358 lbs of 16/30 brad oles ,478 lbs of 16/30 brad t on production.	ady sand, ATP 2483 psi, ISIP 406 psi. 40 Holes dy sand, ATP 972 psi, ISIP 700 psi.  y sand, ATP 876 psi, ISIP 316 psi.  and belief. I further certify that any pit or belowran (attached) alternative OCD-approved plan .
08/20/04 Patterson ran Acoustic Cement 08/26/04 Patterson perf'd 1st stage - HES frac'd 1st stage - Pumped Patterson perf'd 2nd stage - HES frac'd 2nd stage - Pumped Patterson perf'd 3rd stage - HES frac'd 3rd stage - Pumped Patterson perf'd 4th stage - Pumped Patterson perf'd 4th stage - Pumped 08/29/04 RIH tubing, rods and pump.  I hereby certify that the information ab grade tank has been/will be constructed or close SIGNATURE Sharley A Mitch	2057'- 2064' 28 Holes Delta Frac fluid at 19.5 bpm with 38 1899'- 1901', 1988'- 1990', 1996'- Delta Frac fluid at 16.9 bpm with 2- 1276'- 1278', 1285'- 1288', 1327'- Delta Frac fluid at 20.0 bpm with 40 1151'- 1154', 1192'- 1194' 20 H Delta Frac fluid at 17.8 bpm with 32 Well is ready to be tested and pure solutions of the best	1998' 24 Holes 4,904 lbs of 16/30 br 1330', 1336'- 1338' ,358 lbs of 16/30 brad oles ,478 lbs of 16/30 brad t on production.  st of my knowledge  , a general permit □ o	ady sand, ATP 2483 psi, ISIP 406 psi.  40 Holes dy sand, ATP 972 psi, ISIP 700 psi.  y sand, ATP 876 psi, ISIP 316 psi.  and belief. I further certify that any pit or belowran (attached) alternative OCD-approved plan .  DATE 09/20/04
08/20/04 Patterson ran Acoustic Cement 08/26/04 Patterson perf'd 1st stage - HES frac'd 1st stage - Pumped Patterson perf'd 2nd stage - HES frac'd 2nd stage - Pumped Patterson perf'd 3rd stage - HES frac'd 3rd stage - HES frac'd 3rd stage - Pumped Patterson perf'd 4th stage - HES frac'd 4th stage - Pumped 08/29/04 RIH tubing, rods and pump.	2057'- 2064' 28 Holes Delta Frac fluid at 19.5 bpm with 38 1899'- 1901', 1988'- 1990', 1996'- Delta Frac fluid at 16.9 bpm with 2- 1276'- 1278', 1285'- 1288', 1327'- Delta Frac fluid at 20.0 bpm with 40 1151'- 1154', 1192'- 1194' 20 H. I Delta Frac fluid at 17.8 bpm with 32. Well is ready to be tested and pure over is true and complete to the besosed according to NMOCD guidelines.	1998' 24 Holes 4,904 lbs of 16/30 br 1330', 1336'- 1338' ,358 lbs of 16/30 brad oles ,478 lbs of 16/30 brad t on production.  st of my knowledge  , a general permit □ o	ady sand, ATP 2483 psi, ISIP 406 psi.  40 Holes dy sand, ATP 972 psi, ISIP 700 psi.  y sand, ATP 876 psi, ISIP 316 psi.  and belief. I further certify that any pit or belowran (attached) alternative OCD-approved plan .  DATE 09/20/04
08/20/04 Patterson ran Acoustic Cement 08/26/04 Patterson perf'd 1st stage - HES frac'd 1st stage - Pumped Patterson perf'd 2nd stage - HES frac'd 2nd stage - Pumped Patterson perf'd 3rd stage - HES frac'd 3rd stage - Pumped Patterson perf'd 4th stage - HES frac'd 4th stage - HES frac'd 4th stage - Pumped 08/29/04 RIH tubing, rods and pump.  I hereby certify that the information ab grade tank has been/will be constructed or cle SIGNATURE Subject Mich.  Type or print name Shirley A Mitch.  For State Use Only	2057'- 2064' 28 Holes Delta Frac fluid at 19.5 bpm with 38 1899'- 1901', 1988'- 1990', 1996'- Delta Frac fluid at 16.9 bpm with 2- 1276'- 1278', 1285'- 1288', 1327'- Delta Frac fluid at 20.0 bpm with 40 1151'- 1154', 1192'- 1194' 20 H I Delta Frac fluid at 17.8 bpm with 32. Well is ready to be tested and pure bove is true and complete to the best osed according to NMOCD guidelines  E-mail address: Shirley	1998' 24 Holes 4,904 lbs of 16/30 br 1330', 1336'- 1338' ,358 lbs of 16/30 brace oles ,478 lbs of 16/30 brace t on production.  st of my knowledge  , a general permit □ o   Regulatory Ar	ady sand, ATP 2483 psi, ISIP 406 psi.  40 Holes dy sand, ATP 972 psi, ISIP 700 psi.  y sand, ATP 876 psi, ISIP 316 psi.  and belief. I further certify that any pit or below- r an (attached) alternative OCD-approved plan   DATE 09/20/04  om Telephone No. (505) 445-6785
08/20/04 Patterson ran Acoustic Cement 08/26/04 Patterson perf'd 1st stage - HES frac'd 1st stage - Pumped Patterson perf'd 2nd stage - HES frac'd 2nd stage - Pumped Patterson perf'd 3rd stage - HES frac'd 3rd stage - Pumped Patterson perf'd 4th stage - Pumped Patterson perf'd 4th stage - Pumped 08/29/04 RIH tubing, rods and pump.  I hereby certify that the information ab grade tank has been/will be constructed or close SIGNATURE Sharley A Mitch	2057'- 2064' 28 Holes Delta Frac fluid at 19.5 bpm with 38 1899'- 1901', 1988'- 1990', 1996'- Delta Frac fluid at 16.9 bpm with 2- 1276'- 1278', 1285'- 1288', 1327'- Delta Frac fluid at 20.0 bpm with 40 1151'- 1154', 1192'- 1194' 20 H I Delta Frac fluid at 17.8 bpm with 32. Well is ready to be tested and pure bove is true and complete to the best osed according to NMOCD guidelines  E-mail address: Shirley	1998' 24 Holes 4,904 lbs of 16/30 br 1330', 1336'- 1338' ,358 lbs of 16/30 brad oles ,478 lbs of 16/30 brad t on production.  st of my knowledge  , a general permit □ o	ady sand, ATP 2483 psi, ISIP 406 psi.  40 Holes dy sand, ATP 972 psi, ISIP 700 psi.  y sand, ATP 876 psi, ISIP 316 psi.  and belief. I further certify that any pit or below- r an (attached) alternative OCD-approved plan   DATE 09/20/04  om Telephone No. (505) 445-6785