

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-007-20206
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Coalbed Methane		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator EL PASO ENERGY RATON, L.L.C.		6. State Oil & Gas Lease No.
3. Address of Operator PO BOX 190 RATON, NM 87740		7. Lease Name or Unit Agreement Name: VPR A
4. Well Location Unit Letter P : 646' feet from the South line and 1151' feet from the East line Section 23 Township 32N Range 20E NMPM Colfax County		8. Well No. 56
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 7674' (GR)		9. Pool name or Wildcat

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Work Performed 4/16/02 thru 4/19/02 for P & A:

- 1) Fished tubing and rods from well.
RIH open-ended with 2 7/8" tubing. Spot balanced cement plug 1825'-1995'. SION.
- 2) Tag cement plug at 1700'. RU wireline. Perforated squeeze holes @ 1580'.
TIH and set cement retainer @ 1520'. Attempt to fill annulus. Would not test. Apparent casing leak
Above 1520'. Mixed and pumped 182 sx. Cement below retainer. Stung out and left 70 sx. Cement above retainer.
SION.
- 3) Tagged TOC @ 1380'. Attempt to fill casing. POOH with 2 7/8" tubing.
- 4) Tie on to 5 1/2" casing. Mix and pump 525 sx. (23.5 bbls) 13 ppg. Cement down casing. Pressure to 500 psi.
- 5) Cut off casing below ground level. Welded on 1/2" plate cap. Welded dry hole marker on cap inscribed:
- 6) El Paso, VPRA56, 646'FSL, 1151'FEL, Sec. 23-32N-20E

API No. 30-007-20206

OK
5/20/02
REJ

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Donald R. Lankford TITLE Engineer DATE 04/22/02

Type or print name Donald R. Lankford Telephone No. (505) 445-6721

(This space for State use)

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 5/20/02

Conditions of approval, if any: