Submit 3 Copies To Appropriate District	State of New Mexico			Form C-103
Office District 1	Energy, Minerals and Natural Resources		WELL LEVIL	Revised March 25, 1999
1625 N. French Dr., Hobbs, NM 87240			WELL API NO.	20.007.20506
District II 811 South First, Artesia, NM 87210	OIL CONSERVATION DIVISION		5. Indicate Type	30-007-20596
District III	1220 South St. Frances		STATE	FEE I
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505			Gas Lease No.
1220 South St. Frances, Santa Fe, NM			o. State Off &	das Lease No.
87505 SLINDRY NO	TICES AND REPORTS ON WELLS		7 Lease Name (	or Unit Agreement Name:
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A.		7. Bouse Hume (	on one Agreement Name.	
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			VPR B	
1. Type of Well:				, 11(1)
Oil Well Gas Well	Other X Coalbed Methane			
2. Name of Operator			8. Well No.	85
	ENERGY RATON, L.L.C.			
3. Address of Operator	400 D / NIE 05540		9. Pool name or	Wildcat
4. Well Location	190, Raton, NM 87740	<u></u>		<u></u>
4. Well Location				
Unit Letter M: 1187 feet from the South line and 549 feet from the West line				
Section 22 Tow	nship 30N Range 18E	NMPM		County
	10. Elevation (Show whether Di		.)	
11 Charles	8,222' Appropriate Box to Indicate Na	GL)	Compart on Other	· Dot-
	NTENTION TO:	1	_	
PERFORM REMEDIAL WORK		REMEDIAL WORK	SEQUENT RE	EPURT OF: ALTERING CASING
TENTONIA NEWIEDIAE WORK E	I TEOCAND ABANDON	NEMILDIAL WORK	`	ALTERING CASING L
TEMPORARILY ABANDON	☐ CHANGE PLANS ☐	COMMENCE DRII	LING OPNS. 🌉	PLUG AND
PULL OR ALTER CASING	☐ MULTIPLE ☐	CASING TEST AN	ın 🗆	ABANDONMENT —
FULL OR ALTER CASING	COMPLETION	CEMENT JOB		
OTHER.				
OTHER:		OTHER:		
12. Describe proposed or completed operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.				
·				
03/04/05 Spud @ 6:30 p.m. Drill 11" surface hole to 325'. Run 7 jts. of 8 5/8", 24#, J55 ST&C casing to 315'.				
Halliburton mixed and pumped 100 sks Midcon II PP, 14 ppg, yield 1.66 at 4 bpm with 100 psi with 6% salt, 5#/sx gilsonite, .3% versaset and .25 #/sk flocele. Circulate 6 bbls of cement to surface. WOC 8 hrs.				
Test surface 8 5/8" csg to 500 psi for 30 minutes.				
03/05/05 Drill 7 7/8" hole from 325' - 2,635'. Reached TD 2,635' at 10:30 p.m.				
MIRU Patterson & log well. Logger's TD at 2,606'. Ran 62 jts of 5 ½", 15.5#, J55 LT&C casing at 2,565'.				
MIRU Halliburton. Pumped 332 sks Midcon II PP, 13 ppg, Yield 2.04 at 4 bpm.				
Plug down with 11	15 psi. Float held. Circulated 13 bl	bls of cement to surf	ace. Well shut in	l.
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE Shully Metchell TITLE Regulatory Analyst DATE03/18/05				
3.00.00	7.000	regulator, rinary.	<u></u> _D/116	03/10/03
Type or print name Shirle	y A Mitchell	Telephone No.	(505) 445-6785	
(This space for State use)	~ N			
APPPROVED BY	C Hoffer TITLE C	ISTRICT SU	PERVISOR	DATE 3/24/05
Conditions of approval, if any	IIILE •			DATE