

District I  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(505) 393-6161 Fax:(505) 393-0720

District II  
1301 W. Grand Ave., Artesia, NM 88210  
Phone:(505) 748-1283 Fax:(505) 748-9720

District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170

District IV  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
Energy, Minerals and Natural Resources

Form C-103  
Permit 68596

**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

WELL API NUMBER  
30-025-38642

5. Indicate Type of Lease  
S

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name  
SILVER OAK

8. Well Number  
001

9. OGRID Number  
237788

10. Poolname or Wildcat

**SUNDRY NOTICES AND REPORTS ON WELLS**

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFRENT RESERVIOR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:O

2. Name of Operator  
PLANTATION OPERATING LLC

3. Address of Operator  
4700 W. SAM HOUSTON PKWY N. , , SUITE 140 HOUSTON , TX 77041

4. Well Location  
Unit Letter 2 : 660 feet from the N line and 1980 feet from the E line  
Section 6 Township 19S Range 35E NMPM Lea County

11. Elevation (Show whether DR, KB, BT, GR, etc.)  
3938 GR

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit Type \_\_\_\_\_ Depth to Groundwater \_\_\_\_\_ Distance from nearest fresh water well \_\_\_\_\_ Distance from nearest surface water \_\_\_\_\_

Pit Liner Thickness: \_\_\_\_\_ mil Below-Grade Tank: Volume \_\_\_\_\_ bbls; Construction Material \_\_\_\_\_

**12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data**

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE OF PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

Other:

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐ ALTER CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDON ☐

CASING/CEMENT JOB ☐

Other: **Drilling/Cement** ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1/17/2008 - 1/23/2008: Drill 11" hole to TD 3450'. Called Chris Williams at the NMOCD--Hobbs, NM to request that our 8 5/8" 32#/ft casing be set at a shallower depth. Received verbal approval at 0920 hrs 1/21/08. TD 11" hole 1200 hrs 1/21/08 at 3450'. Run 81 jnts, 3454', 8-5/8" 32# J55 LT&C csg. Set float shoe at 3450', Float Collar at 3411'. Cement 8 5/8" casing w/ 900 sx BJ Lite (35.65:6) + 1/4# Celloflake + 5# Salt Yield--1.88 cu ft, Wt--12.8#/gal. Continued - See attached.

See Attached

**1/15/2008** Spudded well.

**Casing and Cement Program**

| Date     | String | Fluid Type | Hole Size | Csg Size | Weight lb/ft | Grade | Est TOC | Dpth Set | Sacks | Yield | Class   | 1" Dpth | Pres Held | Pres Drop | Open Hole |
|----------|--------|------------|-----------|----------|--------------|-------|---------|----------|-------|-------|---------|---------|-----------|-----------|-----------|
| 01/16/08 | Surf   | FreshWater | 17.5      | 13.375   | 48           | H-40  | 0       | 425      | 440   | 1.34  | C       |         | 600       | 0         | Y         |
| 01/21/08 | Int1   | Brine      | 11        | 8.625    | 32           | J55   | 0       | 3450     | 900   | 1.88  | BJ Lite |         | 3000      | 0         | Y         |
| 01/21/08 | Int1   | Brine      | 11        | 8.625    | 32           | J55   | 0       | 3450     | 200   | 1.34  | C       |         | 3000      | 0         | Y         |

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐ , a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Electronically Signed

TITLE Engineering Tech

DATE 2/7/2008

Type or print name Kimberly K Faldyn

E-mail address kfaldyn@plantationpetro.com

Telephone No. 281-598-7551

**For State Use Only:**

APPROVED BY: Paul Kautz

TITLE Geologist

DATE 2/8/2008 11:45:27 AM

Silver Oak #1 – Intermediate Csg Work Description  
Continued:

Tail w/ 200 sx Class "C" + 1% CaCl<sub>2</sub> (Yield--1.34 cu ft, Wt--14.8#/gal). Plug down at 0815 hrs, CST, 1/22/2008. Circ 215 sx to the surface. Notified NMOCD--Hobbs of running csg. WOC 35 hrs. NU 13-5/8" 10M BOP. Test BOP to 3000 psi—OK. TIH and tag at 2944'. Drill cmt, float and shoe. Test 8-5/8" csg to 1500 psi for 30 min – OK. Drill out at 1900 hrs on 1/23/2008.