<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240

Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170 <u>District IV</u>

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 State of New Mexico

Energy, Minerals and Natural Resources

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505 Form C-101 August 1, 2011

Permit 134875

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

1. Operator DEVON ENERGY PRO	OGRID Number 6137		
20 N Broadway Oklahoma City, OK 73102		3. API Number 30-015-39373	
4. Property Code	5. Property Name	6. Wett No.	
38568	ONYX PWU 29	003H	

7. Surface Location

							2.0		
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
L	29	198	29E	L	2145	S	330	W	EDDY

8. Pool Information

*	
SCANLON DRAW;BONE SPRING	55510

Additional Well Information

		Additional Well Infolia	Intion	39
9. Work Type New Well	10. Weti Type OIL	11. Cable/Rotary	12. Lease Type State	13. Ground Level Elevation 3305
14. Multiple	15. Proposed Depth	16. Formation	17. Contractor	18. Spud Date
N	12206	Bone Spring		9/15/2011
Depth to Ground	water	Distance from nearest fresh water	r well	Distance to nearest surface water

19. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	300	500	0
Int1	12.25	9.625	40	3000	1050	0
Prod	8.75	5.5	17	12206	400	2500
Prod	8.75	5.5	17	7100	2300	0

Casing/Cement Program: Additional Comments

13 3/8 w/500 sx C1 C + 2% CaC1 + 1/4 tb/sx Cello flake, 9 5/8 w/1050 sx C1 C + 2% CaC1 + 1/4 tb/sx Cello flake, 5 1/2 w/2700 sx C1 C + 2% CaC1 + 1/4 tb/sx Cello flake, 5 1/2 w/2700 sx C1 C + 2% CaC1 + 1/4 tb/sx Cello flake, DV tool 2 4500′. An 8-3/4″ pilot hole will be drilled to 8,160-ft and plugged back to KOP with approx 250 sxs, Class H, 15.6 ppg, 1.18 cf/sk cement. The pilot hole will be cemented from the pilot hole TD to the KOP. Actual cement volumes will be adjusted based on fluid caliper and caliper log data. Mud: 0-300′ fresh, 8.4-9.0, 30-34 visc, N/C water loss. 300-3000′ brine, 9.8-10.0, 28-32 visc, N/C water loss. 300-12206′ fresh, 8.6-9.0, 28-32 visc, N/C-12 water loss.

Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
Annular	5000	5000	
Pipe	5000	5000	
DoubleRam	5000	5000	

of my knowledge and belief.	ation given above is true and complete to the best lling pit will be constructed according to	OIL CONSERVATION DIVISION			
	meral permit , or an (attached) alternative	Approved By: Randy Dade			
Printed Name: Electronic	cally filed by Randy Bolles	Title: District Supervisor			
Title: Manager, Regulato	ry Affairs	Approved Date: 9/1/2011	Expiration Date: 9/1/2013		
Email Address: randy.bo	illes@dvn.com		920 593		
Date: 8/31/2011	Phone: 405-228-8588	Conditions of Approval Attached			

District I 1625 N. French Dr., Hobbs, NM 88240

Phone:(575) 393-6161 Fax:(575) 393-0720 <u>District II</u>

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

<u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 <u>District IV</u>

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 State of New Mexico

Energy, Minerals and Natural Resources

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505 Form C-102 August 1, 2011

Permit 134875

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number	2. Pool Code		ol Name
30-015-39373	55510		W;BONE SPRING
4. Property Code	5. Property Name		6. Well No.
38568	ONYX PWU 29		003H
7. OGRID No. 6137	8. Operator Name DEVON ENERGY PRODUCTION COMPANY, LP		9. Elevation 3305


10. Surface Location

	UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
1	L	29	198	29E		2145	S	330	W	EDDY

11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
I	29	198	29E	I	2145	S	330	E	EDDY
12. Dedicated Acres 160.00		13. J	oint or Infill	14	. Consolidation	Code		15. Order No.	

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 8/31/2011

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Filimon Jaramillo Date of Survey: 7/6/2011 Certificate Number: 12797

Permit Comments

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: ONYX PWU 29 #003H

API: 30-015-39373

Created By	Comment	Comment Date
YSASAS	No H2S is expected to be encountered.	7/21/2011
YSASAS	C-102 & C-144 CLEZ to be mailed next day via Fed-Ex.	7/21/2011
YSASAS	Depth to groundwater is 50' or more, but less than 100', distance to surface water is approximately 1000'; well is not in a wellhead protection area.	7/21/2011
YSASAS	NOI to withdraw permit submitted to NMOCD on 08/23/2011 to withdraw Onyx PWU 29 Federal 3H permit for geological reasons - API # 30-015-38661; Sec 29-T19S-R29E, SL: 330' FNL & 1700' FEL, BHL: 330' FSL & 1700' FEL. Sundry not yet approved. Subsequent location staked 07/08/2011 to replace initial location staked 11/16/2011.	7/21/2011
YSASAS	The BOP system used to drill the intermediate hole will consist of a 13-5/8" 3M Triple Ram and Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order No. 2 as a 3M system prior to drilling out the surface casing shoe. The BOP system used to drill the production hole will consist of a 13-5/8" 3M Triple Ram and Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order No. 2 as a 3M system prior to drilling out the intermediate casing shoe. The pipe rams will be operated and checked as per Onshore Order No 2. A 2" kill line and 3" chok	
YSASAS	BOP CONT: choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP.	8/29/2011
Artesia	Land S/S	9/1/2011

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137

Well: ONYX PWU 29 #003H

API: 30-015-39373

OCD Reviewer	Condition
Artesia	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string