

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

Form C-101
August 1, 2011
Permit 143864

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

1. Operator Name and Address DEVON ENERGY PRODUCTION COMPANY, LP 20 N Broadway Oklahoma City, OK 73102		2. OGRID Number 6137
		3. API Number 30-015-40025
4. Property Code 39110	5. Property Name LONGBOARD PWU 20	6. Well No. 002H

7. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
E	20	19S	29E	E	1675	N	330	W	EDDY

8. Pool Information

PARKWAY;WOLFCAMP	49637
------------------	-------

Additional Well Information

9. Work Type New Well	10. Well Type OIL	11. Cable/Rotary	12. Lease Type State	13. Ground Level Elevation 3340
14. Multiple N	15. Proposed Depth 13560	16. Formation Wolfcamp	17. Contractor	18. Spud Date 3/1/2012
Depth to Ground water		Distance from nearest fresh water well		Distance to nearest surface water

19. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	300	335	0
Int1	12.25	9.625	40	2700	1135	0
Prod	8.75	5.5	17	7100	1545	0
Prod	8.75	5.5	17	13560	1175	2200

Casing/Cement Program: Additional Comments

13 3/8 w/335 sx C1 C + 2% CaCl + 1/4 lb/sx Cello flake, 9 5/8 w/2700 sx C1 C + 2% CaCl + 1/4 lb/sx Cello flake, 5 1/2 w/2720 sx C1 C + 2% CaCl + 1/4 lb/sx Cello flake. An 8 3/4" pilot hole will be drilled to 10,286' and plugged back to KOP with approximately 575 sxs of Class H, 15.6 pgg, 1.18 cf/sk cement. All cement volumes based on at least 25% excesses. Actual cement volumes will be adjusted based on fluid caliper and caliper log data. Mud: 0-300' fresh, 8.4-9.0, 30-34 visc, N/C water loss. 300-2700' brine, 9.8-10.0, 28-32 visc, N/C water loss. 2700-13560' fresh, 8.6-9.0, 28-32 visc, N/C-12 water loss.

Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
Annular	3000	3000	
Pipe	3000	3000	
DoubleRam	3000	3000	

I hereby certify that the information given above is true and complete to the best of my knowledge and belief. I further certify that the drilling pit will be constructed according to NMOCD guidelines <input type="checkbox"/> , a general permit <input type="checkbox"/> , or an (attached) alternative OCD-approved plan <input type="checkbox"/> .	OIL CONSERVATION DIVISION	
Printed Name: Electronically filed by Randy Bolles	Approved By: Randy Dade	
Title: Manager, Regulatory Affairs	Title: District Supervisor	
Email Address: randy.bolles@dmn.com	Approved Date: 3/8/2012	Expiration Date: 3/8/2014
Date: 3/6/2012	Phone: 405-228-8588	Conditions of Approval Attached

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

Form C-102
August 1, 2011
Permit 143864

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number 30-015-40025	2. Pool Code 49637	3. Pool Name PARKWAY;WOLFCAMP
4. Property Code 39110	5. Property Name LONGBORD PWU 20	6. Well No. 002H
7. OGRID No. 6137	8. Operator Name DEVON ENERGY PRODUCTION COMPANY, LP	9. Elevation 3340



10. Surface Location

UL - Lot E	Section 20	Township 19S	Range 29E	Lot Idn	Feet From 1675	N/S Line N	Feet From 330	E/W Line W	County EDDY
---------------	---------------	-----------------	--------------	---------	-------------------	---------------	------------------	---------------	----------------

11. Bottom Hole Location If Different From Surface

11. Bottom Hole Location is Different From Surface									
UL - Lot H	Section 20	Township 19S	Range 29E	Lot Idn H	Feet From 1850	N/S Line N	Feet From 660	E/W Line E	County EDDY
12. Dedicated Acres 160.00		13. Joint or Infill		14. Consolidation Code			15. Order No.		

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles
Title: Manager, Regulatory Affairs
Date: 3/6/2012

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Filimon Jaramillo
Date of Survey: 1/26/2012
Certificate Number: 12797

Permit Comments

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137

Well: LONGBOARD PWU 20 #002H

API: 30-015-40025

Created By	Comment	Comment Date
YSASAS	No H2S is expected to be encountered.	3/3/2012
YSASAS	C-102 to be mailed via Fed-Ex next day.	3/3/2012
YSASAS	Depth to groundwater is 50' or more, but less than 100', distance to surface water is approximately 1000'; well is not in wellhead protection area.	3/3/2012
YSASAS	The BOP system used to drill the intermediate hole will consist of a 13-5/8" 3M Triple Ram and Annular preventer. The BOP system will be tested as a 3M system prior to drilling out the surface casing shoe. The BOP system used to drill the production hole will consist of a 13-5/8" 3M Triple Ram and Annular preventer. The BOP system will be tested as a 3M system prior to drilling out the intermediate casing shoe. In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP.	3/6/2012
CSHAPARD	Land s/S	3/8/2012

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137

Well: LONGBOARD PWU 20 #002H

API: 30-015-40025

OCD Reviewer	Condition
CSHAPARD	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string