District I 1625 N. French Dr., Hobbs, NM 88240

Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 State of New Mexico

Energy, Minerals and Natural Resources

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505 Form C-101 August 1, 2011

Permit 143387

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

1. Oper DEVON ENERGY I	OGRID Number 6137			
2 Oklaho	3. API Number 30-015-40107			
4. Property Code	5. Property Name	6. Well No.		
39132	BIG ARISTOTLE 27 STATE			

7. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
A	34	218	31E	A	660	N	690	E	EDDY

8. Pool Information

LOST TANK:DELAWARE	40299

Additional Well Information

9. Work Type New Well	10. We		11. Cable/Rotary	12. Lease Type State	13. Ground Level Elevation 3492
14. Multiple 15. Proposed Depth N 13317		16. Formation Delaware	17. Contractor	18. Spud Date	
Depth to Ground	water		Distance from nearest fresh water	r well	Distance to nearest surface water

19. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	650	950	0
Int1	12.25	9.625	40	4150	1300	0
Prod	8.75	5.5	17	13317	950	0
Prod	8.75	5.5	17	7200	2265	3650

Casing/Cement Program: Additional Comments

Surface Lead w/700 sx C1 C + 2% bwoc Calcium Chloride + 0.125 lbs/sack CF + 4% bwoc Bentonite + 81.4% FW, 13.5 ppg, 1.75 cf/sk. Tail w/250 sx C1 C + 2% bwoc Calcium Chloride + 0.125 lbs/sack CF + 56.3% FW, 14.8 ppg, 1.35 cf/sk.Intermediate lead w/1,000 sx(60:40) Poz (Fly Ash):C1 C + 5% bwow Sodium Chloride + 0.125 lbs/sack CF + 6% bwoc Bentonite + 107.8% FW, 12.5 ppg, 1.73 cf/sk. Tail w/300 sx (60:40) Poz C1 C + 5% bwow Sodium Chloride + 0.125 lbs/sack CF + 0.4% bwoc Sodium Metasilicate + 4% bwoc MPA-5 + 52.7% Wtr, 14.8 ppg, 1.38 cf/sk. Production 1st stage: Lead w/755 sx 35:65 Poz (Fly Ash):C1 H + 5% bwow Sodium Chloride + 0.3% bwoc CD-32 + 0.5% bwoc FL-25 + 2% bwoc Bentonite + 0.6% bwoc Sodium Metasilicate + 0.5% bwoc FL-52A + 102.5% FW, 12.5 ppg, 2.00 cf/sk. Tail w/1510 sx (50:50) Poz (Fly Ash):C1 H + 1% bwow Sodium Chloride + 0.2% bwoc R-3 + 0.125 lbs/sack CF + 0.5% bwoc BA-10A + 4% bwoc MPA-5 + 58.3% FW, 14.2 ppg, 1.28 cf/sk. Second Stage DV tool @ 5500': Lead w/800 sx C1 C + 1%

Proposed Blowout Prevention Program

T	ype	Working Pressure	Test Pressure	Manufacturer
An	nular	3000	3000	
Dout	hleRam	3000	3000	

of my knowledge and belief.	iven above is true and complete to the best it will be constructed according to	OIL CONSERVATION DIVISION			
NMOCD guidelines , a general p OCD-approved plan .	permit , or an (attached) alternative	Approved By: Randy Dade			
Printed Name: Electronically f	iled by Randy Bolles	Title: District Supervisor			
Title: Manager, Regulatory At	fairs	Approved Date: 3/27/2012	Expiration Date: 3/27/2014		
Email Address: randy.bolles@	dvn.com				
Date: 3/22/2012	Phone: 405-228-8588	Conditions of Approval Atta	ched		

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II 811 S. First St., Artesia, NM 88210

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico

Energy, Minerals and Natural Resources

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505 Form C-102 August 1, 2011

Permit 143387

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number 30-015-40107	2. Pool Code 3. Pool 40299 LOST TANK		;DELAWARE
4. Property Code 39132	5. Property Name BIG ARISTOTLE 27 STATE		6. Well No. 002
7. OGRID No. 6137	8. Operator No DEVON ENERGY PRODUCT	9. Elevation 3492	


10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
A	34	218	31E		660	N	690	E	EDDY

11. Bottom Hole Location If Different From Surface

			Dottom			The state of the s			
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
A	27	218	31E	A	330	N	660	E	EDDY
1	cated Acres	13. J	oint or Infitt	14	. Consolidation	Code		15. Order No.	

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 3/22/2012

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Filimon Jaramillo Date of Survey: 12/18/2011 Certificate Number: 12797

Permit Comments

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: BIG ARISTOTLE 27 STATE #002

API: 30-015-40107

Created By	Comment	Comment Date
barnettj	BOP DESIGN: The BOP system used to drill the intermediate and production holes will consist of a 13-5/8" 3M Triple Ram and Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order No. 2 as a 3M system prior to drilling out the prior casing shoe. The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additiona	3/22/2012
CSHAPARD	Land s/S	3/26/2012

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP, 6137

Well: BIG ARISTOTLE 27 STATE #002

API: 30-015-40107

OCD Reviewer	Condition
CSHAPARD	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string