District I 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico

Energy, Minerals and Natural Resources

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Form C-101 August 1, 2011

Permit 148693

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

1. Operate DEVON ENERGY PR	OGRID Number 6137		
333 W. Sheridan Avenue Oklahoma City, OK 73102		3. API Number 30-015-40289	
4. Property Code	5. Property Name	6. Well No.	
38434	TURQUOISE PWU 27	008H	

7. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
M	27	198	29E	M	390	S	340	W	EDDY

8. Pool Information

FARKWAT, BOINE SPRING 4902	PARKWAY;BONE SPRING	49622
----------------------------	---------------------	-------

Additional Well Information

	T	Multional Wen Informa	tion .	27	
9. Work Type New Well	10. Well Type OIL	11. Cable/Rotary	12. Lesse Type State	13. Ground Level Elevation 3302	
14. Multiple 15. Proposed Depth N 11506		h 16. Formation 1st Bone Spring Sand	17. Contractor	18. Spud Date	
Depth to Ground	water	Distance from nearest fresh water v	vel1	Distance to nearest surface water	

19. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	300	340	0
Int1	12.25	9.625	40	3500	1130	0
Prod	8.75	5.5	17	11506	1820	0
Prod	8.75	5.5	17	6400	585	2850

Casing/Cement Program: Additional Comments

Surf - 340 sx C1 C + 2% bwoc Calcium Chloride + 0.125#/sx CF + 4% bwoc Bentonite, 14.8 ppg, 1.35 cf/sk Intermediate - Lead:830 sx (60:40) Poz (Fly Ash):Cl C + 5% bwow Sodium Chloride + 0.125#/sx CF + 5% bwoc Bentonite, 12.7 ppg, 1.73 cf/sk. Tail:300 sx (60:40)Poz CIC + 5% bwow Sodium Chloride + 0.125 #/sx CF + 0.4% bwoc Sodium Metasilicate + 4% bwoc MPA,, 14.8 ppg, 1.33 cf/sk. Prod - Lead 1:585 sx(35:65) Poz (Fly Ash):Cl H + 5% bwow Sodium Chloride + 0.3% bwoc CD-32 + 0.5% bwoc FL-25 + 2% bwoc Bentonite + 0.6% bwoc Sodium Metasilicate + 0.5% bwoc FL-52A, 11.8 ppg, 2.52 cf/sk. Lead 2:375 sx(50:50) Poz (Fly Ash):Cl H + 1% bwow Sodium Chloride + 0.2% bwoc R-3 + 0.125#/sx CF + 0.5% bwoc BA-10A + 4% bwoc MPA-5, 12.5 ppg, 1.95 cf/sk. Tail:1445 sx (35:65) Poz (Fly Ash):C1 H + 5% bwow Sodium Chloride + 0.3% bwoc CD-32 + 0.5% bwoc FL-25 + 2% bwoc Bentonite + 0.6% bwoc Sodium Metasilicate + 0.5% bwoc FL-52A, 14.8 ppg, 1.22 cf/sk.

Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
DoubleRam	3000	3000	
Annular	3000	3000	

of my knowledge and belief.	given above is true and complete to the best pit will be constructed according to	OIL CONSERVATION DIVISION		
	l permit , or an (attached) alternative	Approved By: Randy Dade		
Printed Name: Electronically	filed by Randy Bolles	Title: District Supervisor		
Title: Manager, Regulatory	Affairs	Approved Date: 5/15/2012	Expiration Date: 5/15/2014	
Email Address: randy.bolles	@dvn.com			
Date: 5/14/2012	Phone: 405-228-8588	Conditions of Approval Atta	ched	

District I 1625 N. French Dr., Hobbs, NM 88240

Phone:(575) 393-6161 Fax:(575) 393-0720 <u>District II</u>

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico

Energy, Minerals and Natural Resources

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505 Form C-102 August 1, 2011

Permit 148693

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number 30-015-40289	2. Pool Code 49622		Name SONE SPRING
4. Property Code 38434	5. Property Name TURQUOISE PWU 27		6. Weii No. 008H
7. OGRID No. 6137	8. Operator Name DEVON ENERGY PRODUCTION COMPANY, LP		9. Elevation 3302


10. Surface Location

-	UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
5	M	27	198	29E		390	S	340	W	EDDY

11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
P	27	198	29E	P	660	S	330	E	EDDY
	cated Acres	13. J	oint or Infill	14	. Consolidation	Code		15. Order No.	

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 5/14/2012

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Filimon Jaramillo Date of Survey: 5/3/2012 Certificate Number: 12797

Permit Comments

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: TURQUOISE PWU 27 #008H API: 30-015-40289

Created By	Comment	Comment Date
barnettj	Pressure Control Equipment BOP DESIGN: The BOP system used to drill the intermediate and production holes will consist of a 13-5/8" 3M Double Ram and Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order No. 2 as a 3M system prior to drilling out the prior casing shoe. The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and	5/14/2012
barnettj	This well to be pad drilled with the Turquoise PWU 27- 4H. APD is approved.	5/14/2012
CSHAPARD	Land s/S	5/15/2012

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP, 6137

Well: TURQUOISE PWU 27 #008H

API: 30-015-40289

OCD Reviewer	Condition
CSHAPARD	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string