<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

Phone:(575) 748-1283 Fax:(575) 748-9720 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 State of New Mexico

Energy, Minerals and Natural Resources

Form C-101 August 1, 2011

Permit 152320

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

DEVON ENERGY PR	Operator Name and Address DEVON ENERGY PRODUCTION COMPANY, LP			
	City, OK 73102	3. API Number 30-015-40509		
4. Property Code	5. Property Name	6. Well No.		
38555	CORAL PWU 28	005H		

7. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
D	28	198	29E	D	205	N	185	W	EDDY

8. Pool Information

PARKWAY:BONE SPRING	49622

Additional Well Information

9. Work Type New Well	10. Wet OI		11. Cable/Rotary	12. Lease Type State	13. Ground Level Elevation 3323
14. Multiple N	1010000	osed Depth 468	16. Formation 2nd Bone Spring Sand	17. Contractor	18. Spud Date
Depth to Ground	water		Distance from nearest fresh water w	rel1	Distance to nearest surface water

19. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	300	340	0
Int1	12.25	9.625	40	3300	1050	0
Prod	8.75	5.5	17	11468	1430	0
Prod	8.75	5.5	17	6300	665	2800

Casing/Cement Program: Additional Comments

13-3/8 Lead: w/340sx HalCem-C + 2% CaCl-Flake + 0.125#/sx Poly-EF, Yld. 1.35 cf/sx, FW 14.8 ppg. 9-5/8 Lead: w/760sx EconoCem-HLC + 5% Salt + 0.125#/sx Poly-EF, Yld. 1.85 cf/sx, FW 12.9 ppg. Tail: w/290sx HalCem-C + 0.125#/sx Poly-EF. Yld. 1.33 cf/sx, FW 14.8 ppg. 5-1/2 Lead: w/665sx EconoCem-HLH + 0.125#/sx Poly-EF + 0.10% HR-601, Yld. 1.95 cf/sx, FW 12.5 ppg. Tail: w/1430sx VersaCem-H + 0.125#lb/sx + 0.10% HR-601 + 1#/sx. Yld. 1.22 cf/sx, FW 14.5 ppg. TVD 7030

Proposed Blowout Prevention Program

-										
	Type	Working Pressure	Test Pressure	Manufacturer						
	Annular	3000	3000							
	DoubleRam	3000	3000							

I hereby certify that the information g of my knowledge and belief. I further certify that the drilling p.	iven above is true and complete to the best	OIL CONSERVATION DIVISION Approved By: Randy Dade		
NMOCD guidelines , a general p OCD-approved plan .	ermit , or an (attached) alternative			
Printed Name: Electronically fr	led by Randy Bolles	Title: District Supervisor		
Title: Manager, Regulatory Af	fairs	Approved Date: 7/23/2012	Expiration Date: 7/23/2014	
Email Address: randy.bolles@	dvn.com			
Date: 7/20/2012	Phone: 405-228-8588	Conditions of Approval Attached		

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phony (575) 303 6161 Page (575) 303 073

Phone:(575) 393-6161 Fax:(575) 393-0720 <u>District II</u>

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III 1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170 <u>District IV</u> 1220 S. St Francis Dr. Santa Fe. NM 8750

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico

Energy, Minerals and Natural Resources

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505 Form C-102 August 1, 2011

Permit 152320

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number	2. Pool Code	Name
30-015-40509	49622	SONE SPRING
4. Property Code	5. Property 1	6. Well No.
38555	CORAL PW	005H
7. OGRID No.	8. Operator 1	9. Elevation
6137	DEVON ENERGY PRODUC	3323

10. Surface Location

3	UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
	D	28	198	29E		205	N	185	W	EDDY

11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
A	28	198	29E	A	330	N	330	E	EDDY
12. Dedicated Acres 160.00		13. J	oint or Infill	14	. Consolidation	Code		15. Order No.	

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

0		

OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 7/20/2012

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Filimon Jaramillo Date of Survey: 4/30/2012 Certificate Number: 12797

Permit Comments

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: CORAL PWU 28 #005H

API: 30-015-40509

Created By	Comment	Comment Date				
morawford	The BOP system used to drill the intermediate and production holes will consist of a 13-5/8" 3M Triple Ram and Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order No. 2 as a 3M system prior to drilling out the prior casing shoe.					
morawford	The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP.	7/19/2012				
morawford	Mud: 0-300' FW, 8.4-9.0, 28-34, NC 300'-3,300' Brine, 9.8-10.2, 28-32, NC 3,300'-11,468' FW, 8.6-9.0, 28-32, NC-12	7/19/2012				
mcrawford	No H2S is anticipated to be encountered.	7/19/2012				
CSHAPARD	Land s/S	7/23/2012				

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP, 6137

Well: CORAL PWU 28 #005H

API: 30-015-40509

OCD Reviewer	Condition
CSHAPARD	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string