District I 1625 N. French Dr., Hobbs, NM 88240

Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 State of New Mexico

Energy, Minerals and Natural Resources

Form C-101 August 1, 2011

Permit 153455

# Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Phone: (505) 476-3470 Fax: (505) 476-3462

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

1. Operator	Name and Address	2. OGRID Number	
	DDUCTION COMPANY, LP	6137	
333 W. Sheridan Avenue Oklahoma City, OK 73102		3. API Number	
Oktationa	Chy, Ok 75102	30-015-40590	
4. Property Code	5. Property Name	6. Well No.	
38432	AGATE PWU 21	005H	

7. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
D	21	198	29E	D	1250	N	330	W	EDDY

#### 8. Pool Information

	1
SCANLON DRAW;BONE SPRING	55510

#### Additional Well Information

9. Work Type New Well	10. We		11. Cable/Rotary	12. Lease Type State	13. Ground Level Elevation 3322
14. Multiple N	401007	osed Depth	16. Formation 1st Bone Spring Sand	17. Contractor	18. Spud Date
Depth to Ground	water		Distance from nearest fresh water w	rel1	Distance to nearest surface water

19. Proposed Casing and Cement Program

Туре	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	275	310	0
Int1	12.25	9.625	40	3050	965	0
Prod	8.75	5.5	17	11310	1290	0
Prod	8.75	5.5	17	6252	640	2550

#### Casing/Cement Program: Additional Comments

13-3/8 Lead: w/310sxs ClassC Cmt + 2% bwoc CalChl + 0.125#/sx Poly-EF + 63.1% FW, 14.8 ppg. Yld: 1.35 cf/sx 9-5/8 Lead: w/700sxs(65:35)ClassC Cmt:Poz(Fly Ash): + 5% bwow Sodium Chl + 0.125#/sxs Poly-EF + 6% bwoc Bentonite + 70.9% FW, 12.9 ppg. Yld: 1.85 cf/sx. Tail: w/265sxs ClassC Cmt + 0.125#/sx Poly-EF + 63.5% Water, 14.8 ppg. Yld: 1.33 cf/sx 5-1/2 1st Lead: w/250sxs(50:50)ClassH Cmt:Poz(Fly Ash) + 10% bwoc Bentonite + 8#/sx Sod Chl + 0.125#/sx Poly-EF + 0.3% bwoc HR-601 + 0.3% bwoc Econolite + 77.2% FW, 11.8 ppg. Yld: 2.52 cf/sx. 2nd Lead: w/390sxs(65:35)ClassH Cmt:Poz(Fly Ash) + 6% bwoc Bentonite + 0.125#/sx Poly-EF + 0.1% bwoc HR-601 + 74.1% FW, 12.5 ppg. Yld: 1.95 cf/sx. Tail: w/1290sxs(50:50)ClassH Cmt:Poz (Fly Ash) + 1#/sx Sod Chl + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.1% bwoc HR-601 + 2% bwoc Bentonite + 58.8% FW, 14.5 ppg. Yld: 1.22 cf/sx TVD: 6991

Proposed Blowout Prevention Program

Туре	Working Pressure	Test Pressure	Manufacturer
DoubleRam	3000	3000	3
Annular	3000	3000	

of my knowledge and belief.	tion given above is true and complete to the best ing pit will be constructed according to	OIL CONSERVATION DIVISION		
NMOCD guidelines, a gen OCD-approved plan	eral permit 🗆, or an (attached) alternative	Approved By: Randy Dade		
Printed Name: Electronica	illy filed by Randy Bolles	Title: District Supervisor		
Title: Manager, Regulator	y Affairs	Approved Date: 8/14/2012	Expiration Date: 8/14/2014	
Email Address: randy.bol	les@dvn.com			
Date: 8/13/2012	Phone: 405-228-8588	Conditions of Approval Attac	ched	

#### District I 1625 N. French Dr., Hobbs, NM 88240

Phone:(575) 393-6161 Fax:(575) 393-0720 <u>District II</u>

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III

District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

### State of New Mexico

## Energy, Minerals and Natural Resources

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505 Form C-102 August 1, 2011

Permit 153455

#### WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number	2. Pool Code	ol Name
30-015-40590	55510	W;BONE SPRING
4. Property Code	5. Property Nam	6. Well No.
38432	AGATE PWU	005H
7. OGRID No. 6137	8. Operator Nam DEVON ENERGY PRODUCTION	9. Elevation 3322

#### 10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
D	21	198	29E		1250	N	330	W	EDDY

#### 11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
A	21	198	29E	A	990	N	330	E	EDDY
	cated Acres	13. J	oint or Infill	14	. Consolidation (	Code	15. Order No.		

# NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

0		
,		

#### OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 8/13/2012

### SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Filimon Jaramillo Date of Survey: 5/2/2012 Certificate Number: 12797

# **Permit Comments**

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: AGATE PWU 21 #005H

API: 30-015-40590

Created By	Comment	Comment Date
morawford	The BOP system used to drill the intermediate hole will consist of a 13-5/8" 3M Triple Ram and Annular preventer. The BOP system will be tested as a 3M system prior to drilling out the surface casing shoe. The BOP system used to drill the production hole will consist of a 13-5/8" 3M Triple Ram and Annular preventer. The BOP system will be tested as a 3M system prior to drilling out the intermediate casing shoe.	8/13/2012
mcrawford	In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 3,000 psi wp.	8/13/2012
morawford	No H2S is anticipated to be encountered.	8/13/2012
marawford	Mud: 0-275' FW, 8.4-9.0, 30-34, NC 275'-3,050' Brine, 9.6-10, 28-32, NC 3,050'-11,310' FW, 8.6-9.0, 28-32, NC-12	8/13/2012
CSHAPARD	Land s/S	8/14/2012

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP, 6137

Well: AGATE PWU 21 #005H

API: 30-015-40590

OCD Reviewer	Condition
CSHAPARD	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string