District I 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

Energy, Minerals and Natural Resources

August 1, 2011 Permit 153727

Form C-101

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

State of New Mexico

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

DEVON ENERGY P	or Name and Address RODUCTION COMPANY, LP	OGRID Number 6137		
333 W. Sheridan Avenue		3. API Number		
Oklahoma City, OK 73102		30-015-40606		
4. Property Code	5. Property Name	6. Well No.		
38500	JASPER 32 STATE COM	008H		

7. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
В	32	198	29E	В	175	N	1365	E	EDDY

8. Pool Information

WINCHESTER:BONE SPRING	65010

Additional Well Information

			radicional Well Informa	tion .	22
9. Work Type New Well	10. Wet OI		11. Cable/Rotary	12. Lesse Type State	13. Ground Level Elevation 3267
14. Multiple 15. Proposed Depth N 11536		16. Formation 17. Contract 1st Bone Spring Sand		18. Spud Date	
Depth to Ground	water		Distance from nearest fresh water w	rel1	Distance to nearest surface water

19. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	370	410	0
Int1	12.25	9.625	40	3300	1035	0
Prod	8.75	5.5	17	11536	1330	0
Prod	8.75	5.5	17	6516	610	2800

Casing/Cement Program: Additional Comments

13-3/8 - Lead: w/410sxs ClassC Cmt + 2% bwoc CalChl + 0.125#/sx Poly-EF + 63.1% FW, 14.8 ppg. Yld: 1.35 cf/sx 9-5/8 - Lead: w/750sxs(65:35)ClassC Cmt:Poz(Fly Ash): + 5% bwow SodChl + 0.125#/sx Poly-EF + 6% bwoc Bentonite + 70.9% FW, 12.9 ppg. Yld: 1.85 cf/sx. Tail: w/285sxs ClassC Cmt + 0.125#/sx Poly-EF + 63.5% Water, 14.8 ppg. Yld: 1.33 cf/sx 5-1/2 - 1st Lead: w/220sxs (50:50)ClassH Cmt:Poz(Fly Ash) + 10% bwoc Bentonite + 8#/sx SodChl + 0.125#/sx Poly-EF + 0.3% bwoc HR-601 + 0.3% bwoc Econolite + 77.2% FW, 11.8 ppg. Yld: 2.52 cf/sx. 2 2nd Lead: w/390sxs(65:35) ClassH Cmt:Poz(Fly Ash) + 6% bwoc Bentonite + 0.125#/sxs Poly-EF + 0.1% bwoc HR-601 + 74.1% FW, 12.5 ppg. Yld: 1.95 cf/sx. Tail: w/1330sxs(50:50)ClassH Cmt:Poz(Fly Ash) + 1#/sx SodChl + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.1% bwoc HR-601 + 2% bwoc Bentonite + 58.8% FW, 14.5 ppg. Yld: 1.22 cf/sx TVD 6992

Proposed Blowout Prevention Program

Туре	Working Pressure	Test Pressure	Manufacturer
Annular	3000	3000	
DoubleRam	3000	3000	

of my knowledge and belief.	tion given above is true and complete to the best ing pit will be constructed according to	OIL CONSERVATION DIVISION		
NMOCD guidelines, a gen OCD-approved plan	eral permit 🗆, or an (attached) alternative	Approved By: Randy Dade		
Printed Name: Electronica	ally filed by Randy Bolles	Title: District Supervisor		
Title: Manager, Regulator	y Affairs	Approved Date: 8/17/2012	Expiration Date: 8/17/2014	
Email Address: randy.bol	les@dvn.com			
Date: 8/16/2012	Phone: 405-228-8588	Conditions of Approval Attac	ched	

District I 1625 N. French Dr., Hobbs, NM 88240

Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170 District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico

Energy, Minerals and Natural Resources

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Form C-102 August 1, 2011

Permit 153727

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number	2. Pool Code	3. Pool Name	PRING
30-015-40606	65010	WINCHESTER;BONE S	
4. Property Code	5. Property Name		Well No.
38500	JASPER 32 STATE COM		008H
7. OGRID No.	8. Operator Nam		Elevation
6137	DEVON ENERGY PRODUCTION		3267


10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
В	32	198	29E		175	N	1365	E	EDDY

11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
P	32	198	29E	P	330	S	990	E	EDDY
	cated Acres	13. J	oint or Infill	14	. Consolidation (Code		15. Order No.	

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 8/16/2012

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Filimon Jaramillo Date of Survey: 8/16/2012 Certificate Number: 12797

Permit Comments

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: JASPER 32 STATE COM #008H

API: 30-015-40606

Created By	Comment	Comment Date
morawford	The BOP system used to drill the intermediate hole will consist of a 13-5/8" 3M Triple Ram and Annular preventer. The BOP system will be tested as a 3M system prior to drilling out the surface casing shoe. The BOP system used to drill the production hole will consist of a 13-5/8" 3M Triple Ram and Annular preventer. The BOP system will be tested as a 3M system prior to drilling out the intermediate casing shoe.	8/16/2012
mcrawford	In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP.	8/16/2012
morawford	No H2S is anticipated to be encountered.	8/16/2012
marawford	Mud: 0-370' FW, 8.4-9.0, 30-34, NC 370'-3,300' Brine, 9.6-10, 28-32, NC 3,300'-11,536' FW, 8.6-9.0, 28-32, NC-12	8/16/2012
CSHAPARD	Land s/S	8/17/2012

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: JASPER 32 STATE COM #008H

API: 30-015-40606

OCD Reviewer	Condition
CSHAPARD	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string