<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III 1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division

August 1, 2011

Form C-101

1220 S. St Francis Dr. Santa Fe, NM 87505

DEVON ENERGY PR	or Name and Address ODUCTION COMPANY, LP	OGRID Number 6137
	333 W. Sheridan Avenue Oklahoma City, OK 73102	3. API Number 30-015-41008
4. Property Code	5. Property Name	6. Well No.
38433	DIAMOND PWU 22	006H

7 Surface Location

W 198	100	2 19-	19	7.0	di lace Loc	ution	20	2	
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
E	22	198	29E	E	2220	N	250	W	EDDY

8. Proposed Bottom Hole Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
H	22	198	29E	H	1980	N	330	E	Eddy

9. Pool Information

TURKEY TRACK:BONE SPRING	60660

Additional Well Information

11. Work Type 12. Weil Type New Weil OIL			13. Cable/Rotary	14. Lease Type State	15. Ground Level Elevation 3332
16. Multiple 17. Proposed Depth N 11500		18. Formation 2nd Bone Spring Sand	19. Contractor	20. Spud Date	
Depth to Ground water			Distance from nearest fresh water w	rel1	Distance to nearest surface water

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	200	250	0
Int1	12.25	9.625	40	3500	1150	0
Prod	8.75	5.5	17	11500	670	2950
Prod	8.75	5.5	17	6315	1315	0

Casing/Cement Program: Additional Comments

13-3/8": TOC @ surf. Tail: 250 sx Cl C + 2% bwoc CaCl + 0.125 lbs/sk Poly-E-Flake + 56.3% FW, 14.8 ppg, Yld: 1.35 cf/sk. 9-5/8": Lead: 850 sx 65:35) Cl C:Poz(Fly Ash): + 5% bwow NaCl + 0.125 lbs/sk Poly-E-Flake + 6% bwoc Bent + 107.9% FW, 12.5 ppg, Yld: 2.05 cf/sk, Tail: 300 sx (60:40)Poz(Fly Ash):Cl C Cmt + 5% bwow NaCl + 0.125bs/sk Cello Flake + 0.2% bwoc Sodium Metasilicate + 0.5%bwoc BA-10A + 4% bwoc MPA-5 + 65.2% FW, 13.8ppg, Yld: 1.38 cf/sk, TOC @ surf. 5-1/2": 1st Lead:350 sx (50:50)Poz(Fly Ash):Cl H + 0.5% bwoc FL-52 + 0.3% bwoc ASA-01 + 10% bwoc Bent + 0.1% bwoc R-3 + 130.7% FW, 11.8 ppg, Yld: 2.30 cf/sk, 2nd Lead:320 sx(35:65)Poz(Fly Ash):Cl H + 3% bwow NaCl + 0.2% bwoc R-3 + 0.125 lbs/sk Cello Flake + 0.7% bwoc FL-52 + 0.3% bwoc ASA-301 + 6% bwoc bent + 105.5% FW, 12.5 ppg, Yld: 2.01 cf/sk, Taii:1315 sx(50:50)Poz(Fly Ash):Cl H + 5% bwow NaC1 + 0.3% bwoc CD-32 + 0.5% bwoc FL-25 + 0.4% bwoc FL-52 + 0.4% bwoc Sodium Metasil + 57.3% FW, 14.2 ppg, Yld: 1.28 cf/sk.

22 Proposed Rlowout Prevention Program

	zzi i i oposeu Dionout	Trevention Trogram	
Type	Working Pressure	Test Pressure	Manufacturer
Annular	3000	3000	
DoubleRam	3000	3000	

 I hereby certify that the in best of my knowledge and bel 	formation given above is true and complete to the ief.	OIL CONSERVATION DIVISION				
	plied with 19.15.14.9 (A) NMAC And/or	Approved By: Randy Dade				
Signature:		oli francia di Para Artini				
Printed Name: Electronic	cally filed by Randy Bolles	Title: District Supervisor				
Title: Manager, Regulato	ry Affairs	Approved Date: 1/23/2013	Expiration Date: 1/23/2015			
Email Address: randy.bo	illes@dvn.com					
Date: 1/22/2013	Phone: 405-228-8588	Conditions of Approval Attached				

District I 1625 N. French Dr., Hobbs, NM 88240 Phone: (575) 393-6161 Fax: (575) 393-0720 <u>District II</u> 811 S. First St., Artesia, NM 88210 Phone: (575) 748-1283 Fax: (575) 748-9720

Phone:(575) 748-1283 Fax:(575) 748-9720 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

<u>District IV</u> 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division

August 1, 2011 Permit 161183

Form C-102

Dil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number 30-015-41008	2. Pool Code 60660	3. Pool Name TURKEY TRACK;BONE SPRING		
4. Property Code 38433	5. Property I DIAMOND I		6. Well No. 006H	
7. OGRID No. 6137	8. Operator Name DEVON ENERGY PRODUCTION COMI		9. Elevation 3332	


10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
E	22	198	29E		2220	N	250	W	EDDY

11 Rottom Hole Location If Different From Surface

			Doctor			ution it Di			an our ance		
UL - Lot	Section	Township	Range	Lot I	idn	Feet From	N/S L	ine	Feet From	E/W Line	County
7.5%	cated Acres	13. 1	oint or Infill		14.	Consolidation (Code			15. Order No.	

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 1/22/2013

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Frank Jaramillo Date of Survey: 9/5/2012 Certificate Number: 12797

Permit Comments

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: DIAMOND PWU 22 #006H API: 30-015-41008

Created By	Comment	Comment Date
priechers	The BOP system used to drill the intermediate hole will consist of a 13-5/8" 3M Triple Ram and Annular preventer. The BOP system will be tested as a 3M system prior to drilling out the surface casing shoe.	1/22/2013
priechers	The BOP system used to drill the production hole will consist of a 13-5/8" 3M Triple Ram and Annular preventer. The BOP system will be tested as a 3M system prior to drilling out the intermediate casing shoe.	1/22/2013
priechers	In addition to the rams and annular preventer, additional BOP accessories include a kelly codk, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP.	1/22/2013
CSHAPARD	Land s/S	1/23/2013

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP, 6137

Well: DIAMOND PWU 22 #006H

API: 30-015-41008

OCD Reviewer	Condition
CSHAPARD	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string