<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

# State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division

Santa Fe, NM 87505

1220 S. St Francis Dr.

Form C-101 August 1, 2011

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

1. Ope	rator Name and Address	<ol><li>OGRID Number</li></ol>
	PRODUCTION COMPANY, LP V. Sheridan Avenue	6137
4 Table 1	oma City, OK 73102	3. API Number
Oklani	ma City, OK 73102	30-025-41094
4. Property Code	5. Property Name	6. Well No.
39319	IRONHOUSE 19 STATE COM	002H

7. Surface Location

97	100	0		7.0	urrace Loc	Ition	N1 22	0.000		
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County	
P	19	188	35E	P	410	S	630	E	LEA	

8. Proposed Bottom Hole Location

- 2	5	31		0.	Troposco	Dottom II	ole Locatio		10	
	UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
	A	19	188	35E	A	330	N	660	E	Lea

#### 9. Pool Information

WC-025 G-06 \$183518A:BONE SPRING	97930

Additional Well Information

11. Work Type 12. Well Ty New Well OIL			13. Cable/Rotary	14. Lease Type State	15. Ground Level Elevation 3931
16. Multiple 17. Proposed Depth N 13762		18. Formation 2nd Bone Spring Sand	19. Contractor	20. Spud Date	
Depth to Ground	water		Distance from nearest fresh water w	rel1	Distance to nearest surface water

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	1825	1575	0
Int1	12.25	9.625	40	3200	920	0
Prod	8.75	5.5	17	13762	1300	2700
Prod	8.75	5.5	17	8500	1070	0

# Casing/Cement Program: Additional Comments

13-3/8" Surface Lead: 1060 sx Cl C Cmnt + 2% bwoc CaCl2 + 0.125 #/sx Poly-E-Flake + 4% bwoc Bent + 70.1% FW, 13.5 ppg, Yld: 1.75 cf/sx. TOC @ surface. Tail: 515 sx Cl C Cmnt + 2% bwoc CaCl2 + 0.125 #/sx Poly-E-Flake + 63.1% FW, 14.8 ppg, Yld: 1.35 cf/sx. 9-5/8" Intermediate Lead: 560 sx (65:35) Cl C Cmnt:Poz (Fly Ash): +5% bwow CaCL + 0.125 #/sx Poly-E-Flake +6% bwoc Bent + 70.9% FW, 12.9 ppg, Yld: 1.85 cf/sx. TOC @ surface. Tail: 360 sx Cl C Cmnt + 0.125 #/sx Poly-E-Flake + 63.5% W, 14.8 ppg, Yld: 1.33 cf/sx. 5-1/2" Production Lead:1070 sx(65:35) Cl H Cmnt:Poz (Fly Ash) + 6% bwoc Bent + 0.2% bwoc HR-601 + 74.1% FW, 12.5 ppg, Yld: 1.95 cf/sx. Tail: 1300 sx(50:50) Cl H Cmnt:Poz (Fly Ash) + 1 #/sx CaCL + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.1% bwoc HR-601 + 2% bwoc Bent + 58.8% FW, 14.5 ppg, Yld: 1.22 cf/sk.

22. Proposed Blowout Prevention Program

	22. I roposed Blowout I revention I rogram								
Туре	Working Pressure	Test Pressure	Manufacturer						
Annular	3000	3000							
DoubleRam	3000	3000	(A)						

best of my knowledge and belief.	n given above is true and complete to the	OIL CONSERVATION DIVISION				
I further certify I have complied w: 19.15.14.9 (B) NMAC ⊠, if applica	ith 19.15.14.9 (A) NMAC 🛮 and/or able.	Approved By: Paul Kautz				
Signature:		11 (110 ) 11 (110 )				
Printed Name: Electronically fi	led by Randy Bolles	Title: Geologist				
Title: Manager, Regulatory Aft	fairs	Approved Date: 4/5/2013	Expiration Date: 4/5/2015			
Email Address: randy.bolles@e	ivn.com	200 kg				
Date: 4/4/2013	Phone: 405-228-8588	Conditions of Approval Attached				

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

# State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr.

Form C-102 August 1, 2011

Santa Fe, NM 87505

## WELL LOCATION AND ACREAGE DEDICATION PLAT

ALM PRINTED TO NOT A TO SEE TO A TO	The state of the s	The second second second	our terror
API Number	2. Pool Code	3. Por	ol Name
30-025-41094	97930	WC-025 G-06 S183	518A;BONE SPRING
1. Property Code	5. Propert	y Name	6. Well No.
39319	IRONHOUSE 19	STATE COM	002H
7. OGRID No.	8. Operato	or Name	9. Elevation
6137	DEVON ENERGY PRODU	ICTION COMPANY, LP	3931


### 10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
P	19	188	35E		410	S	630	E	LEA

#### 11. Bottom Hole Location If Different From Surface

UL - Lot	Section 19	Township 18S	Range 35E	Lot Idn A	Feet From 330	N/S Line	Feet From 660	E/W Line E	County LEA
	cated Acres	13. J	oint or Infill	14	. Consolidation	Code		15. Order No.	

# NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



## OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 4/4/2013

## SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Filimon Jaramillo Date of Survey: 3/21/2013 Certificate Number: 12797

# **Permit Comments**

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: IRONHOUSE 19 STATE COM #002H API: 30-025-41094

Created By	Comment	Comment Date
dœok	The BOP system used to drill the intermediate hole will consist of a 13-5/8" Double Ram and Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order 2. A 3M system will be installed and tested prior to drilling out the surface casing shoe. The BOP system used to drill the production hole will consist of a 13-5/8" Double Ram and Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order 2. A 3M system will be installed prior to drilling out the intermediate casing shoe.	4/3/2013
dœok	The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 5,000 psi WP.	4/3/2013
pkautz	Land s/S	4/4/2013
CHERRERA	OCD RECEIVED FORM C144 CLEZ. OCD PERMIT #P1-06007	4/5/2013

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP, 6137

Well: IRONHOUSE 19 STATE COM #002H

API: 30-025-41094

OCD Reviewer	Condition
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
pkautz	In order to seal off protectable water, the surface asing must be set 25' below top of Rustler Anhydrite.