<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505

Phone:(505) 476-3470 Fax:(505) 476-3462

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

State of New Mexico

Energy, Minerals and Natural Resources

Form C-101 August 1, 2011

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

COG OF	Name and Address ERATING LLC	OGRID Number 229137
	oncho Center nd, TX 79701	3. API Number 30-025-41108
4. Property Code	5. Property Name	6. Wett No.
39815	VAN GOGH FEE	001H

7. Surface Location

				7.0	difface Loc	ution	300		
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
N	11	24S	34E	N	150	S	1980	W	LEA

8. Proposed Bottom Hole Location

- 6					Tropose	DOTTOIL AL	ore mocure			
	UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
	C	11	24S	34E	С	330	N	1980	W	Lea

9. Pool Information

RED HILLS:BONE SPRING, NORTH	06434
RED HILLS:BONE SPRING, NORTH	90434

Additional Well Information

11. Work Type New Well	12. Well Type OIL	13. Cable/Rotary	14. Lease Type Private	15. Ground Level Elevation 3502
16. Multiple N	17. Proposed Depth 15393	18. Formation Bone Spring	19. Contractor	20. Spud Date 4/19/2013
Depth to Ground	water	Distance from nearest fresh water	r well	Distance to nearest surface water

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	54.5	1200	900	25timated 100
Int1	12.25	9.625	36	5100	1100	
Prod	7.875	5.5	17	15393	2200	4900

Casing/Cement Program: Additional Comments

Plan to drill a 17-1/2" hole to 1200' with Fresh Water. Run 13-3/8", 54.5#, J-55 csg and cmt to surface. Drill 12-1/4" hole to 5100' with Brine, and run 9-5/8", 36#/40#, J55 and cement to surface. Drill 7-7/8" vertical, curve and lateral with cut brine to approx 15,393' MD. Run 5-1/2", 17#, P-110 csg and cement to 4900' in 1 stage.

22. Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
DoubleRam	3000	3000	Cameron

 I hereby certify that the information best of my knowledge and belief. 	given above is true and complete to the	OIL CONSERVATION DIVISION				
I further certify I have complied with 19.15.14.9 (B) NMAC ⊠, if applicab	1 19.15.14.9 (A) NMAC ⊠ and/or le.	Approved By: Paul Kautz				
Signature:						
Printed Name: Electronically file	d by Diane Kuykendall	Title: Geologist				
Title: Production Reporting Mgr		Approved Date: 4/12/2013	Expiration Date: 4/12/2015			
Email Address: dkuykendall@co	nchoresources.com					
Date: 4/11/2013	Phone: 432-683-7443	Conditions of Approval Attached				

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

WELL LOCATION AND ACREAGE DEDICATION PLAT

", EEE	Document in the liter	CHOL DEDICHTION	LLIL
I Number	2. Pool Code	3.	Pool Name
5-41108	96434	RED HILLS;BONE SPRING, NORTH	
erty Code	5. Property	y Name	6. Well No.
815	VAN GOO	GH FEE	001H
RID No.	8. Operato	or Name	9. Elevation
9137	COG OPERA	ATING LLC	3502
RID No.	8. Operato	or Name	


10 Surface Location

- 7						dirince Do	· · · · · · · · · · · · · · · · · · ·			
	UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
	N	11	24S	34E		150	S	1980	W	LEA

11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
С	11	24S	34E	С	330	N	1980	W	LEA
	cated Acres	13. J	oint or Infill	14	. Consolidation	Code		15. Order No.	

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

Form C-102

August 1, 2011

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Diane Kuykendall Title: Production Reporting Mgr

Date: 4/11/2013

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Chad Harcrow Date of Survey: 2/8/2013 Certificate Number: 17777

Permit Comments

Operator: COG OPERATING LLC , 229137 Well: VAN GOGH FEE #001H

API: 30-025-41108

Created By	Comment	Comment Date
mreyes1	OIL: COG Operating has conducted a review to determine if an H2S contingency plan is required for the above referenced well. We were able to conclude that any potential hazardous volume would be minimal. H2S concentrations of wells in this area from surface to TD are low enough; therefore we do not believe that an H2S Contingency Plan would be necessary.	4/11/2013
pkautz	Land p/P	4/11/2013
CHERRERA	OCD RECEIVED FORM C144 CLEZ. OCD PERMIT # P1-08044	4/12/2013

Permit Conditions of Approval Operator: COG OPERATING LLC , 229137 Well: VAN GOGH FEE #001H API: 30-025-41108

OCD Reviewer	Condition
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
pkautz	In order to seal off protectable water, surface casing must be set 25' below top of Rustler Anhydrite.