District I 1625 N. French Dr., Hobbs, NM 88240 Phone;(575) 393-6161 Fax:(575) 393-0720 District II 811 S. First St., Artesia, NM 88210 Phone;(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505

Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division 1220 S. St Francis Dr.

Santa Fe, NM 87505

Form C-101 August 1, 2011

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

1. Operato	Name and Address	2. OGRID Number		
	N OIL & GAS INC Iira Vista Blvd.	15363 3. API Number		
	o. TX 75093			
Light	, 1A /3073	30-025-41230		
4. Property Code	5. Property Name	6. Well No.		
8127	JACKSON UNIT	025H		

7. Surface Location

	7. Surface Location									
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County	
0	22	24S	33E	0	200	S	1430	E	LEA	l

8. Proposed Bottom Hole Location

2	C. I Toposcu Bottom IIole Eccution								
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
A	22	24S	33E	1	330	N	970	E	Lea

9. Pool Information

TRIPLE X:BONE SPRING	59900

Additional Well Information

OIL	1117 1117171	State	15. Ground Level Elevation 3543 20. Spud Date	
7. Proposed Depth	18. Formation	19. Contractor		
11164	164 2nd Bone Spring Sand		1/8/2014	
	7. Proposed Depth	7. Proposed Depth 18. Formation	7. Proposed Depth 18. Formation 19. Contractor	

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	16	13.375	54.5	1480	800	0
Int1	12.25	9.625	40	5184	1375	0
Prod	8.5	7	26	10920	700	4000
Liner1	6.125	4.5	11.6	14980	500	10820

Casing/Cement Program: Additional Comments

Cement with 50% excess and circulate to surface on surface casing and intermediate casing. Cement with 50% excess on production casing to bring TOC to 4,000' MD. Cement liner with 25% excess to bring TOC to 10,820' MD.

22. Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer	
Annular	5000	5000	Schaffer	
DoubleRam	5000	5000	Schaffer	

best of my knowledge and bel		OIL CONSERVATION DIVISION Approved By: Paul Kautz				
I further certify I have comp 19.15.14.9 (B) NMAC ⊠, if	olied with 19.15.14.9 (A) NMAC and/or applicable.					
Signature:						
Printed Name: Electronic	ally filed by Michael Daugherty	Title: Geologist				
Title: COO		Approved Date: 6/18/2013	Expiration Date: 6/18/2015			
Email Address: ccottrell(@jdmii.com	1111	A STATE OF THE STA			
Date: 6/18/2013	Phone: 972-931-0700	Conditions of Approval Attached				

District 1
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720
District III
1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico Energy, Minerals & Natural Resources Department OIL CONSERVATION DIVISION 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-102 Revised August 1, 2011 Submit one copy to appropriate District Office

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

1	API Numbe	er ² Pool Co			ie	³ Pool Name				
				59900 Triple X; Bone Spring						
4 Property	Code				§ Property	Name			⁶ Well Number	
8127					JACKSON	N UNIT			25H	
² OGRID	No.				⁸ Operator	Name	Michael Marijani, inc. inc. and in fina full microscopic constants on the second constant species constants.		⁹ Elevation	
1536	3			MU	RCHISON OI	L & GAS, INC.			3543.4	
					10 Surface	Location		····		
UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West li	ne County	
O	22	24 S	33 E		200	SOUTH	1430	EAST	LEA	
			н Вс	ttom Ho	le Location I	f Different Froi	m Surface			
UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West li	ne County	
A	22	24 S	33 E	3 E 330 NORTH 970 EAST				EAST	LEA	
Dedicated Acre	s 13 Joint o	r Infill	Consolidation	Code 15 O	rder No.	o Leavent and the second and the sec	J	in the state of th		
160										

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.

	N89'38'39"E	2639.39 FT	N89"38'39"E	2639 39 FT		17 OPERATOR CERTIFICATION
	NW CORNER SEC. 22	N/4 CORNER SEC. 2	2 BOTTO	M_ 0	7	l hereby certify that the information contained herein is true and complete
	COMPUTED NMDOT HWY 128 ROW MAP	COMPUTED	OF HOU	970'-	eu a	to the best of my knowledge and belief, and that this organization either
	HWT 125 RUW MAP	POTT	OM OF HOLE	•	l	owns a working interest or unleased mineral interest in the land including
z		LAT. =	32'12'34.028"N	NE CORNER SEC. 22 COMPUTED NIMBOT	SS	the proposed bottom hole location or has a right to drill this well at this
8		LONG. =	103'33'17.227"W	HWY 128 ROW MAP	200.2	location pursuant to a contract with an owner of such a mineral or working
N00'24'28		I amount of the second	,	14.00	120	interest. If to a voluntary pooling agreement of a compulsory pooling
28,		days days			54"E	office pretofort entered by his division.
₹	ALTO THE THE PROPERTY SECURIOR SECURIOR SECURIOR SECURIOR SE	NOTE:			1	1/1/2 hours 11/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1
2639.	V-100	LATITUDE AND LONGITUDE COORDINATE			637	Signature Date
9.66		USING THE NORTH AMERICAN DATUM OF IN DEGREES MINUTES DECIMAL SECOND	DS FORMAT.		2637.95	Michael S. Daugherty
3 F		BASIS OF BEARING IS NEW MEXICO ST (NAD83) COORDINATES MODIFIED TO S			T	Printed Name
-						
						mdaugherty@jdmii.com
	W/4 CORNER SEC. 22	September 2		E/4 CORNER SEC. 22		E-mail Address
	LAT. =- 32'12'11.212"N -		Transaction and American Statement S	LONG. = 32'12'11.177"N		
	LONG. = 103'34'07.372"W	1		EDITO: - 103 33 03,833 W		*SURVEYOR CERTIFICATION
		1				I hereby certify that the well location shown on this
7		Savan		· · · · · · · · · · · · · · · · · · ·	S	plat was plotted from field notes of actual surveys
N00.23		And the second s	1	management	500'27'32	made by me or under my supervision, and that the
23		ŧ į			27'	same is true and correct to the best of my belief.
51		ł.			32"	
¥	Angle opposition engagement described allowants.	IACKSO)	V UNIT #25H	THE COURSE CONTROL CONTROL MARKET MARKET MARKET TO	2	MARCH 26/2013
264			EV. = 3543.4	- Tanaharan	2639	Date of Survey
2640.18		LAT. = 32*11*47.0	155"N (NAD83) 13'33'22.553"W		9.70	
8 FI				SE CORNER SEC. 22 LAT. = 32'11'45.061"N	1_ 1	John Caniel
-			JRFACE NCATION	LONG. = 103'33'05.912"W		Signature and Seal of Professional Surveyor
	SW CORNER SEC. 22	S/4 CORNER SEC. 2	22			Certificate Number: FILMON F. LAR SMILLO, PLS 12797
	LAT. = 32'11'45.091"N LONG. = 103'34'07.377"W	LAT. = 32°11'45.087' LONG. = 103'33'36.614		1430°	-	SURVEY NO. 1663
		V 2643.98 FT	S89'38'33'W	2638.73 FT	J	y

Permit Comments

Operator: MURCHISON OIL & GAS INC , 15363 Well: JACKSON UNIT #025H

API: 30-025-41230

Created By	Comment	Comment Date		
pkautz	land s/S	6/18/2013		
CHERRERA	OCD RECIEVED FORM C144 CLEZ. OCD PERMIT # P1-06388	6/18/2013		

Permit Conditions of Approval

Operator: MURCHISON OIL & GAS INC , 15363 Well: JACKSON UNIT #025H API: 30-025-41230

OCD Reviewer	Condition
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
pkautz	in order to seal off protectable water, surface casing must be set 25' below top Rustler Anhydrite