<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III 1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170 District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

Oil Conservation Division

Form C-101 August 1, 2011

1220 S. St Francis Dr. Santa Fe, NM 87505

State of New Mexico

Energy, Minerals and Natural Resources

DEVON ENERGY PRO	Operator Name and Address DEVON ENERGY PRODUCTION COMPANY, LP 333 W. Sheridan Avenue			
	heridan Avenue City, OK 73102	3. API Number 30-025-41303		
4. Property Code	5. Property Name	6. Wett No.		
30884	THISTLE UNIT	065		

7. Surface Location

	7. Surface Location												
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County				
P	33	238	33E	P	124	S	1058	E	LEA	l			

8. Proposed Bottom Hole Location

	C. I toposca Bottom Hote Eccation										
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County		
A	33	238	33E	A	330	N	660	E	Lea		

9. Pool Information

TRIPLE X;BONE SPRING	59900

Additional Well Information

11. Work Type 12. Weil Typ New Well OIL			13. Cable/Rotary	14. Lease Type State	15. Ground Level Elevation 3648
16. Multiple 17. Proposed Depth N 15894		7	18. Formation 2nd Bone Spring Sand	19. Contractor	20. Spud Date
Depth to Ground	water		Distance from nearest fresh water w	rel1	Distance to nearest surface water

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	1325	1175	0
Int1	12.25	9.625	40	5250	1450	0
Prod	8.75	5.5	17	15894	1300	4750
Prod	8.75	5.5	17	10500	1050	0

Casing/Cement Program: Additional Comments

13-3/8" Surface: Lead w/660 sx Cl C cmt + 2% bwoc CaCl2 + 0.125 #/sx Poly-E-Flake + 4% bwoc Bent + 70.1% FW, 13.5 ppg, Yld: 1.75 cf/sx, TOC @ surface. Tail w/515 sx Cl C cmt + 2% bwoc CaCl2 + 0.125 #/sx Poly-E-Flake + 63.1% FW, 14.8 ppg, Yld: 1.35 cf/sx. 9-5/8" Intermediate: Lead w/1090 sx (65:35) C1 C cmt:Poz (Fly Ash): +5% bwow CaCL + 0.125 #/sx Poly-E-Flake + 6% bwoc Bent + 70.9% FW, 12.9 ppg, Yld: 1.85 cf/sx; TOC @ surface. Tail w/360 sx C1 C cmt + 0.125 #/sx Poly-E-Flake + 63.5% W, 14.8 ppg, Yld: 1.33 cf/sx. 5-1/2" Production: Lead w/1050 sx (65:35) C1 H cmt:Poz (Fly Ash) + 6% bwoc Bent + 0.2% bwoc HR-601 + 74.1% FW, 12.5 ppg, Yld: 1.95 cf/sx. Tail w/1300 sx (50:50) Cl H cmt:Poz (Fly Ash) + 1 #/sx CaCL + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.1% bwoc HR-601 + 2% bwoc Bent + 58.8% FW, 14.5 ppg, Yld: 1.22 cf/sx; TOC @ 4750′.

22. Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
Annular	3000	3000	
DoubleRam	3000	3000	

best of my knowledge and belie		OIL CONSERVATION DIVISION Approved By: Paul Kautz			
I further certify I have compl 19.15.14.9 (B) NMAC \square , if a	lied with 19.15.14.9 (A) NMAC 🛮 and/or pplicable.				
Signature:					
Printed Name: Electronica	ally filed by Randy Bolles	Title: Geologist	11111		
Title: Manager, Regulator	y Affairs	Approved Date: 7/31/2013	Expiration Date: 7/31/2015		
Email Address: randy.boll	les@dvn.com		50 - W		
Date: 7/29/2013	Phone: 405-228-8588	Conditions of Approval Attached			

<u>District I</u>
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
<u>District II</u>

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III

District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phones(505) 334-6178 Fax.(505) 334-6170
District IV
1220 S. St Francis Dr., Sants Fe, NM 87505
Phones(505) 476-3470 Fax.(505) 476-3462

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505 Form C-102 August 1, 2011

Permit 170750

WELL LOCATION AND ACREAGE DEDICATION PLAT

State of New Mexico

Energy, Minerals and Natural Resources

	TELE LOCATION ALID MCIG	LIGE DEDICATION TEA	
1. API Number	2. Pool Code	3. Pool	Name
30-025-41303	59900	TRIPLE X;BC	ONE SPRING
4. Property Code	5. Property	Name	6. Well No.
30884	THISTLE	UNIT	065
7. OGRID No.	8. Operator	Name	9. Elevation
6137	DEVON ENERGY PRODUC	TION COMPANY, LP	3648


10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
P	33	238	33E		124	S	1058	E	LEA

11. Bottom Hole Location If Different From Surface

UL - Lot	Section 33	Township 238	Range 33E	Lot Idn A	Feet From 330	N/S Line	Feet From 660	E/W Line E	County LEA
	cated Acres	13. J	oint or Infill	14	. Consolidation	Code		15. Order No.	

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 7/29/2013

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Filimon Jaramillo Date of Survey: 7/19/2013 Certificate Number: 12797

Permit Comments

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: THISTLE UNIT #065 API: 30-025-41303

Created By	Comment	Comment Date	
DMULL	LAND S/s	7/31/2013	

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP, 6137

Well: THISTLE UNIT #065

API: 30-025-41303

OCD Reviewer	Condition	
DMULL	Will require a directional survey with the C-104	
DMULL	Pit construction and closure must satisfy all requirements of your approved plan, O.C.D. Rule 19.15.2.50, and the Pit and Below-Grade Tank Guidelines	
DMULL	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string	
pkautz	In order to seal off protectable water, surface casing must be set 25' below top of Rustler Anhydrite	