<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division

Revised July 18, 2013

Permit 171736

Form C-101

1220 S. St Francis Dr. Santa Fe, NM 87505

APPLICATION FOR PERMIT	TO DRILL, RE-ENTER.	DEEPEN, PLUGBACK	OR ADD A ZONE

COG	erator Name and Address OPERATING LLC	OGRID Number 229137
	One Concho Center Midland, TX 79701 3. API Number 30-025-41346	
4. Property Code 40076	5. Property Name DOS ABUELOS FEE	6. Wett No. 001H

7. Surface Location

	7. Surface Escation									
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County	
C	20	188	34E	C	190	N	2310	W	LEA	

8. Proposed Bottom Hole Location

				rioposco	L DOUGHI LL	ore motures			
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
N	20	188	34E	N	330	S	2260	W	Lea

9. Pool Information

MESCALERO ESCARPE;BONE SPRING	45793
-------------------------------	-------

Additional Well Information

11. Work Type 12. Well Type New Well OIL		Type 13. Cable/Rotary 14. L Pr Pr		15. Ground Level Elevation 4059	
16. Multiple 17. Proposed Depth N 14351		18. Formation Bone Spring	19. Contractor	20. Spud Date 8/22/2013	
Depth to Ground	water		Distance from nearest fresh water	r well	Distance to nearest surface water

☐ We will be using a closed-loop system in lieu of lined pits

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	54.5	1850	1240	
Int1	12.25	9.625	36	3400	850	
Prod	7.875	5.5	17	14351	2240	

Casing/Cement Program: Additional Comments

Drill 17-1/2" hole to ~1850' w/ fresh water spud mud. Run 13-3/8" 54.5# J55 STC casing to TD and cement to surface in one stage.

Will use 1" tubing and Class C w/ 2% CaCl2 to cement to surface, if necessary. Drill 12-1/4" hole to ~3400' with saturated brine water

Run 9-5/8" 36# J55 LTC casing to TD and cement to surface in one stage. Drill 7-7/8" vertical hole, curve, and lateral to 14351' with cut brine. Run 5-1/2" 17# P110 LTC casing to TD and circulate cement to surface in one stage. "I further certify that I will comply with Rule 19.15.17 NMAC by using a Closed Loop System."

22. Proposed Blowout Prevention Program

9	ZZ. I Toposcu Dionout	Trevention Trogram	
Type	Working Pressure	Test Pressure	Manufacturer
DoubleRam	3000	3000	Shaeffer

best of my knowledge and bel		OIL CONSERVATION DIVISION Approved By: Paul Kautz			
I further certify I have comp 19.15.14.9 (B) NMAC ⊠, if	plied with 19.15.14.9 (A) NMAC and/or applicable.				
Signature:		10.4 (10.4/10.10 pp.) pp.			
Printed Name: Electronic	cally filed by Diane Kuykendall	Title: Geologist	0.00		
Title: Production Report	ing Mgr	Approved Date: 8/15/2013	Expiration Date: 8/15/2015		
Email Address: dkuyken	dall@conchoresources.com	444	1550 700		
Date: 8/15/2013	Phone: 432-683-7443	Conditions of Approval Attached			

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III 1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170 District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division

August 1, 2011

Form C-102

1220 S. St Francis Dr. Santa Fe, NM 87505

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number	2. Pool Code	MESCALERO	3. Pool Name
30-025-41346	45793		ESCARPE;BONE SPRING
4. Property Code	5. Proper		6. Well No.
40076	DOS ABU		001H
7. OGRID No.	8. Operati		9. Elevation
229137	COG OPER.		4059


10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
C	20	188	34E		190	N	2310	W	LEA

11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
N	20	188	34E	N	330	S	2260	W	LEA
	cated Acres	13. J	oint or Infill	14	. Consolidation	Code		15. Order No.	

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Diane Kuykendall Title: Production Reporting Mgr

Date: 8/15/2013

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Chad Harcrow Date of Survey: 5/6/2013 Certificate Number: 17777

Permit Comments

Operator: COG OPERATING LLC , 229137 Well: DOS ABUELOS FEE #001H

API: 30-025-41346

Created By	Comment	Comment Date
mreyes1	OIL: COG Operating has conducted a review to determine if an H2S contingency plan is required for the above referenced well. We were able to conclude that any potential hazardous volume would be minimal. H2S concentrations of wells in this area from surface to TD are low enough; therefore we do not believe that an H2S Contingency Plan would be necessary.	8/15/2013
DMULL	P/p checked by DM	8/15/2013

Permit Conditions of Approval

Operator: COG OPERATING LLC , 229137

Well: DOS ABUELOS FEE #001H

API: 30-025-41346

OCD Reviewer	Condition	
DMULL	Pit construction and closure must satisfy all requirements of your approved plan, O.C.D. Rule 19.15.2.50, and the Pit and Below-Grade Tank Guidelines	
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string	
pkautz	In order to seal off protectable water, surface casing must be set 25' below top of Rustler Anhydrite	