District I

1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-8161 Fax:(575) 393-0720 District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170 **District IV** 

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

# State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Form C-101 August 1, 2011

Permit 176571

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE					
1. Operator Name and Address	2. OGRID Number				
DEVON ENERGY PRODUCTION COMPANY, LP	6137				
333 W. Sheridan Avenue	3. API Number				
Oklahoma City, OK 73102	30-025-41487				

4. Property Code 5. Property Name 6. Well No. 30884 THISTLE UNIT 061H

7. Surface Location

ſ	UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
	M	22	238	33E		200	S	660	W	Lea

9 Dronosed Bottom Hole Location

					o. Froposeu bot	tom note Location		and the same of th		
ſ	UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
	D	22	238	33E	D	330	N	660	W	Lea

9 Pool Information

orr our morn	iddoi:	7/2
TRIPLE X:BONE SPRING		59900

Additional Well Information

		Traditional Tron Internation			
11. Work Type	12. Well Type	13. Cable/Rotary	14. Lease Type	15. Ground Level Elevation	
New Well	OIL		State	3701	
16. Multiple	17. Proposed Depth	18. Formation	19. Contractor	20. Spud Date	
N	15783	2nd Bone Spring Sand	30.000.000.000.000.000.000.000	1/12/2014	
Depth to Ground water		Distance from nearest fresh water well		Distance to nearest surface water	

## ☑ We will be using a closed-loop system in lieu of lined pits

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Size	Casing Weight/ft	Setting Depth	Sads of Cement	Estimated TOC	
Surf	17.5	13.375	48	1350	1250	0	
Int1	12.25	9.625	40	5250	1570	0	
Prod	8.75	5.5	17	15783	2180	4750	

# Casing/Cement Program: Additional Comments

13-3/8" Surface: Lead: 690 sx CI C Cmt + 0.25 #/sx Poly-E-Flake + 4% bwoc Bent + 70.8% FW, 13.5 ppg, YId: 1.75 cf/sx. Water Requirement: 9.07 gal/sx. Mix Water Volume: 149bbls. TOC @ surface. Tail: 560 sx CI C Cmt + 0.125 #/sx Poly-E-Flake + 63.1% FW, 14.8 ppg, Yld: 1.33 cf/sx. 9-5/8" Intermediate: Lead: 1140 sx (65:35) CI C Cmt: Poz (Fly Ash): 6% BWOC Bent + 5% BWOW Sodium Chloride + 0.125 #/sx Poly-E-Flake + 70.9 % FW, 12.9 ppg, Yld: 1.85 cf/sx. TOC @ surface. Tail: 430 sx CI C Cmt + 0.125 #/sx Poly-E-Flake + 63.9% FW, 14.8 ppg, Yld: 1.33 cf/sx. 5-1/2" Production: Lead #1: 550 sx (50:50) Cl H Cmt. Poz (Fly Ash) + 10% BWOC Bent + 1 #/sx of Kol-Seal + 0.3% BWOC HR-601 + 0.5 #/sx D-Air 5000 + 76.4% FW, 11.9 ppg, Yld: 2.26 cf/sx. TOC @ 4750ft.

22 Dropogod Plowout Provention Program

<u> </u>	22.1 Toposca Biomout Tevendon Trogram							
Туре	Type Working Pressure		Test Pressure	Manufacturer				
Annular		3000	3000					
Double Ram		3000	3000					

knowledge and b	belief. have complied with 19.15.14.9 (A)	true and complete to the best of my  NMAC 🗵 and/or 19.15.14.9 (B) NMAC		OIL CONSERVATION	ON DIVISION
Printed Name:	Electronically filed by Randy Bollo	es	Approved By:	Paul Kautz	
Title:	Title: Manager, Regulatory Affairs			Geologist	
Email Address: randy.bolles@dvn.com		Approved Date:	11/6/2013	Expiration Date: 11/6/2015	
Date:	11/6/2013 Phone: 405-228-8588		Conditions of App	roval Attached	

District I 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

# State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Form C-102 August 1, 2011

Permit 176571

## WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number	2. Pool Code	3. Pool Name				
30-025-41487	59900	TRIPLE X;BONE SPRING				
4. Property Code	5. Property Name	6. Well No.				
30884	THISTLE UNIT	061H				
7. OGRID No.	8. Operator Name	9. Elevation				
6137	DEVON ENERGY PRODUCTION COMPANY, LP	3701				

### 10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
M	22	238	33E		200	S	660	W	Lea

### 11 Bottom Hole Location If Different From Surface

			1 III DOLLO	III IIIOIO LOGGI	on a Dinoroller roll	ouridoo			
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
D	22	238	33E	W 200 CO. 1	330	N	660	W	Lea
12. Dedicated Acres		13. Joint or Infill		14. Consolidation Cod	le		15. Order No.		
160.00								10 (44 (15))	

	organization either o a right to drill this we	OPERATOR CERTIFICATION  he information contained herein is true and complete to the best of my knowledge and belief, and that this  swns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has  ell at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling  sulsory pooling order heretofore entered by the division.
	E-Signed By:	Randy Bolles
	Title:	Manager, Regulatory Affairs
	Date:	11/6/2013
		SURVEYOR CERTIFICATION  the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision true and correct to the best of my belief.
0	Surveyed By: Date of Survey:	Filimon Jaramillo 10/16/2013
	Certificate Number:	PLS 12797

Form APD Comments

District IV

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-8161 Fax:(575) 393-0720 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

# State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Permit 176571

# **PERMIT COMMENTS**

Operator Name and Address:	API Number:
DEVON ENERGY PRODUCTION COMPANY, LP [6137]	30-025-41487
333 W. Sheridan Avenue	Well:
Oklahoma City, OK 73102	THISTLE UNIT #061H

Created By	Comment	Comment Date
dcook	5-1/2" Production: Lead #2: 330 sx (65:35) Cl H Cmt: Poz (Fly Ash) + 6% BWOC Bent + 0.25% BWOC HR-601 + 0.125 #/sx Poly-E-Flake + 74.1 % FW, 12.5 ppg, Yld: 1.95 cf/sx. Water Requirement: 10.79 gal/sx. Mix Water Volume: 85bbls. TOC @ 8728ft. Tail: 1300 sx (50:50) Cl H Cmt: Poz (Fly Ash) + 1 #/sx Sodium Chloride + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.2% bwoc HR-601 + 2% bwoc Bent + 58.8% FW, 14.5 ppg, Yld: 1.22 cf/sx. Water Requirement: 5.38 gal/sx. Mix Water Volume: 167bbls.	11/6/2013
dcook	The BOP system used to drill the intermediate hole will consist of a 13-5/8" 3M Double Ram and Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order No. 2 as a 3M system prior to drilling out the surface casing shoe. The BOP system used to drill the production hole will consist of a 13-5/8" 3M Double Ram and Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order No. 2 as a 3M system prior to drilling out the intermediate casing shoe.	11/6/2013
dcook	The BOP system used to drill the intermediate hole will consist of a 13-5/8" 3M Double Ram and Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order No. 2 as a 3M system prior to drilling out the surface casing shoe. The BOP system used to drill the production hole will consist of a 13-5/8" 3M Double Ram and Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order No. 2 as a 3M system prior to drilling out the intermediate casing shoe.	11/6/2013
dcook	The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP. Devon requests a variance to use a flexible line with flanged ends between the BOP and the choke manifold (choke line). The line will be kept as straight as possib	11/6/2013
pkautz	Land s/S	11/6/2013

Form APD Conditions

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-8161 Fax:(575) 393-0720 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III
1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

# State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Permit 176571

### PERMIT CONDITIONS OF APPROVAL

Operator Name and Address:	API Number:
DEVON ENERGY PRODUCTION COMPANY, LP [6137]	30-025-41487
333 W. Sheridan Avenue	Well:
Oklahoma City, OK 73102	THISTLE UNIT #061H

OCD Reviewer	Condition
pkautz	Will require a directional survey with the C-104
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
pkautz	Surface casing must be set 25' below top of Rustler Anhydrite in order to seal off protectable water.