

Submit within 45 days of well completion

State of New Mexico

Energy, Minerals and Natural Resources

Oil Conservation Division

1220 S. St Francis Dr.

Santa Fe, NM 87505

Revised November 6, 2013

1. WELL API NO:
30-025-24968

2. Well Name:
H T MATTERN NCT B #019

3. Well Number:
019

4. Surface Hole Location:
Unit:E Lot:2 Section:31 Township:21S Range:37E
Feet from:1830 N/S Line:N
Feet from:660 E/W Line:W

5. Bottom Hole Location:
Unit:E Lot:2 Section:31 Township:21S Range:37E
Feet from:1830 N/S Line:N
Feet from:660 E/W Line:W

6. latitude: 32.4375778412798 longitude: - 103.208221093002

7. County: Lea

8. Operator Name and Address:
CHEVRON U S A INC
Attn: Sandy Stedman-Daniel
P.O. Box 2100
Houston 77252

9. OGRID: 4323

10. Phone Number: 505-333-1941

11. Last Fracture Date: 11/22/2013 Frac Performed by: Baker Hughes

12. Production Type:
O

13. Pool Code(s):
60240

14. Gross Fractured Interval:
6,150 ft to 6,429 ft

15. True Vertical Depth (TVD):
6,799 ft

16. Total Volume of Fluid Pumped:
116,970 gals

17. Total Volume of Re-Use Water Pumped:
N/A

18. Percent of Re-Use Water In Fluid Pumped:
Not Disclosed

19. HYDRAULIC FLUID COMPOSITION AND CONCENTRATION:

Trade Name	Supplier	Purpose	Ingredients	(CAS #) Chemical Abstract Service #	Maximum Ingredient Concentration in Additive (% by mass)	Maximum Ingredient Concentration in HF Fluid (% by mass)
Water	Operator	Carrier	Water	7732-18-5	100%	77.63727%
HCl, 10.1 - 15%	Baker Hughes	Acidizing	Hydrochloric Acid	7647-01-0	15%	0.46175%
			Water	7732-18-5	85%	2.61659%
Activator, Superset U, 275 gl tote	Baker Hughes	Activator	Denatured Ethanol	64-17-5	45%	0.01114%
			Di (Ethylene Glycol) Ethyl Ether Acetate	112-15-2	55%	0.01362%
Alpha 114, 265 gl tote	Baker Hughes	Biocide	Glutaraldehyde	111-30-8	30%	0.00555%
			Quaternary Ammonium Compound	68424-85-1	5%	0.00093%
GBW-5, 5-10 lb bg/carton 50 lb pail	Baker Hughes	Breaker	Ammonium persulphate	7727-54-0	100%	0.01592%
EnZyme G-I	Baker Hughes	Breaker	Contains non-hazardous ingredients which are listed in in the non-MSDS section of the report	NA	100%	0.03982%
ClayCare, 260 gl tote	Baker Hughes	Clay Control	Choline Chloride	67-48-1	75%	0.06083%
			Water	7732-18-5	30%	0.02433%
Cl-14, 55 gl drum	Baker Hughes	Corrosion Inhibitor	Fatty Acids	Trade Secret	10%	0.00058%
			Methanol	67-56-1	100%	0.00577%
			Olefin	Trade Secret	5%	0.00029%
			Polyoxyalkylenes	Trade Secret	30%	0.00173%
			Propargyl Alcohol	107-19-7	5%	0.00029%
ZZ XLW-10A (use L488507 -3300W)	Baker Hughes	Crosslinker	Ethylene Glycol	107-21-1	30%	0.03185%
			Sodium Hydroxide	1310-73-2	10%	0.01062%
			Sodium Tetraborate Decahydrate	1303-96-4	30%	0.03185%
FRW-18, 260 gl tote	Baker Hughes	Friction Reducer	Petroleum Distillates	64742-47-8	30%	0.01224%
GW-4LDF	Baker Hughes	Gelling Agent	Guar Gum	9000-30-0	60%	0.33048%
			Petroleum Distillate Blend (1)	64742-47-8	70%	0.38556%
			Petroleum Distillate Blend (3)	8042-47-5	70%	0.38556%
			Petroluem Distillate Blend (2)	64742-55-8	70%	0.38556%
Ferrotrol 280L , 55 gl drum	Baker Hughes	Iron Control	2-Mercaptoethanol	60-24-2	100%	0.01169%
			Ammonium Hydroxide	1336-21-6	5%	0.00058%
			Cupric Chloride	7447-39-4	5%	0.00058%
NE-23, 55 gl drum	Baker Hughes	Non-emulsifier	Isopropanol	67-63-0	30%	0.00102%
NE-35, 330 gl tote	Baker Hughes	Non-emulsifier	Mixture of Surfactants	Trade Secret	50%	0.01992%
			Propylene Glycol	57-55-6	30%	0.01195%
Sand, White, 16/30	Baker Hughes	Proppant	Crystalline Silica (Quartz)	14808-60-7	100%	14.10773%
S-8C, Sand, 100 mesh, bulk	Baker Hughes	Proppant	Crystalline Silica (Quartz)	14808-60-7	100%	0.66869%
Super LC, 16/30	Baker Hughes	Proppant	Hexamethylenetetramine	100-97-0	0.01%	0.00024%
			Phenol-formaldehyde Resin	9003-35-4	5%	0.12092%
			Silicon Dioxide (Silica Sand)	14808-60-7	97%	2.34587%
ScaleTrol 720	Baker Hughes	Scale Inhibitor	Calcium Chloride	10043-52-4	5%	0.00261%
			Ethylene Glycol	107-21-1	30%	0.01564%
Flo-Back 40, 330 gl tote	Baker Hughes	Surfactant	Amphoteric Surfactant	Trade Secret	40%	0.01817%
Ingredients shown above are subject to 29 CFR 1910			Benzyl Chloride	100-44-7	0%	3.39E-05%
			Ethanol	64-17-5	0%	5.55E-05%
			Ethoxylated Alcohol	Trade Secret	0%	0.0008161%
			Ethoxylated Nonylphenol	9016-45-9	0%	0.0001694%
			Formaldehyde	50-00-0	0%	5.77E-05%
			Glycol Ether	Trade Secret	0%	0.0001694%
			Hemicellulase Enzyme Concentrate	9025-56-3	0%	0.0011947%
			Hydrochloric Acid	7647-01-0	0%	5.77E-05%
			Methanol	67-56-1	0%	2.59E-05%
			Modified Thiorea Polymer	68527-49-1	0%	0.000404%
			Olefin Sulfonate	Trade Secret	0%	0.0020323%
			Poly (acrylamide-co-acrylic acid)	Trade Secret	0%	0.0122414%
			Polyacrylate	Trade Secret	0%	0.010426%
			Polyester	Trade Secret	0%	0.0005081%
			Potassium Chloride	7447-40-7	0%	2.61E-05%
			Quaternary Amine Compounds	Trade Secret	0%	0.0010162%
			Salt	Trade Secret	0%	0.0020402%
			Sodium Chloride	7647-14-5	0%	0.0136418%
			Sorbitan Monooleate	Trade Secret	0%	0.0020402%
			Water	7732-18-5	0%	0.1573138%

20. I, as Operator, hereby certify that the information shown on this disclosure form is true and complete to the best of my knowledge and belief.

Signature: Signed Electronically

Printed Name: Cindy Herrera-Murillo

Title: Permitting Specialist

Date: 12/17/2013

E-mail Address: eeof@chevron.com

NMOCD does not require the reporting of information beyond MSDS data as described in 29 CFR 1910.1200. NMOCD does not require the reporting or disclosure of proprietary, trade secret or confidential business information.