

Submit within 45 days of well completion	State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505	Revised November 6, 2013				
		1. WELL API NO. 30-025-41575				
		2. Well Name: MARATHON ROAD 15 PA FEDERAL #001H				
		3. Well Number: 001H				
HYDRAULIC FRACTURING FLUID DISCLOSURE ☒ Original ☐ Amendment		4. Surface Hole Location: Unit:P Lot:P Section:15 Township:20S Range:34E Feet from:300 N/S Line:S Feet from:330 E/W Line:E				
		5. Bottom Hole Location: Unit:A Lot:A Section:15 Township:20S Range:34E Feet from:330 N/S Line:N Feet from:795 E/W Line:E				
		6. Latitude: Longitude: 32.5667247472745 - 103.540586487749				
		7. County: Lea				
8. Operator Name and Address: MEWBOURNE OIL CO Po Box 5270 Hobbs 88241		9. OGRID: 14744	10. Phone Number: 575-393-5905			
11. Last Fracture Date: 3/11/2014 Frac Performed by: Baker Hughes		12. Production Type: O				
13. Pool Code(s): 37570		14. Gross Fractured Interval: 10,941 ft to 10,965 ft				
15. True Vertical Depth (TVD): 10,953 ft		16. Total Volume of Fluid Pumped: 1,766,982 gals				
17. Total Volume of Re-Use Water Pumped: N/A		18. Percent of Re-Use Water in Fluid Pumped: Not Disclosed				
19. HYDRAULIC FLUID COMPOSITION AND CONCENTRATION:						
Trade Name	Supplier	Purpose	Ingredients	(CAS #) Chemical Abstract Service #	Maximum Ingredient Concentration in Additive (% by mass)	Maximum Ingredient Concentration in HF Fluid (% by mass)
Water	Operator	Carrier	Water	7732-18-5	100%	84.06716%
Superset-W, 330 gl tote	Baker Hughes	Activator	Methanol	67-56-1	50%	0.01793%
			Poly (Oxyethylene) Nonylphenol Ether	9016-45-9	50%	0.01793%
Alpha 125	Baker Hughes	Biocide	Water	7732-18-5	75%	0.01526%
GBW-5	Baker Hughes	Breaker	Ammonium persulphate	7727-54-0	100%	0.00571%
Enzyme G-I	Baker Hughes	Breaker	Contains non-hazardous ingredients which are listed in in the non-MSDS section of the report	NA	100%	0.02236%
High Perm CRB	Baker Hughes	Breaker	Ammonium Persulphate	7727-54-0	100%	0.00314%
XLW-10A	Baker Hughes	Crosslinker	Ethylene Glycol	107-21-1	30%	0.01646%
			Sodium Hydroxide	1310-73-2	10%	0.00549%
			Sodium Tetraborate Decahydrate	1303-96-4	30%	0.01646%
MaxPerm-20A, 265 gallon tote	Baker Hughes	Friction Reducer	Oxyalkylated Alcohol	Trade Secret	5%	0.0007%
			Petroleum Distillates	64742-47-8	30%	0.0042%
			Polyacrylate	Trade Secret	60%	0.00841%
			Sodium Chloride	7647-14-5	3%	0.00042%
GW-4LDF	Baker Hughes	Gelling Agent	Guar Gum	9000-30-0	60%	0.00328%
			Petroleum Distillate Blend (1)	64742-47-8	70%	0.00382%
			Petroleum Distillate Blend (3)	8042-47-5	70%	0.00382%
			Petroluem Distillate Blend (2)	64742-55-8	70%	0.00382%
GW-4	Baker Hughes	Gelling Agent	Guar Gum	9000-30-0	100%	0.15943%
NE-35, 330 gl tote	Baker Hughes	Non-emulsifier	Mixture of Surfactants	Trade Secret	50%	0.04683%
			Propylene Glycol	57-55-6	30%	0.0281%
Sand, White, 100 mesh	Baker Hughes	Proppant	Crystalline Silica (Quartz)	14808-60-7	100%	0.71818%
Optiprop G2, 20/40	Baker Hughes	Proppant	Non-Hazardous Ingredient	Trade Secret	100%	14.78371%
Ingredients shown above are subject to 29 CFR 1910			Cured Resin	Trade Secret	0%	0.0007532%
			Glutaraldehyde	111-30-8	0%	0.0061054%
			Hemicellulase Enzyme Concentrate	9025-56-3	0%	0.0006708%
			Methanol	67-56-1	0%	5.09E-05%
			Oleate Ester	1338-43-8	0%	0.0004204%
			Polysorbate	9005-65-6	0%	0.0004204%
			Water	7732-18-5	0%	0.0389723%
20. I, as Operator, hereby certify that the information shown on this disclosure form is true and complete to the best of my knowledge and belief.						
Signature: Signed Electronically Printed Name: NM Young Title: Manager						
Date: 4/14/2014						
E-mail Address: myoung@mewbourne.com						

NMOCD does not require the reporting of information beyond MSDS data as described in 29 CFR 1910.1200. NMOCD does not require the reporting or disclosure of proprietary, trade secret or confidential business information.