

Submit within 45 days of well completion	State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505	Revised November 6, 2013
HYDRAULIC FRACTURING FLUID DISCLOSURE <input checked="" type="checkbox"/> Original <input type="checkbox"/> Amendment		1. WELL API NO: 30-015-42365
		2. Well Name: POKER LAKE UNIT CVX JV BS #029H
		3. Well Number: 029H
HYDRAULIC FRACTURING FLUID DISCLOSURE <input checked="" type="checkbox"/> Original <input type="checkbox"/> Amendment		4. Surface Hole Location: Unit: M Lot: M Section: 2 Township: 25S Range: 30E Feet from: 170 N/S Line: S Feet from: 660 E/W Line: W
		5. Bottom Hole Location: Unit: M Lot: M Section: 2 Township: 25S Range: 30E Feet from: 170 N/S Line: S Feet from: 660 E/W Line: W
		6. Latitude: 32.1529570392842 Longitude: -103.858081604623
		7. County: Eddy
8. Operator Name and Address: BOPCO, L.P. 6 Desta Drive, Ste 3700 P. O. Box 2760 Midland 79702		9. OGRID: 260737
		10. Phone Number: 432-683-2277
11. Last Fracture Date: 7/25/2014 Frac Performed by: Cudd Energy Services		12. Production Type: O
13. Pool Code(s): 97913		14. Gross Fractured Interval: Confidential
15. True Vertical Depth (TVD): 10,462 ft		16. Total Volume of Fluid Pumped: 5,757,291 gals
17. Total Volume of Re-Use Water Pumped: N/A		18. Percent of Re-Use Water in Fluid Pumped: Not Disclosed

19. HYDRAULIC FLUID COMPOSITION AND CONCENTRATION:						
Trade Name	Supplier	Purpose	Ingredients	(CAS #) Chemical Abstract Service #	Maximum Ingredient Concentration in Additive (% by mass)	Maximum Ingredient Concentration in HF Fluid (% by mass)
Water		Carrier / Base Fluid		7732-18-5	100%	90.70022%
Sand		Proppant	Silicon Dioxide	14808-60-7	100%	2.34166%
AGA-380	Chemplex, L.C.	Acid Gellant	Acetic Acid	64-19-7	1%	2E-05%
			Sodium Bisulfite (Trade Secret)	7631-90-5	64%	0.00103%
			Petroleum Distillate	64742-47-8	35%	0.00056%
FR-620	Chemplex	Friction Reducer	Polyacrylamide derivatives	Mixture	100%	0.00054%
			Petroleum Distillate	64742-47-8	100%	0.00047%
15% Hydrochloric Acid	Reagent	Scale Dissolver	37% Hydrochloric Acid	7647-01-0	15%	0.25103%
			Water	7732-18-5	85%	1.42249%
I-122	Chemplex, L.C.	Acid Corrosion Inhibitor	Methanol	67-56-1	70%	0.00107%
			Propargyl alcohol	107-19-7	8%	0.00021%
			Alcohol Ethoxylate Surfactants	Trade Secret	30%	0.0008%
			n-olefins	Trade Secret	10%	0.00027%
			thiourea-formaldehyde copolymer	68527-49-1	30%	0.0008%
SG-15G	PIP Technology	Polymer	Guar Gum	9000-30-0	50%	0.05807%
			Petroleum Distillate (Mineral Oil)	64742-47-8	55%	0.06387%
			Bentonite Clay	14808-60-7	2%	0.00232%
			Surfactant	68439-51-0	2%	0.00232%
GB-2	Fritz Industries, Inc.	Breaker	Ammonium Persulfate	7727-54-0	99.9%	0.00271%
GB-125	Benchmark	Breaker	Silica Crystalline-Quartz	14808-60-7	10%	0.00286%
NE-227	CESI	Non-emulsifier	Isopropanol	67-63-0	15%	0.00686%
			Methanol	67-56-1	15%	0.00686%
			Ethoxylated Nonylphenol	9016-45-9	20%	0.00915%
FE-4	Chemplex, L.C.	Iron Control Additive	Citric Acid Anhydrous	77-92-9	55%	0.00507%
			Water	7732-18-5	55%	0.00507%
Garnett, Pearl RCS	Preferred Sands	RCS Proppants	Quartz(SiO2)	14808-60-7	98%	4.97485%
			Polyurethane Resin	Proprietary	5%	0.25382%
			Colorant	Proprietary	1%	0.05076%

20. I, as Operator, hereby certify that the information shown on this disclosure form is true and complete to the best of my knowledge and belief.

Signature: Signed Electronically Printed Name: Emma Z Galindo Title: Engineering Assistant

Date: 8/13/2014

E-mail Address: ezgalindo@basspet.com

NMOCD does not require the reporting of information beyond MSDS data as described in 29 CFR 1910.1200. NMOCD does not require the reporting or disclosure of proprietary, trade secret or confidential business information.