## Form C-103 District I State of New Mexico 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 August 1, 2011 Energy, Minerals and Natural Resources Permit 201052 District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 WELL API NUMBER Oil Conservation Division 30-015-41359 District III 1000 Rio Brazos Rd., Aztec, NM 87410 5. Indicate Type of Lease 1220 S. St Francis Dr. Phone:(505) 334-6178 Fax:(505) 334-6170 District IV Santa Fe, NM 87505 6. State Oil & Gas Lease No 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS IRRITABLE 22 STATE COM (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: 8. Well Number 002H 2. Name of Operator 9. OGRID Numbe DEVON ENERGY PRODUCTION COMPANY, LP 6137 3. Address of Operato 10. Pool name or Wildcat 333 W. Sheridan Avenue, Oklahoma City, OK 73102 4. Well Location : 330 feet from the N Unit Letter B line and feet 1980 from the E Township 25S Range 27E NMPM County Eddy 11. Elevation (Show whether DR, KB, BT, GR, etc.) 3079 GR Pit or Below-grade Tank Application Or Closure \_\_\_ Depth to Groundwater\_\_\_\_ Distance from nearest fresh water well Distance from nearest surface water Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTER CASING TEMPORARILY ABANDON CHANGE OF PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB X Other: Drilling/Cement Other: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. Drilling, Casing & Cement Operations.2/7/2015 Spudded well. Casing and Cement Program Est TOC Dpth Set String Weight Grade Sacks Yield Class Dpth Held Size Size lb/ft Hole 02/07/15 Surf 17.5 13.375 48 H40 0 668 710 1 32 C Y 12.25 **ECONOCEMHL** 9 625 155 2225 Y 02/15/15 Int1 36 0 620 1.87 02/15/15 Int1 12.25 9.625 36 J55 0 2225 260 1.32 HALCEMC Y 03/05/15 Prod 8.75 5.5 17 P110 6906 12150 415 1.2 Y Prod P110 3 48 TUNEDI IGHT 03/05/15 8.75 5.5 17 12150 630 Y 0 03/05/15 Prod 8.5 7 29 P110 0 12150 950 1.23 VERSACEM-H I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines $\square$ , a general permit $\square$ or an (attached) alternative OCD-approved plan $\square$ . SIGNATURE Electronically Signed TITLE Manager, Regulatory Affairs DATE 3/9/2015

randy.bolles@dvn.com

District Supervisor

Telephone No.

DATE

405-228-8588

3/10/2015 6:27:29 AM

E-mail address

TITLE

Type or print name

For State Use Only:

Randy Bolles

Randy Dade

Comments

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
311 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV

District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Permit 201052

## DRILLING COMMENTS

Operator:	OGRID:	
DEVON ENERGY PRODUCTION COMPANY, LP	6137	
333 W. Sheridan Avenue	Permit Number:	
Oklahoma City, OK 73102	201052	
Constitution of the Consti	Permit Type:	
	Drilling	

## Comments

Created	Comment	Comment
Ву		Date
Lmorris	Rig Released 3/7/2015 @ 12:00.	3/9/2015
Lmorris	Surface Casing Cement: Amount Circulated is reported in bbls.	3/9/2015
Lmorris	Intermediate Casing Cement: Amount Circulated is reported in bbls (30).	3/9/2015
Lmorris	Production Casing & Cement as follows: RIH w/ 112 jts 5 1/2" 17# P110 csg, followed by 160 jts 7" 29# P110 csg, set @ 12150'. RIH w/ Whipstock Plug (staged from 3500' to 7140'), set top of Whipstock @ 7129'. Cement: 415 sx CIH, yld 1.20 cu ft/sk, set top of cmt @ 6906' & bottom @ 7960'. Production Cement: Lead w/ 630 sx Tuned Light, yld 3.48 cu ft/sk. Tail w/ 950 sx Versacem-H, yld 1.23 cu ft/sk.	3/9/2015