

Submit within 45 days of well completion

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

Revised November 6, 2013

1. WELL API NO:
30-015-42734

2. Well Name:
CEDAR 11 STATE #001H

3. Well Number:
001H

HYDRAULIC FRACTURING FLUID
DISCLOSURE
☒ Original
☐ Amendment

4. Surface Hole Location:
Unit:L Lot:L Section:11 Township:21S Range:27E
Feet from:1345 N/S Line:S
Feet from:200 E/W Line:W

5. Bottom Hole Location:
Unit:L Lot:L Section:11 Township:21S Range:27E
Feet from:1345 N/S Line:S
Feet from:200 E/W Line:W

6. latitude:
32.4911925725872 longitude:
-104.168469180773

7. County:
Eddy

8. Operator Name and Address:
DEVON ENERGY PRODUCTION COMPANY, LP
333 W. Sheridan Avenue
Oklahoma City 73102

9. OGRID:
6137

10. Phone Number:
405-228-8588

11. Last Fracture Date:
10/20/2015 Frac Performed by:
FTS International Services

12. Production Type:
O

13. Pool Code(s):
3713

14. Gross Fractured Interval:
Confidential

15. True Vertical Depth (TVD):
7,685 ft

16. Total Volume of Fluid Pumped:
7,438,473 gals

17. Total Volume of Re-Use Water Pumped:
N/A

18. Percent of Re-Use Water in Fluid Pumped:
Not Disclosed

19. HYDRAULIC FLUID COMPOSITION AND CONCENTRATION:

Trade Name	Supplier	Purpose	Ingredients	(CAS #) Chemical Abstract Service #	Maximum Ingredient Concentration in Additive (% by mass)	Maximum Ingredient Concentration in HF Fluid (% by mass)
Water	Operator	Carrier	Water	7732-18-5		100%
Hydrochloric Acid (HCl)	FTSI	Acid	Hydrogen Chloride	7647-01-0		37%
			Water	7732-18-5		63%
CS POLYBREAK 210	FTSI	Polymer breaker	Sodium chlorite	7758-19-2		5%
			Water	7732-18-5		95%
			Sodium Hydroxide	1310-73-2		0%
FRW-200	FTSI	Friction reducer	Petroleum distillate hydrotreated light	64742-47-8		26%
			Acrylamide P/W acrylic acid, ammonium salt	26100-47-0		25%
			Water	7732-18-5		48%
			Sorbitan Monooleate	1338-43-8		3%
			Alcohols (C12-C14), ethoxylated	68439-50-9		4%
			Alcohols (C12-C16), ethoxylated	68551-12-2		4%
			Alcohols (C10-C16), ethoxylated	68002-97-1		4%
			Acrylamide	79-06-1		0.1%
			Dewaxed heavy paraffinic	64742-65-0		1.5%
			Ammonium Acrylate	10604-69-0		0.5%
			Ammonium Chloride	12125-02-9		12%
			Polyethylene glycol monooleate	9004-66-0		3%
			Alkylpolyoxyethyleneoxyethanol	84133-50-6		1%
			Sorbitol Tetraoleate	61723-83-9		2%
			Copolymer of acrylamide and sodium acrylate	25987-30-8		33%
			Surfactant	Proprietary		7%
			Hydrotreated heavy paraffinic	64742-54-7		5%
			Isopropanol	67-63-0		0.3%
			2-Butoxyethanol	111-76-2		10%
			2-Propanol	67-63-0		10%
			Dodecylbenzenesulfonic acid	27176-87-0		5%
			Water	7732-18-5		90%
			Sulfuric Acid	7664-93-9		0.01%
			Sulfur Dioxide	7446-09-5		0%
			Benzene, C10-16 Alkyl Derivatives	68648-87-3		0.04%
			Unsulphonated Matter	Proprietary		0.03%
			Water	7732-18-5		30%
			Choline Chloride	67-48-1		75%
			Tetrasodium EDTA	64-02-8		41%
			Sodium Hydroxide	1310-73-2		2%
			Trisodium Nitrotriacetic acid	5064-31-3		2%
			Ethylendiaminetriacetic acid, trisodium salt	19019-43-3		0.8%
			Water	7732-18-5		60%
			Sodium formate	141-53-7		0.8%
			Sodium glycolate	2836-32-0		1.5%
			Iminodiacetate disodium salt	17593-73-6		0.2%
			Isopropanol	67-63-0		30%
			Dimethylformamide	68-12-2		10%
			Organic amine resin salt	Proprietary		30%
			Quaternary ammonium compound	Proprietary		10%
			Aromatic aldehyde	Proprietary		10%
			Ethylene Glycol	107-21-1		30%
			Water	7732-18-5		5%
			Fatty Acid	Proprietary		0.1%
			Fatty Acid Salt	Proprietary		0.1%
			Aliphatic alcohol	Proprietary		0.1%
			Alkylene Oxide Block Polymer	Proprietary		10%
			Diethylene glycol	111-46-6		1%
			Potassium carbonate	584-08-7		48%
			Potassium hydroxide	1310-58-3		20%
			Water	7732-18-5		55%
			Sodium metaborate	10555-76-7		25%
			Boric acid	10043-35-3		15%
			Potassium hydroxide	1310-58-3		12%
			Water	7732-18-5		75%
			proprietary (borate) Salt	1319-33-1		40%
			Hydrated aluminium-magnesium silicate (palygorskite)	12174-11-7		5%
			calcium carbonate	1317-65-3		5%
			polyanionic cellulose	9004-32-4		1%
			modified polyacrylate	trade secret		1%
			magnesium	16389-88-1		1%
			water	7732-18-5		50%
			potassium formate	590-29-4		35%
			crystalline silica, quartz	14808-60-7		0.05%
			sodium chloride	7647-14-5		0.01%
			Guar gum	9000-30-0		50%
			Raffinates, Sorption Process	64741-85-1		55%
			Quartz	14808-60-7		4%
			Isotridecanol, ethoxylated	9043-30-5		2%
			Ammonium Persulfate	7727-54-0		84%
			Cured acrylic resin	25085-19-2		22%
			Talc	14807-96-6		0.6%
			Ammonium Persulfate	7727-54-0		100%
			Dazomet (Tetrahydro-3, 5-dimethyl-2H-1, 3, 5-thiadiazine-2-thione, Sodium Hydroxide)	533-74-4		24%
			Water	7732-18-5		23%
			Silica, Quartz	14808-60-7		55%
						100%

20/40 White

FTSI

proppant

Silica, Quartz

14808-60-7

100%

89.2196564%

20. I, as Operator, hereby certify that the information shown on this disclosure form is true and complete to the best of my knowledge and belief.

Signature:
SIGNED ELECTRONICALLY
Date:
3/2/2016
E-mail Address:
rebecca.deal@dmv.com

Printed Name:
Rebecca Deal

Title:
Regulatory Professional

NMOCOD does not require the reporting of information beyond MSDS data as described in 29 CFR 1910.1200. NMOCOD does not require the reporting or disclosure of proprietary, trade secret or confidential business information.