For State Use Only:

APPROVED BY:

Kurt Simmons

12/21/2020 3:06:36 PM

Form C-103 State of New Mexico 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 **Energy, Minerals and Natural Resources** Permit 290239 District II 811 S. First St., Artesia, NM 88210 WELL APLNIIMBER Oil Conservation Division Phone:(575) 748-1283 Fax:(575) 748-9720 30-015-47691 **District III** 5. Indicate Type of Lease 1220 S. St Francis Dr. 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 6 State Oil & Gas Lease No. District IV **Santa Fe, NM 87505** 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS SILVER BULLET 16 W1DM (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: 8. Well Number 001H 2. Name of Operator 9. OGRID Number MEWBOURNE OIL CO 14744 3. Address of Operator 10. Pool name or Wildcat P.O. Box 5270, Hobbs, NM 88241 4. Well Location Section <u>D</u> : <u>226</u> feet from the N line and feet 330 from the W Township 26S Range 29E NMPM County Eddy 11. Elevation (Show whether DR, KB, BT, GR, etc.) 2942 GR Pit or Below-grade Tank Application or Closure ___ Distance from nearest fresh water well_ Pit Type _ __ Depth to Groundwater Distance from nearest surface water Pit Liner Thickness: bbls: Construction Material ____ mil Below-Grade Tank: Volume_ 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF NOTICE OF INTENTION TO: PLUG AND ABANDON ALTER CASING PERFORM REMEDIAL WORK REMEDIAL WORK TEMPORARILY ABANDON CHANGE OF PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON CASING/CEMENT JOB PULL OR ALTER CASING MULTIPLE COMPL X Other: Other: Drilling/Cement 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. Spud 17 1/2" hole. TD @ 585'. Ran 570' 13 3/8" 54.5# J55 ST&C csg. Cmt w/600 sks Class C w/1% CaCl2. Mixed @ 14.8 PPG w/1.34 yd. Displaced w/84 BFW. Plug down @ 4:30 A.M. 11/24/20. Did not circ cmt. Slow rate lift pressure @ 200 psi @ 4 BPM. Ran temp surv. TOC @ 130'. Cmt w/1" pipe. Tag @ 110'. Ran 1" pipe in 2 stages w/375 sks Class C w/2% CaCl2. Mixed @ 14.8 PPG w/1.34 yd. Circ 41 sks to the pits. Test BOPE to 5000# & annular to 3500#. Tested csg to 1500# for 30 mins, held OK. FIT to 10.5 PPG EMW. See Attached 11/23/2020 Spudded well. **Casing and Cement Program** Date String Fluid Hole Csg Size Weight Grade Est Dpth Sacks Yield Class Pres Pres Open TOC Dpth Held Size lb/ft Drop Hole Type Set С Υ 11/23/20 Surf FreshWater 17.5 13 375 54.5 .155 0 570 975 1 34 110 1500 0 11/26/20 Int1 Brine 12.25 9.625 40 HCL80 0 2800 700 2.07 С 0 1500 0 Υ 12/03/20 Int2 Mud 8 75 7 20 HCP110 0 10265 800 3.18 C/H 0 1500 0 Υ 12/08/20 Mud 6.125 4.5 13.5 HCP110 0 14464 350 1.74 Н 0 2500 Υ Liner1 I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines _, a general permit _ or an (attached) alternative OCD-approved plan _ TITLE SIGNATURE DATE Electronically Signed Vice President Operations 12/21/2020 Type or print name E-mail address Telephone No. 903-561-2900 Monty Whetstone prodmgr@mewbourne.com

Petroleum Specialist - A

State of New Mexico State of New Mexico
Incept Description Desc
SILS First St., Artesia, NM 88210 DIC CONSERVATION DIVISION
District III - (505) 334-6178 1220 South St. Francis Dr. Santa Fe, NM 87505 6. State Oil & Gas Lease No.
Santa Fe, NM 87505 6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other 2. Name of Operator Mewbourne Oil Company 3. Address of Operator PO Box \$5270, Hobbs NM 88240 4. Well Location Unit Letter D : 225 feet from the North line and 330 feet from the West line Section 16 Township 268 Range 29E NMPM Eddy County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON ABANDON ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB NOWNHOLE COMMINGLE DOWNHOLE COMMINGLE CLOSED-LOOP SYSTEM ULTIPLE COMPL TOTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimate of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 11126/20 Title Public Response of the Public Response of th
CDD NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Oil Well
RNOPICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS GOMENCE ORBILLING OPNS. PAND A PULL OR ALTER CASING MULTIPLE COMPL GOMENCE ORBING/CEMENT JOB CASING/CEMENT JOB CASING Completion or recompletion or recompletion. 11.26/20 Time to the pits. Set Cass C w/0.2% fluid loss. Mixed @ 14.8#g w/1.33 yd. Displaced w/208 bbls of FW. Plug down @ 11:00 PM 11/26/20 for sins, held OK.
2. Name of Operator Mewbourne Oil Company 147444 10. Pool name or Wildcat PO Box 5270, Hobbs NM 88240 10. Pool name or Wildcat Purple Sage Wolfcamp (gas) 4. Well Location
Mewbourne Oil Company 14744 10. Pool name or Wildcat Purple Sage Wolfcamp (gas) 4. Well Location Unit Letter D : 225 feet from the North line and 330 feet from the West line Section 16 Township 26S Range 29E NMPM Eddy County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 2942' GL GL GL GL GL GL GL GL
3. Address of Operator PO Box 5270, Hobbs NM 88240 4. Well Location Unit Letter D :
4. Well Location Unit Letter D : 225 feet from the North line and 330 feet from the West line Section 16 Township 26S Range 29E NMPM Eddy County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 2942' GL 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. P AND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB CASING/CEMENT JOB OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimate of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 11/26/20 11/26/20 11/26/20 12 I/4" hole @ 2815'. Ran 2800' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Class C (65:35 Poz) w/additives. Mixed @ 12.4 w/2.07 yd. Tail w/200 sks Class C w/0.2% fluid loss. Mixed @ 14.8#/g w/1.33 yd. Displaced w/208 bbls of FW. Plug down @ 11:00 PM 11/26/20 sks of cmt to the pits. Set Cameron mandrel hanger through BOP w/115k#. At 11:30 A.M. 11/27/20, tested csg to 1500# for 30 mins, held OK.
Unit Letter D : 225
Section 16 Township 26S Range 29E NMPM Eddy County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 2942' GL 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS. P AND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB AND A CASING/CEMENT JOB OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimate of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 11/26/20 TD'ed 12 1/4" hole @ 2815'. Ran 2800' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Class C (65:35 Poz) w/additives. Mixed @ 12.4 w/2.07 yd. Tail w/200 sks Class C w/0.2% fluid loss. Mixed @ 14.8#/g w/1.33 yd. Displaced w/208 bbls of FW. Plug down @ 11:00 PM 11/26/20 55 sks of cmt to the pits. Set Cameron mandrel hanger through BOP w/115k#. At 11:30 A.M. 11/27/20, tested csg to 1500# for 30 mins, held OK.
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 2942' GL 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS. P AND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB AND A DOWNHOLE COMMINGLE OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimate of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 11/26/20 11/26/20 11/26/20 11/26/20 11/26/20 11/26/20 11/26/20 11/26/20 12/26/20 13/26/20 14/26/20 15/26/20 15/26/20 15/26/20 15/26/20 16/26/20 16/26/20 17/26/20 18/2
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. P AND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimate of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 11/26/20
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PAND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PAND A CASING/CEMENT JOB OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimate of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1/26/20 To ed 12 1/4" hole @ 2815'. Ran 2800' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Class C (65:35 Poz) w/additives. Mixed @ 12.4 w/2.07 yd. Tail w/200 sks Class C w/0.2% fluid loss. Mixed @ 14.8#/g w/1.33 yd. Displaced w/208 bbls of FW. Plug down @ 11:00 PM 11/26/20 sks of cmt to the pits. Set Cameron mandrel hanger through BOP w/115k#. At 11:30 A.M. 11/27/20, tested csg to 1500# for 30 mins, held OK.
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PAND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB CLOSED-LOOP SYSTEM COTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimate of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1/26/20 CD'ed 12 1/4" hole @ 2815'. Ran 2800' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Class C (65:35 Poz) w/additives. Mixed @ 12.4 w/2.07 yd. Tail w/200 sks Class C w/0.2% fluid loss. Mixed @ 14.8#/g w/1.33 yd. Displaced w/208 bbls of FW. Plug down @ 11:00 PM 11/26/20 is sks of cmt to the pits. Set Cameron mandrel hanger through BOP w/115k#. At 11:30 A.M. 11/27/20, tested csg to 1500# for 30 mins, held OK.
PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PAND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB DOWNHOLE COMMINGLE COMPL OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimate of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1/26/20 Toled 12 1/4" hole 2815'. Ran 2800' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Class C (65:35 Poz) w/additives. Mixed 12.4 w/2.07 yd. Tail w/200 sks Class C w/0.2% fluid loss. Mixed 14.8#/g w/1.33 yd. Displaced w/208 bbls of FW. Plug down 11:00 PM 11/26/20 sks of cmt to the pits. Set Cameron mandrel hanger through BOP w/115k#. At 11:30 A.M. 11/27/20, tested csg to 1500# for 30 mins, held OK.
TEMPORARILY ABANDON
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB DOWNHOLE COMMINGLE CLOSED-LOOP SYSTEM OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimate of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1/26/20 D'ed 12 1/4" hole @ 2815'. Ran 2800' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Class C (65:35 Poz) w/additives. Mixed @ 12.4 v/2.07 yd. Tail w/200 sks Class C w/0.2% fluid loss. Mixed @ 14.8#/g w/1.33 yd. Displaced w/208 bbls of FW. Plug down @ 11:00 PM 11/26/20 sks of cmt to the pits. Set Cameron mandrel hanger through BOP w/115k#. At 11:30 A.M. 11/27/20, tested csg to 1500# for 30 mins, held OK.
DOWNHOLE COMMINGLE CLOSED-LOOP SYSTEM OTHER:
CLOSED-LOOP SYSTEM OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimate of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1/26/20 D'ed 12 1/4" hole @ 2815'. Ran 2800' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Class C (65:35 Poz) w/additives. Mixed @ 12.4 //2.07 yd. Tail w/200 sks Class C w/0.2% fluid loss. Mixed @ 14.8#/g w/1.33 yd. Displaced w/208 bbls of FW. Plug down @ 11:00 PM 11/26/20 //2.5 sks of cmt to the pits. Set Cameron mandrel hanger through BOP w/115k#. At 11:30 A.M. 11/27/20, tested csg to 1500# for 30 mins, held OK.
OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimate of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1/26/20 1/26/20 1/26/20 1/26/20 1/20
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimate of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1/26/20
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1/26/20 To be 12 1/4" hole @ 2815'. Ran 2800' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Class C (65:35 Poz) w/additives. Mixed @ 12.4 y/2.07 yd. Tail w/200 sks Class C w/0.2% fluid loss. Mixed @ 14.8#/g w/1.33 yd. Displaced w/208 bbls of FW. Plug down @ 11:00 PM 11/26/20 5 sks of cmt to the pits. Set Cameron mandrel hanger through BOP w/115k#. At 11:30 A.M. 11/27/20, tested csg to 1500# for 30 mins, held OK.
proposed completion or recompletion. 1/26/20 D'ed 12 1/4" hole @ 2815'. Ran 2800' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Class C (65:35 Poz) w/additives. Mixed @ 12.4 v/2.07 yd. Tail w/200 sks Class C w/0.2% fluid loss. Mixed @ 14.8#/g w/1.33 yd. Displaced w/208 bbls of FW. Plug down @ 11:00 PM 11/26/20 5 sks of cmt to the pits. Set Cameron mandrel hanger through BOP w/115k#. At 11:30 A.M. 11/27/20, tested csg to 1500# for 30 mins, held OK.
TD'ed 12 1/4" hole @ 2815'. Ran 2800' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Class C (65:35 Poz) w/additives. Mixed @ 12.4 v/2.07 yd. Tail w/200 sks Class C w/0.2% fluid loss. Mixed @ 14.8#/g w/1.33 yd. Displaced w/208 bbls of FW. Plug down @ 11:00 PM 11/26/20 is sks of cmt to the pits. Set Cameron mandrel hanger through BOP w/115k#. At 11:30 A.M. 11/27/20, tested csg to 1500# for 30 mins, held OK.
w/2.07 yd. Tail w/200 sks Class C w/0.2% fluid loss. Mixed @ 14.8#/g w/1.33 yd. Displaced w/208 bbls of FW. Plug down @ 11:00 PM 11/26/20 sks of cmt to the pits. Set Cameron mandrel hanger through BOP w/115k#. At 11:30 A.M. 11/27/20, tested csg to 1500# for 30 mins, held OK.
5 sks of cmt to the pits. Set Cameron mandrel hanger through BOP w/115k#. At 11:30 A.M. 11/27/20, tested csg to 1500# for 30 mins, held OK.
est to EMW of 9.5 PPG. Drilled out with 8 3/4" bit. 2/03/2020
Dred 8 3/4" hole @ 10280' Ran 10265' of 7" 29# HCP110 LT&C csg. Cemented w/400 sks Lite Class C w/additives. Mixed @ 10.5#/g w/3.18 yi
//400 sks Class H w/additives. Mixed @ 15.6#/g w/1.18 yd. Displaced w/380 bbls OBM. Bump plug w/835#. Set Cameron mandrel hanger through
30P w/230k#. Plug down @ 9:30 A.M. 12/30/20. Circ 27 sks to pits. At 4:00 A.M. 12/04/20 tested csg to 1500# 30 mins, held OK. FIT test to 13.
MW. Drilled out with 6 1/8" bit. 2/08/2020
706/2020 TD'ed 6 1/8" hole @ 14464' MD. Ran 4 ½" 13.5# HCP110 CDC-HTQ csg from TOL @ 9336' to 14464'. Cement w/350 sks Poz H
35:65:6) w/additives. Mixed @ 13.5#/g w/1.74 yd. Followed w/5 bbls sugar BW. Plug down @ 2:45 A.M. 12/09/20. Bump plug
v/3200#. Set packer w/100k#. Sting out of PBR w/1500# on DP. Displaced 7" csg w/380 bbls sugar BW. Circ 96 sks of cmt off of 1
op to the pit. At 3:15 A.M., 12/09/20, test liner top to 2500# for 30 mins, held OK. Top of liner @ 9336'. Rig released @ 2:30 P.M.
Bis Balance Date: 12/00/2020
Spud Date: 11/23/2020 Rig Release Date: 12/09/2020
hereby certify that the information above is true and complete to the best of my knowledge and belief.
SIGNATURE Jakie Lathan TITLE Regulatory DATE 12/18/2020
Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: _575-393-5905 PHONE: _575-3905 PHONE: _575

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone: (575) 748-1283 Fax: (575) 748-9720 District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

Comments

Permit 290239

DRILLING COMMENTS

Operator:	OGRID:
MEWBOURNE OIL CO	14744
P.O. Box 5270	Permit Number:
Hobbs, NM 88241	290239
	Permit Type:
	Drilling

Comments

Created By	Comment	Comment Date
jlathan	Details on additional drilling and casing ran added on the attached sundry	12/21/2020