

1625 N. French Dr., Hobbs, NM 88240

District II

811 S. First St., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals & Natural ResourcesForm C-104
Revised August 1, 2011Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Submit one copy to appropriate District Office

☐ AMENDED REPORT

I. REQUEST FOR ALLOWABLE AND AUTHORIZATION TO TRANSPORT

¹ Operator name and Address XTO Energy, Inc. 6401 HOLIDAY HILL ROAD BLDG 5 MIDLAND, TX 79707		² OGRID Number 373075
		³ Reason for Filing Code/ Effective Date NW
⁴ API Number 30 - 015-45919	⁵ Pool Name PURPLE SAGE: WOLFMP CAMP	⁶ Pool Code 98220
⁷ Property Code 325388	⁸ Property Name POKER LAKE UNIT 29 BS	⁹ Well Number 703H

II. ¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South Line	Feet from the	East/West line	County
F	29	25S	31E		2310	North	1920	West	EDDY

¹¹ Bottom Hole Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
N	32	25S	31E		194	South	1587	West	Eddy

¹² Lse Code F	¹³ Producing Method Code F	¹⁴ Gas Connection Date	¹⁵ C-129 Permit Number	¹⁶ C-129 Effective Date	¹⁷ C-129 Expiration Date
-----------------------------	--	-----------------------------------	-----------------------------------	------------------------------------	-------------------------------------

III. Oil and Gas Transporters

¹⁸ Transporter OGRID	¹⁹ Transporter Name and Address	²⁰ O/G/W
373075	XTO Permian Operating, LLC 6401 Holiday Hill Rd, bldg 5, Midland, TX 79707	G
34053	Plains Marketing, LP	O
005380	XTO Energy, Inc. 6401 Holiday Hill Rd, bldg 5, Midland, TX 79707	W

IV. Well Completion Data

²¹ Spud Date 11/29/2019	²² Ready Date 1/12/2021	²³ TD 19288MD 11545 TVD	²⁴ PBD 19286MD 11545 TVD	²⁵ Perforations 11850 - 19126	²⁶ DHC, MC
²⁷ Hole Size	²⁸ Casing & Tubing Size	²⁹ Depth Set	³⁰ Sacks Cement		
17.5	13.375	945	1215		
12.25	9.625	4100	1663		
8.75	7	11500	1626		
6	4.5/2.875	19288/ 10676	659		

V. Well Test Data

³¹ Date New Oil 1/13/2021	³² Gas Delivery Date 1/13/2021	³³ Test Date 1/15/2021	³⁴ Test Length 24 hrs	³⁵ Tbg. Pressure 960	³⁶ Csg. Pressure 1260
³⁷ Choke Size	³⁸ Oil 1242	³⁹ Water 4968	⁴⁰ Gas 7761		⁴¹ Test Method Flowing
⁴² I hereby certify that the rules of the Oil Conservation Division have been complied with and that the information given above is true and complete to the best of my knowledge and belief. Signature: <i>Cassie Evans</i>			OIL CONSERVATION DIVISION Approved by: Kurt Simmons		
Printed name: Cassie Evans			Title: NMOCD, Santa Fe		
Title: Regulatory Analyst			Approval Date: 03/24/2021		
E-mail Address: cassie.evans@exxonmobil.com					
Date: 3/9/21		Phone: 432.218.3671			

District I

1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II

811 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720

District III

1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102

Revised August 1, 2011

Submit one copy to appropriate

District Office

☒ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

AS-DRILLED PLAT

¹ API Number 30-015-45919	² Pool Code 98220	³ Pool Name PURPLE SAGE; WOLFCAMP (GAS)
⁴ Property Code 325388	⁵ Property Name POKER LAKE UNIT 29 BS	⁶ Well Number 703H
⁷ OGRID No. 373075	⁸ Operator Name XTO PERMIAN OPERATING, LLC.	⁹ Elevation 3,359'

¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
F	29	25 S	31 E		2,310	NORTH	1,920	WEST	EDDY

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
N	32	25 S	31 E		194	SOUTH	1,587	WEST	EDDY

¹² Dedicated Acres 480	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.
--------------------------------------	-------------------------------	----------------------------------	-------------------------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division. NOTE: AS-DRILLED BOTTOM HOLE PLOTTED FROM DATA FURNISHED BY XTO ENERGY.

	GEODETIC COORDINATES NAD 83 NME SURFACE LOCATION Y= 401,323.5 X= 705,650.7 LAT.= 32.102206°N LONG.= 103.802684°W FIRST TAKE POINT NAD 83 NME Y= 400,630.0 X= 705,323.7 LAT.= 32.100304°N LONG.= 103.803751°W KICK OFF POINT NAD 83 NME Y= 401,227.4 X= 705,313.2 LAT.= 32.101946°N LONG.= 103.803776°W KICK OFF POINT NAD 27 NME Y= 401,169.5 X= 664,127.7 LAT.= 32.101822°N LONG.= 103.803297°W GEODETIC COORDINATES NAD 27 NME SURFACE LOCATION Y= 401,265.6 X= 664,465.2 LAT.= 32.102082°N LONG.= 103.802205°W FIRST TAKE POINT NAD 27 NME Y= 400,572.1 X= 664,138.2 LAT.= 32.100180°N LONG.= 103.803272°W	LAST TAKE POINT NAD 83 NME Y= 393,363.9 X= 705,333.1 LAT.= 32.080331°N LONG.= 103.803836°W BOTTOM HOLE LOCATION NAD 83 NME Y= 393,202.0 X= 705,328.6 LAT.= 32.079886°N LONG.= 103.803853°W CORNER COORDINATES TABLE NAD 83 NME A - Y= 400,984.0 N, X= 706,383.3 E B - Y= 400,975.3 N, X= 705,056.4 E C - Y= 398,334.2 N, X= 706,368.7 E D - Y= 398,321.1 N, X= 705,044.2 E E - Y= 395,671.4 N, X= 706,385.5 E F - Y= 395,661.7 N, X= 705,058.7 E G - Y= 393,015.9 N, X= 706,402.2 E H - Y= 393,006.1 N, X= 705,072.1 E CORNER COORDINATES TABLE NAD 27 NME A - Y= 400,926.1 N, X= 665,197.8 E B - Y= 400,917.4 N, X= 663,870.9 E C - Y= 398,276.4 N, X= 665,183.1 E D - Y= 398,263.3 N, X= 663,858.6 E E - Y= 395,613.6 N, X= 665,199.8 E F - Y= 395,603.9 N, X= 663,873.0 E G - Y= 392,958.2 N, X= 665,216.4 E H - Y= 392,948.4 N, X= 663,886.3 E	17 OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division. <i>Cassie Evans</i> 03/09/21 Signature Date Cassie Evans Printed Name cassie.evans@exxonmobil.com E-mail Address
	18 SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. 2-3-2021 Date of Survey Signature and Seal of Professional Surveyor: <i>Mark Dillon Harp</i> MARK DILLON HARP 23786 Certificate Number LM 2017071011		
	2017071011-XTO-POKER LAKE UNIT 29 BS 703H (703H) EDDY.DWG\2017071011-XTO-POKER LAKE UNIT 29 BS 703H AS-DRILLED.dwg		

Intent ☐ As Drilled ☒API #
30-015-45919

Operator Name: XTO PERMIAN OPERATING, LLC.	Property Name: POKER LAKE UNIT 29 BS	Well Number 703H
---	---	---------------------

Kick Off Point (KOP)

UL F	Section 29	Township 25S	Range 31E	Lot	Feet 2,404	From N/S FNL	Feet 1,583	From E/W FWL	County EDDY
Latitude 32.101946					Longitude 103.803776				NAD 83

First Take Point (FTP)

UL K	Section 29	Township 25S	Range 31E	Lot	Feet 2,306	From N/S FSL	Feet 1,595	From E/W FWL	County EDDY
Latitude 32.100304					Longitude 103.803751				NAD 83

Last Take Point (LTP)

UL N	Section 32	Township 25S	Range 31E	Lot	Feet 356	From N/S FSL	Feet 1,592	From E/W FWL	County EDDY
Latitude 32.080331					Longitude 103.803836				NAD 83

Is this well the defining well for the Horizontal Spacing Unit? ☐Is this well an infill well? ☐

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API #

Operator Name:	Property Name:	Well Number
----------------	----------------	-------------

KZ 06/29/2018



XTO Energy

Eddy County, NM (Nad-27 / East Zone)

PLU 29 Big Sinks

#703H

OH

Design: OH

End Of Well Report

02 January, 2020



I **Larry Wright**, certify that I am employed by **Wellbenders Directional Services**. That I did on the day(s) of **11/28/19** thru **01/01/20** conduct or supervise the taking of a **MWD Survey** from a depth of **192'** to a depth of **19288'**; that the data is true, correct, complete and within the limitations of the tool as set forth by **Wellbenders Directional Services**; that I am authorized and qualified to make this report; that this survey was conducted at the request of **XTO Energy Inc** for the **PLU 29 Big Sinks 703H API No. 30-015-45919** in **Eddy County, New Mexico**; and that I have reviewed this report and find that it conforms to the principles and procedures as set forth by **Wellbenders Directional Services**.

Larry Wright

Larry
Wright

Digitally
signed by Larry
Wright
Date:
2020.01.02
14:45:59 -06'00'

*13901 Hwy 105W, Conroe, Texas
77304
PH 936-539-9602*



Wellbenders

End Of Well Report

Company:	XTO Energy			Local Co-ordinate Reference:	Well #703H
Project:	Eddy County, NM (Nad-27 / East Zone)			TVD Reference:	RKB = 24' @ 3383.00usft
Site:	PLU 29 Big Sinks			MD Reference:	RKB = 24' @ 3383.00usft
Well:	#703H			North Reference:	Grid
Wellbore:	OH			Survey Calculation Method:	Minimum Curvature
Design:	OH			Database:	WBDS_SQL_2

Project	Eddy County, NM (Nad-27 / East Zone)				
Map System:	US State Plane 1927 (Exact solution)		System Datum:	Mean Sea Level	
Geo Datum:	NAD 1927 (NADCON CONUS)				
Map Zone:	New Mexico East 3001				

Site	PLU 29 Big Sinks					
Site Position:			Northing:	401,257.90 usft	Latitude:	32.102077
From:	Map		Easting:	663,265.10 usft	Longitude:	-103.806081
Position Uncertainty:	0.00 usft		Slot Radius:	13.200 in	Grid Convergence:	0.280 °

Well	#703H					
Well Position	+N/-S	0.00 usft	Northing:	401,265.60 usft	Latitude:	32.102082
	+E/-W	0.00 usft	Easting:	664,465.20 usft	Longitude:	-103.802205
Position Uncertainty	0.00 usft		Wellhead Elevation:	0.00 usft	Ground Level:	3,359.00 usft

Wellbore	OH				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2015	11/7/2019	6.793	59.883	47,596.63126338

Design	OH				
Audit Notes:					
Version:	1.0	Phase:	ACTUAL	Tie On Depth:	0.00
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)	
	0.00	0.00	0.00	179.90	

Survey Program	Date	1/2/2020			
From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description	
192.00	19,288.00	Survey #1 (OH)	WBDS_IGRF	OWSG MWD + IGRF or WMM	



Wellbenders End Of Well Report

Company:	XTO Energy	Local Co-ordinate Reference:	Well #703H
Project:	Eddy County, NM (Nad-27 / East Zone)	TVD Reference:	RKB = 24' @ 3383.00usft
Site:	PLU 29 Big Sinks	MD Reference:	RKB = 24' @ 3383.00usft
Well:	#703H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	WBDS_SQL_2

Survey										
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	V. Sec (usft)	CL (usft)	CL Azi (°)	DLeg (°/100ft)	
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
192.00	0.44	195.70	192.00	-0.71	-0.20	0.71	192.00	195.70	0.23	
283.00	0.79	231.38	282.99	-1.44	-0.78	1.44	91.00	218.77	0.55	
374.00	0.97	223.65	373.98	-2.39	-1.81	2.38	91.00	227.12	0.24	
467.00	1.27	219.17	466.96	-3.76	-3.00	3.75	93.00	221.11	0.34	
559.00	1.71	233.58	558.93	-5.36	-4.75	5.35	92.00	227.44	0.62	
651.00	1.71	237.36	650.89	-6.92	-7.01	6.90	92.00	235.47	0.12	
742.00	1.77	244.74	741.85	-8.25	-9.42	8.23	91.00	241.11	0.25	
833.00	1.80	247.38	832.81	-9.40	-12.01	9.38	91.00	246.07	0.10	
1,046.00	1.67	244.92	1,045.71	-12.00	-17.91	11.97	213.00	246.20	0.07	
1,141.00	1.49	246.59	1,140.67	-13.08	-20.30	13.04	95.00	245.71	0.20	
1,234.00	1.27	240.70	1,233.65	-14.06	-22.31	14.02	93.00	243.88	0.28	
1,327.00	1.01	241.49	1,326.63	-14.96	-23.93	14.92	93.00	241.05	0.28	
1,422.00	0.88	259.95	1,421.61	-15.48	-25.38	15.44	95.00	250.08	0.35	
1,516.00	0.88	282.45	1,515.60	-15.45	-26.80	15.41	94.00	271.20	0.37	
1,610.00	0.75	283.59	1,609.59	-15.15	-28.10	15.11	94.00	282.97	0.14	
1,705.00	0.57	273.13	1,704.59	-14.98	-29.18	14.93	95.00	279.08	0.23	
1,799.00	0.44	284.56	1,798.58	-14.87	-29.99	14.81	94.00	278.11	0.17	
1,893.00	0.40	265.40	1,892.58	-14.80	-30.67	14.75	94.00	275.44	0.15	
1,990.00	0.31	277.44	1,989.58	-14.80	-31.27	14.74	97.00	270.65	0.12	
2,082.00	0.22	247.11	2,081.58	-14.83	-31.68	14.78	92.00	264.91	0.18	
2,176.00	0.31	251.16	2,175.58	-14.98	-32.08	14.93	94.00	249.48	0.10	
2,271.00	0.44	224.18	2,270.58	-15.33	-32.58	15.27	95.00	235.29	0.23	
2,366.00	0.44	245.36	2,365.57	-15.74	-33.17	15.68	95.00	234.77	0.17	
2,460.00	0.35	244.39	2,459.57	-16.02	-33.75	15.96	94.00	244.93	0.10	
2,555.00	0.44	275.15	2,554.57	-16.11	-34.38	16.05	95.00	261.56	0.24	
2,650.00	0.62	275.06	2,649.56	-16.03	-35.25	15.97	95.00	275.10	0.19	



Wellbenders

End Of Well Report

Company:	XTO Energy	Local Co-ordinate Reference:	Well #703H
Project:	Eddy County, NM (Nad-27 / East Zone)	TVD Reference:	RKB = 24' @ 3383.00usft
Site:	PLU 29 Big Sinks	MD Reference:	RKB = 24' @ 3383.00usft
Well:	#703H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	WBDS_SQL_2

Survey									
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	V. Sec (usft)	CL (usft)	CL Azi (°)	DLeg (°/100ft)
2,744.00	0.62	270.85	2,743.56	-15.98	-36.27	15.92	94.00	272.95	0.05
2,839.00	0.57	261.88	2,838.55	-16.04	-37.25	15.97	95.00	266.55	0.11
2,934.00	0.70	254.06	2,933.55	-16.26	-38.28	16.20	95.00	257.57	0.16
3,028.00	0.79	251.16	3,027.54	-16.63	-39.44	16.56	94.00	252.52	0.10
3,122.00	0.75	255.29	3,121.53	-17.00	-40.65	16.93	94.00	253.17	0.07
3,216.00	0.75	254.50	3,215.52	-17.32	-41.84	17.24	94.00	254.90	0.01
3,310.00	0.88	258.01	3,309.51	-17.63	-43.14	17.56	94.00	256.40	0.15
3,405.00	0.88	259.24	3,404.50	-17.92	-44.57	17.84	95.00	258.62	0.02
3,500.00	0.70	249.40	3,499.49	-18.26	-45.83	18.18	95.00	254.88	0.24
3,594.00	0.03	233.84	3,593.49	-18.48	-46.38	18.40	94.00	248.77	0.71
3,688.00	1.01	48.48	3,687.49	-17.94	-45.78	17.86	94.00	48.32	1.11
3,782.00	1.54	59.91	3,781.46	-16.76	-44.07	16.68	94.00	55.39	0.62
3,877.00	1.36	82.85	3,876.43	-15.98	-41.85	15.91	95.00	70.66	0.63
3,971.00	1.49	96.29	3,970.40	-15.97	-39.53	15.90	94.00	89.88	0.38
4,025.00	1.41	97.61	4,024.39	-16.14	-38.17	16.07	54.00	96.93	0.16
4,170.00	1.36	96.91	4,169.35	-16.58	-34.69	16.52	145.00	97.27	0.04
4,263.00	1.23	103.33	4,262.32	-16.94	-32.63	16.89	93.00	99.96	0.21
4,357.00	0.13	25.54	4,356.31	-17.08	-31.60	17.03	94.00	97.56	1.29
4,451.00	0.53	276.38	4,450.31	-16.94	-31.98	16.88	94.00	290.52	0.62
4,546.00	0.53	256.69	4,545.31	-16.99	-32.85	16.93	95.00	266.54	0.19
4,640.00	0.66	251.42	4,639.30	-17.26	-33.78	17.20	94.00	253.77	0.15
4,734.00	1.14	286.84	4,733.29	-17.16	-35.19	17.10	94.00	274.00	0.76
4,829.00	2.46	284.38	4,828.24	-16.38	-38.07	16.32	95.00	285.16	1.39
4,922.00	3.16	277.88	4,921.13	-15.54	-42.55	15.46	93.00	280.73	0.83
5,017.00	4.18	275.68	5,015.94	-14.83	-48.58	14.75	95.00	276.63	1.08
5,111.00	4.84	272.60	5,109.64	-14.32	-55.95	14.22	94.00	274.03	0.75
5,205.00	4.26	272.69	5,203.35	-13.97	-63.40	13.86	94.00	272.64	0.62



Wellbenders

End Of Well Report

Company:	XTO Energy	Local Co-ordinate Reference:	Well #703H
Project:	Eddy County, NM (Nad-27 / East Zone)	TVD Reference:	RKB = 24' @ 3383.00usft
Site:	PLU 29 Big Sinks	MD Reference:	RKB = 24' @ 3383.00usft
Well:	#703H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	WBDS_SQL_2

Survey									
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	V. Sec (usft)	CL (usft)	CL Azi (°)	DLeg (°/100ft)
5,299.00	4.13	272.60	5,297.10	-13.65	-70.27	13.53	94.00	272.65	0.14
5,394.00	4.35	270.93	5,391.84	-13.44	-77.29	13.31	95.00	271.74	0.27
5,488.00	4.31	269.61	5,485.57	-13.41	-84.39	13.26	94.00	270.27	0.11
5,581.00	4.40	271.28	5,578.30	-13.35	-91.45	13.19	93.00	270.45	0.17
5,675.00	4.26	263.11	5,672.03	-13.69	-98.52	13.52	94.00	267.26	0.67
5,769.00	4.26	258.19	5,765.77	-14.82	-105.40	14.64	94.00	260.65	0.39
5,864.00	4.04	256.08	5,860.52	-16.35	-112.11	16.15	95.00	257.16	0.28
5,957.00	4.22	255.29	5,953.28	-18.01	-118.60	17.80	93.00	255.68	0.20
6,050.00	4.04	253.53	6,046.04	-19.80	-125.05	19.59	93.00	254.43	0.24
6,145.00	4.18	253.00	6,140.80	-21.77	-131.57	21.54	95.00	253.26	0.15
6,239.00	4.09	253.97	6,234.55	-23.69	-138.07	23.45	94.00	253.48	0.12
6,334.00	4.18	254.06	6,329.30	-25.58	-144.65	25.33	95.00	254.02	0.09
6,427.00	4.57	251.33	6,422.03	-27.70	-151.42	27.43	93.00	252.63	0.48
6,520.00	5.05	253.27	6,514.70	-30.06	-158.85	29.78	93.00	252.35	0.54
6,615.00	4.70	249.84	6,609.36	-32.61	-166.51	32.31	95.00	251.62	0.48
6,709.00	4.79	253.62	6,703.04	-35.04	-173.89	34.74	94.00	251.75	0.35
6,803.00	4.75	254.76	6,796.71	-37.17	-181.41	36.85	94.00	254.19	0.11
6,896.00	5.41	254.06	6,889.35	-39.39	-189.34	39.05	93.00	254.39	0.71
6,991.00	4.97	254.41	6,983.96	-41.72	-197.61	41.38	95.00	254.23	0.46
7,085.00	5.01	252.48	7,077.60	-44.05	-205.45	43.69	94.00	253.44	0.18
7,180.00	4.92	252.30	7,172.25	-46.54	-213.28	46.17	95.00	252.39	0.10
7,275.00	4.92	252.30	7,266.90	-49.02	-221.04	48.63	95.00	252.30	0.00
7,370.00	4.75	250.72	7,361.56	-51.55	-228.64	51.15	95.00	251.52	0.23
7,464.00	5.05	255.82	7,455.21	-53.85	-236.32	53.44	94.00	253.35	0.56
7,558.00	5.19	259.16	7,548.84	-55.66	-244.51	55.24	94.00	257.51	0.35
7,653.00	5.05	255.46	7,643.46	-57.52	-252.78	57.08	95.00	257.34	0.38
7,770.00	4.70	252.12	7,760.04	-60.29	-262.32	59.83	117.00	253.85	0.39



Wellbenders End Of Well Report

Company:	XTO Energy	Local Co-ordinate Reference:	Well #703H
Project:	Eddy County, NM (Nad-27 / East Zone)	TVD Reference:	RKB = 24' @ 3383.00usft
Site:	PLU 29 Big Sinks	MD Reference:	RKB = 24' @ 3383.00usft
Well:	#703H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	WBDS_SQL_2

Survey									
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	V. Sec (usft)	CL (usft)	CL Azi (°)	DLeg (°/100ft)
7,842.00	4.75	246.50	7,831.79	-62.38	-267.86	61.91	72.00	249.30	0.65
7,937.00	4.84	253.62	7,926.46	-65.08	-275.32	64.60	95.00	250.09	0.63
8,030.00	4.75	260.91	8,019.14	-66.79	-282.88	66.30	93.00	257.23	0.66
8,124.00	4.31	260.30	8,112.84	-68.00	-290.21	67.50	94.00	260.62	0.47
8,219.00	4.40	260.91	8,207.57	-69.18	-297.33	68.66	95.00	260.61	0.11
8,313.00	5.10	264.52	8,301.25	-70.15	-305.05	69.62	94.00	262.85	0.81
8,407.00	5.27	257.57	8,394.86	-71.48	-313.42	70.93	94.00	260.99	0.69
8,501.00	5.05	252.48	8,488.48	-73.65	-321.58	73.09	94.00	255.08	0.54
8,594.00	5.23	245.36	8,581.11	-76.65	-329.34	76.08	93.00	248.86	0.71
8,688.00	4.22	236.92	8,674.79	-80.33	-336.13	79.74	94.00	241.59	1.30
8,782.00	3.34	235.16	8,768.58	-83.78	-341.27	83.18	94.00	236.14	0.94
8,876.00	3.21	238.50	8,862.43	-86.72	-345.77	86.11	94.00	236.80	0.25
8,970.00	2.64	229.01	8,956.31	-89.51	-349.64	88.90	94.00	234.22	0.79
9,063.00	1.80	193.68	9,049.24	-92.34	-351.61	91.72	93.00	214.79	1.68
9,157.00	0.70	159.49	9,143.22	-94.31	-351.75	93.70	94.00	184.29	1.36
9,252.00	0.84	80.03	9,238.21	-94.73	-350.87	94.12	95.00	115.44	1.04
9,347.00	0.84	48.39	9,333.20	-94.15	-349.66	93.54	95.00	64.21	0.48
9,441.00	1.10	35.91	9,427.19	-92.96	-348.61	92.35	94.00	41.31	0.35
9,534.00	1.27	33.10	9,520.17	-91.38	-347.53	90.77	93.00	34.40	0.19
9,628.00	1.23	27.30	9,614.15	-89.61	-346.50	89.00	94.00	30.25	0.14
9,721.00	1.32	15.96	9,707.12	-87.69	-345.74	87.09	93.00	21.43	0.29
9,815.00	1.19	17.63	9,801.10	-85.72	-345.15	85.12	94.00	16.75	0.14
9,909.00	0.79	358.30	9,895.09	-84.14	-344.87	83.54	94.00	9.94	0.55
10,004.00	0.40	27.92	9,990.08	-83.19	-344.74	82.59	95.00	8.16	0.51
10,098.00	0.35	116.51	10,084.08	-83.03	-344.33	82.43	94.00	68.49	0.56
10,192.00	0.75	162.12	10,178.08	-83.74	-343.88	83.14	94.00	148.01	0.60
10,286.00	1.05	121.34	10,272.07	-84.78	-342.96	84.18	94.00	138.19	0.73



Wellbenders End Of Well Report

Company:	XTO Energy	Local Co-ordinate Reference:	Well #703H
Project:	Eddy County, NM (Nad-27 / East Zone)	TVD Reference:	RKB = 24' @ 3383.00usft
Site:	PLU 29 Big Sinks	MD Reference:	RKB = 24' @ 3383.00usft
Well:	#703H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	WBDS_SQL_2

Survey									
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	V. Sec (usft)	CL (usft)	CL Azi (°)	DLeg (°/100ft)
10,380.00	1.23	127.14	10,366.05	-85.83	-341.42	85.24	94.00	124.47	0.23
10,476.00	1.54	159.05	10,462.02	-87.66	-340.14	87.07	96.00	144.93	0.85
10,571.00	1.10	148.06	10,556.99	-89.63	-339.20	89.04	95.00	154.47	0.53
10,658.00	0.92	148.85	10,643.98	-90.93	-338.39	90.34	87.00	148.42	0.21
10,813.00	4.54	174.41	10,798.78	-98.11	-337.15	97.52	155.00	170.18	2.41
10,844.00	6.21	175.46	10,829.65	-101.00	-336.90	100.41	31.00	175.02	5.40
10,876.00	7.49	181.07	10,861.42	-104.81	-336.80	104.22	32.00	178.53	4.51
10,907.00	8.73	186.05	10,892.11	-109.17	-337.09	108.58	31.00	183.75	4.59
10,940.00	9.73	179.00	10,924.68	-114.45	-337.30	113.86	33.00	182.34	4.57
10,971.00	11.34	176.45	10,955.16	-120.11	-337.07	119.52	31.00	177.63	5.41
11,003.00	13.50	176.80	10,986.41	-126.98	-336.66	126.39	32.00	176.64	6.75
11,034.00	15.58	177.57	11,016.41	-134.75	-336.29	134.17	31.00	177.21	6.74
11,065.00	17.62	178.01	11,046.12	-143.60	-335.95	143.02	31.00	177.80	6.59
11,097.00	20.22	178.04	11,076.39	-153.97	-335.59	153.39	32.00	178.03	8.13
11,128.00	22.21	177.96	11,105.28	-165.18	-335.20	164.60	31.00	178.00	6.42
11,159.00	24.29	178.37	11,133.76	-177.41	-334.81	176.83	31.00	178.17	6.73
11,190.00	26.60	178.00	11,161.76	-190.72	-334.38	190.14	31.00	178.18	7.47
11,222.00	28.46	177.85	11,190.13	-205.50	-333.85	204.92	32.00	177.92	5.82
11,253.00	30.44	179.15	11,217.12	-220.74	-333.45	220.16	31.00	178.52	6.71
11,284.00	32.29	178.05	11,243.59	-236.87	-333.06	236.29	31.00	178.59	6.25
11,316.00	35.26	177.49	11,270.19	-254.64	-332.36	254.06	32.00	177.76	9.33
11,347.00	37.00	178.56	11,295.23	-272.91	-331.73	272.33	31.00	178.04	5.97
11,378.00	39.05	179.07	11,319.65	-292.00	-331.34	291.42	31.00	178.82	6.69
11,410.00	41.80	179.38	11,344.00	-312.75	-331.06	312.17	32.00	179.23	8.62
11,441.00	42.65	180.39	11,366.96	-333.58	-331.02	333.00	31.00	179.89	3.51
11,449.00	42.81	180.30	11,372.84	-339.01	-331.05	338.43	8.00	180.34	2.14
11,511.00	45.96	181.32	11,417.14	-382.36	-331.68	381.78	62.00	180.82	5.21



Wellbenders

End Of Well Report

Company:	XTO Energy	Local Co-ordinate Reference:	Well #703H
Project:	Eddy County, NM (Nad-27 / East Zone)	TVD Reference:	RKB = 24' @ 3383.00usft
Site:	PLU 29 Big Sinks	MD Reference:	RKB = 24' @ 3383.00usft
Well:	#703H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	WBDS_SQL_2

Survey									
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	V. Sec (usft)	CL (usft)	CL Azi (°)	DLeg (°/100ft)
11,543.00	51.36	178.44	11,438.27	-406.38	-331.60	405.80	32.00	179.82	18.17
11,574.00	56.89	176.59	11,456.43	-431.46	-330.50	430.88	31.00	177.48	18.48
11,605.00	61.25	175.71	11,472.36	-457.98	-328.71	457.41	31.00	176.14	14.27
11,636.00	65.33	178.41	11,486.29	-485.63	-327.30	485.06	31.00	177.08	15.29
11,667.00	68.55	178.90	11,498.44	-514.14	-326.63	513.57	31.00	178.66	10.49
11,699.00	71.83	180.68	11,509.28	-544.24	-326.53	543.67	32.00	179.80	11.51
11,730.00	77.58	178.52	11,517.45	-574.13	-326.31	573.56	31.00	179.59	19.73
11,761.00	83.28	179.45	11,522.61	-604.68	-325.77	604.11	31.00	178.99	18.62
11,792.00	87.02	180.37	11,525.23	-635.56	-325.73	634.99	31.00	179.91	12.42
11,837.00	89.79	181.89	11,526.48	-680.53	-326.61	679.96	45.00	181.13	7.02
11,887.00	89.40	182.05	11,526.83	-730.50	-328.33	729.93	50.00	181.97	0.84
11,981.00	87.75	181.12	11,529.17	-824.43	-330.93	823.85	94.00	181.59	2.01
12,075.00	86.20	180.92	11,534.13	-918.28	-332.60	917.70	94.00	181.02	1.66
12,169.00	87.80	179.66	11,539.05	-1,012.15	-333.08	1,011.56	94.00	180.29	2.17
12,264.00	87.07	180.37	11,543.30	-1,107.05	-333.10	1,106.47	95.00	180.01	1.07
12,358.00	88.11	180.01	11,547.25	-1,200.96	-333.41	1,200.38	94.00	180.19	1.17
12,452.00	86.96	180.29	11,551.30	-1,294.88	-333.66	1,294.29	94.00	180.15	1.26
12,547.00	88.19	176.02	11,555.32	-1,389.72	-330.60	1,389.14	95.00	178.15	4.67
12,641.00	92.28	177.45	11,554.93	-1,483.54	-325.25	1,482.97	94.00	176.73	4.61
12,736.00	91.67	177.99	11,551.66	-1,578.41	-321.47	1,577.85	95.00	177.72	0.86
12,830.00	89.82	178.70	11,550.44	-1,672.36	-318.76	1,671.80	94.00	178.35	2.11
12,924.00	89.87	179.12	11,550.69	-1,766.34	-316.97	1,765.78	94.00	178.91	0.45
13,019.00	89.54	179.95	11,551.18	-1,861.33	-316.20	1,860.78	95.00	179.53	0.94
13,113.00	89.20	178.58	11,552.21	-1,955.32	-314.99	1,954.77	94.00	179.27	1.50
13,207.00	86.93	178.21	11,555.39	-2,049.22	-312.36	2,048.67	94.00	178.40	2.45
13,301.00	88.45	179.65	11,559.18	-2,143.12	-310.61	2,142.58	94.00	178.93	2.23
13,396.00	90.94	181.36	11,559.68	-2,238.11	-311.45	2,237.56	95.00	180.51	3.18



Wellbenders

End Of Well Report

Company:	XTO Energy	Local Co-ordinate Reference:	Well #703H
Project:	Eddy County, NM (Nad-27 / East Zone)	TVD Reference:	RKB = 24' @ 3383.00usft
Site:	PLU 29 Big Sinks	MD Reference:	RKB = 24' @ 3383.00usft
Well:	#703H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	WBDS_SQL_2

Survey									
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	V. Sec (usft)	CL (usft)	CL Azi (°)	DLeg (°/100ft)
13,490.00	91.69	181.73	11,557.53	-2,332.05	-313.98	2,331.50	94.00	181.54	0.89
13,584.00	90.60	181.04	11,555.65	-2,426.00	-316.25	2,425.44	94.00	181.38	1.37
13,679.00	89.68	180.78	11,555.42	-2,520.99	-317.76	2,520.43	95.00	180.91	1.01
13,773.00	89.40	181.02	11,556.17	-2,614.97	-319.24	2,614.41	94.00	180.90	0.39
13,867.00	91.02	182.37	11,555.83	-2,708.93	-322.02	2,708.36	94.00	181.69	2.24
13,961.00	90.80	182.57	11,554.33	-2,802.83	-326.07	2,802.25	94.00	182.47	0.32
14,055.00	90.46	181.99	11,553.30	-2,896.75	-329.81	2,896.17	94.00	182.28	0.72
14,150.00	90.74	182.49	11,552.30	-2,991.67	-333.52	2,991.08	95.00	182.24	0.60
14,243.00	90.29	180.63	11,551.47	-3,084.62	-336.05	3,084.03	93.00	181.56	2.06
14,338.00	89.03	180.36	11,552.03	-3,179.62	-336.87	3,179.02	95.00	180.50	1.36
14,432.00	88.75	180.33	11,553.85	-3,273.60	-337.44	3,273.00	94.00	180.35	0.30
14,526.00	88.84	181.10	11,555.83	-3,367.57	-338.61	3,366.97	94.00	180.72	0.82
14,620.00	88.00	180.60	11,558.42	-3,461.52	-340.00	3,460.92	94.00	180.85	1.04
14,714.00	90.07	182.33	11,560.00	-3,555.47	-342.41	3,554.87	94.00	181.47	2.87
14,808.00	88.70	178.34	11,561.01	-3,649.44	-342.96	3,648.84	94.00	180.34	4.49
14,901.00	87.75	177.73	11,563.89	-3,742.34	-339.77	3,741.74	93.00	178.04	1.21
14,996.00	90.90	177.81	11,565.01	-3,837.25	-336.07	3,836.66	95.00	177.77	3.32
15,090.00	89.85	174.33	11,564.40	-3,931.01	-329.63	3,930.43	94.00	176.07	3.87
15,184.00	94.13	182.45	11,561.13	-4,024.82	-326.99	4,024.24	94.00	178.38	9.76
15,278.00	92.73	182.84	11,555.51	-4,118.55	-331.32	4,117.96	94.00	182.65	1.55
15,372.00	92.20	182.76	11,551.46	-4,212.35	-335.90	4,211.75	94.00	182.80	0.57
15,465.00	88.92	179.87	11,550.55	-4,305.29	-338.04	4,304.70	93.00	181.31	4.70
15,559.00	89.29	180.27	11,552.02	-4,399.28	-338.15	4,398.69	94.00	180.07	0.58
15,653.00	89.48	180.07	11,553.03	-4,493.28	-338.43	4,492.68	94.00	180.17	0.29
15,746.00	89.12	179.25	11,554.17	-4,586.27	-337.88	4,585.67	93.00	179.66	0.96
15,841.00	89.57	178.03	11,555.25	-4,681.23	-335.63	4,680.64	95.00	178.64	1.37
15,934.00	89.57	176.84	11,555.95	-4,774.13	-331.46	4,773.55	93.00	177.43	1.28



Wellbenders

End Of Well Report

Company:	XTO Energy	Local Co-ordinate Reference:	Well #703H
Project:	Eddy County, NM (Nad-27 / East Zone)	TVD Reference:	RKB = 24' @ 3383.00usft
Site:	PLU 29 Big Sinks	MD Reference:	RKB = 24' @ 3383.00usft
Well:	#703H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	WBDS_SQL_2

Survey									
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	V. Sec (usft)	CL (usft)	CL Azi (°)	DLeg (°/100ft)
16,029.00	90.18	176.34	11,556.16	-4,868.97	-325.81	4,868.39	95.00	176.59	0.83
16,123.00	90.29	176.41	11,555.77	-4,962.78	-319.87	4,962.21	94.00	176.37	0.14
16,217.00	88.87	176.10	11,556.46	-5,056.57	-313.73	5,056.02	94.00	176.26	1.55
16,311.00	88.75	176.11	11,558.41	-5,150.33	-307.35	5,149.79	94.00	176.10	0.13
16,405.00	91.13	176.15	11,558.51	-5,244.11	-301.00	5,243.58	94.00	176.13	2.53
16,499.00	94.53	182.34	11,553.87	-5,337.93	-299.76	5,337.40	94.00	179.24	7.51
16,593.00	90.97	183.01	11,549.36	-5,431.70	-304.14	5,431.16	94.00	182.68	3.85
16,687.00	88.78	180.70	11,549.56	-5,525.64	-307.18	5,525.10	94.00	181.86	3.39
16,781.00	95.99	182.36	11,545.65	-5,619.46	-309.69	5,618.91	94.00	181.53	7.87
16,875.00	93.60	182.19	11,537.80	-5,713.05	-313.40	5,712.50	94.00	182.27	2.55
16,968.00	92.65	182.21	11,532.73	-5,805.84	-316.97	5,805.28	93.00	182.20	1.02
17,063.00	91.47	181.49	11,529.31	-5,900.73	-320.03	5,900.16	95.00	181.85	1.45
17,158.00	89.51	179.84	11,528.50	-5,995.71	-321.14	5,995.14	95.00	180.66	2.70
17,251.00	90.01	182.29	11,528.89	-6,088.69	-322.86	6,088.12	93.00	181.07	2.69
17,345.00	90.63	185.52	11,528.36	-6,182.46	-329.26	6,181.87	94.00	183.90	3.50
17,439.00	92.09	186.83	11,526.13	-6,275.88	-339.37	6,275.28	94.00	186.17	2.09
17,533.00	89.59	185.07	11,524.76	-6,369.35	-349.11	6,368.73	94.00	185.95	3.25
17,627.00	83.87	179.78	11,530.12	-6,463.04	-353.09	6,462.42	94.00	182.43	8.28
17,721.00	83.30	175.83	11,540.63	-6,556.37	-349.52	6,555.75	94.00	177.81	4.22
17,815.00	88.70	175.92	11,547.18	-6,649.86	-342.78	6,649.25	94.00	175.88	5.75
17,909.00	91.53	177.00	11,546.99	-6,743.67	-336.97	6,743.07	94.00	176.46	3.22
18,003.00	91.27	177.41	11,544.69	-6,837.53	-332.39	6,836.94	94.00	177.21	0.52
18,097.00	89.37	176.71	11,544.17	-6,931.40	-327.57	6,930.82	94.00	177.06	2.15
18,191.00	88.53	176.25	11,545.89	-7,025.21	-321.80	7,024.63	94.00	176.48	1.02
18,284.00	86.85	177.18	11,549.64	-7,117.97	-316.47	7,117.41	93.00	176.71	2.06
18,379.00	88.89	178.57	11,553.17	-7,212.83	-312.95	7,212.28	95.00	177.88	2.60
18,454.00	88.61	178.44	11,554.81	-7,287.79	-311.00	7,287.24	75.00	178.51	0.41



Wellbenders

End Of Well Report

Company:	XTO Energy	Local Co-ordinate Reference:	Well #703H
Project:	Eddy County, NM (Nad-27 / East Zone)	TVD Reference:	RKB = 24' @ 3383.00usft
Site:	PLU 29 Big Sinks	MD Reference:	RKB = 24' @ 3383.00usft
Well:	#703H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	WBDS_SQL_2

Survey										
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	V. Sec (usft)	CL (usft)	CL Azi (°)	DLeg (°/100ft)	
18,525.00	88.09	177.68	11,556.85	-7,358.72	-308.60	7,358.17	71.00	178.06	1.30	
18,620.00	91.44	180.65	11,557.24	-7,453.68	-307.21	7,453.14	95.00	179.17	4.71	
18,714.00	91.97	180.82	11,554.44	-7,547.64	-308.42	7,547.09	94.00	180.73	0.59	
18,808.00	90.52	181.58	11,552.40	-7,641.59	-310.39	7,641.04	94.00	181.20	1.74	
18,901.00	90.85	181.09	11,551.29	-7,734.56	-312.55	7,734.00	93.00	181.34	0.64	
18,995.00	91.53	180.98	11,549.34	-7,828.52	-314.25	7,827.96	94.00	181.04	0.73	
19,089.00	90.94	182.08	11,547.31	-7,922.46	-316.76	7,921.90	94.00	181.53	1.33	
19,183.00	90.60	181.49	11,546.05	-8,016.41	-319.69	8,015.84	94.00	181.78	0.72	
19,233.00	90.27	181.48	11,545.67	-8,066.39	-320.98	8,065.82	50.00	181.48	0.66	
19,288.00	90.27	181.48	11,545.41	-8,121.37	-322.40	8,120.80	55.00	181.48	0.00	
Final Station Closure Distance= 8127.77 /Direction= 182.27 - Projection to Bit: 19288.00' MD/ 11545.41' TVD - TD: Latitude = 32.079761 / Longitude = -103.803375 - TD: Y= 393144.23 / X= 664142.80										

Design Annotations				
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
19,288.00	11,545.41	-8,121.37	-322.40	Final Station Closure Distance= 8127.77 /Direction= 182.27
19,288.00	11,545.41	-8,121.37	-322.40	Projection to Bit: 19288.00' MD/ 11545.41' TVD
19,288.00	11,545.41	-8,121.37	-322.40	TD: Latitude = 32.079761 / Longitude = -103.803375
19,288.00	11,545.41	-8,121.37	-322.40	TD: Y= 393144.23 / X= 664142.80

Checked By: _____	Approved By: _____	Date: _____
-------------------	--------------------	-------------



XTO Energy Inc
EMHC.W4.4A.293
22777 Springwoods Village Pkwy
Spring TX 77389-1425
832-625-4370 - Direct Phone
carlos.salinas@exxonmobil.com

February 4, 2021

New Mexico Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, New Mexico 87505

RE: **Waiver of Objection: Non-Standard Spacing Unit or Units**

Any combination of the N/2 of Sections 28 & 29, all of Sections 32 & 33, Township 25 South, Range 31 East, and all of Section 4, Township 26 South, Range 31 East, Eddy County, New Mexico. For the following wells:

- PLU 28 Big Sinks 102H, 104H, 106H, 108H, 121H, 122H, 123H, 124H, 125H, 126H, 127H, 128H, 701H, 703H, 705H, 707H, 901H, 903H, 905H, 907H (20 wells)
- PLU 29 Big Sinks 102H, 104H, 106H, 108H, 121H, 122H, 123H, 124H, 125H, 126H, 127H, 128H, 701H, 703H, 705H, 707H, 901H, 903H, 905H, 907H (20 wells)

To whom it may concern:

As operator of the Poker Lake Unit, and 100% owner of leasehold on adjoining sections, XTO Permian Operating, LLC ("XTO") hereby waives its own right to object to the application for an administrative order from the New Mexico Oil Conservation Division approving XTO's future application(s) for a non-standard spacing unit(s) comprised of any combination of the above described lands and wells in Eddy County, New Mexico.

Should you have any questions regarding XTO's self-waiver, please do not hesitate to contact the undersigned at the information provided.

Sincerely,

A handwritten signature in blue ink, appearing to read 'C.R. Salinas'.

C.R. Salinas
Sr. Landman – Delaware Basin
XTO Energy Inc.
832.625.4370
carlos.salinas@exxonmobil.com

Submit To Appropriate District Office Two Copies <u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 811 S. First St., Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505			Form C-105 Revised April 3, 2017					
WELL COMPLETION OR RECOMPLETION REPORT AND LOG								1. WELL API NO. 30-015-45919		
4. Reason for filing: ☒ COMPLETION REPORT (Fill in boxes #1 through #31 for State and Fee wells only) ☐ C-144 CLOSURE ATTACHMENT (Fill in boxes #1 through #9, #15 Date Rig Released and #32 and/or #33; attach this and the plat to the C-144 closure report in accordance with 19.15.17.13.K NMAC)								5. Lease Name or Unit Agreement Name POKER LAKE UNIT 29 BS		
								6. Well Number: 703H		
7. Type of Completion: ☒ NEW WELL ☐ WORKOVER ☐ DEEPENING ☐ PLUGBACK ☐ DIFFERENT RESERVOIR ☐ OTHER										
8. Name of Operator XTO ENERGY, INC						9. OGRID 373075				
10. Address of Operator 6401 HOLIDAY HILL RD BLDG #5, MIDLAND TX 79707						11. Pool name or Wildcat Purple Sage Wolfcamp (Gas)				
12. Location	Unit Ltr	Section	Township	Range	Lot	Feet from the	N/S Line	Feet from the	E/W Line	County
Surface:	F	29	25S	31E		2310	North	1920	West	Eddy
BH:	N	32	25S	31E		194	South	1587	West	Eddy
13. Date Spudded 11/29/2019	14. Date T.D. Reached 12/31/2020		15. Date Rig Released 1/5/2020			16. Date Completed (Ready to Produce) 1/12/2021		17. Elevations (DF and RKB, RT, GR, etc.) 3359' GL		
18. Total Measured Depth of Well 19,288'			19. Plug Back Measured Depth 19,286'			20. Was Directional Survey Made? Yes		21. Type Electric and Other Logs Run CBL		
22. Producing Interval(s), of this completion - Top, Bottom, Name 11,850 - 19,126 Purple Sage; Wolfcamp (Gas)										
23. CASING RECORD (Report all strings set in well)										
CASING SIZE		WEIGHT LB./FT.		DEPTH SET		HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED
13 3/8"		54.5		945'		17 1/2"		1215		
9 5/8"		40		4100'		12 1/4"		1663		
7"		32		11,500'		8 3/4"		1626		
4 1/2"		13.5		19,288		6"		659		
24. LINER RECORD										
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN		25. TUBING RECORD				
						SIZE		DEPTH SET	PACKER SET	
						2 7/8"		10,676	10,661	
26. Perforation record (interval, size, and number) 11,850 - 19,126 4spf, 864 Total Shots 36 stages						27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.				
						DEPTH INTERVAL		AMOUNT AND KIND MATERIAL USED		
						11,850 - 19,126		403,484 bbl fluid + 18,399,770 lbs proppant		
28. PRODUCTION										
Date First Production 01/13/2021		Production Method (Flowing, gas lift, pumping - Size and type pump) Flowing				Well Status (Prod. or Shut-in) Producing				
Date of Test 1/15/2021	Hours Tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl 1242	Gas - MCF 7761	Water - Bbl. 4968	Gas - Oil Ratio 6249			
Flow Tubing Press. 960	Casing Pressure 1260	Calculated 24-Hour Rate	Oil - Bbl. 1242	Gas - MCF 7761	Water - Bbl. 4968	Oil Gravity - API - (Corr.)				
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold								30. Test Witnessed By		
31. List Attachments C-104 NW, C-102 & Supplement, Directional Survey (Log uploaded to NMOCD)										
32. If a temporary pit was used at the well, attach a plat with the location of the temporary pit.								33. Rig Release Date:		
34. If an on-site burial was used at the well, report the exact location of the on-site burial:										
Latitude				Longitude				NAD83		
I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief										
Signature Cassie Evans			Printed Name Cassie Evans			Title Regulatory Analyst			Date 03/09/21	
E-mail Address cassie.evans@exxonmobil.com										

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well and not later than 60 days after completion of closure. When submitted as a completion report, this shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 11, 12 and 26-31 shall be reported for each zone.

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn A"
T. Salt 438'	T. Strawn	T. Kirtland	T. Penn. "B"
B. Salt 3124'	T. Atoka	T. Fruitland	T. Penn. "C"
T. Yates	T. Miss	T. Pictured Cliffs	T. Penn. "D"
T. 7 Rivers	T. Devonian	T. Cliff House	T. Leadville
T. Queen	T. Silurian	T. Menefee	T. Madison
T. Grayburg	T. Montoya	T. Point Lookout	T. Elbert
T. San Andres	T. Simpson	T. Mancos	T. McCracken
T. Glorieta	T. McKee	T. Gallup	T. Ignacio Otzte
T. Paddock	T. Ellenburger	Base Greenhorn	T. Granite
T. Blinebry	T. Gr. Wash	T. Dakota	
T. Tubb	T. Delaware Sand 3,342'	T. Morrison	
T. Drinkard	T. Bone Springs 7,019'	T. Todilto	
T. Abo	T. Rustler 239'	T. Entrada	
T. Wolfcamp 10,383'	T.	T. Wingate	
T. Penn	T.	T. Chinle	
T. Cisco (Bough C)	T.	T. Permian	

No. 1, from.....to.....

No. 2, from.....to.....

No. 3, from.....to.....

No. 4, from.....to.....

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

[illegible]

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 20347

CONDITIONS OF APPROVAL

Operator: XTO PERMIAN OPERATING LLC. BUILDING 5 MIDLAND, TX79707		6401 HOLIDAY HILL ROAD	OGRID: 373075	Action Number: 20347	Action Type: C-104C
OCD Reviewer ksimmons			Condition None		