

Form 3160-3
(June 2015)FORM APPROVED
OMB No. 1004-0137
Expires: January 31, 2018

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of work: ☐ DRILL ☐ REENTER 1b. Type of Well: ☐ Oil Well ☐ Gas Well ☐ Other 1c. Type of Completion: ☐ Hydraulic Fracturing ☐ Single Zone ☐ Multiple Zone		5. Lease Serial No. 6. If Indian, Allottee or Tribe Name 7. If Unit or CA Agreement, Name and No. 8. Lease Name and Well No.
2. Name of Operator		9. API Well No. 30 015 48119
3a. Address	3b. Phone No. (include area code)	10. Field and Pool, or Exploratory
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface At proposed prod. zone		11. Sec., T. R. M. or Blk. and Survey or Area
14. Distance in miles and direction from nearest town or post office*		12. County or Parish
13. State		
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any)	16. No of acres in lease	17. Spacing Unit dedicated to this well
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft.	19. Proposed Depth	20. BLM/BIA Bond No. in file
21. Elevations (Show whether DF, KDB, RT, GL, etc.)	22. Approximate date work will start*	23. Estimated duration
24. Attachments		

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162.3-3 (as applicable)

- | | |
|---|---|
| 1. Well plat certified by a registered surveyor.
2. A Drilling Plan.
3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
5. Operator certification.
6. Such other site specific information and/or plans as may be requested by the BLM. |
|---|---|

25. Signature	Name (Printed/Typed)	Date
Title		
Approved by (Signature)	Name (Printed/Typed)	Date
Title		
Office		

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
 Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.



(Continued on page 2)

*(Instructions on page 2)

INSTRUCTIONS

GENERAL: This form is designed for submitting proposals to perform certain well operations, as indicated on Federal and Indian lands and leases for action by appropriate Federal agencies, pursuant to applicable Federal laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from local Federal offices.

ITEM I: If the proposal is to redrill to the same reservoir at a different subsurface location or to a new reservoir, use this form with appropriate notations. Consult applicable Federal regulations concerning subsequent work proposals or reports on the well.

ITEM 4: Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local Federal offices for specific instructions.

ITEM 14: Needed only when location of well cannot readily be found by road from the land or lease description. A plat, or plats, separate or on the reverse side, showing the roads to, and the surveyed location of, the well, and any other required information, should be furnished when required by Federal agency offices.

ITEMS 15 AND 18: If well is to be, or has been directionally drilled, give distances for subsurface location of hole in any present or objective productive zone.

ITEM 22: Consult applicable Federal regulations, or appropriate officials, concerning approval of the proposal before operations are started.

ITEM 24: If the proposal will involve hydraulic fracturing operations, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The Privacy Act of 1974 and regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 25 U.S.C. 396; 43 CFR 3160

PRINCIPAL PURPOSES: The information will be used to: (1) process and evaluate your application for a permit to drill a new oil, gas, or service well or to reenter a plugged and abandoned well; and (2) document, for administrative use, information for the management, disposal and use of National Resource Lands and resources including (a) analyzing your proposal to discover and extract the Federal or Indian resources encountered; (b) reviewing procedures and equipment and the projected impact on the land involved; and (c) evaluating the effects of the proposed operation on the surface and subsurface water and other environmental impacts.

ROUTINE USE: Information from the record and/or the record will be transferred to appropriate Federal, State, and local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecution, in connection with congressional inquiries and for regulatory responsibilities.

EFFECT OF NOT PROVIDING INFORMATION: Filing of this application and disclosure of the information is mandatory only if you elect to initiate a drilling or reentry operation on an oil and gas lease.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM connects this information to an evaluation of the technical, safety, and environmental factors involved with drilling for oil and/or gas on Federal and Indian oil and gas leases. This information will be used to analyze and approve applications. Response to this request is mandatory only if the operator elects to initiate drilling or reentry operations on an oil and gas lease. The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Connection Clearance Officer (WO-630), 1849 C Street, N.W., Mail Stop 401 LS, Washington, D.C. 20240.

Additional Operator Remarks

Location of Well

0. SHL: SWNW / 1864 FNL / 236 FWL / TWSP: 19S / RANGE: 30E / SECTION: 32 / LAT: 32.6190543 / LONG: -104.0019877 (TVD: 0 feet, MD: 0 feet)

PPP: SENW / 1980 FNL / 1321 FWL / TWSP: 19S / RANGE: 30E / SECTION: 33 / LAT: 32.6186993 / LONG: -103.9812831 (TVD: 9542 feet, MD: 15761 feet)

PPP: SWNW / 1980 FNL / 0 FWL / TWSP: 19S / RANGE: 30E / SECTION: 33 / LAT: 32.6187075 / LONG: -103.9855759 (TVD: 9515 feet, MD: 14439 feet)

PPP: SWNW / 1980 FNL / 100 FWL / TWSP: 19S / RANGE: 30E / SECTION: 32 / LAT: 32.618738 / LONG: -104.0024296 (TVD: 9292 feet, MD: 9350 feet)

BHL: SENE / 1980 FNL / 10 FEL / TWSP: 19S / RANGE: 30E / SECTION: 33 / LAT: 32.6186742 / LONG: -103.9684372 (TVD: 9621 feet, MD: 19717 feet)

BLM Point of Contact

Name: Gavin Mickwee

Title: Land Law Examiner

Phone: (575) 234-5972

Email: gmickwee@blm.gov

Review and Appeal Rights

A person contesting a decision shall request a State Director review. This request must be filed within 20 working days of receipt of the Notice with the appropriate State Director (see 43 CFR 3165.3). The State Director review decision may be appealed to the Interior Board of Land Appeals, 801 North Quincy Street, Suite 300, Arlington, VA 22203 (see 43 CFR 3165.4). Contact the above listed Bureau of Land Management office for further information.

DISTRICT I
1625 N. French Dr., Hobbs, N.M. 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

DISTRICT II
811 S. First St., Artesia, N.M. 88210
Phone: (575) 748-1283 Fax: (575) 748-9720

DISTRICT III
1000 Rio Brazos Rd., Aztec, N.M. 87410
Phone: (505) 334-6178 Fax: (505) 334-6170

DISTRICT IV
1220 S. St. Francis Dr., Santa Fe, N.M. 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, N.M. 87505

Form C-102

Revised August 1, 2011

Submit one copy to appropriate
District Office

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

¹ API Number 30-015 48119	² Pool Code 49622	³ Pool Name Parkway; Bone Spring
⁴ Property Code 330007	⁵ Property Name Crazy Horse 32 State Fed Com	
⁷ OGRID No. 371449	⁶ Operator Name Colgate Operating, LLC	⁸ Well Number 132H
		⁹ Elevation 3319

¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
E	32	19 S	30 E		1864	North	236	West	Eddy

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
H	33	19 S	30 E		1980	North	10	East	Eddy

¹² Dedicated Acres 320	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.
---	-------------------------------	----------------------------------	-------------------------

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

16

Legend:

- = Surface Location
- = Bottom Hole Location
- △ = First Take Point (FTP)
- = Last Take Point (LTP)
- ⊕ = Found 1916 USGLO Brass Cap
- ⊙ = Found Monument

BOTTOM HOLE LOCATION
NAD 83 NMSPC ZONE 3001
Y= 588997.32 N
X= 653685.16 E
LAT.= 32.6186742° N
LONG.= 103.9684372° W

17 OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

Mikah Thomas 10/14/2020
Signature Date
Mikah Thomas
Printed Name
mthomas@colgateenergy.com
E-mail Address

18 SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

9/03/20
Date of Survey
Signature and Seal of Professional Surveyor
MARSHALL W. LINDEEN
NEW MEXICO
17078
9-26-20
PROFESSIONAL SURVEYOR

Certificate Number

16

Legend:

- = Surface Location
- = Bottom Hole Location
- △ = First Take Point (FTP)
- = Last Take Point (LTP)
- ⊕ = Found 1916 USGLO Brass Cap
- ⊙ = Found Monument

BOTTOM HOLE LOCATION
NAD 83 NMSPC ZONE 3001
Y= 588997.32 N
X= 653685.16 E
LAT.= 32.6186742° N
LONG.= 103.9684372° W

SURFACE LOCATION
NAD 83 NMSPC ZONE 3001
Y= 589101.76 N
X= 643354.82 E
LAT.= 32.6190543° N
LONG.= 104.0019877° W

FIRST TAKE POINT
NAD 83 NMSPC ZONE 3001
1980' FNL, 100' FWL
SEC. 32, T19S, R30E
Y= 588986.27 N
X= 643219.14 E
LAT.= 32.6187380° N
LONG.= 104.0024296° W

LAST TAKE POINT
NAD 83 NMSPC ZONE 3001
1980' FNL, 100' FEL
SEC. 33, T19S, R30E
Y= 588997.18 N
X= 653595.16 E
LAT.= 32.6186747° N
LONG.= 103.9687295° W

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Submit Original
to Appropriate
District Office

GAS CAPTURE PLAN

Date: 08/25/2020

☒ Original Operator & OGRID No.: Colgate Operating, LLC (371449)
☐ Amended - Reason for Amendment: _____

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

Well(s)/Production Facility – Name of facility

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Crazy Horse 32 State Fed Com 132H	30-015					

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to LM Touchdown, LLC and will be connected to LM Touchdown, LLC low/high pressure gathering system located in Eddy County, New Mexico. It will require 10' of pipeline to connect the facility to low/high pressure gathering system. Colgate Operating, LLC provides (periodically) to LM Touchdown, LLC a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, Colgate Operating, LLC and LM Touchdown, LLC have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at LM Touchdown, LLC Processing Plant located in Sec. 22, Twn. 19S Rng. 28E Eddy County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to production facilities. During flowback, the fluids and sand content will be monitored. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on LM Touchdown, LLC system at that time. Based on current information, it is Colgate Operating, LLC belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation – On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas – On lease
 - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines

- NGL Removal – On lease
 - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines

Drilling Program**Colgate Energy**

Crazy Horse 32 State Fed Com 132H

1,864' FNL & 236' FWL (SHL)

Sec 32-T19S-R30E

Eddy County, New Mexico

The estimated tops of geologic formations are as follows:

Formation:	TVD	Subsea
Rustler	195	3150
Top of Salt	445	2900
Base of Salt	1345	2000
Yates	1495	1850
Capitan	1870	1475
Delaware Mountain Group	3465	-120
Lower Brushy Canyon*	5935	-2590
Bone Spring Lime	6195	-2850
1st Bone Spring Sand*	7525	-4180
2nd Bone Spring Sand*	8265	-4920
3rd Bone Spring Sand*	9160	-5815
Wolfcamp A*	9645	-6300

Formations anticipated to contain fresh water, oil or gas are as follows:

Water	Fresh water is anticipated at 65' and will be protected by setting a water protection string at 400' and cementing to surface.
Water	The Capitan Reef is anticipated to contain usable water and will be protected by setting an intermediate casing string at 3390' and cementing to surface using a stage tool and external casing packer.
Hydrocarbons	Oil and gas are anticipated in the above (*) formations. These zones will be protected by casing as necessary.

Proposed casing program is as follows:

Name	Hole Size	Casing Size	Weight & Grade	Thread Collar	Top Csg	Setting Depth	Collapse	Burst	Tension
Surface	24	18.625	87.5# J-55 (new)	BTC	0	400'	1.125	1.2	1.6
Intermediate I	17 1/2	13 3/8	54.5# J-55 (new)	BTC	0	1,700'	1.125	1.2	1.6
Intermediate II	12 1/4	9 5/8	36# J-55 (new)	BTC	0	3,390'	1.125	1.2	1.6
Production	8 3/4	5 1/2	20# HCP-110 (new)	CDC HTQ	0	19,716'	1.125	1.2	1.6

SF Values will meet or exceed

Proposed cementing program is as follows:

Name	Slurry	Sacks	Yield	Weight	Excess	Top Cement	Blend
Surface	Tail	515	1.8	13.5	100%	0'	Class C w/ salt, accelerator, extender and LCM additives
Intermediate I	Lead	745	2.19	12.7	100%	0'	Class C w/ salt, extender and LCM additives
	Tail	222	1.33	14.8	25%	1,360'	Class C w/ accelerator & LCM additives
Intermediate II	Lead	134	4.41	10.6	100%	1,770'	Class C w/ accelerator, extender and LCM additives
	Tail	200	1.33	14.8	25%	2,712'	Class C w/ accelerator & LCM additives
2nd Stage	Lead	102	4.41	10.6	100%	0'	Class C w/ accelerator, extender and LCM additives
	Tail	100	1.33	14.8	25%	1,092'	Class C w/ accelerator & LCM additives
Production	Tail	4273	1.24	14.2	20%	2,050'	Class H w/ Fluid Loss, Dispersant, Retarder & LCM additives

Proposed casing and cementing accessories are as follows: (Casing will be centralized per Onshore Order 2.III.B.1.f)

Surface:	1 centralizer 5' above shoe held in place with stop ring; 1 centralizer per joint for following 2 joints then every other joint to surface
Intermediate I:	2 centralizers on 1st joint, 1 centralizer on 2nd joint, 1 centralizer every 4th joint to surface
Intermediate II:	2 centralizers on 1st joint, 1 centralizer on 2nd joint, 1 centralizer every 4th joint to surface
	Stage tool and external casing packer will be placed at approximately 1770' to ensure intermediate casing string is adequately cemented.
Production:	2 centralizers on bottom joint, 1 centralizer on 2nd joint, 1 centralizer every 3rd joint to 2890'

Proposed pressure control equipment is as follows (see schematics below):

Well control equipment with working pressure ratings in excess of anticipated maximum surface pressure will be utilized for well control from drill out of surface casing to TMD. A diverter system will be installed on 18-5/8" casing once set & cemented. A 13-5/8" multi-bowl wellhead will be SOW installed to 13-3/8" casing once set & cemented. A 13-5/8" 10M BOP will be nipped up to the 13-5/8" multi-bowl wellhead through the completion of the drilling operation. A rotating head will also be installed and utilized as needed. All BOPE connections shall be flanged, welded or clamped. All choke lines shall be straight unless targeted with running tees or tee blocks are used, and choke lines shall be anchored to prevent whip and reduce vibrations. All valves in the choke line & the choke manifold shall be full opening as to not cause restrictions and to allow for straight fluid paths to minimize potential erosion. All gauges utilized in the well control system shall be of a type designed for drilling fluid service. A top drive inside BOP valve will be utilized at all times. Subs equipped with full opening valves sized to fit the drill pipe and collars will be available on the rig floor in the open position. The key to operate said valve equipped subs will be on the rig floor at all times. The accumulator system will have sufficient capacity to open the HCR and close all three sets of rams plus the annular preventer while retaining at least 300 psi above precharge on the closing manifold (accumulator system shall be capable of doing so without using the closing unit pumps). The fluid reservoir capacity will be double the usable fluid volume of the accumulator system capacity, and the fluid level will be maintained at the manufacturer's recommended level. Prior to connecting the closing unit to the BOP stack, an accumulator precharge pressure test shall be performed to ensure the precharge pressure is within 100 psi of the desired precharge pressure (only nitrogen gas will be used to precharge). Two independent power sources will be made available at all times to power the closing unit pumps so that the pumps can automatically start when the closing valve manifold pressure has decreased to the pre-set level. Closing unit pumps will be sized to allow opening of HCR and closing of annular preventer on 5" drill pipe achieving at least 200 psi above precharge pressure with the accumulator system isolated from service in less than two minutes. A valve shall be installed in the closing line as close to the annular preventer as possible to act as a locking device; the valve shall be maintained in the open position and shall be closed only when the power source for the accumulator system is inoperative. Remote controls capable of opening and closing all preventers & the HCR shall be readily accessible to the driller; master controls with the same capability will be operable at the accumulator. The wellhead will be a multi-bowl speed head allowing for hang-off of intermediate I casing & isolation of the 13-3/8" x 9-5/8" annulus without breaking the connection between the BOP & wellhead to install an additional casing head. A wear bushing will be installed & inspected frequently to guard against internal wear to wellhead.

A request for variance of pressure control equipment as follows:

1. Colgate Energy requests a variance to drill this well using a co-flex line between the BOP and choke manifold. Certification for proposed co-flex hose is attached. The hose is not required by the manufacturer to be anchored. In the event the specific hose is not available, one of equal or higher rating will be used.
2. Colgate Energy requests a variance to Onshore Order #2's requirement that a 2M system with annular preventer be installed prior to drilling of the surface casing shoe due to the shallow setting depth of the surface casing. The diverter system adequately meets the requirements for the preferred method for handling a well control event in a situation where the existing casing shoe is not adequate for a hard shut-in due to the likelihood of an underground blowout with the potential to breach surface.

BOPE will be tested per the following procedure:

Once surface casing is set and diverter system installed on 18-5/8" casing, pressure tests will be performed by a third party tester to 500 psi. After intermediate I casing is set and the BOPE installed, pressure tests of BOPE will be performed by a third party tester utilizing water and a test plug to 250 psi low and 10,000 psi high. To deem a pressure test successful, pressure must be maintained for ten minutes without any bleed-off. A valve on the wellhead below seat of test plug will be open at all time during BOPE tests to guard against damage to casing. The BOPE will be re-tested in this manner after any connection breaks or passage of allotted time (25 days). Any BOPE which fails to pass pressure tests after initial install will be replaced prior to drilling out of intermediate I casing shoe. If at any time a BOPE component cannot function to secure the hole, the hole shall be secured utilizing a retrievable packer, and the non-functioning BOPE component shall be repair or replaced. After repair or replacement, a pressure test of the repaired or replaced component and any connections broken to repair or replace the non-functioning component will be tested in the same manner as described for initial install of BOPE. The annular preventer will be function tested at least weekly, and the ram-type preventers will be function tested on each trip. BOPE pit level drills will be conducted weekly with each drilling crews. All pressure tests performed on BOPE and BOPE pit level drills will be logged in the drilling log. Isolation of 13-3/8" x 9-5/8" casing annulus shall be confirmed by pressure testing of wellhead sealing component after said sealing component is installed.

Each casing string will be tested once installed in the wellbore per the following procedure:

After cement has been allowed to sit undisturbed for eighteen hours and has reached a compressive strength of 500 psi, the 18-5/8" surface casing will be pressured to 1,500 psi and held for 30 minutes. Lab reports with the 500 psi compressive strength time for the cement will be onsite for review. A casing test will be deemed successful if test pressure does not decline more than 10% over the thirty minute period. The casing pressure test will be completed against the cement head. After cement has been allowed to sit undisturbed for eighteen hours and has reached a compressive strength of 500 psi, the 13-3/8" intermediate I casing will be pressured to 1,500 psi and held for 30 minutes. Lab reports with the 500 psi compressive strength time for the cement will be onsite for review. A casing test will be deemed successful if test pressure does not decline more than 10% over the thirty minute period. The casing pressure test will be completed against the blind rams of 13-5/8" 10M BOPE prior to PU tools to drill out. After cement has been allowed to sit undisturbed for eighteen hours and has reached a compressive strength of 500 psi, the 9-5/8" intermediate II casing will be pressured to 2,500 psi and held for 30 minutes. Lab reports with the 500 psi compressive strength time for the cement will be onsite for review. A casing test will be deemed successful if test pressure does not decline more than 10% over the thirty minute period. Casing pressure test will be completed against the lower pipe rams of 13-5/8" 10M BOPE immediately prior to drilling out float equipment. Casing pressure test on 5-1/2" production casing will occur more than 72 hours after cement is placed and reached ultimate compressive strength. Lab reports with the 500 psi compressive strength time for the cement will be onsite for review. A casing test will be deemed successful if test pressure does not decline more than 10% over the thirty minute period. Casing will be tested by pressuring up to 10,000 psi and holding pressure for 30 minutes prior to the beginning of perforating & stimulating operations.

Each casing string will be cemented per the following cementing procedure:

Cement will be placed on all casing strings utilizing the pump and plug method. A float will be installed in the casing shoe and float collar on all casing strings to hold cement in place once pumping is completed. A top plug will be utilized on all casing strings to prevent contamination of the cement by the displacement fluid. A preflush fluid will be pumped prior to cement to aid in removal of drilling mud from the wellbore, eliminate drilling mud contamination of the cement slurry and prepare the surface of both the wellbore and casing for cement.

Proposed mud system is as follows:

<u>Name</u>	<u>Hole Size</u>	<u>Mud Weight</u>	<u>Viscosity</u>	<u>Fluid Loss</u>	<u>Type Mud</u>
Surface	24"	8.6 - 9.0	28 - 34	NC	FW Spud Mud
Intermediate I	17-1/2"	10.0 - 10.2	30 - 32	NC	Brine Water
Intermediate II	12-1/4"	8.4 - 8.9	28 - 30	NC	Aerated Fresh Water
Production	8-3/4"	9.0 - 10.0	32 - 35	NC	Cut-brine poly-oil mud

All necessary mud products for weight addition and fluid loss control will be on location at all times. Mud program is subject to change due to hole conditions. The mud monitoring system is an electronic Pason system satisfying requirements of Onshore Order #1. Both visual and electronic mud monitoring equipment will be utilized to detect volume changes indicating loss or gain of circulating system fluid volume. Slow pump rates will be taken & recorded hourly in the drilling log. Mud engineer will perform tests and provide written report at least every 12 hours while circulating. A trip tank will be utilized and trip sheet will be recorded to ensure wellbore is taking proper fill or displacing proper fluid volume during all tripping operations. Gas detecting equipment will be utilized to monitor for hydrocarbon gas at the shakers while drilling and/or circulating. H2S monitoring equipment with both visual & auditory alarms will be installed and operational at the shakers, rig floor and cellar while drilling and/or circulating. A flare system with an effective method for ignition & discharge more than 100 feet from the wellbore will be utilized to gather and burn all gas; lines will be straight unless targeted with running tees. A mud gas separator will be installed and operable prior to drill out of surface casing.

Proposed testing, surveying, logging and coring program is as follows:

No open-hole logs are planned at this time. Directional surveys will be collected at no greater than 200' intervals while drilling through the MWD tools. A GR log will be collected while drilling through the MWD tools from intermediate casing to TD. No DSTs or cores are planned at this time. No CBL or temperature logs planned at this time. A formation integrity test (FIT) will be performed on all casing strings after BOPE is installed to at least 1 ppge over planned section mud weight after drilling ten feet of new hole.

Anticipated potential hazards are as follows:

No abnormal pressures or temperatures are expected. In accordance with Onshore Order No. 6, Colgate Energy does not anticipate that there will be enough H₂S from the surface to the Wolfcamp formations to meet the BLM's minimum requirements for the submission of an "H₂S Drilling Operation Plan" or "Public Protection Plan" for the drilling and completion of this well. Since we have an H₂S safety package on all wells, attached is an "H₂S Drilling Operations Plan". Adequate flare lines will be installed off the mud/gas separator where gas may be flared safely. All personnel will be familiar with all aspects of safe operation of equipment being used.

Estimated BHP: 8.3 lbs/gal gradient or less

Estimated BHT: 120° F

Aerate drilling well control plan is as follows:

Should a formation influx occur while aerate drilling, Colgate Energy's protocol will be to immediately remove the air supply from the stand pipe using the air manifold at the rig floor. This would allow the mud pumps to quickly fill the annulus of the wellbore with non-aerated drilling mud in order to significantly increase the hydrostatic barrier between the formation of influx and surface. In the event an additional influx is observed once a full hydrostatic column of drilling mud is in place, all well control practices and procedures will be identical to mud drilling, well control protocols. During BOP drills performed weekly with each rig crew, emphasis will be placed on well control situations occurring while aerate drilling (specifically identifying the steps at the air manifold required to remove the air injection from the standpipe to allow the mud pumps to fill the wellbore with non-aerated drilling mud in order to regain a full hydrostatic column).

Planned commencement of operations is as follows:

Road and location construction will begin after BLM approval of APD. Anticipated spud date as soon as approved. Drilling expected to take 30 days. If production casing is run an additional 60 days will be required to complete and construct surface facilities.



Colgate Energy

Eddy County, NM (N83-NME)

Crazy Horse 32 State Fed Com

Crazy Horse 32 State Fed Com 132H

Permit

Plan: ADP-Rev2 v3

Standard Planning Report

19 October, 2020



Planning Report

Database:	EDM 5000.14 Single User Db	Local Co-ordinate Reference:	Well Crazy Horse 32 State Fed Com 132H
Company:	Colgate Energy	TVD Reference:	3319+25 @ 3344.00usft
Project:	Eddy County, NM (N83-NME)	MD Reference:	3319+25 @ 3344.00usft
Site:	Crazy Horse 32 State Fed Com	North Reference:	Grid
Well:	Crazy Horse 32 State Fed Com 132H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Permit		
Design:	ADP-Rev2 v3		

Project	Eddy County, NM (N83-NME)		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site	Crazy Horse 32 State Fed Com				
Site Position:		Northing:	586,991.40 usft	Latitude:	32.61325351
From:	Map	Easting:	643,359.01 usft	Longitude:	-104.00199549
Position Uncertainty:	0.00 usft	Slot Radius:	13-3/16 "	Grid Convergence:	0.18 °

Well	Crazy Horse 32 State Fed Com 132H					
Well Position	+N/-S	2,110.36 usft	Northing:	589,101.76 usft	Latitude:	32.61905427
	+E/-W	-4.19 usft	Easting:	643,354.82 usft	Longitude:	-104.00198773
Position Uncertainty		0.00 usft	Wellhead Elevation:		Ground Level:	3,319.00 usft

Wellbore	Permit				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2020	9/27/2020	6.86	60.22	47,758.17784157

Design	ADP-Rev2 v3				
Audit Notes:	ADP-Rev2 v3 formation change -no charge 10/19/2020				
Version:		Phase:	PLAN	Tie On Depth:	0.00
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)	
	0.00	0.00	0.00	89.94	

Plan Survey Tool Program	Date	10/19/2020			
Depth From (usft)	Depth To (usft)	Survey (Wellbore)	Tool Name	Remarks	
1	0.00	19,716.52 ADP-Rev2 v3 (Permit)	OWSG MWD Rev 4		
			OWSG MWD - Standard		



Planning Report

Database:	EDM 5000.14 Single User Db	Local Co-ordinate Reference:	Well Crazy Horse 32 State Fed Com 132H
Company:	Colgate Energy	TVD Reference:	3319+25 @ 3344.00usft
Project:	Eddy County, NM (N83-NME)	MD Reference:	3319+25 @ 3344.00usft
Site:	Crazy Horse 32 State Fed Com	North Reference:	Grid
Well:	Crazy Horse 32 State Fed Com 132H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Permit		
Design:	ADP-Rev2 v3		

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
1,925.00	0.00	0.00	1,925.00	0.00	0.00	0.00	0.00	0.00	0.00	
2,095.20	2.55	238.11	2,095.14	-2.00	-3.22	1.50	1.50	0.00	238.11	
6,834.62	2.55	238.11	6,829.86	-113.54	-182.46	0.00	0.00	0.00	0.00	
7,004.82	0.00	0.00	7,000.00	-115.54	-185.68	1.50	-1.50	0.00	180.00	00-EON (CH32-132H)
8,871.82	0.00	0.00	8,867.00	-115.54	-185.68	0.00	0.00	0.00	0.00	
9,762.63	89.08	89.94	9,439.88	-114.95	378.09	10.00	10.00	10.10	89.94	
14,385.26	89.08	89.94	9,514.00	-110.07	5,000.12	0.00	0.00	0.00	0.00	03-V-5000-132H
14,396.62	88.85	89.94	9,514.21	-110.06	5,011.49	2.00	-2.00	0.00	-179.98	
19,386.26	88.85	89.94	9,614.00	-104.79	10,000.12	0.00	0.00	0.00	0.00	05-V-10000-132H
19,626.53	88.85	89.94	9,618.81	-104.54	10,240.34	0.00	0.00	0.00	0.00	06-LTP(CH32-132H)
19,716.55	88.85	89.94	9,620.61	-104.44	10,330.34	0.00	0.00	0.00	0.00	07-PBHL(CH32-132H)



Planning Report

Database:	EDM 5000.14 Single User Db	Local Co-ordinate Reference:	Well Crazy Horse 32 State Fed Com 132H
Company:	Colgate Energy	TVD Reference:	3319+25 @ 3344.00usft
Project:	Eddy County, NM (N83-NME)	MD Reference:	3319+25 @ 3344.00usft
Site:	Crazy Horse 32 State Fed Com	North Reference:	Grid
Well:	Crazy Horse 32 State Fed Com 132H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Permit		
Design:	ADP-Rev2 v3		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100.00	0.00	0.00	100.00	0.00	0.00	0.00	0.00	0.00	0.00
194.00	0.00	0.00	194.00	0.00	0.00	0.00	0.00	0.00	0.00
Rustler									
200.00	0.00	0.00	200.00	0.00	0.00	0.00	0.00	0.00	0.00
300.00	0.00	0.00	300.00	0.00	0.00	0.00	0.00	0.00	0.00
400.00	0.00	0.00	400.00	0.00	0.00	0.00	0.00	0.00	0.00
444.00	0.00	0.00	444.00	0.00	0.00	0.00	0.00	0.00	0.00
Top of Salt									
500.00	0.00	0.00	500.00	0.00	0.00	0.00	0.00	0.00	0.00
600.00	0.00	0.00	600.00	0.00	0.00	0.00	0.00	0.00	0.00
700.00	0.00	0.00	700.00	0.00	0.00	0.00	0.00	0.00	0.00
800.00	0.00	0.00	800.00	0.00	0.00	0.00	0.00	0.00	0.00
900.00	0.00	0.00	900.00	0.00	0.00	0.00	0.00	0.00	0.00
1,000.00	0.00	0.00	1,000.00	0.00	0.00	0.00	0.00	0.00	0.00
1,100.00	0.00	0.00	1,100.00	0.00	0.00	0.00	0.00	0.00	0.00
1,200.00	0.00	0.00	1,200.00	0.00	0.00	0.00	0.00	0.00	0.00
1,300.00	0.00	0.00	1,300.00	0.00	0.00	0.00	0.00	0.00	0.00
1,344.00	0.00	0.00	1,344.00	0.00	0.00	0.00	0.00	0.00	0.00
Base of Salt									
1,400.00	0.00	0.00	1,400.00	0.00	0.00	0.00	0.00	0.00	0.00
1,494.00	0.00	0.00	1,494.00	0.00	0.00	0.00	0.00	0.00	0.00
Yates									
1,500.00	0.00	0.00	1,500.00	0.00	0.00	0.00	0.00	0.00	0.00
1,600.00	0.00	0.00	1,600.00	0.00	0.00	0.00	0.00	0.00	0.00
1,700.00	0.00	0.00	1,700.00	0.00	0.00	0.00	0.00	0.00	0.00
1,800.00	0.00	0.00	1,800.00	0.00	0.00	0.00	0.00	0.00	0.00
1,869.00	0.00	0.00	1,869.00	0.00	0.00	0.00	0.00	0.00	0.00
Capitan									
1,900.00	0.00	0.00	1,900.00	0.00	0.00	0.00	0.00	0.00	0.00
1,925.00	0.00	0.00	1,925.00	0.00	0.00	0.00	0.00	0.00	0.00
Start Build 1.50									
2,000.00	1.13	238.11	2,000.00	-0.39	-0.63	-0.63	1.50	1.50	0.00
2,095.20	2.55	238.11	2,095.14	-2.00	-3.22	-3.22	1.50	1.50	0.00
Start 4739.42 hold at 2095.20 MD									
2,100.00	2.55	238.11	2,099.94	-2.12	-3.40	-3.40	0.00	0.00	0.00
2,200.00	2.55	238.11	2,199.84	-4.47	-7.18	-7.19	0.00	0.00	0.00
2,300.00	2.55	238.11	2,299.74	-6.82	-10.96	-10.97	0.00	0.00	0.00
2,400.00	2.55	238.11	2,399.64	-9.18	-14.75	-14.76	0.00	0.00	0.00
2,500.00	2.55	238.11	2,499.54	-11.53	-18.53	-18.54	0.00	0.00	0.00
2,600.00	2.55	238.11	2,599.44	-13.88	-22.31	-22.32	0.00	0.00	0.00
2,700.00	2.55	238.11	2,699.34	-16.24	-26.09	-26.11	0.00	0.00	0.00
2,800.00	2.55	238.11	2,799.24	-18.59	-29.87	-29.89	0.00	0.00	0.00
2,900.00	2.55	238.11	2,899.14	-20.94	-33.66	-33.68	0.00	0.00	0.00
3,000.00	2.55	238.11	2,999.05	-23.30	-37.44	-37.46	0.00	0.00	0.00
3,100.00	2.55	238.11	3,098.95	-25.65	-41.22	-41.25	0.00	0.00	0.00
3,200.00	2.55	238.11	3,198.85	-28.00	-45.00	-45.03	0.00	0.00	0.00
3,300.00	2.55	238.11	3,298.75	-30.36	-48.78	-48.82	0.00	0.00	0.00
3,400.00	2.55	238.11	3,398.65	-32.71	-52.57	-52.60	0.00	0.00	0.00
3,465.42	2.55	238.11	3,464.00	-34.25	-55.04	-55.08	0.00	0.00	0.00
DLWR Mnt. Group									
3,500.00	2.55	238.11	3,498.55	-35.06	-56.35	-56.38	0.00	0.00	0.00
3,600.00	2.55	238.11	3,598.45	-37.42	-60.13	-60.17	0.00	0.00	0.00



Planning Report

Database:	EDM 5000.14 Single User Db	Local Co-ordinate Reference:	Well Crazy Horse 32 State Fed Com 132H
Company:	Colgate Energy	TVD Reference:	3319+25 @ 3344.00usft
Project:	Eddy County, NM (N83-NME)	MD Reference:	3319+25 @ 3344.00usft
Site:	Crazy Horse 32 State Fed Com	North Reference:	Grid
Well:	Crazy Horse 32 State Fed Com 132H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Permit		
Design:	ADP-Rev2 v3		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
3,700.00	2.55	238.11	3,698.35	-39.77	-63.91	-63.95	0.00	0.00	0.00
3,800.00	2.55	238.11	3,798.25	-42.12	-67.69	-67.74	0.00	0.00	0.00
3,900.00	2.55	238.11	3,898.15	-44.48	-71.48	-71.52	0.00	0.00	0.00
4,000.00	2.55	238.11	3,998.05	-46.83	-75.26	-75.31	0.00	0.00	0.00
4,100.00	2.55	238.11	4,097.95	-49.18	-79.04	-79.09	0.00	0.00	0.00
4,200.00	2.55	238.11	4,197.85	-51.54	-82.82	-82.88	0.00	0.00	0.00
4,300.00	2.55	238.11	4,297.76	-53.89	-86.60	-86.66	0.00	0.00	0.00
4,400.00	2.55	238.11	4,397.66	-56.24	-90.39	-90.44	0.00	0.00	0.00
4,500.00	2.55	238.11	4,497.56	-58.60	-94.17	-94.23	0.00	0.00	0.00
4,600.00	2.55	238.11	4,597.46	-60.95	-97.95	-98.01	0.00	0.00	0.00
4,700.00	2.55	238.11	4,697.36	-63.30	-101.73	-101.80	0.00	0.00	0.00
4,800.00	2.55	238.11	4,797.26	-65.66	-105.51	-105.58	0.00	0.00	0.00
4,900.00	2.55	238.11	4,897.16	-68.01	-109.29	-109.37	0.00	0.00	0.00
5,000.00	2.55	238.11	4,997.06	-70.36	-113.08	-113.15	0.00	0.00	0.00
5,100.00	2.55	238.11	5,096.96	-72.72	-116.86	-116.93	0.00	0.00	0.00
5,200.00	2.55	238.11	5,196.86	-75.07	-120.64	-120.72	0.00	0.00	0.00
5,300.00	2.55	238.11	5,296.76	-77.42	-124.42	-124.50	0.00	0.00	0.00
5,400.00	2.55	238.11	5,396.66	-79.78	-128.20	-128.29	0.00	0.00	0.00
5,500.00	2.55	238.11	5,496.56	-82.13	-131.99	-132.07	0.00	0.00	0.00
5,600.00	2.55	238.11	5,596.47	-84.48	-135.77	-135.86	0.00	0.00	0.00
5,700.00	2.55	238.11	5,696.37	-86.84	-139.55	-139.64	0.00	0.00	0.00
5,800.00	2.55	238.11	5,796.27	-89.19	-143.33	-143.43	0.00	0.00	0.00
5,900.00	2.55	238.11	5,896.17	-91.54	-147.11	-147.21	0.00	0.00	0.00
5,937.87	2.55	238.11	5,934.00	-92.43	-148.55	-148.64	0.00	0.00	0.00
Lower Brushy Canyon									
6,000.00	2.55	238.11	5,996.07	-93.90	-150.90	-150.99	0.00	0.00	0.00
6,100.00	2.55	238.11	6,095.97	-96.25	-154.68	-154.78	0.00	0.00	0.00
6,198.13	2.55	238.11	6,194.00	-98.56	-158.39	-158.49	0.00	0.00	0.00
Bone Spring Lime									
6,200.00	2.55	238.11	6,195.87	-98.60	-158.46	-158.56	0.00	0.00	0.00
6,300.00	2.55	238.11	6,295.77	-100.96	-162.24	-162.35	0.00	0.00	0.00
6,400.00	2.55	238.11	6,395.67	-103.31	-166.02	-166.13	0.00	0.00	0.00
6,500.00	2.55	238.11	6,495.57	-105.66	-169.81	-169.92	0.00	0.00	0.00
6,600.00	2.55	238.11	6,595.47	-108.02	-173.59	-173.70	0.00	0.00	0.00
6,700.00	2.55	238.11	6,695.37	-110.37	-177.37	-177.49	0.00	0.00	0.00
6,800.00	2.55	238.11	6,795.27	-112.72	-181.15	-181.27	0.00	0.00	0.00
6,834.62	2.55	238.11	6,829.86	-113.54	-182.46	-182.58	0.00	0.00	0.00
Start Drop -1.50									
6,900.00	1.57	238.11	6,895.20	-114.78	-184.46	-184.58	1.50	-1.50	0.00
7,004.82	0.00	0.00	7,000.00	-115.54	-185.68	-185.80	1.50	-1.50	0.00
Start 1867.00 hold at 7004.82 MD - 00-EON (CH32-132H)									
7,100.00	0.00	0.00	7,095.18	-115.54	-185.68	-185.80	0.00	0.00	0.00
7,200.00	0.00	0.00	7,195.18	-115.54	-185.68	-185.80	0.00	0.00	0.00
7,300.00	0.00	0.00	7,295.18	-115.54	-185.68	-185.80	0.00	0.00	0.00
7,400.00	0.00	0.00	7,395.18	-115.54	-185.68	-185.80	0.00	0.00	0.00
7,500.00	0.00	0.00	7,495.18	-115.54	-185.68	-185.80	0.00	0.00	0.00
7,528.82	0.00	0.00	7,524.00	-115.54	-185.68	-185.80	0.00	0.00	0.00
1st Bone Spring Sand									
7,600.00	0.00	0.00	7,595.18	-115.54	-185.68	-185.80	0.00	0.00	0.00
7,700.00	0.00	0.00	7,695.18	-115.54	-185.68	-185.80	0.00	0.00	0.00
7,800.00	0.00	0.00	7,795.18	-115.54	-185.68	-185.80	0.00	0.00	0.00
7,900.00	0.00	0.00	7,895.18	-115.54	-185.68	-185.80	0.00	0.00	0.00
8,000.00	0.00	0.00	7,995.18	-115.54	-185.68	-185.80	0.00	0.00	0.00
8,100.00	0.00	0.00	8,095.18	-115.54	-185.68	-185.80	0.00	0.00	0.00



Planning Report

Database:	EDM 5000.14 Single User Db	Local Co-ordinate Reference:	Well Crazy Horse 32 State Fed Com 132H
Company:	Colgate Energy	TVD Reference:	3319+25 @ 3344.00usft
Project:	Eddy County, NM (N83-NME)	MD Reference:	3319+25 @ 3344.00usft
Site:	Crazy Horse 32 State Fed Com	North Reference:	Grid
Well:	Crazy Horse 32 State Fed Com 132H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Permit		
Design:	ADP-Rev2 v3		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
8,200.00	0.00	0.00	8,195.18	-115.54	-185.68	-185.80	0.00	0.00	0.00
8,268.82	0.00	0.00	8,264.00	-115.54	-185.68	-185.80	0.00	0.00	0.00
2nd Bone Spring SD									
8,300.00	0.00	0.00	8,295.18	-115.54	-185.68	-185.80	0.00	0.00	0.00
8,400.00	0.00	0.00	8,395.18	-115.54	-185.68	-185.80	0.00	0.00	0.00
8,500.00	0.00	0.00	8,495.18	-115.54	-185.68	-185.80	0.00	0.00	0.00
8,600.00	0.00	0.00	8,595.18	-115.54	-185.68	-185.80	0.00	0.00	0.00
8,700.00	0.00	0.00	8,695.18	-115.54	-185.68	-185.80	0.00	0.00	0.00
8,800.00	0.00	0.00	8,795.18	-115.54	-185.68	-185.80	0.00	0.00	0.00
8,871.82	0.00	0.00	8,867.00	-115.54	-185.68	-185.80	0.00	0.00	0.00
KOP: 8871.82' MD, -185.80' VS, 8867.00' TVD									
8,900.00	2.82	89.94	8,895.17	-115.54	-184.99	-185.11	10.00	10.00	0.00
8,950.00	7.82	89.94	8,944.94	-115.53	-180.35	-180.47	10.00	10.00	0.00
9,000.00	12.82	89.94	8,994.12	-115.52	-171.40	-171.52	10.00	10.00	0.00
9,050.00	17.82	89.94	9,042.33	-115.51	-158.20	-158.32	10.00	10.00	0.00
9,100.00	22.82	89.94	9,089.20	-115.49	-140.84	-140.96	10.00	10.00	0.00
9,150.00	27.82	89.94	9,134.38	-115.47	-119.46	-119.59	10.00	10.00	0.00
9,178.21	30.64	89.94	9,159.00	-115.46	-105.69	-105.81	10.00	10.00	0.00
3rd Bone Spring SD									
9,200.00	32.82	89.94	9,177.53	-115.44	-94.23	-94.35	10.00	10.00	0.00
9,250.00	37.82	89.94	9,218.31	-115.41	-65.34	-65.46	10.00	10.00	0.00
9,300.00	42.82	89.94	9,256.43	-115.38	-32.99	-33.11	10.00	10.00	0.00
9,350.00	47.82	89.94	9,291.57	-115.34	2.55	2.43	10.00	10.00	0.00
01-FTP (CH32-132H)									
9,400.00	52.82	89.94	9,323.49	-115.30	41.01	40.89	10.00	10.00	0.00
9,450.00	57.82	89.94	9,351.93	-115.26	82.12	82.00	10.00	10.00	0.00
9,500.00	62.82	89.94	9,376.68	-115.21	125.54	125.42	10.00	10.00	0.00
9,550.00	67.82	89.94	9,397.55	-115.16	170.96	170.84	10.00	10.00	0.00
9,600.00	72.82	89.94	9,414.39	-115.11	218.02	217.90	10.00	10.00	0.00
9,650.00	77.82	89.94	9,427.06	-115.06	266.38	266.26	10.00	10.00	0.00
9,700.00	82.82	89.94	9,435.46	-115.01	315.65	315.53	10.00	10.00	0.00
9,750.00	87.82	89.94	9,439.54	-114.96	365.47	365.35	10.00	10.00	0.00
9,762.63	89.08	89.94	9,439.88	-114.95	378.09	377.97	10.00	10.00	0.00
EOC: 9762.63' MD, 377.97' VS, 9439.88' TVD									
9,800.00	89.08	89.94	9,440.48	-114.91	415.46	415.34	0.00	0.00	0.00
9,900.00	89.08	89.94	9,442.09	-114.80	515.44	515.32	0.00	0.00	0.00
10,000.00	89.08	89.94	9,443.69	-114.69	615.43	615.31	0.00	0.00	0.00
10,100.00	89.08	89.94	9,445.29	-114.59	715.42	715.30	0.00	0.00	0.00
10,200.00	89.08	89.94	9,446.90	-114.48	815.40	815.28	0.00	0.00	0.00
10,300.00	89.08	89.94	9,448.50	-114.38	915.39	915.27	0.00	0.00	0.00
10,400.00	89.08	89.94	9,450.10	-114.27	1,015.38	1,015.26	0.00	0.00	0.00
10,500.00	89.08	89.94	9,451.71	-114.17	1,115.37	1,115.25	0.00	0.00	0.00
10,600.00	89.08	89.94	9,453.31	-114.06	1,215.35	1,215.23	0.00	0.00	0.00
10,700.00	89.08	89.94	9,454.91	-113.96	1,315.34	1,315.22	0.00	0.00	0.00
10,800.00	89.08	89.94	9,456.52	-113.85	1,415.33	1,415.21	0.00	0.00	0.00
10,900.00	89.08	89.94	9,458.12	-113.75	1,515.31	1,515.19	0.00	0.00	0.00
11,000.00	89.08	89.94	9,459.72	-113.64	1,615.30	1,615.18	0.00	0.00	0.00
11,100.00	89.08	89.94	9,461.33	-113.53	1,715.29	1,715.17	0.00	0.00	0.00
11,200.00	89.08	89.94	9,462.93	-113.43	1,815.28	1,815.16	0.00	0.00	0.00
11,300.00	89.08	89.94	9,464.53	-113.32	1,915.26	1,915.14	0.00	0.00	0.00
11,400.00	89.08	89.94	9,466.14	-113.22	2,015.25	2,015.13	0.00	0.00	0.00
11,500.00	89.08	89.94	9,467.74	-113.11	2,115.24	2,115.12	0.00	0.00	0.00
11,600.00	89.08	89.94	9,469.34	-113.01	2,215.22	2,215.10	0.00	0.00	0.00



Planning Report

Database:	EDM 5000.14 Single User Db	Local Co-ordinate Reference:	Well Crazy Horse 32 State Fed Com 132H
Company:	Colgate Energy	TVD Reference:	3319+25 @ 3344.00usft
Project:	Eddy County, NM (N83-NME)	MD Reference:	3319+25 @ 3344.00usft
Site:	Crazy Horse 32 State Fed Com	North Reference:	Grid
Well:	Crazy Horse 32 State Fed Com 132H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Permit		
Design:	ADP-Rev2 v3		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
11,700.00	89.08	89.94	9,470.95	-112.90	2,315.21	2,315.09	0.00	0.00	0.00	
11,800.00	89.08	89.94	9,472.55	-112.80	2,415.20	2,415.08	0.00	0.00	0.00	
11,884.93	89.08	89.94	9,473.91	-112.71	2,500.12	2,500.00	0.00	0.00	0.00	
02-V-2500-132H										
11,900.00	89.08	89.94	9,474.15	-112.69	2,515.19	2,515.07	0.00	0.00	0.00	
12,000.00	89.08	89.94	9,475.76	-112.59	2,615.17	2,615.05	0.00	0.00	0.00	
12,100.00	89.08	89.94	9,477.36	-112.48	2,715.16	2,715.04	0.00	0.00	0.00	
12,200.00	89.08	89.94	9,478.96	-112.37	2,815.15	2,815.03	0.00	0.00	0.00	
12,300.00	89.08	89.94	9,480.57	-112.27	2,915.13	2,915.01	0.00	0.00	0.00	
12,400.00	89.08	89.94	9,482.17	-112.16	3,015.12	3,015.00	0.00	0.00	0.00	
12,500.00	89.08	89.94	9,483.77	-112.06	3,115.11	3,114.99	0.00	0.00	0.00	
12,600.00	89.08	89.94	9,485.38	-111.95	3,215.09	3,214.98	0.00	0.00	0.00	
12,700.00	89.08	89.94	9,486.98	-111.85	3,315.08	3,314.96	0.00	0.00	0.00	
12,800.00	89.08	89.94	9,488.58	-111.74	3,415.07	3,414.95	0.00	0.00	0.00	
12,900.00	89.08	89.94	9,490.19	-111.64	3,515.06	3,514.94	0.00	0.00	0.00	
13,000.00	89.08	89.94	9,491.79	-111.53	3,615.04	3,614.92	0.00	0.00	0.00	
13,100.00	89.08	89.94	9,493.39	-111.43	3,715.03	3,714.91	0.00	0.00	0.00	
13,200.00	89.08	89.94	9,495.00	-111.32	3,815.02	3,814.90	0.00	0.00	0.00	
13,300.00	89.08	89.94	9,496.60	-111.21	3,915.00	3,914.89	0.00	0.00	0.00	
13,400.00	89.08	89.94	9,498.20	-111.11	4,014.99	4,014.87	0.00	0.00	0.00	
13,500.00	89.08	89.94	9,499.81	-111.00	4,114.98	4,114.86	0.00	0.00	0.00	
13,600.00	89.08	89.94	9,501.41	-110.90	4,214.97	4,214.85	0.00	0.00	0.00	
13,700.00	89.08	89.94	9,503.01	-110.79	4,314.95	4,314.83	0.00	0.00	0.00	
13,800.00	89.08	89.94	9,504.62	-110.69	4,414.94	4,414.82	0.00	0.00	0.00	
13,900.00	89.08	89.94	9,506.22	-110.58	4,514.93	4,514.81	0.00	0.00	0.00	
14,000.00	89.08	89.94	9,507.82	-110.48	4,614.91	4,614.80	0.00	0.00	0.00	
14,100.00	89.08	89.94	9,509.43	-110.37	4,714.90	4,714.78	0.00	0.00	0.00	
14,200.00	89.08	89.94	9,511.03	-110.27	4,814.89	4,814.77	0.00	0.00	0.00	
14,300.00	89.08	89.94	9,512.63	-110.16	4,914.88	4,914.76	0.00	0.00	0.00	
14,385.26	89.08	89.94	9,514.00	-110.07	5,000.12	5,000.00	0.00	0.00	0.00	
Start DLS 2.00 TFO -179.98 - 03-V-5000-132H										
14,396.62	88.85	89.94	9,514.21	-110.06	5,011.49	5,011.37	2.00	-2.00	0.00	
Start 4989.64 hold at 14396.62 MD										
14,400.00	88.85	89.94	9,514.27	-110.05	5,014.86	5,014.74	0.00	0.00	0.00	
14,438.59	88.85	89.94	9,515.04	-110.01	5,053.44	5,053.33	0.00	0.00	0.00	
Sec: 32.61870750, -103.98557590 - Sec: 14438.59' MD, 9515.04' TVD										
14,500.00	88.85	89.94	9,516.27	-109.95	5,114.84	5,114.72	0.00	0.00	0.00	
14,600.00	88.85	89.94	9,518.27	-109.84	5,214.82	5,214.70	0.00	0.00	0.00	
14,700.00	88.85	89.94	9,520.27	-109.74	5,314.80	5,314.68	0.00	0.00	0.00	
14,800.00	88.85	89.94	9,522.27	-109.63	5,414.78	5,414.66	0.00	0.00	0.00	
14,900.00	88.85	89.94	9,524.27	-109.53	5,514.76	5,514.64	0.00	0.00	0.00	
15,000.00	88.85	89.94	9,526.27	-109.42	5,614.74	5,614.62	0.00	0.00	0.00	
15,100.00	88.85	89.94	9,528.27	-109.32	5,714.72	5,714.60	0.00	0.00	0.00	
15,200.00	88.85	89.94	9,530.27	-109.21	5,814.70	5,814.58	0.00	0.00	0.00	
15,300.00	88.85	89.94	9,532.27	-109.10	5,914.68	5,914.56	0.00	0.00	0.00	
15,400.00	88.85	89.94	9,534.27	-109.00	6,014.66	6,014.54	0.00	0.00	0.00	
15,500.00	88.85	89.94	9,536.27	-108.89	6,114.64	6,114.52	0.00	0.00	0.00	
15,600.00	88.85	89.94	9,538.27	-108.79	6,214.62	6,214.50	0.00	0.00	0.00	
15,700.00	88.85	89.94	9,540.27	-108.68	6,314.60	6,314.48	0.00	0.00	0.00	
15,760.56	88.85	89.94	9,541.48	-108.62	6,375.15	6,375.03	0.00	0.00	0.00	
Fed Lease: 32.61869938, -103.98128316 - Fed Lease: 15760.56' MD, 6375.03' VS, 9541.48' TVD										
15,800.00	88.85	89.94	9,542.27	-108.58	6,414.58	6,414.46	0.00	0.00	0.00	
15,900.00	88.85	89.94	9,544.27	-108.47	6,514.56	6,514.44	0.00	0.00	0.00	



Planning Report

Database:	EDM 5000.14 Single User Db	Local Co-ordinate Reference:	Well Crazy Horse 32 State Fed Com 132H
Company:	Colgate Energy	TVD Reference:	3319+25 @ 3344.00usft
Project:	Eddy County, NM (N83-NME)	MD Reference:	3319+25 @ 3344.00usft
Site:	Crazy Horse 32 State Fed Com	North Reference:	Grid
Well:	Crazy Horse 32 State Fed Com 132H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Permit		
Design:	ADP-Rev2 v3		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
16,000.00	88.85	89.94	9,546.27	-108.37	6,614.54	6,614.42	0.00	0.00	0.00
16,100.00	88.85	89.94	9,548.27	-108.26	6,714.52	6,714.40	0.00	0.00	0.00
16,200.00	88.85	89.94	9,550.27	-108.15	6,814.50	6,814.38	0.00	0.00	0.00
16,300.00	88.85	89.94	9,552.27	-108.05	6,914.48	6,914.36	0.00	0.00	0.00
16,400.00	88.85	89.94	9,554.27	-107.94	7,014.46	7,014.34	0.00	0.00	0.00
16,500.00	88.85	89.94	9,556.27	-107.84	7,114.44	7,114.32	0.00	0.00	0.00
16,600.00	88.85	89.94	9,558.27	-107.73	7,214.42	7,214.30	0.00	0.00	0.00
16,700.00	88.85	89.94	9,560.27	-107.63	7,314.40	7,314.28	0.00	0.00	0.00
16,800.00	88.85	89.94	9,562.27	-107.52	7,414.38	7,414.26	0.00	0.00	0.00
16,885.76	88.85	89.94	9,563.99	-107.43	7,500.12	7,500.00	0.00	0.00	0.00
04-V-7500-132H									
16,900.00	88.85	89.94	9,564.27	-107.41	7,514.36	7,514.24	0.00	0.00	0.00
17,000.00	88.85	89.94	9,566.27	-107.31	7,614.34	7,614.22	0.00	0.00	0.00
17,100.00	88.85	89.94	9,568.27	-107.20	7,714.32	7,714.20	0.00	0.00	0.00
17,200.00	88.85	89.94	9,570.27	-107.10	7,814.30	7,814.18	0.00	0.00	0.00
17,300.00	88.85	89.94	9,572.27	-106.99	7,914.28	7,914.16	0.00	0.00	0.00
17,400.00	88.85	89.94	9,574.27	-106.89	8,014.26	8,014.14	0.00	0.00	0.00
17,500.00	88.85	89.94	9,576.27	-106.78	8,114.24	8,114.12	0.00	0.00	0.00
17,600.00	88.85	89.94	9,578.27	-106.68	8,214.22	8,214.10	0.00	0.00	0.00
17,700.00	88.85	89.94	9,580.27	-106.57	8,314.20	8,314.08	0.00	0.00	0.00
17,800.00	88.85	89.94	9,582.27	-106.46	8,414.18	8,414.06	0.00	0.00	0.00
17,900.00	88.85	89.94	9,584.27	-106.36	8,514.16	8,514.04	0.00	0.00	0.00
18,000.00	88.85	89.94	9,586.27	-106.25	8,614.14	8,614.02	0.00	0.00	0.00
18,100.00	88.85	89.94	9,588.27	-106.15	8,714.12	8,714.00	0.00	0.00	0.00
18,200.00	88.85	89.94	9,590.27	-106.04	8,814.10	8,813.98	0.00	0.00	0.00
18,300.00	88.85	89.94	9,592.27	-105.94	8,914.08	8,913.96	0.00	0.00	0.00
18,400.00	88.85	89.94	9,594.27	-105.83	9,014.06	9,013.94	0.00	0.00	0.00
18,500.00	88.85	89.94	9,596.27	-105.73	9,114.04	9,113.92	0.00	0.00	0.00
18,600.00	88.85	89.94	9,598.27	-105.62	9,214.02	9,213.90	0.00	0.00	0.00
18,700.00	88.85	89.94	9,600.27	-105.51	9,314.00	9,313.88	0.00	0.00	0.00
18,800.00	88.85	89.94	9,602.27	-105.41	9,413.98	9,413.86	0.00	0.00	0.00
18,900.00	88.85	89.94	9,604.27	-105.30	9,513.96	9,513.84	0.00	0.00	0.00
19,000.00	88.85	89.94	9,606.27	-105.20	9,613.94	9,613.82	0.00	0.00	0.00
19,100.00	88.85	89.94	9,608.27	-105.09	9,713.92	9,713.80	0.00	0.00	0.00
19,200.00	88.85	89.94	9,610.27	-104.99	9,813.90	9,813.78	0.00	0.00	0.00
19,300.00	88.85	89.94	9,612.28	-104.88	9,913.88	9,913.76	0.00	0.00	0.00
19,386.26	88.85	89.94	9,614.00	-104.79	10,000.12	10,000.01	0.00	0.00	0.00
Start 240.27 hold at 19386.26 MD - 05-V-10000-132H									
19,400.00	88.85	89.94	9,614.28	-104.78	10,013.86	10,013.74	0.00	0.00	0.00
19,500.00	88.85	89.94	9,616.28	-104.67	10,113.84	10,113.72	0.00	0.00	0.00
19,600.00	88.85	89.94	9,618.28	-104.56	10,213.82	10,213.70	0.00	0.00	0.00
19,626.53	88.85	89.94	9,618.81	-104.54	10,240.34	10,240.23	0.00	0.00	0.00
Start 90.02 hold at 19626.53 MD - 06-LTP(CH32-132H)									
19,700.00	88.85	89.94	9,620.28	-104.46	10,313.80	10,313.68	0.00	0.00	0.00
19,716.55	88.85	89.94	9,620.61	-104.44	10,330.34	10,330.23	0.00	0.00	0.00
TD: 19716.54' MD, 10330.22' VS, 9620.61' TVD - 07-PBHL(CH32-132H)									



Planning Report

Database:	EDM 5000.14 Single User Db	Local Co-ordinate Reference:	Well Crazy Horse 32 State Fed Com 132H
Company:	Colgate Energy	TVD Reference:	3319+25 @ 3344.00usft
Project:	Eddy County, NM (N83-NME)	MD Reference:	3319+25 @ 3344.00usft
Site:	Crazy Horse 32 State Fed Com	North Reference:	Grid
Well:	Crazy Horse 32 State Fed Com 132H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Permit		
Design:	ADP-Rev2 v3		

Design Targets									
Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
00-EON (CH32-132H) - plan hits target center - Point	0.00	0.00	7,000.00	-115.54	-185.68	588,986.22	643,169.14	32.61873827	-104.00259197
01-FTP (CH32-132H) - plan misses target center by 198.47usft at 9350.00usft MD (9291.57 TVD, -115.34 N, 2.55 E) - Rectangle (sides W0.00 H50.00 D20.00)	0.00	89.94	9,434.00	-115.49	-135.68	588,986.27	643,219.14	32.61873798	-104.00242958
02-V-2500-132H - plan misses target center by 0.09usft at 11884.93usft MD (9473.91 TVD, -112.71 N, 2500.12 E) - Point	0.00	0.00	9,474.00	-112.71	2,500.12	588,989.05	645,854.94	32.61872278	-103.99386880
03-V-5000-132H - plan hits target center - Point	0.00	0.00	9,514.00	-110.07	5,000.12	588,991.69	648,354.94	32.61870783	-103.98574909
04-V-7500-132H - plan misses target center by 0.01usft at 16885.76usft MD (9563.99 TVD, -107.43 N, 7500.12 E) - Point	0.00	0.00	9,564.00	-107.43	7,500.12	588,994.33	650,854.94	32.61869235	-103.97762939
05-V-10000-132H - plan hits target center - Point	0.00	0.00	9,614.00	-104.79	10,000.12	588,996.97	653,354.94	32.61867635	-103.96950970
06-LTP(CH32-132H) - plan misses target center by 0.04usft at 19626.53usft MD (9618.81 TVD, -104.54 N, 10240.34 E) - Point	0.00	0.00	9,618.81	-104.58	10,240.34	588,997.18	653,595.16	32.61867466	-103.96872950
07-PBHL(CH32-132H) - plan hits target center - Point	0.00	0.00	9,620.61	-104.44	10,330.34	588,997.32	653,685.16	32.61867420	-103.96843719

Formations						
Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)	
194.00	194.00	Rustler				
444.00	444.00	Top of Salt				
1,344.00	1,344.00	Base of Salt				
1,494.00	1,494.00	Yates				
1,869.00	1,869.00	Capitan				
3,465.42	3,464.00	DLWR Mnt. Group				
5,937.87	5,934.00	Lower Brushy Canyon				
6,198.13	6,194.00	Bone Spring Lime				
7,528.82	7,524.00	1st Bone Spring Sand				
8,268.82	8,264.00	2nd Bone Spring SD				
9,178.21	9,159.00	3rd Bone Spring SD				



Planning Report

Database:	EDM 5000.14 Single User Db	Local Co-ordinate Reference:	Well Crazy Horse 32 State Fed Com 132H
Company:	Colgate Energy	TVD Reference:	3319+25 @ 3344.00usft
Project:	Eddy County, NM (N83-NME)	MD Reference:	3319+25 @ 3344.00usft
Site:	Crazy Horse 32 State Fed Com	North Reference:	Grid
Well:	Crazy Horse 32 State Fed Com 132H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Permit		
Design:	ADP-Rev2 v3		

Plan Annotations				
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
1,925.00	1,925.00	0.00	0.00	Start Build 1.50
2,095.20	2,095.14	-2.00	-3.22	Start 4739.42 hold at 2095.20 MD
6,834.62	6,829.86	-113.54	-182.46	Start Drop -1.50
7,004.82	7,000.00	-115.54	-185.68	Start 1867.00 hold at 7004.82 MD
8,871.82	8,867.00	-115.54	-185.68	KOP: 8871.82' MD, -185.80' VS, 8867.00' TVD
9,762.63	9,439.88	-114.95	378.09	EOC: 9762.63' MD, 377.97' VS, 9439.88' TVD
14,385.26	9,514.00	-110.07	5,000.12	Start DLS 2.00 TFO -179.98
14,396.62	9,514.21	-110.06	5,011.49	Start 4989.64 hold at 14396.62 MD
14,438.59	9,515.04	-110.01	5,053.44	Sec: 32.61870750, -103.98557590
14,438.59	9,515.04	-110.01	5,053.44	Sec: 14438.59' MD, 9515.04' TVD
15,760.56	9,541.48	-108.62	6,375.15	Fed Lease: 32.61869938, -103.98128316
15,760.56	9,541.48	-108.62	6,375.15	Fed Lease: 15760.56' MD, 6375.03' VS, 9541.48' TVD
19,386.26	9,614.00	-104.79	10,000.12	Start 240.27 hold at 19386.26 MD
19,626.53	9,618.81	-104.54	10,240.34	Start 90.02 hold at 19626.53 MD
19,716.55	9,620.61	-104.44	10,330.34	TD: 19716.54' MD, 10330.22' VS, 9620.61' TVD



United States Department of the Interior
BUREAU OF LAND MANAGEMENT
Grand Junction, Colorado 81506
<https://www.blm.gov>



Request for Authorization

Date: February 12, 2021

To: Laura Daniel-Davis
Senior Advisor to the Secretary,
Exercising the Delegated Authority of the Assistant Secretary,
Land and Minerals Management

From: Michael D. Nedd
Deputy Director, Operations
Exercising the Delegated Authority of the Director
Bureau of Land Management (BLM)

Bureau/Office: BLM, New Mexico State Office, Carlsbad Field Office

Action for which Approval is Requested:

On behalf of the BLM Carlsbad Field Office, request is made to approve the following Applications for Permit to Drill (APD) for Colgate Energy, located in Eddy County, New Mexico:

APD 10400063575 Crazy Horse 32 State Fed Com 133H
APD 10400063650 Crazy Horse 32 State Fed Com 131H
APD 10400063651 Crazy Horse 32 State Fed Com 132H
APD 10400064274 Crazy Horse 32 State Fed Com 201H
APD 10400064419 Crazy Horse 32 State Fed Com 203H

These five APDs are being submitted as one request because the potential impacts of each APD were analyzed in the same National Environmental Policy Act (NEPA) document, an environmental assessment (EA) DOI-BLM-NM-P020-2021-0198-EA (see Attachment 4). Two of the three associated leases were issued in 1952, prior to the Federal Land Policy and Management Act (FLPMA) or NEPA, and one in 2013, with no major issues raised. No surface disturbance on BLM land is associated with these APDs.

The approval of these APDs is time-sensitive because Colgate Energy is planning to bring a drilling rig into the region and needs to finalize the construction and rig schedule. Having these APDs approved will give them the confidence to keep the rig in New Mexico. In addition, the surface holes for the five APDs are on state land, overlying non-Federal minerals, but the bottom holes are in federal minerals (typically referred to as Fee/Fee/Fed wells). Colgate Energy can drill the state minerals with the same surface disturbance and strand the federal minerals if these APDs are not approved.

One Paragraph Summary of Action:

Colgate Energy has requested to drill five horizontal wells. The non-federal surface disturbance associated with the Crazy Horse project includes a 385-foot by 420-foot well pad, a 355-foot by 455-foot well pad, a 500-foot by 500-foot Central Tank Battery (CTB), 524 feet of new access roads, 352 feet of overhead electric lines, and 1,710 feet of buried 4-inch polyethylene pipelines.

These drilling permits were signed by the Carlsbad Field Office on January 21, 2021, when the Authorizing Officer's delegation of authority to approve APDs had been temporarily suspended by the Acting Secretary of the Interior pursuant to Secretary's Order 3395. On January 28, 2021, the Carlsbad Field Office notified Colgate Energy that the approval was invalid (see Attachment 1).

Positions of Affected Stakeholders:

Although the state of New Mexico will be impacted by ongoing climate change to which fossil fuel combustion contributes, the state is also heavily reliant on the revenue from oil and gas development. The communities of southeast New Mexico support the continuation of drilling operations and related activities.

The Carlsbad Field Office publishes NEPA documents to the national register (ePlanning) at <https://eplanning.blm.gov>. The register allows the public to review and comment online on BLM NEPA and planning projects. There were no comments received concerning this project.

Key Facts:

- The project is in the Permian Basin, an area of active oil and gas development for the past century.
- EA DOI-BLM-NM-P020-2021-0198-EA (see Attachment 4) is available at this ePlanning link:
https://eplanning.blm.gov/public_projects/2003831/200471204/20032229/250038428/EA%20for%20Crazy%20Horse%2032%20State%20Fed%20Com.PDF.
- The Finding of No Significant Impact (see Attachment 3), signed January 4, 2021 is available at:
https://eplanning.blm.gov/public_projects/2003831/200471204/20032228/250038427/Signed%20FONSI%20for%20Crazy%20Horse%2032%20State%20Fed%20Com.PDF.
- The Decision Record for the EA (see Attachment 2) for the APDs was signed on January 4, 2021. The Decision Record is on ePlanning at the following link:
https://eplanning.blm.gov/public_projects/2003831/200471204/20032227/250038426/Signed%20DR%20for%20Crazy%20Horse%2032%20State%20Fed%20Com.PDF.
- The APDs are associated with Fluid Mineral Leases NMNM 0006771A (effective 7/1/1952), NMNM 0006771B (effective 7/1/1952), and NMNM 130861 (issued 11/29/2013).
- No protests were received prior to the lease sales.
- There has been no litigation related to the EA for these APDs.
- There is no environmental analysis for leases NMNM 0006771A or NMNM 0006771B as NEPA was not completed for oil and gas leasing at that time.

- Lease NMNM 130861 was analyzed and offered during the July 2013 Lease Sale; the lease sale analysis for this lease showed potential impacts to cultural resources, development within designated potash area, and slopes or fragile soils - all of which resulted in lease stipulations and notices being applied to the lease. However, this lease will only be penetrated by the subsurface horizontal wellbore and does not contain the surface hole locations.
- The wells are within the Secretary of the Interior's 2012 Order dated December 3, 2012 (Attachment 5). The Order is designed to manage the efficient development of oil, gas, and potash resources. Section 6 of the Order provides general provisions which must be followed to minimize conflict between the industries and ensure the safety of operations. Due to wells being located in an area of barren potash reserves, there would be no affect to the economical potash resources.
- The only primary potential resource conflict identified for the action is cave and karst resources. Stipulations, including special requirements, are identified on pages 61 to 63 of the EA. The applicants design features identified in the EA will help eliminate adverse impacts to the natural and human environment.

Other Relevant Considerations:

This request is associated with DTS# BLM0024995.

Consistent with Secretary's Order 3395 and Section 2 of the Reorganization Plan No. 3 of 1950, 64 Stat. 1262, I ___DO/___DO NOT approve the action(s) set forth above.

Comment:

Signature

Date

Attachments

- 1 – Letter from BLM to Colgate Operating, January 28, 2021
- 2 – Decision Record for Environmental Assessment DOI-BLM-NM-P020-2021-0198-EA
- 3 – Finding of No Significant Impact for Environmental Assessment DOI-BLM-NM-P020-2021-0198-EA
- 4 – Environmental Assessment DOI-BLM-NM-P020-2021-0198-EA
- 5 – 2012 Potash Secretarial Order No. 3324

District I

1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

COMMENTS

Action 20626

COMMENTS

Operator:	OGRID:	Action Number:	Action Type:
COLGATE OPERATING, LLC Suite 1000 Midland, TX79701	371449	20626	FORM 3160-3
300 North Marienfeld Street			

Created By	Comment	Comment Date
kpickford	KP GEO Review 3/26/2021	03/26/2021

District I

1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 20626

CONDITIONS OF APPROVAL

Operator:		OGRID:	Action Number:	Action Type:
COLGATE OPERATING, LLC	300 North Marienfeld Street	371449	20626	FORM 3160-3
Suite 1000	Midland, TX79701			

OCD Reviewer	Condition
kpickford	Notify OCD 24 hours prior to casing & cement
kpickford	Will require a File As Drilled C-102 and a Directional Survey with the C-104
kpickford	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
kpickford	Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system