

Office
 District I – (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II – (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III – (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV – (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM
 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised July 18, 2013

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

WELL API NO. 30-015-20950
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Allied State SWD
8. Well Number 1
9. OGRID Number 018917
10. Pool name or Wildcat SWD Delaware
4. Well Location Unit Letter <u>I</u> : <u>1980</u> feet from the <u>South</u> line and <u>990</u> feet from the <u>East</u> line Section <u>10</u> Township <u>23S</u> Range <u>26E</u> NMPM <u>Eddy</u> County
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3315'

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other SWD

2. Name of Operator
Read & Stevens, Inc.

3. Address of Operator
P.O. Box 1518, Roswell, NM 88202

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
 PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
 DOWNHOLE COMMINGLE ☐
 CLOSED-LOOP SYSTEM ☐
 OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
 COMMENCE DRILLING OPNS. ☐ P AND A ☒
 CASING/CEMENT JOB ☐
 OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

PLEASE SEE ATTACHED PLUG & ABANDON REPORT

Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emnrd.state.nm.us

Spud Date:

09/15/1973

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Kelly Barajas TITLE Production Reporting DATE 05/06/2021

Type or print name Kelly Barajas E-mail address: kbarajas@read-stevens.com PHONE: 575-624-3760

For State Use Only

APPROVED BY: [Signature] TITLE Staff Manager DATE 5/14/2021

Conditions of Approval (if any):

Allied State SWD No. 1
API# 30-015-20950
Read & Stevens, Inc.

4/22/2021

Moved in rig and equipment and rigged up. Started flowing well down into the steel pit. Installed BOP and released on/off tool. Laid down 2 steel tubing stubs and SION.

4/23/2021

Laid down 108 joints of 2 3/8" fiberglass tubing. Picked up on/off tool and RIH with workstring. Latched on to the packer and worked the packer free. POOH with the packer. RIH with 5 1/2" HM CIBP and set at 3250'. SION.

4/26/2021

Circulated hole with MLF and tested casing to 500#. Casing good. Spotted 25 sx on top of CIBP @ 3250'. POOH to 1522. Spotted 25 sx across the base of the salt. POOH to take off CIBP setting tool and pick up a perforated sub. WOC and tag at 1:00pm. RIH and tagged cement at 1283'. POOH to 697 to spot 35 sx of cement across the surface casing shoe and the top of the salt section. POOH 15 stands and SION.

4/27/2021

RIH and tagged cement @ 364'. POOH to 126' and circulate cement to surface with 15 sx. Laid down remaining tubing and rigged down. Dug out wellhead and cut off. Filled up the 13 3/8" x 8 5/8" annuls with 60 sx cement and the 8 5/8 x 5 1/2" annulus with 15 sx cement. Cement remained at the surface in all strings of casing. Installed marker, removed the anchors and back drug the location. Move out equipment.

Read & Stevens Inc



Well Name: Allied State #1 SWD		Field: SWD Delaware	
Location: 1980' FSL & 990' FEL; 10-23S-26E		County: Eddy	State: NM
Elevation: 3,330' GL / 3,315' RKB		Spud Date: 9/15/73	Compl Date: 6/10/11
API#: 30-015-20950	Prepared by: KALE JACKSON	Date: 2/1/21	Rev: 5/7/21

PLUGGED SCHEMATIC
4/27/21

HOLE SIZE	CASING SIZE	DEPTH SET	CMT TOP
17 -1/2"	13-3/8"	439'	SURFACE

NEW PRODUCTION CSG 3/26/11		
CASING SIZE	DEPTH SET	CMT TOP
5-1/2"	3,800'	SURFACE
5-1/2 STC J-55 8rd 15.5#		

HOLE SIZE	CASING SIZE	DEPTH SET	CMT TOP
11"	8-5/8"	5,430'	1,800'

CIBP @ 5,284' w/ 40sx Class C Plug 3/11. OK'D BY NMOCD

CEMENT PLUG 7,251 - 9,670. OK'D BY NMOCD 2/11

TOC @ 9,000'. TEMP SURVEY 11/73

Cmt plug from 126' to surface 4/27/2021

Cmt plug @ 364 - 967'. Top of Salt Plug to 50' above surface shoe. 35 Sx plug

Tagged Base of Salt Plug @ 1,283'. Cmt plug 1,283 - 1,522 25 sx plug 4/26/2021

Set CIBP @ 3,250' w/ 35ft of cmt 4/23/2021

DELAWARE INJ PERFS: 3,300 - 3,550 (102 holes) 5/11

Cut csg @ 3800'. POOH. RIH w/ 117jts of new 5.5 J-55 csg to 3,800'. Cement w/ 450 sxs Class C. 100 sxs cement to surface. Ran CBL 450' - 3,751'. Set CIBP @ 3749 w/ cmt PBTD @ 3740. OK'd by NMOCD 3/11

COLLAPSED CASING & TBG @ 9,670'

CANYON PERFS @ 10,247' - 10,277' . Sqz'd 5/92

PACKER @ 10,494

STRAWN PERFS @ 10,552 - 10,564 & 10,570 - 10,574

CIBP set @ 11,615' w/ 35' cmt 05/92

MORROW PERFS @ 11,663' - 11,776'

TD @ 11,935

PRODUCTION CSG INSTALLED 11/27/73			
HOLE SIZE	CASING SIZE	DEPTH SET	CMT TOP
7-7/8"	5-1/2"	11,935'	9,000'

PB hole & cut 5.5 csg. Run new 5.5 production csg 2011

NOTE: DRAWING NOT TO SCALE

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 27211

CONDITIONS

Operator: READ & STEVENS INC P.O. Box 1518 Roswell, NM 88202	OGRID: 18917
	Action Number: 27211
	Action Type: [C-103] Sub. Plugging (C-103P)

CONDITIONS

Created By	Condition	Condition Date
gcordero	None	5/14/2021