

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Well Number: 6

Sundry Print Repor

Well Name: MOBIL CI Well Location: T19S / R25E / SEC 6 / County or Parish/State: EDDY /

SWSW /

Type of Well: OIL WELL Allottee or Tribe Name:

Unit or CA Number: Lease Number: NMNM0352858B **Unit or CA Name:**

US Well Number: 300152322800S1 Well Status: Producing Oil Well **Operator:** EOG RESOURCES

INCORPORATED

Accepted for record – NMOCD gc 6/02/2021

Notice of Intent

Type of Submission: Notice of Intent Type of Action Plug and Abandonment

Time Sundry Submitted: 10:25 Date Sundry Submitted: 05/17/2021

Date proposed operation will begin: 06/01/2021

Procedure Description: Please see attached. Thank you.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

Mobil_CI_Federal_6_5_17_21_20210517102539.pdf

Conditions of Approval

Specialist Review

Mobil_Cl_6_Sundry_ID_2387500_P_A_20210522172046.pdf

Page 1 of 2

Well Location: T19S / R25E / SEC 6 /

SWSW /

County or Parish/State: Page 2 of

Well Number: 6

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM0352858B

Unit or CA Name:

Unit or CA Number:

US Well Number: 300152322800S1

Well Status: Producing Oil Well

Operator: EOG RESOURCES

INCORPORATED

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

Operator Electronic Signature: TINA HUERTA Signed on: MAY 17, 2021 10:25 AM

Name: EOG RESOURCES INCORPORATED

Title: Regulatory Specialist

Street Address: 104 SOUTH FOURTH STREET

State: NM City: Artesia

Phone: (575) 748-4168

Email address: tina_huerta@eogresources.com

Field Representative

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: LONG VO

BLM POC Phone: 5752345972

Disposition: Approved

Signature: Long Vo

BLM POC Title: Petroleum Engineer

BLM POC Email Address: lvo@blm.gov

Disposition Date: 05/22/2021

Page 2 of 2

API: 30-015-23228

Medium Cave

EOG Resources, Inc. plans to plug and abandon this well as follows:

- 1. MIRU all safety equipment as needed. NU BOP. POOH with production equipment.
- 2. Set a CIBP at 2339 ft with 37 sx Class C cement on top to 1804 ft. WOC and tag. This will cover Yeso perfs and top and Glorieta top. Leak test CIBP
- 3. Spot a 25 sx Class C cement plug from 953 ft 592 ft. WOC and tag. This will cover Intermediate casing shoe.

 4. Spot a 38 sx Class C cement plug from 540 ft up to surface. WOC and tag. Back fill as needed. Very e

Wellbore schematics attached

				1000		OOTAGES:	FOOTAGES: 330' FSL & 940' FWL	40' FWL		API: 30-0 GL: 3627 KB:	API: 30-015-23228 GL: 3627 KB:	28	
					CASING	CASING DETAIL							personal designation of the second se
	√	W	N	/		HOLE SIZE	SIZE	WGHT	GRADE	Top	Bottom Sx Cmt	Smt Cira/TOC	TOC Method
Plug 3: Casing shoe + San	T	71/	/ /	/	A	14 3/4	10 3/4	30	٥	0	355 300		
Andres top + Surface plug					В	9 1/2	7	20	J-55	0	903 700	0 Circ	
					O	6 1/4	412	9.5	J-55	o	3 070	<u>.</u>	- Mariana
					FORMA.	FORMATION TOPS							-
						Management of the same of the	Formation	Top			Formation	Top	
							San Andres	490				***************************************	en en fretskille filmer en freste vergesten en e
	ω	W	Ń				Glorieta	1862					
Plug 2: Casing shoe			1	71									
	and a second				THRING DETAIL	DETAIL	and the first of anyther friend for such than the first of the first o						
	ФРА				34	Joints	Description	Lenoth	GO		Grade Mit (Ib./le):	JAN TAN (4KD).	Dec (4)/0):
	- Addition to						2-3/8" Tuhing	The second secon					סמנו (ונגם):
	-				NOTES	-	Sings of S				_		2,372
	***********				w/SN, pe	W/SN, perf sub & joint anchor @ 2293	nchor @ 2293'	and a make the design of the construction of the state of	ANSWED AND AND AND AND AND AND AND AND AND AN				
												- Control of the Cont	
					PLUGS				en de company de la company de		AASTA VARIOUS VICTARIA ALCONOMISMA	NAME OF TAXABLE PARTY O	
	-				*	SX	Class	Тор	Bottom	V	Notes	After a farmer of the second s	Tao
					T	21/40	O	179 3864	2339	535 10	IBP + Yeso per	CIBP + Yeso perfs + Yeso top + Glorieta	
	PM tempina				CA	25	U	592	953		Casing shoe	PROPRIETO CONTRACTOR C	
	To a second de la constanta de				ო	88	c	c	540		asing shoe + Sa	Casing shoe + San Andres top + Surface	
	No there are no dec						Address of the Control of the Contro				3		X
a 1: CIBP + Yeso perfs +	Restriquia				4					-			
Yeso top + Glorieta top	and the second		$\Delta \ell$				The state of the s						
	COMPANIA DA LA LA LA CANADA DE	77	M		Perforation Detail								
	U		7		II.	Formation	Тор	Bottom	Tre	Treatment			
	Wice William		4		A	Yeso	2,389	3 2,753		15% ac	d. Sand frac'd v	2250 gals 15% acid. Sand frac'd w/60,000 gals treated water 95 000# sand	iter 95 000# sand
					00								
	PBTD:				O							dideciolates de la constante d	
	Ë	24.00							-	Tonichie deministration	Andrew Contraction and State of State o	enterent appropriate descriptions and an experience of the second appropriate second appr	Approximation of the contract

Received by OCD: 5/2	4/20	21			13 A.	[VI		1	. 1	т				 			p PF-100-000		-								P
1			TOC Method									merantum pipejulanen kalekaa aanaan gaa aabaa mamaan				Btm (ftKB):	2,372						ited water,				
			Circ/TOC	Ojrc	Circ	Circ			WOOTPON TO THE THE PARTY OF THE	Top						Wt (lb/ft): Top (ftKB):							2250 gals 15% acid. Sand frac'd w/60,000 gals treated water, 95,000# sand				
5-23228		-	Sx Cmt	300	700	350			PA-A-MILLAND AND AND AND AND AND AND AND AND AND	N.						Wt (Ib/ft):							frac'd w/60, 000# sand				
API: 30-015-23228 GL: 3627 KB:		-	Bottom	355	903	3,070				Formation						Grade	-					Ħ	acid. Sand				
API: GL: KB:		-	do_	0		0	-									₽	***************************************					Treatment	als 15%				
FWL		1	GRADE	c !	000	J-55			defending provinces on the second sec				- ALL COLLEGE		- The state of the	8					nejimejejejenekajuk, kipipejejejejejejejejejejejejejejejejejej	•	2250 ga				
9S-25E			WGHT	30	2	9.5				Top	490	1862			-	Length		3,			de la constanta de la constant	Bottom	2,753				
: Sec. 6-18		-	SIZE	10 3/4		4 1/2		(Formation	San Andres	Glorieta			SETTANDA TO PART OF THE ANALYSIS OF THE ANALYS	Description	2-3/8" Tubing	anchor @ 2293			Andread and the control of the contr	Тор	2,389				114/21
Sec-TWN-RNG: Sec. 6-19S-25E FOOTAGES: 330' FSL & 940' FWL		CASING DETAIL	HOLE SIZE	14 3/4	7/1 6	6 1/4			FORMATION TOPS		. Propriesto de la constitució				TUBING DETAIL	Joints		w/ SN, perf sub & joint anchor @ 2293			Perforation Detail	Formation	Yeso	THE PROPERTY OF THE PROPERTY O			Prepared by: Naomi F 5/14/21
Sec		CASIN	#	∢ a		O			FORMA		A CONTRACTOR OF THE PARTY OF TH		**************************************		TUBING	#	Terror management	w/SN, p			Perforati		A	-			repared
rrent			/	1						/																/	
Federal #6 Current										T														W			PBTD: 3,070 MD TD: 3,100 MD
Mobil CI Fe		_ <							ω	<u> </u>			encentrari endos y columno	Manager gladesten		- Allenton qu					**************************************	Market Market Space	***************************************	(د	1000000 maaaaaa	P. B.
Mo																											Anderstein der Gestein der
Released to Imaging:	6/3/2	202.	19	:53:	52 A	M	mandik soosoojij	Production dates	niin thie kanney	and an article and article article and article article and article and article article article and article article and article article article article and article			and report to be accepted by		- Coloniari					er de calego	R-Garden or Sa	Actividad Drop	(Pert A		6/1505/12th had week	

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and maintained as per API and deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

- 6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with The well bore shall then be capped with a 4-inch pine 10 feet in the cellar or 3 feet below final restored a minimum of 4 hours annuluses.
- The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).
- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well.
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

Received by OCD: 5/24/2021 10:07:25 AM

United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines (Contact service companies, allowing plenty of time to have the risers and power lines and poles removed prior to reclamation, don't wait till the last day and try to get them to remove infrastructure). Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip and seed as specified in the original point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3). Surface Use Plan of
 Operations must include adequate measures for stabilization and reclamation of disturbed lands.
 Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD
 process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you

have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Petroleum Engineering Tech 575-234-5909 (Office), 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Crisha Morgan Environmental Protection Specialist 575-234-5987

Melissa Horn Environmental Protection Specialist 575-234-5951

Kelsey Wade Environmental Protection Specialist 575-234-2220

Trishia Bad Bear, Hobbs Field Station Natural Resource Specialist 575-393-3612

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone: (575) 748-1283 Fax: (575) 748-9720 District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 29198

CONDITIONS

Operator:	OGRID:
EOG RESOURCES INC	7377
P.O. Box 2267	Action Number:
Midland, TX 79702	29198
	Action Type:
	[C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
gcordero	None	6/2/2021