

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT Sundry Print Reports

Well Name: FEDERAL HQ Well Location: T20S / R22E / SEC 32 / County or Parish/State: EDDY /

NWNE /

NIVI

Well Number: 3 Type of Well: CONVENTIONAL GAS Allottee or Tribe Name:

WELL

Lease Number: NMNM21012 Unit or CA Name: Unit or CA Number:

US Well Number: 300153570400S1 **Well Status:** Producing Gas Well **Operator:** EOG RESOURCES

INCORPORATED

Accepted for record – NMOCD gc 6/29/2021

Notice of Intent

Type of Submission: Notice of Intent

Type of Action Plug and Abandonment

Date Sundry Submitted: 06/22/2021 Time Sundry Submitted: 10:10

Date proposed operation will begin: 06/30/2021

Procedure Description: Please see attached. Thank you.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

Federal_HQ_3_6_22_21_20210622100940.pdf

Conditions of Approval

Specialist Review

Federal_HQ_3_Sundry_ID_2504490_P_A_20210627110609.pdf

US Well Number: 300153570400S1

Well Location: T20S / R22E / SEC 32 /

NWNE /

County or Parish/State: Page 2 of

Well Number: 3

Type of Well: CONVENTIONAL GAS

WELL

Unit or CA Number:

Lease Number: NMNM21012

Unit or CA Name:

Allottee or Tribe Name:

Well Status: Producing Gas Well

Operator: EOG RESOURCES

INCORPORATED

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

Operator Electronic Signature: TINA HUERTA Signed on: JUN 22, 2021 10:09 AM

Name: EOG RESOURCES INCORPORATED

Title: Regulatory Specialist

Street Address: 104 SOUTH FOURTH STREET

State: NM City: Artesia

Phone: (575) 748-4168

Email address: tina_huerta@eogresources.com

Field Representative

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: LONG VO

BLM POC Phone: 5752345972

Disposition: Approved

Signature: Long Vo

BLM POC Title: Petroleum Engineer

BLM POC Email Address: lvo@blm.gov

Disposition Date: 06/27/2021

Page 2 of 2

High Care

30-015-35764

EOG Resources, Inc. plans to plug and abandon this well as follows:

- 1. MIRU all safety equipment as needed. NU BOP. POOH with production equipment.
- 2. Set a CIBP at 9200 ft with 4 sx Class H cement on top to 9165 ft. WOC and tag. This will cover Morrow perfs.
- 3. Spot a 25 sx Class H cement plug from 9002 ft 8782 ft. This will cover Atoka top.
- 4. Spot a 25 sx Class H cement plug from 8224 ft 8004 ft. This will cover Strawn top.
- 5. Spot a 25 sx Class C cement plug from 6787 ft 6541 ft. This will cover Cisco top.
- 6. Spot a 25 sx Class C cement plug from 5659 ft 5413 ft. This will cover Wolfcamp top.
- 7. Spot a 25 sx Class C cement plug from 3973 ft 3727 ft. This will cover Abo top.
- 8. Spot a 25 sx Class C cement plug from 3215 ft 2969 ft. This will cover Tubb top.
- 9. Perforate at 1722 ft and 1450 ft. Spot a 49 sx Class C cement plug from 1722 ft 1350 ft. WOC and tag. This will cover casing shoe, U Yeso and Glorieta tops and TOC.
- 10. Perforate at 339 ft. Spot a 32 sx Class C cement plug from 339 ft 237 ft. WOC and tag. This will cover San Andres top.
- 11. Perforate at 100 ft. Spot an 31 sx Class C cement plug from 100 ft up to surface. WOC and tag. Back fill as needed.
- 12. Cut off wellhead and install dry hole marker. Clean location as per regulated.

Wellbore schematics attached

Morrow @ 9244

Folder all HO 3 Proposed Secritive MRIG Sept. 32.20.55-20E April 50-517-537-04	Federal HQ 3 Proposed	Federal HQ 3 Proposed Sec-TWN-RNG; Sec. 32-20.55-22E						<u> </u>	High Cause	3				
1. Motor	10.1407 A	1.4007 A HOLES SECTE SECTE TOP			Se	-TWN-RNG	Sec. 32-2	0.5S-22E . &2536' FE			: 30-015-35704 : 4283			
Colored Colo	Fig. Fig. Fig.	Part	10th Plug		CASING	DETAIL								
Fig. 1, 2007 Fig.	1, 1000 1, 1000	A 14,304 9,505 15,517 J-55 0			#	HOLE SIZE	SIZE	WGHT	GRADE	Top	Bottom	Sx Cmt		TOC Metho
	Control Cont	Formwhelp Form			ď	14 3/4	9 5/8	36	J-55	0	1,622	174	+-	1. T
FORMATION TOPS FORM	Formation Top Formation	FORMATION TOPS FORM	9th Plug		В	8 3/4	5 1/2	15.5: 17	J-55	0	9,633	1875		CBL
Formation Top Top Formation Top Top Top Top Top Top Top Top	Cooker C	FORMATION TOPS FORM												
1- May 1	Committee Top	FORMATION TOPS FORM												
Formation Top Top Formation Top Formation Top Formation Top Form	Formation Top	Formation Top Formation Top Formation Top Formation Top Formation Top Signar			4 14 0 0	Ou OF MOIT								
Company Comp	Communication Communicatio	Sign Author 1942 1942 1942 1943			A PARTIES	TON TOPS	1		1					And the second second
Clean State Stat	Comparison Com	Operation 1420 Operation	TOC by CBL - 1400'			San Andres			Wolfcamp			Formation	Top	-
Tubpe Visco 1672 Sirvan	Tubb State State	Tubb 3050 Albora Strawn Straw				Glorieta	1430		Cisco	999				
TITION OF PARTY TITION OF	TUBING DETAIL TUBING DETAI	TUBING DETAIL TUBING DETAI	stn Plug			Jpper Yeso	1672		Strawn	811				
TUBING DETAIL # Joints FILLIDES FILLIDES FILL	TUBING DETAIL TUBING DETAIL TO STATE THAT AND THAT THE TO STATE THAT THE TO STATE THAT THE TO STATE THAT THE TO STATE THAT THAT THE TO STATE THAT THE TO STATE THAT THAT THAT THAT THAT THAT THAT	TUSING DETAIL TUSING DETAIL TUSING DESCRIPTION TUSING DETAIL TUSING DESCRIPTION T	7th Plug			dbo Abo	3850		Atoka	8897				
TUBING DETAIL TUBING DETAIL Lungin CO ID Condo Wit (Brit); TOp (fittis); Condo Con	## Johns Default ## Johns Default ## SX Class Top Boltom A Notes ## SX Class Top A Notes ## SX Class	## Jonis Describion Langth OD ID ## Jonis Description Langth OD ID ## Jonis Descri							MOIOM	2776				
# John B Description Library CD Create Wit (Brit) Top (46KG)	# Joints Description (Longith 277) 1	## Joints Description Length OD ID			TUBING	DETAIL								
## SXY Class Top Bottom A Neise ## SXY Class Top Bottom Top SXY Class Top SX Class ## SXY Class Top Bottom Top SX Class Top SX Class ## SXY Class Top Bottom Top SX Class Top SX Class ## SXY Class Top Bottom Top SX Class Top SX Class ## SXY Class Top Bottom Top SX Class Top SX Class ## SXY Class Top SX Class Top SX Class ## SXY Class Top SX Class Top SX Class ## SXY Class Top SX Class Top SX Class ## SXY Class Top SX Class Top SX Class ## SXY Class Top SX Class Top SX Class ## SXY Class Top Top SX Class ## SXY Class Top Top SX Class ## SXY Class Top Top Top Top Top ## SX Class Top Top Top Top Top Top ## SX Class Top Top Top Top Top Top Top Top ## SX Class Top	PLIJOS PROPERTY	PLUGS	oth Plug		#	Joints	Description	Length	00	QJ	Grade	Wt (Ib/ft):	Top (ftKB):	Btm (ftKB):
PELUGS Top Boltom A Notes	## SX Chass Top Bottom	PLUGS ## SX Class Top Bottom & A ## SX Class Top Bottom					2-7/8" Tubing a	and packer					9,015	
## \$X\$ Class Top Bottom a Notes ## \$X\$ Class Top Bottom and Notes ## \$X\$ Class Top Bottom and Top Class Top Bottom ## \$X\$ Class Top	HUGS Top Bottom A Notes Top Sessor Top Sessor	## SX Class Top Bottom A 1	5th Plug											
# SX Class Top Bottom A Notes 1	# SXY Class TOP Bottom A Netose	# SX Class Top Bottom A 2			PLUGS									
1 2, 25 H 8762 81002 220 Alberto-perfis 3 25 H 8762 81002 220 Alberto-perfis 4 25 C 6541 6787 246 Cleso Top 5 25 C 6541 6787 246 Cleso Top 6 25 C 2969 3727 3473 246 Alberto-perfis 7 25 C 2969 3727 110 Early Top 8 24,6 C 2969 372 110 Early Top 9 24,6 C 2967 372 110 Early Top 9 24,6 C 2967 372 110 Early Top 10 34,6 C 2967 272 110 Early Top 10 34,6 C 2968 272 272 110 Early Top 10 34,6 C 2968 272 272 110 Early Top 10 34,6 C 2968 272 272 110 Early Top 10 34,6 C 2968 272 272 110 Early Top 10 34,6 C 2968 272	1	1	44 10		#	SX	Class	Тор	Bottom	٥	Notes			Tag
2	2 25	2 25 H 8782 9002 220			-	* 25	r	9765 08	9200	35	Morrow Perfs			>-
1	3 256 H 8004 8124 220 Stream Top 4 256 C 64541 6787 246 Cicco Top 5 256 C 6413 5659 246 Cicco Top 6 256 C 6413 5659 246 Cicco Top 7 256 C 6413 5659 246 Cicco Top 8 49 C 3269 3216 246 Cicco Top 9 326,67 C 267 0 3715 246 Cicco Top 9 326,67 C 267 0 3715 246 Cicco Top 10 341 C 267 0 3715 246 Cicco Top 10 341 C 267 0 3715 246 Cicco Top 10 341 C 267 0 3715 246 Cicco Top 10 341 C 267 275 275 275 275 275 10 3215 246 Cicco Top 11 563 MD	3 25 H 8004 8224 220 4 25 C 6541 6787 246 5 25 C 5413 6787 246 6 25 C 5413 6787 246 7 25 C 3727 3973 246 8 49 C 1360 140 1722 372 9 32 6 339 102 10 34 C 256 339 102 10 34 C 3727 372 372 10 34 C 326 339 102 10 34 C 326 339 326 10 34 C 326 339 326 10 34 C 326 339 326 10 32 C 326 339 326 10 32 C 326 339 326 10 34 C 326 326 10 34 C 326 326 10 34 C 32			2	25	T	8782	9002	220	Atoka Top			z
Second Perfect Section Color Col	1	Performance			e .	25	Ŧ	8004	8224	220	Strawn Top			z
Petro Perfs. 5250" - 9274 2659 246 Workleamp Top C	Control Party: 92291-9274 See	Corrow Perfix: 9259'-9274 Corrow Perfix: 9259'-9276 Corrow Perfix:	projection of the projection o		4 1	25	0	6541	6787	246	Cisco Top			z
10 25 C 2367 246 Abo Top 11 25 C 2367 246 Abo Top 12 25 C 2367 246 Abo Top 13 246 Abo Top 14 25 C 2367 246 Abo Top 15 246 C 2367 246 Abo Top 16 24 C 2367 247 339 102 San Andres Top 17 25 C 236 Abo Top 18 246 C 236 Abo Top 10 24 C 247 Abo Top 10 24 Abo	## 1250	Perform Perfs: 9236" - 9274" Performantion	201.		0	25	0	5413	5659	246	Wolfcamp Top			z
10	1	10 24 246			0 1	25	0 0	3727	3973	246	Abo Top			z
10 24 102 24 24 102 24 102 24 102 24 102 24 102 24 102	Secondary 1722 372 187, Ce 187	10 35 51 51 51 51 51 51 51			α	70	ی د	2909	3215	246	Tubb Top			z
10 21 C C C C C C C C C	10 31 C 00 102 Senfacibles	10 -31 C 0 100	n de la companie		0	30.65	0	750	330	312	Int. Csg. Shoe, U Ye	so/Glorieta Top &	T0C	>
PERFORATION DETAIL Formation Top Bottom Top Bottom Bottom Top B	PERFORATION DETAIL	Perform Perfs: 9250" - 9274" Performation Top Bottom Poster Ionrow Perfs: 9328" - 9376" ADDITIONAL DETAIL Existing CIBP @ 9300" ADDITIONAL DETAIL PBTD: 9,633 MD Preparted by: KJP			19	25		100	001	100	San Andres 1 op			>
Morrow Perfs: 9250'- 9274" PERFORATION DETAIL PERFORATION DETAIL Aforrow Perfs: 9228'- 9376" Morrow Perfs: 9228'- 9376" 9376 Aforrow Perfs: 9328'- 9376" ADDITIONAL DETAIL Existing CIBP @ 9300" Existing CIBP @ 9300" TD: 9,633 MD MD	PERFORATION DETAIL Formation Top Bottom S250 S376 S33 MD S33 MD TD: 9,633 MD TD:	PERFORATION DETAIL Formation Top Bottom Society Societ	nd Plug											
Morrow Perfs: 9250' - 9274" Formation Top Bottom Addrow Perfs: 9328' - 9376' Bottom 9250 9376 Addrow Perfs: 9328' - 9376' Additional Detail Existing CIBP @ 9300' Existing CIBP @ 9300' TD: 9,633 MD TD: 9,633 MD	Vorrow Perfs: 9250' - 9274* Formation Top Bottom Vorrow Perfs: 9328' - 9376* Morrow Perfs: 9328' - 9376* 9376 ADDITIONAL DETAIL Existing CIBP @ 9300' Existing CIBP @ 9300' TD: 9,683 MD	Vorrow Perfs: 9250' - 9274' Formation Top Bottom Aborrow Perfs: 9328' - 9376' 8376 8376 Aborrow Perfs: 9328' - 9376' 8250 8376 Aborrow Perfs: 9328' - 9376' 8376 8376 Aborrow Perfs: 9328' - 9376' 8376 8376 TD: 9,633 MD 8300'			PERFOR	ATION DETAIL								
Morrow 9250 8376 Morrow 9250	Morrow 9250 8376 Morrow 9250	Morrow 9250 9376 Morrow 9250	St Plug			ormation		Sottom						
## ADDITIONAL DETAIL Existing CIBP @ 9300' Existi	## ADDITIONAL DETAIL Existing CIBP @ 9300' B TD: 9,633 MD	ADDITIONAL DETAIL Existing CIBP @ 9300° B TD: 9,633 MD	visting Morrow Berfs: 9250' - 9274'		<	lorrow	9250	9376						
ADDITIONAL DETAIL Existing CIBP @ 9300° Existing CIBP @ 9300° TD: 9,633 MD TD: 9,633 MD	## ADDITIONAL DETAIL Existing CIBP @ 9300° Existing CIBP @ 9300° TD: 9,633 MD TD: 9,633 MD	## ADDITIONAL DETAIL Existing CIBP @ 9300'	visting CIBP @ 9300'	M										
B Existing CIBP @ 9300° TD: 9,633 MD	B Existing CIBP @ 9300° TD: 9,633 MD	Existing CIB @ 9300' B PBTD: 9,633 MD	kisting Morrow Perfs: 9328' - 9376'		OITIONA	AAI DETAIL								
9,300 MD 9,633 MD	9,300 MD 9,633 MD	9,633 MD			Existing CIB	o @ 9300'								
9,300 MD 9,633 MD	9,633 MD	9,633 MD		В										
				9,300	·				Prep	arted by: KJF				

3 Current Control Control MD MD	Sec-TWN-RNG: Sec. 32- 20-5S- 22E API: 30-015-35704 FOOTAGES: 1022' FNL &2536' FEL GL: 4283 KB:	P. T.	SIZE WGHT GRADE Top Bottom S	95/8 36 J-55 0 1,622 174	5 1/2 15.5:17 J-55 9,633 1875 Circ			Formation Top Formation Top	288	Glorieta 1430	1000 3092 Abo 3850	camp	Cisco 6664	Strawn 8114	Atoka 8892	Morrow 9224		Description Length OD ID Grade Wt (Ib/ft): Top (ft/RB):	9,015			Ton (1)	DOLLOTTI	9,370		045,0		Prepared by: DR	
	Current	CASING DETAIL		+			FORMATION TOPS		A								TUBING DETAIL				Y	Formation		8	C			8	

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

- 6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all plugged. Wellhead cut off shall commence within ten (10) calendar days of the well being justification to receive an extension for completing the cut off.

 The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and following information shall be permanently inscribed on the dry hole marker: well name and section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).
- 7. <u>Subsequent Plugging Reporting</u>: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of casing left in the well.
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

Received by OCD: 6/28/2021 10:09:13 AM

United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration. including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines (Contact service companies, allowing plenty of time to have the risers and power lines and poles removed prior to reclamation, don't wait till the last day and try to get them to remove infrastructure). Strip and remove caliche, contour the location to blend with the surrounding landscape. re-distribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3). Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you

have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5. Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- The approved Subsequent Report of Reclamation will be your notice that the native soils, contour
 and seedbed have been reestablished. If the BLM objectives have not been met the operator will
 be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Petroleum Engineering Tech 575-234-5909 (Office), 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Crisha Morgan Environmental Protection Specialist 575-234-5987

Melissa Horn Environmental Protection Specialist 575-234-5951

Kelsey Wade Environmental Protection Specialist 575-234-2220

Trishia Bad Bear, Hobbs Field Station Natural Resource Specialist 575-393-3612

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone: (575) 748-1283 Fax: (575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 34017

CONDITIONS

Operator:	OGRID:
EOG RESOURCES INC	7377
P.O. Box 2267	Action Number:
Midland, TX 79702	34017
	Action Type:
	[C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
gcordero	None	6/29/2021