

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT Sundry Print Report

Well Name: GUMBY BAG FEDERAL Well Location: T19S / R23E / SEC 17 / County or Parish/State: EDDY /

SENW /

County of Parish/State. EDDT

NM

Well Number: 1 Type of Well: CONVENTIONAL GAS Allottee or Tribe Name:

WELL

Lease Number: NMNM92145 Unit or CA Name: Unit or CA Number:

US Well Number: 300153224500S1 Well Status: Gas Well Shut In Operator: EOG RESOURCES

INCORPORATED

Accepted for record – NMOCD gc 8/20/2021

Notice of Intent

Type of Submission: Notice of Intent

Type of Action Plug and Abandonment

Date Sundry Submitted: 08/09/2021 Time Sundry Submitted: 11:28

Date proposed operation will begin: 09/09/2021

Procedure Description: Please see attached procedure. Thank you.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

Gumby_BAG_Federal_1_8_9_21_20210809112758.pdf

Conditions of Approval

Specialist Review

Gumby_Bag_Federal_1_Sundry_ID_2627836_P_A_20210814102819.pdf

Page 1 of 2

ed by OCD: 8/16/2021 5:27:21 AM ell Name: GUMBY BAG FEDERAL County or Parish/State: Page 2 of Well Location: T19S / R23E / SEC 17 /

SENW /

Well Number: 1 Type of Well: CONVENTIONAL GAS Allottee or Tribe Name:

WELL

Lease Number: NMNM92145 **Unit or CA Name: Unit or CA Number:**

US Well Number: 300153224500S1 Well Status: Gas Well Shut In **Operator:** EOG RESOURCES

INCORPORATED

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

Operator Electronic Signature: TINA HUERTA Signed on: AUG 09, 2021 11:28 AM

Name: EOG RESOURCES INCORPORATED

Title: Regulatory Specialist

Street Address: 104 SOUTH FOURTH STREET

City: Artesia State: NM

Phone: (575) 748-4168

Email address: tina_huerta@eogresources.com

Field Representative

Representative Name:

Street Address:

State: City: Zip:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: LONG VO BLM POC Title: Petroleum Engineer

BLM POC Phone: 5752345972 BLM POC Email Address: LVO@BLM.GOV

Disposition: Approved Disposition Date: 08/14/2021

Signature: Long Vo

High Cave

17-195-23E 30-15-32245

Gumby BAG Federal 1 - NOI to P&A


EOG Resources, Inc. plans to plug and abandon this well as follows:

- 1. MIRU all safety equipment as needed. NU BOP. POOH with production equipment.
- 2. Set a CIBP at 7671 ft with 21 sx Class C cement on top to 7468 ft. WOC and tag. This will cover Morrow perfs and Atoka top: 55% Lenk test CIBP.
- 3. Spot a 25 sx Class C cement plug from 7283 ft 7037 ft. This will cover Strawn top.
- 4. Spot a 25 sx Class C cement plug from 6083 ft 5837 ft. This will cover Cisco top.
- 5. Spot a 25 sx Class C cement plug from 4797 ft 4551 ft. This will cover Wolfcamp top.
- 6. Spot a 25 sx Class C cement plug from 3583 ft 3337 ft. This will cover Abo top.
- 7. Spot a 25 sx Class C cement plug from 2990 ft 2744 ft. This will cover L Yeso and Tubb tops.
- 8. Spot a 25 sx Class C cement plug from 2208 ft 1962 ft. This will cover U Yeso and Glorieta tops.
- 9. Perforate at 1635 ft. Spot a 25 sx Class C cement plug from 1635 ft 1389 ft. WOC and tag. This will cover intermediate casing shoe.
- 10. Perforate at 484 ft. Spot a 25 sx Class C cement plug from 484 ft 238 ft. WOC and tag. This will cover surface casing shoe.
- 11. Perforate at 100 ft. Spot a 25 sx Class C cement plug from 100 ft up to surface. WOC and tag.

 Back fill as needed.
- 12. Cut off wellhead and install dry hole marker. Clean location as per regulated.

Wellbore schematics attached

| Control Cont | | Gumby BAG Federal 1 Proposed | pesed | <u> </u> | FOOTAGES: 1650' FNL & 1980' FWL | 1650' FNL | % 1980' FWL | | 요 죠 | GL: 4066 KB: 4084 | | | |
|--|---|------------------------------|-------|----------|---------------------------------|-------------|-------------|--------|----------|----------------------|--------------|------------|-------------|
| A | TOC~50' | | | | | | | | | | | | |
| A A A A A A A A A A | | | | CASING | DETAIL | | | | - | | | | |
| FORMATION TOPS | | | | | HOLE SIZE | SIZE | WGHT | GRADE | + | | Sx Cmt | Circ/TOC | TOC Method |
| Committee Comm | 210 | | | < 1 | 17 1/2 | 13 3/8 | 48 | | 0 | 361 | 1342 | 1"ed | |
| FORMATION TOPS Formation Top | | | | n | 12 1/4 | 8/9 6 | 36 | | 1 | 1,512 | 1106 | 1"ed | |
| FORMATION TOPS Formation Top Coronation Top | | | | O | 8 3/4 | 5 1/2 | 15.5/17 | | 20 | 7,980 | 2310 | | 50 by CBL |
| Colon Colo | | | | | | | | | | | | | |
| Formation Top | | | | FORMA | TION TOPS | | | | | | | | |
| Chorder Chor | | | | | | | Ton | | | - Council | 101 | | |
| Tubble State Sta | | M | / | | | LO | | | | Formation | | | |
| Class Clas | 4 to 0 | | | | | Glorieta | 2046 | | 1 | Cisco | 0969 | | |
| Tuber Tube | S. C. | 0 | | | | Upper Yeso | 2158 | | | Strawn | 7160 | | |
| Control Ports, 7772 - 7786 Control Ports, 7772 Control Ports, 7772 Control Ports, 7772 Control Ports, 7772 - 7786 Contro | | | | | | Tubb | 2803 | | | Atoka | 7518 | | |
| TUBING DETAIL WC AF72 Cleaker Cleak | 7th Plua | | | | | Lower reso | 2940 | | | Morrow | 1771 | | |
| TOTAL TOTA | | | | | | ADO | 3400 | | | Chester | 18/3 | | |
| TUBING DETAIL Company | | | | | | MC | 46/4 | | | | | | |
| ## 2.7/8 Pacient Greek Pacient Column C | | | | 0 | | | | | | | | | |
| Procision Control Co | 210 | | | DRING | DETAIL | | | | | | | | |
| PLUGS Packet @ 7682 Top Bottom A Notes | 7 | | | # | Joints | Description | Length | 3 | <u>-</u> | Grade | Wt (lb/ft): | Top (#KB): | Btm (ftKB): |
| Perform Perfix: 7772 - 7788' PRIVICES PRIVICES THUGS T | | | | | 27/8 | | | | | | 1 | | |
| ## SX Class Top Bottom A, Morey Peris & Atokia Top 1 | 210 | | | | Packer @ 7692 | | | | | | | | |
| ## SX Class Top Bottom | Shrang | | | 90110 | | | | | | | | | |
| orrow Perfs: 7772* - 7789* | | | | 30 3 | >3 | 200 | T. | - | ŀ | | | | - |
| 2 25 C 7/037 7/283 246 Strawn Top 4 25 C 6,837 6,083 246 Strawn Top 5 25 C 6,837 6,083 246 Strawn Top 5 25 C 6,837 6,083 246 Strawn Top 6 25 C 4,597 248 Worldemp Top 7 25 C 1,982 248 Lover Yeso & Tubb Top 8 25 C 1,389 1,635 246 Int. Csg. Shoe 9 25 C 1,389 1,635 246 Strate Plug 10 25 C 0 140 247 248 Strate Plug 10 25 C 0 140 247 248 Strate Plug 10 25 C 0 140 247 248 Strate Plug 10 25 C 0 140 247 248 Strate Plug 10 25 C 0 140 247 248 Strate Plug 10 25 C 0 140 247 248 Strate Plug 10 25 C 0 140 247 248 Strate Plug 10 25 C 0 140 247 248 Strate Plug 10 25 C 0 140 247 248 Strate Plug 10 25 C 0 140 247 248 Strate Plug 10 25 C 0 140 247 248 Strate Plug 10 25 C 0 248 24 | | | | + - | 35 16 | Class | 7 468 | 7 8717 | 200 | Morrow Perfe & Atok | Notes Top | | - ag |
| orrow Perfs. 7772* - 7788* PETTO: Marrow Ma | Hth Plug | | | 0 | 70 | | 7 037 | 7 283 | 246 | Officers Top | 20.0 | | - 2 |
| orrow Perfs: 7772 - 7788' PBTD: MD PBTD: MD A 2 25 C 4,551 4,797 248 Workleamy Top- C 3,337 3,553 246 Abor Top C 3,337 3,553 246 Abor Top C 3,344 2,990 246 Lower Yeso & Tubb Top- C 3,347 2,990 246 Lower Yeso & Subreal Top- B 25 C 2,744 2,990 246 Lower Yeso & Subreal Top- C 3,347 2,990 246 Lower Yeso & Subreal Top- B 25 C 2,744 2,990 246 Lower Yeso & Subreal Top- C 3,347 2,990 246 Lower Yeso & Subreal Top- B 25 C 2,744 2,990 246 Lower Yeso & Subreal Top- B 25 C 2,344 2,990 246 Lower Yeso & Subreal Top- B 25 C 1,399 246 Lower Yeso & Subreal Top- B 25 C 1,399 246 Lower Yeso & Subreal Top- B 25 C 0 1,496 2,268 246 Lower Yeso & Subreal Top- B 25 C 0 1,399 246 Lower Yeso & Subreal Top- B 25 C 0 1,399 246 Lower Yeso & Subreal Top- B 25 C 0 1,399 246 Lower Yeso & Subreal Top- B 25 C 0 1,399 246 Lower Yeso & Subreal Top- B 25 C 0 1,399 246 Lower Yeso & Subreal Top- B 25 C 0 1,399 246 Lower Yeso & Subreal Top- B 25 C 0 1,399 246 Lower Yeso & Subreal Top- B 25 C 0 1,399 246 Lower Yeso & Subreal Top- B 26 C 0 1,399 246 Lower Yeso & Subreal Top- B 27 C 1,399 246 Lower Yeso & Subreal Top- B 27 C 1,399 246 Lower Yeso & Subreal Top- B 27 C 1,399 246 Lower Yeso & Subreal Top- B 28 C 0 1,399 246 Lower Yeso & Subreal Top- B 28 C 0 1,399 246 Lower Yeso & Subreal Top- B 28 C 0 1,399 246 Lower Yeso & Subreal Top- B 28 C 0 1,399 246 Lower Yeso & Subreal Top- B 28 C 0 1,399 246 Lower Yeso & Subreal Top- B 28 C 0 1,399 246 Lower Yeso & Subreal Top- B 28 C 0 1,399 246 Lower Yeso & Subreal Top- B 28 C 0 1,399 246 Lower Yeso & Subreal Top- B 28 C 0 1,399 246 Lower Yeso & Subreal Top- B 28 C 0 1,399 246 Lower Yeso & Subreal Top- B 28 C 0 1,399 246 Lower Yeso & Subreal Top- B 28 C 0 1,399 246 Lower Yeso & Subreal Top- B 28 C 0 1,399 246 Lower Yeso & Subreal Top- B 29 C 0 1,399 246 Lower Yeso & Subreal Top- B 29 C 0 1,399 246 Lower Yeso & Subreal Top- B 29 C 0 1,390 246 Lower Yeso & Subreal Top- B 29 C 0 1,390 246 Lower Yeso & Subreal Top- B 20 C 0 1,390 246 Lower Yeso & Subreal Top- B 20 C 0 1, | | | | 7 0 | 52 | ٥ | 1,037 | 505,7 | 240 | Strawn Top | | | z |
| orrow Perfs: 7772- 7788 PETD: MD PETD: MD KLIP PETD: MD K | | | | | 25 | o e | 5,837 | 6,083 | 246 | Cisco Top | | | z |
| orrow Perfs: 7772 - 7788' PETD: MD | | | | 4 | 52 | 0 | 4,551 | 4,797 | 246 | Wolfcamp Top | | | z |
| orrow Perfs: 7772' - 7788' PETC: MD PRID: MD | | | | 2 | 25 | O | 3,337 | 3,583 | 246 | Abo Top | | | z |
| 7 25 C 1,962 2,208 246 Upper Yeso & Glorieta Top 8 25 C 1,389 1,635 246 Int. Csg. Shoe 9 25 C 2,38 444 246 Sur. Csg. Shoe 10 25 C 0 1,967 | ard Flug | | | 9 | 25 | O | 2,744 | 2,990 | 246 | Lower Yeso & Tubb | Тор | | z |
| S 25 C 1,389 1,635 246 Int. Cog. Shoe | | | | 7 | 25 | O | 1,962 | 2,208 | 246 | Upper Yeso & Glorie | sta Top | | z |
| 10 25 C 0 190 Surface Plug 100 25 C 0 190 190 Surface Plug 100 | | | | 80 | 25 | O | 1,389 | 1,635 | 246 | Int. Csg. Shoe | | | > |
| Orrow Perfs: 7772' - 7788' 40 25 C 0 196 146 | | | | 6 | 25 | O | 238 | 484 | 246 | Sur. Csg. Shoe | | | > |
| forrow Perfs: 7772' - 7788' Perforation Detail Perforation Detail 7772 7788 Performation 7772 7788 PRTD: MD K.I.P. | nd Plug | | | 10 | 25 | ပ | 0 | 100 | 100 | | | | > |
| forrow Perfs: 7772' - 7788' Performation Detail Performation Detail C Morrow 7772 PBTD: MD K, ID | | | | | | | | 92 | 200 | | × | | |
| Orrow Perfs: 7772' - 7788' Perforation Detail Perforation Detail Pormation Top Bottom Morrow 7772 Post PBTD: MD K.I.D. | | | | | | | | | | | | | |
| PBTD: MD K.IP | st Plug | | | | | | | | | | | | |
| Perforation Detail Formation Top Bottom T772 | | | | | | | | | | | | | |
| Formation Top Bottom Morrow 7772 C MD Morrow Morrow 7772 C MD Morrow M | Existing Morrow Perfs: 7772' - 7788' | W | ₩- | Perforat | | | | | | | | | |
| C MD K. IP | | | | | | | Bottom | | | | | | |
| DW S | | | | 2 | | | 7788 | | | | | | |
| MD | | V | | | | | | | | | | | |
| OW | | 0 | | | | | | | | | | | |
| | | | | א | | | | | | | | | |



BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

- 6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.
- The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).
- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

Received by OCD: 8/16/2020 21 AM

United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/mm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration. including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines (Contact service companies, allowing plenty of time to have the risers and power lines and poles removed prior to reclamation, don't wait fill the last day and try to get them to remove infrastructure). Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point, If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reener (APD, Form 3160-3). Surface Use plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up from in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements, if you have an approved Surface Use Plan of Operation and/or an approved Surface Use Plan of Operation and Operation approved Surface Use Plan of Operation and Operation approved Surface Use Plan of Operation approved Surface Use Plan of Operation and Operation approved Surface Use Plan of Operation ap approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you

have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation. equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved. releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work

If there are any questions, please feel free to contact any of the following specialists:

Supervisory Petroleum Engineering Tech 575-234-5909 (Office), 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Crisha Morgan Environmental Protection Specialist

Melissa Hom Environmental Protection Specialist

Kelsey Wade Environmental Protection Specialist 575-234-2220

Trishia Bad Bear, Hobbs Field Station Natural Resource Specialist 575-393-3612

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone: (575) 748-1283 Fax: (575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 41979

CONDITIONS

| Operator: | OGRID: |
|-------------------|-------------------------------------|
| EOG RESOURCES INC | 7377 |
| P.O. Box 2267 | Action Number: |
| Midland, TX 79702 | 41979 |
| | Action Type: |
| | [C-103] NOI Plug & Abandon (C-103F) |

CONDITIONS

| Created By | Condition | Condition Date |
|------------|-----------|----------------|
| gcordero | None | 8/20/2021 |