

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals & Natural Resources

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-104
Revised August 1, 2011

Submit one copy to appropriate District Office

☐ AMENDED REPORT

I. REQUEST FOR ALLOWABLE AND AUTHORIZATION TO TRANSPORT

¹ Operator name and Address Devon Energy Production Company, L.P. 333 West Sheridan, Oklahoma City, OK 73102		² OGRID Number 6137
		³ Reason for Filing Code/ Effective Date NW / 6/2/21
⁴ API Number 30-015-47101	⁵ Pool Name ; LIVINGSTON RIDGE; BONE SPRING	⁶ Pool Code 39350
⁷ Property Code 325761	⁸ Property Name BORA BORA 13 24 FEDERAL COM	⁹ Well Number 212H

II. ¹⁰ Surface Location

Ul or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
N	12	23S	31E		250	South	1455	West	EDDY

¹¹ Bottom Hole Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
M	24	23S	31E		114	South	646	West	EDDY
¹² Lse Code F	¹³ Producing Method Code		¹⁴ Gas Connection Date 6/2/21		¹⁵ C-129 Permit Number		¹⁶ C-129 Effective Date		¹⁷ C-129 Expiration Date

III. Oil and Gas Transporters

¹⁸ Transporter OGRID	¹⁹ Transporter Name and Address	²⁰ O/G/W
036785	DCP Midstream P.O. Box 50020 Midland, TX 79710-0020	Gas
320009	EnLink Midstream Operating, LP 2501 Cedar Springs Road, Suite 100, Dallas, TX 75201	Oil

IV. Well Completion Data

²¹ Spud Date 11/29/20	²² Ready Date 6/2/21	²³ TD 20585	²⁴ PBTD 20578.2 MD/ 10469	²⁵ Perforations 10808 - 20568	²⁶ DHC, MC
²⁷ Hole Size		²⁸ Casing & Tubing Size		²⁹ Depth Set	³⁰ Sacks Cement
17.5		13.375		902.8	970
12.25		9 5/8		4506.5	1125
8.75		5.5		12581	
8.5		5.5		20581	3315

V. Well Test Data Tubing set: N/A

³¹ Date New Oil 6/9/21	³² Gas Delivery Date 6/9/21	³³ Test Date 6/9/21	³⁴ Test Length 24 hrs	³⁵ Tbg. Pressure psi	³⁶ Csg. Pressure psi
³⁷ Choke Size	³⁸ Oil 2221 bbl	³⁹ Water 7034 bbl	⁴⁰ Gas 2731 mcf		⁴¹ Test Method
⁴² I hereby certify that the rules of the Oil Conservation Division have been complied with and that the information given above is true and complete to the best of my knowledge and belief. Signature: 			OIL CONSERVATION DIVISION		
Printed name: Jenny Harms			Approved by: KURT SIMMONS		
Title: Regulatory Specialist			Title: NMOCD, SANTA FE		
E-mail Address: jenny.harms@dvn.com			Approval Date: 08/23/2021		
Date: 7/1/2021		Phone: 405-552-6560			

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720
District III
1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102
Revised August 1,
2011
Submit one copy to appropriate
District Office

☒ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT AS-DRILLED

¹ API Number 30-015-47101	² Pool Code 39350	³ Pool Name LIVINGSTON RIDGE; BONE SPRING
⁴ Property Code 325761	⁵ Property Name BORA BORA 13-24 FED COM	⁶ Well Number 212H
⁷ OGRID No. 6137	⁸ Operator Name DEVON ENERGY PRODUCTION COMPANY, L.P.	⁹ Elevation 3488.9


¹⁰ Surface Location

UL or lot no. N	Section 12	Township 23 S	Range 31 E	Lot Idn	Feet from the 250	North/South line SOUTH	Feet from the 1455	East/West line WEST	County EDDY
---------------------------	----------------------	-------------------------	----------------------	---------	-----------------------------	----------------------------------	------------------------------	-------------------------------	-----------------------

¹¹ Bottom Hole Location If Different From Surface

UL or lot no. M	Section 24	Township 23 S	Range 31 E	Lot Idn	Feet from the 114	North/South line SOUTH	Feet from the 646	East/West line WEST	County EDDY
¹² Dedicated Acres 320	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.						

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.

NW CORNER SEC. 12 LAT. = 32.3262057°N LONG. = 103.7400123°W NMSP EAST (FT) N = 482913.26 E = 724607.20 W/4 CORNER SEC. 12 LAT. = 32.3189531°N LONG. = 103.7400200°W NMSP EAST (FT) N = 480274.75 E = 724619.44 SECTION CORNER LAT. = 32.3116999°N LONG. = 103.7400280°W NMSP EAST (FT) N = 477836.10 E = 724631.57 W/4 CORNER SEC. 13 LAT. = 32.3044481°N LONG. = 103.7400341°W NMSP EAST (FT) N = 474997.91 E = 724644.28 SECTION CORNER LAT. = 32.2971988°N LONG. = 103.7400387°W NMSP EAST (FT) N = 472360.64 E = 724657.46 W/4 CORNER SEC. 24 LAT. = 32.2899463°N LONG. = 103.7400405°W NMSP EAST (FT) N = 469722.24 E = 724671.51 SW CORNER SEC. 24 LAT. = 32.2826895°N LONG. = 103.7400440°W NMSP EAST (FT) N = 467082.26 E = 724685.03		N/4 CORNER SEC. 12 LAT. = 32.3262026°N LONG. = 103.7314852°W NMSP EAST (FT) N = 482926.80 E = 727241.16 SEC. 12 BORA BORA 13-24 FED COM 212H ELEV. = 3488.9' LAT. = 32.3123865°N (NAD83) LONG. = 103.7353184°W NMSP EAST (FT) N = 477893.95 E = 726085.16 QUARTER CORNER LAT. = 32.3116989°N LONG. = 103.7314958°W NMSP EAST (FT) N = 477850.42 E = 727267.52 KICK OFF POINT 81' FNL, 1008 FWL LAT. = 32.3114777°N LONG. = 103.7367663°W FIRST TAKE POINT 691' FNL, 856' FWL LAT. = 32.3098013°N LONG. = 103.7372610°W QUARTER CORNER LAT. = 32.2971983°N LONG. = 103.7315037°W NMSP EAST (FT) N = 472375.15 E = 727294.69 LAST TAKE POINT 131' FSL, 647' FWL LAT. = 32.2830494°N LONG. = 103.7379520°W S/4 CORNER SEC. 24 LAT. = 32.2826866°N LONG. = 103.7315057°W NMSP EAST (FT) N = 467095.89 E = 727323.70		NE CORNER SEC. 12 LAT. = 32.3262014°N LONG. = 103.7229554°W NMSP EAST (FT) N = 482941.27 E = 729875.98 E/4 CORNER SEC. 12 LAT. = 32.3189486°N LONG. = 103.7229585°W NMSP EAST (FT) N = 480302.72 E = 729890.06 SECTION CORNER LAT. = 32.3116930°N LONG. = 103.7229595°W NMSP EAST (FT) N = 477663.17 E = 729904.77 E/4 CORNER SEC. 13 LAT. = 32.3044384°N LONG. = 103.7229618°W NMSP EAST (FT) N = 475023.97 E = 729919.08 SECTION CORNER LAT. = 32.2971933°N LONG. = 103.7229608°W NMSP EAST (FT) N = 472388.26 E = 729934.39 E/4 CORNER SEC. 24 LAT. = 32.2899374°N LONG. = 103.7229663°W NMSP EAST (FT) N = 469748.62 E = 729947.72 SE CORNER SEC. 24 LAT. = 32.2826831°N LONG. = 103.7229675°W NMSP EAST (FT) N = 467109.55 E = 729962.38		17 OPERATOR CERTIFICATION <i>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.</i>  Signature Date JENNY HARMS Printed Name JENNY.HARMS@DVN.COM E-mail Address	
AS-DRILLED BOTTOM OF HOLE LAT. = 32.2830028°N LONG. = 103.7379539°W NMSP EAST (FT) N = 467199.80 E = 725330.31 LAST TAKE POINT 131' FSL, 647' FWL LAT. = 32.2830494°N LONG. = 103.7379520°W LTP BOTTOM OF HOLE LAT. = 32.2826866°N LONG. = 103.7315057°W NMSP EAST (FT) N = 467095.89 E = 727323.70		18 SURVEYOR CERTIFICATION <i>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</i> JUNE 8, 2021 Date of Survey		 Signature and Seal of Professional Surveyor: Certificate Number: WILLIAM F. JARAMILLA, PLS 12797 Survey No. 7138A			

Intent ☐ As Drilled ☐

API #		
Operator Name:	Property Name:	Well Number

Kick Off Point (KOP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
Latitude					Longitude				NAD

First Take Point (FTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
Latitude					Longitude				NAD

Last Take Point (LTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
Latitude					Longitude				NAD

Is this well the defining well for the Horizontal Spacing Unit? ☐ YESIs this well an infill well? ☐ NO

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API #		
Operator Name:	Property Name:	Well Number

KZ 06/29/2018



Final MWD Survey Certification

Eddy County, NM

Client: DEVON ENERGY

Well Name: Bora Bora 13-24 FED COM 212H

Total Job No: SW-200632

API No: 3001547101

Start Date: November 29, 2020

End Date: January 1, 2021

Measured Start Depth: 0'

Measured End Depth: 20585'

I, Jerry Jackson, MWD Operator, certify that; I am employed by Total Directional Services, LLC and we conducted or supervised the taking of these open hole MWD surveys at the request of this client. This data is true, correct, complete and within the limitations of the tool as set forth by Total Directional Services, LLC. I am authorized and qualified to make this report and have reviewed this report and find that it conforms to the principals and procedures as set forth by Total Directional Services, LLC.

Date: 1/1/2021

Signed: *Jerry Jackson*



Devon Energy

Eddy County, NM (NAD83)

Bora Bora 13-24 Fed Com

Bora Bora 13-24 Fed Com 212H

OH

Design: OH

Standard Survey Report

04 January, 2021





Total Directional Services

Survey Report



Company:	Devon Energy	Local Co-ordinate Reference:	Well Bora Bora 13-24 Fed Com 212H
Project:	Eddy County, NM (NAD83)	TVD Reference:	3488.9' GE + 30' KB @ 3518.90usft
Site:	Bora Bora 13-24 Fed Com	MD Reference:	3488.9' GE + 30' KB @ 3518.90usft
Well:	Bora Bora 13-24 Fed Com 212H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	EDM 5000.15 Single User Db

Project	Eddy County, NM (NAD83)		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site		Bora Bora 13-24 Fed Com			
Site Position:		Northing:	477,557.32 usft	Latitude:	32.311421
From:	Map	Easting:	728,695.61 usft	Longitude:	-103.726875
Position Uncertainty:	0.00 usft	Slot Radius:	13-3/16 "	Grid Convergence:	0.32 °

Well	Bora Bora 13-24 Fed Com 212H					
Well Position	+N/-S	0.00 usft	Northing:	477,893.95 usft	Latitude:	32.312387
	+E/-W	0.00 usft	Easting:	726,085.16 usft	Longitude:	-103.735319
Position Uncertainty		0.00 usft	Wellhead Elevation:	usft	Ground Level:	3,488.90 usft

Wellbore	OH				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2020	11/16/2020	6.70	59.98	47,589.05005732

Design	OH				
Audit Notes:					
Version:	1.0	Phase:	ACTUAL	Tie On Depth:	0.00
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)	
	0.00	0.00	0.00	184.04	

Survey Program	Date	1/4/2021			
From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description	
149.00	20,527.00	Survey #1 - MWD (OH)	OWSG (Rev2) MWD	OWSG MWD - Standard	
20,585.00	20,585.00	Survey #2 - Proj to TD (OH)	BLIND	OWSG BLIND	

Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
SHL (Bora Bora 13-24 Fed Com 212H)										
149.00	0.30	42.90	149.00	0.29	0.27	-0.30	0.20	0.20	0.00	
244.00	0.50	35.90	244.00	0.80	0.68	-0.85	0.22	0.21	-7.37	
338.00	0.60	31.70	337.99	1.55	1.18	-1.63	0.11	0.11	-4.47	
432.00	0.70	41.00	431.99	2.41	1.81	-2.53	0.15	0.11	9.89	
527.00	0.60	39.30	526.98	3.23	2.51	-3.40	0.11	-0.11	-1.79	
622.00	0.60	22.40	621.98	4.07	3.01	-4.28	0.19	0.00	-17.79	
716.00	0.50	22.00	715.97	4.91	3.35	-5.13	0.11	-0.11	-0.43	
811.00	0.50	15.70	810.97	5.69	3.62	-5.93	0.06	0.00	-6.63	



Total Directional Services

Survey Report



Company:	Devon Energy	Local Co-ordinate Reference:	Well Bora Bora 13-24 Fed Com 212H
Project:	Eddy County, NM (NAD83)	TVD Reference:	3488.9' GE + 30' KB @ 3518.90usft
Site:	Bora Bora 13-24 Fed Com	MD Reference:	3488.9' GE + 30' KB @ 3518.90usft
Well:	Bora Bora 13-24 Fed Com 212H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	EDM 5000.15 Single User Db

Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
837.00	0.50	10.40	836.97	5.91	3.67	-6.16	0.18	0.00	-20.38
989.00	0.30	47.00	988.96	6.84	4.08	-7.11	0.21	-0.13	24.08
1,084.00	0.70	274.00	1,083.96	7.05	3.69	-7.29	0.98	0.42	-140.00
1,179.00	0.80	273.40	1,178.95	7.13	2.45	-7.28	0.11	0.11	-0.63
1,273.00	1.00	256.70	1,272.94	6.98	0.99	-7.03	0.35	0.21	-17.77
1,367.00	0.80	255.60	1,366.93	6.63	-0.44	-6.58	0.21	-0.21	-1.17
1,462.00	0.90	246.00	1,461.92	6.16	-1.77	-6.02	0.18	0.11	-10.11
1,556.00	0.90	247.60	1,555.91	5.58	-3.12	-5.34	0.03	0.00	1.70
1,650.00	1.00	239.30	1,649.89	4.88	-4.51	-4.55	0.18	0.11	-8.83
1,745.00	1.10	227.30	1,744.88	3.83	-5.89	-3.41	0.25	0.11	-12.63
1,840.00	1.20	228.40	1,839.86	2.56	-7.31	-2.03	0.11	0.11	1.16
1,935.00	1.30	226.60	1,934.84	1.15	-8.83	-0.53	0.11	0.11	-1.89
2,031.00	1.30	228.60	2,030.81	-0.31	-10.44	1.05	0.05	0.00	2.08
2,126.00	1.20	232.50	2,125.79	-1.63	-12.04	2.48	0.14	-0.11	4.11
2,221.00	1.20	230.10	2,220.77	-2.88	-13.59	3.83	0.05	0.00	-2.53
2,317.00	1.20	216.90	2,316.75	-4.32	-14.97	5.37	0.29	0.00	-13.75
2,412.00	1.10	227.10	2,411.73	-5.74	-16.23	6.87	0.24	-0.11	10.74
2,507.00	1.80	232.40	2,506.70	-7.27	-18.08	8.53	0.75	0.74	5.58
2,603.00	3.20	248.50	2,602.61	-9.17	-21.77	10.68	1.62	1.46	16.77
2,698.00	4.90	248.40	2,697.36	-11.64	-28.01	13.58	1.79	1.79	-0.11
2,794.00	6.70	249.00	2,792.87	-15.16	-37.05	17.73	1.88	1.88	0.63
2,889.00	7.10	251.30	2,887.18	-19.02	-47.79	22.34	0.51	0.42	2.42
2,985.00	6.70	249.90	2,982.49	-22.85	-58.67	26.93	0.45	-0.42	-1.46
3,081.00	6.40	244.40	3,077.86	-27.09	-68.75	31.86	0.72	-0.31	-5.73
3,176.00	6.70	233.60	3,172.24	-32.66	-77.99	38.07	1.33	0.32	-11.37
3,272.00	7.10	228.20	3,267.55	-39.94	-86.92	45.96	0.79	0.42	-5.63
3,368.00	6.90	226.60	3,362.83	-47.86	-95.53	54.47	0.29	-0.21	-1.67
3,463.00	6.10	226.70	3,457.22	-55.24	-103.35	62.38	0.84	-0.84	0.11
3,559.00	5.10	226.60	3,552.76	-61.67	-110.16	69.27	1.04	-1.04	-0.10
3,654.00	4.50	222.60	3,647.43	-67.32	-115.75	75.30	0.72	-0.63	-4.21
3,750.00	5.20	212.30	3,743.09	-73.77	-120.63	82.08	1.16	0.73	-10.73
3,846.00	5.60	206.00	3,838.66	-81.65	-125.00	90.25	0.74	0.42	-6.56
3,941.00	5.50	212.00	3,933.22	-89.68	-129.45	98.57	0.62	-0.11	6.32
4,036.00	5.90	212.40	4,027.75	-97.66	-134.48	106.89	0.42	0.42	0.42
4,132.00	6.00	210.30	4,123.23	-106.16	-139.65	115.73	0.25	0.10	-2.19
4,227.00	6.90	222.40	4,217.63	-114.66	-146.01	124.66	1.71	0.95	12.74
4,322.00	6.20	223.40	4,312.01	-122.60	-153.38	133.10	0.75	-0.74	1.05
4,418.00	5.80	229.60	4,407.49	-129.51	-160.63	140.50	0.79	-0.42	6.46
4,450.00	5.60	231.70	4,439.33	-131.53	-163.09	142.69	0.90	-0.63	6.56
4,610.00	5.30	228.50	4,598.60	-141.27	-174.75	153.22	0.27	-0.19	-2.00
4,705.00	5.20	226.60	4,693.21	-147.13	-181.17	159.52	0.21	-0.11	-2.00
4,801.00	5.20	227.00	4,788.81	-153.09	-187.51	165.91	0.04	0.00	0.42
4,897.00	5.80	242.10	4,884.37	-158.32	-194.98	171.66	1.63	0.63	15.73



Total Directional Services

Survey Report



Company:	Devon Energy	Local Co-ordinate Reference:	Well Bora Bora 13-24 Fed Com 212H
Project:	Eddy County, NM (NAD83)	TVD Reference:	3488.9' GE + 30' KB @ 3518.90usft
Site:	Bora Bora 13-24 Fed Com	MD Reference:	3488.9' GE + 30' KB @ 3518.90usft
Well:	Bora Bora 13-24 Fed Com 212H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	EDM 5000.15 Single User Db

Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
4,992.00	6.00	241.50	4,978.87	-162.94	-203.58	176.87	0.22	0.21	-0.63	
5,087.00	5.80	240.10	5,073.37	-167.70	-212.11	182.22	0.26	-0.21	-1.47	
5,183.00	5.60	237.10	5,168.89	-172.66	-220.25	187.74	0.37	-0.21	-3.13	
5,279.00	5.50	238.10	5,264.44	-177.64	-228.08	193.26	0.14	-0.10	1.04	
5,374.00	5.10	237.80	5,359.04	-182.29	-235.52	198.43	0.42	-0.42	-0.32	
5,469.00	5.80	240.80	5,453.61	-186.89	-243.29	203.55	0.80	0.74	3.16	
5,565.00	6.20	241.50	5,549.08	-191.73	-252.08	209.00	0.42	0.42	0.73	
5,660.00	6.20	240.90	5,643.53	-196.67	-261.07	214.56	0.07	0.00	-0.63	
5,756.00	6.10	239.90	5,738.97	-201.75	-270.01	220.26	0.15	-0.10	-1.04	
5,851.00	5.90	239.00	5,833.45	-206.79	-278.56	225.89	0.23	-0.21	-0.95	
5,946.00	5.80	238.60	5,927.96	-211.81	-286.84	231.48	0.11	-0.11	-0.42	
6,041.00	5.30	238.00	6,022.51	-216.64	-294.66	236.85	0.53	-0.53	-0.63	
6,136.00	6.60	237.90	6,117.00	-221.86	-303.01	242.65	1.37	1.37	-0.11	
6,232.00	6.50	238.30	6,212.37	-227.65	-312.30	249.07	0.11	-0.10	0.42	
6,327.00	6.20	239.40	6,306.79	-233.09	-321.30	255.13	0.34	-0.32	1.16	
6,423.00	6.10	240.60	6,402.24	-238.23	-330.20	260.89	0.17	-0.10	1.25	
6,518.00	6.00	240.50	6,496.71	-243.15	-338.92	266.41	0.11	-0.11	-0.11	
6,613.00	5.80	240.70	6,591.20	-247.95	-347.43	271.79	0.21	-0.21	0.21	
6,692.55	5.80	240.70	6,670.35	-251.88	-354.44	276.21	0.00	0.00	0.00	
S12/13 Crossing										
6,708.00	5.80	240.70	6,685.72	-252.64	-355.80	277.07	0.00	0.00	0.00	
6,804.00	5.90	238.80	6,781.22	-257.57	-364.25	282.58	0.23	0.10	-1.98	
6,899.00	6.10	237.60	6,875.70	-262.81	-372.69	288.40	0.25	0.21	-1.26	
6,994.00	5.80	237.40	6,970.19	-268.10	-380.99	294.26	0.32	-0.32	-0.21	
7,090.00	5.70	236.60	7,065.70	-273.34	-389.06	300.05	0.13	-0.10	-0.83	
7,185.00	5.40	237.40	7,160.26	-278.34	-396.76	305.59	0.33	-0.32	0.84	
7,280.00	5.10	236.00	7,254.86	-283.11	-404.03	310.86	0.34	-0.32	-1.47	
7,375.00	5.30	236.00	7,349.47	-287.93	-411.17	316.16	0.21	0.21	0.00	
7,471.00	5.10	235.40	7,445.07	-292.83	-418.36	321.56	0.22	-0.21	-0.63	
7,566.00	3.50	235.10	7,539.80	-296.89	-424.21	326.02	1.68	-1.68	-0.32	
7,661.00	2.30	228.90	7,634.68	-299.80	-428.03	329.19	1.30	-1.26	-6.53	
7,757.00	2.20	224.80	7,730.60	-302.37	-430.78	331.95	0.20	-0.10	-4.27	
7,852.00	2.20	221.70	7,825.53	-305.03	-433.27	334.78	0.13	0.00	-3.26	
7,948.00	2.30	218.70	7,921.46	-307.91	-435.70	337.82	0.16	0.10	-3.13	
8,043.00	2.50	215.10	8,016.38	-311.09	-438.09	341.16	0.26	0.21	-3.79	
8,138.00	1.40	241.10	8,111.32	-313.35	-440.30	343.57	1.46	-1.16	27.37	
8,234.00	1.50	236.50	8,207.29	-314.61	-442.37	344.97	0.16	0.10	-4.79	
8,329.00	1.60	226.70	8,302.26	-316.20	-444.37	346.71	0.30	0.11	-10.32	
8,424.00	1.90	268.70	8,397.22	-317.15	-446.91	347.83	1.35	0.32	44.21	
8,519.00	2.20	263.20	8,492.16	-317.40	-450.30	348.32	0.38	0.32	-5.79	
8,615.00	1.00	258.80	8,588.12	-317.78	-452.95	348.88	1.26	-1.25	-4.58	
8,710.00	0.00	45.80	8,683.11	-317.94	-453.76	349.10	1.05	-1.05	0.00	
8,805.00	0.60	124.80	8,778.11	-318.22	-453.35	349.36	0.63	0.63	0.00	
8,901.00	1.50	131.10	8,874.09	-319.34	-451.99	350.37	0.94	0.94	6.56	



Total Directional Services

Survey Report



Company:	Devon Energy	Local Co-ordinate Reference:	Well Bora Bora 13-24 Fed Com 212H
Project:	Eddy County, NM (NAD83)	TVD Reference:	3488.9' GE + 30' KB @ 3518.90usft
Site:	Bora Bora 13-24 Fed Com	MD Reference:	3488.9' GE + 30' KB @ 3518.90usft
Well:	Bora Bora 13-24 Fed Com 212H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	EDM 5000.15 Single User Db

Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
8,996.00	0.90	145.50	8,969.07	-320.77	-450.63	351.70	0.70	-0.63	15.16
9,092.00	0.60	342.30	9,065.07	-320.91	-450.36	351.83	1.55	-0.31	-170.00
9,187.00	0.40	219.90	9,160.07	-320.69	-450.72	351.63	0.93	-0.21	-128.84
9,283.00	0.70	165.10	9,256.06	-321.52	-450.79	352.46	0.60	0.31	-57.08
9,378.00	1.10	147.50	9,351.05	-322.85	-450.15	353.74	0.51	0.42	-18.53
9,474.00	1.40	145.10	9,447.03	-324.59	-448.98	355.39	0.32	0.31	-2.50
9,569.00	1.30	141.90	9,542.00	-326.38	-447.65	357.09	0.13	-0.11	-3.37
9,665.00	1.20	132.60	9,637.98	-327.92	-446.24	358.53	0.24	-0.10	-9.69
9,760.00	1.20	169.70	9,732.96	-329.57	-445.33	360.11	0.80	0.00	39.05
9,797.00	1.50	180.80	9,769.95	-330.44	-445.27	360.97	1.07	0.81	30.00
KOP									
9,876.00	4.00	188.50	9,848.85	-334.20	-445.69	364.75	3.19	3.16	9.75
9,972.00	14.40	192.90	9,943.49	-349.19	-448.86	379.93	10.85	10.83	4.58
9,984.69	15.73	192.27	9,955.74	-352.41	-449.58	383.19	10.58	10.50	-4.99
100' FNL HL Crossing									
10,067.00	24.40	189.80	10,032.98	-380.12	-454.85	411.20	10.58	10.53	-3.00
10,162.00	34.10	190.90	10,115.77	-425.71	-463.25	457.27	10.23	10.21	1.16
10,258.00	42.80	193.30	10,190.89	-483.99	-475.86	516.30	9.19	9.06	2.50
10,353.00	49.10	193.30	10,256.90	-550.41	-491.56	583.65	6.63	6.63	0.00
10,448.00	53.80	193.50	10,316.09	-622.66	-508.78	656.94	4.95	4.95	0.21
10,544.00	61.60	194.60	10,367.35	-701.31	-528.50	736.78	8.18	8.13	1.15
10,639.00	72.10	195.20	10,404.65	-785.60	-550.94	822.44	11.07	11.05	0.63
10,734.00	76.60	195.90	10,430.27	-873.70	-575.47	912.05	4.79	4.74	0.74
10,740.39	77.19	195.85	10,431.72	-879.68	-577.17	918.14	9.29	9.26	-0.76
LP (Bora Bora 13-24 Fed Com 212H)									
10,829.00	85.40	195.20	10,445.12	-964.01	-600.59	1,003.91	9.29	9.26	-0.74
10,925.00	87.20	196.20	10,451.31	-1,056.23	-626.51	1,097.72	2.14	1.88	1.04
11,021.00	91.00	195.80	10,452.82	-1,148.48	-652.96	1,191.61	3.98	3.96	-0.42
11,115.00	91.40	196.10	10,450.85	-1,238.84	-678.79	1,283.56	0.53	0.43	0.32
11,209.00	88.60	193.80	10,450.85	-1,329.65	-703.04	1,375.85	3.85	-2.98	-2.45
11,304.00	88.30	191.00	10,453.42	-1,422.39	-723.43	1,469.79	2.96	-0.32	-2.95
11,398.00	88.80	188.80	10,455.80	-1,514.95	-739.58	1,563.27	2.40	0.53	-2.34
11,493.00	90.20	186.70	10,456.63	-1,609.07	-752.39	1,658.06	2.66	1.47	-2.21
11,588.00	89.30	184.70	10,457.04	-1,703.60	-761.83	1,753.01	2.31	-0.95	-2.11
11,682.00	89.70	185.10	10,457.86	-1,797.25	-769.85	1,846.99	0.60	0.43	0.43
11,777.00	89.20	183.40	10,458.77	-1,891.98	-776.89	1,941.99	1.87	-0.53	-1.79
11,871.00	89.10	180.60	10,460.17	-1,985.90	-780.17	2,035.91	2.98	-0.11	-2.98
11,965.00	90.10	181.30	10,460.83	-2,079.89	-781.73	2,129.77	1.30	1.06	0.74
12,060.00	89.70	178.70	10,460.99	-2,174.88	-781.73	2,224.52	2.77	-0.42	-2.74
12,154.00	89.50	178.60	10,461.65	-2,268.85	-779.52	2,318.10	0.24	-0.21	-0.11
12,249.00	90.40	180.60	10,461.73	-2,363.84	-778.85	2,412.81	2.31	0.95	2.11
12,343.00	89.80	179.90	10,461.57	-2,457.84	-779.26	2,506.61	0.98	-0.64	-0.74
12,437.00	91.30	180.40	10,460.66	-2,551.83	-779.51	2,600.38	1.68	1.60	0.53



Total Directional Services

Survey Report



Company:	Devon Energy	Local Co-ordinate Reference:	Well Bora Bora 13-24 Fed Com 212H
Project:	Eddy County, NM (NAD83)	TVD Reference:	3488.9' GE + 30' KB @ 3518.90usft
Site:	Bora Bora 13-24 Fed Com	MD Reference:	3488.9' GE + 30' KB @ 3518.90usft
Well:	Bora Bora 13-24 Fed Com 212H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	EDM 5000.15 Single User Db

Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
12,533.00	91.00	180.20	10,458.74	-2,647.81	-780.01	2,696.16	0.38	-0.31	-0.21	
12,563.00	90.70	179.70	10,458.29	-2,677.81	-779.99	2,726.08	1.94	-1.00	-1.67	
12,657.00	91.10	180.30	10,456.82	-2,771.79	-779.99	2,819.84	0.77	0.43	0.64	
12,753.00	90.30	180.30	10,455.64	-2,867.79	-780.49	2,915.62	0.83	-0.83	0.00	
12,848.00	90.80	180.70	10,454.73	-2,962.78	-781.32	3,010.44	0.67	0.53	0.42	
12,943.00	90.10	180.70	10,453.98	-3,057.77	-782.48	3,105.27	0.74	-0.74	0.00	
13,039.00	89.80	180.90	10,454.07	-3,153.76	-783.82	3,201.12	0.38	-0.31	0.21	
13,134.00	88.00	178.80	10,455.89	-3,248.73	-783.57	3,295.84	2.91	-1.89	-2.21	
13,229.00	88.40	179.30	10,458.88	-3,343.67	-782.00	3,390.43	0.67	0.42	0.53	
13,324.00	89.00	179.90	10,461.03	-3,438.64	-781.33	3,485.12	0.89	0.63	0.63	
13,419.00	89.60	180.70	10,462.19	-3,533.63	-781.83	3,579.91	1.05	0.63	0.84	
13,515.00	90.10	180.10	10,462.44	-3,629.63	-782.50	3,675.72	0.81	0.52	-0.63	
13,610.00	90.10	179.60	10,462.28	-3,724.63	-782.25	3,770.46	0.53	0.00	-0.53	
13,705.00	90.60	179.20	10,461.70	-3,819.62	-781.26	3,865.15	0.67	0.53	-0.42	
13,801.00	91.40	179.70	10,460.02	-3,915.60	-780.34	3,960.83	0.98	0.83	0.52	
13,896.00	89.60	179.30	10,459.19	-4,010.59	-779.51	4,055.52	1.94	-1.89	-0.42	
13,991.00	90.80	179.70	10,458.86	-4,105.58	-778.68	4,150.22	1.33	1.26	0.42	
14,087.00	89.30	179.60	10,458.78	-4,201.58	-778.09	4,245.94	1.57	-1.56	-0.10	
14,182.00	89.80	179.00	10,459.52	-4,296.57	-776.93	4,340.61	0.82	0.53	-0.63	
14,277.00	90.40	179.00	10,459.36	-4,391.55	-775.27	4,435.24	0.63	0.63	0.00	
14,372.00	88.40	178.70	10,460.35	-4,486.52	-773.37	4,529.84	2.13	-2.11	-0.32	
14,468.00	88.30	178.30	10,463.12	-4,582.45	-770.86	4,625.35	0.43	-0.10	-0.42	
14,563.00	89.60	179.10	10,464.86	-4,677.41	-768.70	4,719.92	1.61	1.37	0.84	
14,658.00	90.90	180.80	10,464.44	-4,772.40	-768.62	4,814.68	2.25	1.37	1.79	
14,753.00	90.00	179.60	10,463.70	-4,867.39	-768.95	4,909.46	1.58	-0.95	-1.26	
14,848.00	90.60	179.30	10,463.20	-4,962.39	-768.04	5,004.15	0.71	0.63	-0.32	
14,943.00	92.00	180.10	10,461.04	-5,057.36	-767.54	5,098.85	1.70	1.47	0.84	
15,039.00	90.50	180.50	10,458.95	-5,153.33	-768.04	5,194.62	1.62	-1.56	0.42	
15,134.00	91.80	183.10	10,457.04	-5,248.26	-771.03	5,289.52	3.06	1.37	2.74	
15,230.00	91.00	181.70	10,454.70	-5,344.14	-775.04	5,385.45	1.68	-0.83	-1.46	
15,325.00	89.80	181.70	10,454.03	-5,439.09	-777.86	5,480.36	1.26	-1.26	0.00	
15,415.66	89.32	180.17	10,454.73	-5,529.74	-779.34	5,570.89	1.76	-0.53	-1.68	
S13/24 Crossing										
15,420.00	89.30	180.10	10,454.78	-5,534.08	-779.35	5,575.22	1.76	-0.53	-1.68	
15,515.00	88.00	178.30	10,457.02	-5,629.03	-778.03	5,669.85	2.34	-1.37	-1.89	
15,611.00	88.00	178.10	10,460.37	-5,724.93	-775.01	5,765.29	0.21	0.00	-0.21	
15,706.00	88.00	178.60	10,463.69	-5,819.83	-772.28	5,859.76	0.53	0.00	0.53	
15,801.00	88.00	178.80	10,467.00	-5,914.75	-770.13	5,954.29	0.21	0.00	0.21	
15,897.00	89.00	178.70	10,469.51	-6,010.69	-768.03	6,049.85	1.05	1.04	-0.10	
15,993.00	92.00	179.50	10,468.68	-6,106.66	-766.53	6,145.48	3.23	3.13	0.83	
16,088.00	92.60	180.00	10,464.86	-6,201.59	-766.11	6,240.14	0.82	0.63	0.53	
16,183.00	90.80	180.60	10,462.05	-6,296.54	-766.61	6,334.89	2.00	-1.89	0.63	
16,279.00	88.80	178.30	10,462.38	-6,392.52	-765.69	6,430.57	3.17	-2.08	-2.40	
16,374.00	89.60	178.60	10,463.71	-6,487.48	-763.12	6,525.11	0.90	0.84	0.32	



Total Directional Services

Survey Report



Company:	Devon Energy	Local Co-ordinate Reference:	Well Bora Bora 13-24 Fed Com 212H
Project:	Eddy County, NM (NAD83)	TVD Reference:	3488.9' GE + 30' KB @ 3518.90usft
Site:	Bora Bora 13-24 Fed Com	MD Reference:	3488.9' GE + 30' KB @ 3518.90usft
Well:	Bora Bora 13-24 Fed Com 212H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	EDM 5000.15 Single User Db

Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
16,469.00	89.40	178.60	10,464.54	-6,582.45	-760.80	6,619.68	0.21	-0.21	0.00
16,565.00	89.40	179.20	10,465.54	-6,678.42	-758.95	6,715.29	0.62	0.00	0.63
16,660.00	89.80	179.60	10,466.20	-6,773.41	-757.96	6,809.97	0.60	0.42	0.42
16,756.00	91.20	180.40	10,465.37	-6,869.41	-757.96	6,905.73	1.68	1.46	0.83
16,851.00	91.00	179.90	10,463.54	-6,964.39	-758.21	7,000.49	0.57	-0.21	-0.53
16,946.00	88.90	179.80	10,463.63	-7,059.38	-757.96	7,095.23	2.21	-2.21	-0.11
17,042.00	88.90	179.70	10,465.47	-7,155.37	-757.54	7,190.95	0.10	0.00	-0.10
17,137.00	88.30	179.70	10,467.79	-7,250.34	-757.04	7,285.64	0.63	-0.63	0.00
17,233.00	89.60	180.10	10,469.55	-7,346.32	-756.88	7,381.38	1.42	1.35	0.42
17,328.00	88.60	179.90	10,471.04	-7,441.30	-756.88	7,476.13	1.07	-1.05	-0.21
17,424.00	88.90	180.10	10,473.14	-7,537.28	-756.88	7,571.87	0.38	0.31	0.21
17,520.00	89.20	180.10	10,474.73	-7,633.27	-757.04	7,667.63	0.31	0.31	0.00
17,615.00	89.00	180.10	10,476.22	-7,728.26	-757.21	7,762.39	0.21	-0.21	0.00
17,711.00	89.50	180.80	10,477.48	-7,824.24	-757.96	7,858.19	0.90	0.52	0.73
17,806.00	89.50	180.80	10,478.30	-7,919.23	-759.29	7,953.04	0.00	0.00	0.00
17,901.00	87.80	180.10	10,480.54	-8,014.20	-760.04	8,047.82	1.94	-1.79	-0.74
17,996.00	89.00	178.20	10,483.20	-8,109.14	-758.63	8,142.43	2.36	1.26	-2.00
18,091.00	88.20	176.80	10,485.52	-8,204.02	-754.48	8,236.78	1.70	-0.84	-1.47
18,187.00	90.30	176.90	10,486.77	-8,299.86	-749.21	8,332.02	2.19	2.19	0.10
18,282.00	90.20	177.60	10,486.36	-8,394.75	-744.65	8,426.35	0.74	-0.11	0.74
18,377.00	92.20	180.10	10,484.37	-8,489.70	-742.75	8,520.93	3.37	2.11	2.63
18,473.00	92.20	179.90	10,480.68	-8,585.63	-742.75	8,616.62	0.21	0.00	-0.21
18,569.00	92.30	179.90	10,476.91	-8,681.55	-742.58	8,712.29	0.10	0.10	0.00
18,664.00	91.50	181.50	10,473.76	-8,776.49	-743.74	8,807.08	1.88	-0.84	1.68
18,759.00	91.90	181.50	10,470.95	-8,871.42	-746.22	8,901.94	0.42	0.42	0.00
18,855.00	91.80	181.60	10,467.85	-8,967.33	-748.82	8,997.80	0.15	-0.10	0.10
18,950.00	90.00	181.90	10,466.36	-9,062.27	-751.72	9,092.71	1.92	-1.89	0.32
19,046.00	90.20	182.00	10,466.19	-9,158.22	-754.99	9,188.65	0.23	0.21	0.10
19,141.00	88.90	180.00	10,466.93	-9,253.19	-756.64	9,283.50	2.51	-1.37	-2.11
19,237.00	89.20	180.40	10,468.53	-9,349.18	-756.98	9,379.27	0.52	0.31	0.42
19,332.00	88.30	179.50	10,470.60	-9,444.15	-756.90	9,474.01	1.34	-0.95	-0.95
19,427.00	88.40	179.30	10,473.33	-9,539.11	-755.90	9,568.66	0.24	0.11	-0.21
19,523.00	88.00	179.40	10,476.35	-9,635.05	-754.81	9,664.29	0.43	-0.42	0.10
19,619.00	87.70	179.20	10,479.95	-9,730.98	-753.64	9,759.89	0.38	-0.31	-0.21
19,714.00	88.70	178.50	10,482.93	-9,825.91	-751.74	9,854.46	1.28	1.05	-0.74
19,809.00	88.90	178.40	10,484.92	-9,920.86	-749.17	9,948.98	0.24	0.21	-0.11
19,905.00	91.10	179.90	10,484.92	-10,016.84	-747.74	10,044.63	2.77	2.29	1.56
20,000.00	92.40	180.40	10,482.02	-10,111.79	-747.99	10,139.36	1.47	1.37	0.53
20,095.00	92.60	179.90	10,477.88	-10,206.70	-748.24	10,234.05	0.57	0.21	-0.53
20,191.00	91.70	180.50	10,474.28	-10,302.63	-748.58	10,329.77	1.13	-0.94	0.63
20,286.00	89.80	180.50	10,473.03	-10,397.61	-749.40	10,424.57	2.00	-2.00	0.00
20,381.00	89.70	180.50	10,473.45	-10,492.61	-750.23	10,519.39	0.11	-0.11	0.00
20,477.00	91.70	181.50	10,472.28	-10,588.58	-751.91	10,615.24	2.33	2.08	1.04



Total Directional Services

Survey Report



Company:	Devon Energy	Local Co-ordinate Reference:	Well Bora Bora 13-24 Fed Com 212H
Project:	Eddy County, NM (NAD83)	TVD Reference:	3488.9' GE + 30' KB @ 3518.90usft
Site:	Bora Bora 13-24 Fed Com	MD Reference:	3488.9' GE + 30' KB @ 3518.90usft
Well:	Bora Bora 13-24 Fed Com 212H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	EDM 5000.15 Single User Db

Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
20,527.00	91.90	181.70	10,470.71	-10,638.54	-753.30	10,665.17	0.57	0.40	0.40
20,585.00	91.90	181.70	10,468.78	-10,696.48	-755.02	10,723.09	0.00	0.00	0.00
BHL - PBHL (Bora Bora 13-24 Fed Com 212H)									

Design Annotations				
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
6,692.55	6,670.35	-251.88	-354.44	S12/13 Crossing
9,797.00	9,769.95	-330.44	-445.27	KOP
9,984.69	9,955.74	-352.41	-449.58	100' FNL HL Crossing
15,415.66	10,454.73	-5,529.74	-779.34	S13/24 Crossing
20,585.00	10,468.78	-10,696.48	-755.02	BHL

Checked By: _____ Approved By: _____ Date: _____

Submit 1 Copy To Appropriate District Office
 District I – (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II – (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III – (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV – (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

Form C-103
 Revised August 1, 2011

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-47101
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐		5. Indicate Type of Lease STATE ☐ FEE ☐
2. Name of Operator Devon Energy Production Company, L.P.		6. State Oil & Gas Lease No.
3. Address of Operator 333 West Sheridan, Oklahoma City, OK 73102		7. Lease Name or Unit Agreement Name BORA BORA 13 24 FEDERAL COM
4. Well Location Unit Letter N : 250 feet from the South line and 1455 feet from the West line Section 12 Township 23S Range 31E NMPM County EDDY		8. Well Number 212H
11. Elevation (Show whether DR, RKB, RT, GR, etc.)		9. OGRID Number 6137
10. Pool name or Wildcat ; LIVINGSTON RIDGE; BONE SPRING		

GL: 3488.9

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
 PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
 DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
 COMMENCE DRILLING OPNS. ☐ P AND A ☐
 CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: COMPLETION ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.
 5/13/2021-5/20/2021: MIRU WL & PT. PT csg to 12000 PSI for 30min, OK. Ran CBL, ETOC 4550' TIH w/pump through frac plug and guns. Perf BONESPRING, 10808-20568. Frac totals 19516175# prop, 335149 bbl fluid, 45 bbls acid. DO plugs & CO to PBTD with float collar 20578.2 MD/ 10469 TVD. CHC, FWB, ND BOP. Tubing set:N/A TOP: 6/2/2021
 RUSTLER-1025
 SALT-1330
 BASE OF SALT-4280
 LAMAR-4280
 BELL CANYON-4525
 CHERRY CANYON-5460
 Brushy Canyon-6710
 1st Bone Spring Lime-8430
 Bone Spring 1st-8430
 Bone Spring 2nd-10090
 3rd Bone Spring Lime-10600
 Bone Spring 3rd-11320
 Wolfcamp-11750
 Strawn-13425

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jenny Harms TITLE _____ DATE _____

Type or print name Jenny Harms E-mail address jenny.harms@dvn.com PHONE: 7/1/2021

For State Use Only Jenny Harms Regulatory Specialist 405-552-6560

APPROVED BY: _____ TITLE _____ DATE _____

Conditions of Approval (if any):

Submit To Appropriate District Office Two Copies <u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 811 S. First St., Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505				Form C-105 Revised August 1, 2011					
		1. WELL API NO. 30-015-47101		2. Type of Lease ☐ STATE ☐ FEE ☒ FED/INDIAN		3. State Oil & Gas Lease No.					
WELL COMPLETION OR RECOMPLETION REPORT AND LOG											
4. Reason for filing: ☒ COMPLETION REPORT (Fill in boxes #1 through #31 for State and Fee wells only) ☐ C-144 CLOSURE ATTACHMENT (Fill in boxes #1 through #9, #15 Date Rig Released and #32 and/or #33; attach this and the plat to the C-144 closure report in accordance with 19.15.17.13.K NMAC)						5. Lease Name or Unit Agreement Name BORA BORA 13 24 FEDERAL COM					
						6. Well Number: 212H					
7. Type of Completion: ☒ NEW WELL ☐ WORKOVER ☐ DEEPENING ☐ PLUGBACK ☐ DIFFERENT RESERVOIR ☐ OTHER											
8. Name of Operator Devon Energy Production Company, L.P.						9. OGRID 6137					
10. Address of Operator 333 West Sheridan Avenue, Oklahoma City, OK 73102						11. Pool name or Wildcat ; LIVINGSTON RIDGE; BONE SPRING					
12. Location	Unit Ltr	Section	Township	Range	Lot	Feet from the	N/S Line	Feet from the	E/W Line	County	
Surface:	N	12	23S	31E		250	South	1455	West	EDDY	
BH:	M	24	23S	31E		114	South	646	West	EDDY	
13. Date Spudded 11/29/20	14. Date T.D. Reached 1/1/21	15. Date Rig Released 1/5/21		16. Date Completed (Ready to Produce) 6/2/21		17. Elevations (DF and RKB, RT, GR, etc.) 3488.9 GL					
18. Total Measured Depth of Well 20585 MD, 10468 TVD		19. Plug Back Measured Depth 20578.2 MD/ 10469		20. Was Directional Survey Made? Yes		21. Type Electric and Other Logs Run CBL					
22. Producing Interval(s), of this completion - Top, Bottom, Name 10808-20568, LIVINGSTON RIDGE; BONE SPRING											
23. CASING RECORD (Report all strings set in well)											
CASING SIZE		WEIGHT LB./FT.		DEPTH SET		HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED	
13.375		54.5		902.8		17.5		970			
9 5/8		40		4506.5		12.25		1125			
5.5		20		12581		8.75					
5.5		20		20581		8.5		3315		TOC @ 4550	
24. LINER RECORD								25. TUBING RECORD			
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN		SIZE	DEPTH SET		PACKER SET		
							n/a				
26. Perforation record (interval, size, and number) 10808 - 20568, total 1144 holes						27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED 10808-20568 Acidize and frac in 39 stages.					
28. PRODUCTION											
Date First Production 6/2/21		Production Method (<i>Flowing, gas lift, pumping - Size and type pump</i>)				Well Status (<i>Prod. or Shut-in</i>) Producing					
Date of Test 6/9/21	Hours Tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl 2221	Gas - MCF 2731	Water - Bbl. 7034	Gas - Oil Ratio 1229				
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (<i>Corr.</i>)					
29. Disposition of Gas (<i>Sold, used for fuel, vented, etc.</i>) Sold								30. Test Witnessed By			
31. List Attachments Directional Survey											
32. If a temporary pit was used at the well, attach a plat with the location of the temporary pit.											
33. If an on-site burial was used at the well, report the exact location of the on-site burial:											
Latitude				Longitude				NAD 1927 1983			
I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief											
Signature 		Printed Name Jenny Harms		Title Regulatory Specialist		Date 7/1/2021					
E-mail Address jenny.harms@dvn.com											

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well and not later than 60 days after completion of closure. When submitted as a completion report, this shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 11, 12 and 26-31 shall be reported for each zone.

Southeastern New Mexico		Northwestern New Mexico	
RUSTLER - 1025			
SALT - 1330			
BASE OF SALT - 4280			
LAMAR - 4280			
BELL CANYON - 4525			
CHERRY CANYON - 5460			
Brushy Canyon - 6710			
1st Bone Spring Lime - 8430			
Bone Spring 1st - 8430			
Bone Spring 2nd - 10090			
3rd Bone Spring Lime - 10600			
Bone Spring 3rd - 11320			
Wolfcamp - 11750			
Strawn - 13425			

No. 1, from.....	to.....	No. 3, from.....	to.....
No. 2, from.....	N/A	No. 4, from.....	N/A
N/A	N/A	N/A	N/A

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

ACKNOWLEDGMENTS

Action 34752

ACKNOWLEDGMENTS

Operator: DEVON ENERGY PRODUCTION COMPANY, LP 333 West Sheridan Ave. Oklahoma City, OK 73102	OGRID: 6137
	Action Number: 34752
	Action Type: [C-104] Completion Packet (C-104C)

ACKNOWLEDGMENTS

☒	I hereby certify that the required Water Use Report has been, or will be, submitted for this wells completion.
☒	I hereby certify that the required FracFocus disclosure has been, or will be, submitted for this wells completion.

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720

District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720

District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 34752

CONDITIONS

Operator: DEVON ENERGY PRODUCTION COMPANY, LP 333 West Sheridan Ave. Oklahoma City, OK 73102	OGRID: 6137
	Action Number: 34752
	Action Type: [C-104] Completion Packet (C-104C)

CONDITIONS

Created By	Condition	Condition Date
ksimmons	None	8/23/2021