

Submit 1 Copy To Appropriate District Office
 District I - (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II - (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III - (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV - (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

Form C-103
 Revised July 18, 2013

SUNDY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-25-28905
1. Type of Well: Oil Well ☐ Gas Well ☒ Other SWD		5. Indicate Type of Lease STATE ☒ FEE ☐
2. Name of Operator SUNDOWN ENERGY LP		6. State Oil & Gas Lease No. 96101
3. Address of Operator 16400 DALLAS PARKWAY, STE. 100 DALLAS, TX 75248		7. Lease Name or Unit Agreement Name Kochia AAM State
4. Well Location Unit Letter <u>O</u> : 990 feet from the <u>SOUTH</u> line and 2310 feet from the <u>EAST</u> line Section 35 Township 15S Range 36E NMPM LEA County		8. Well Number 1 SWD
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3855' GR		9. OGRID Number 232611
		10. Pool name or Wildcat Devonian

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	P AND A ☒
PULL OR ALTER CASING ☐	MULTIPLE COMPL ☐	CASING/CEMENT JOB ☐	PNR ☐
DOWNHOLE COMMINGLE ☐			
CLOSED-LOOP SYSTEM ☐			
OTHER: ☐		OTHER: Did not convert to inj. ☐	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- 1) Set CIBP @ 13,600'.
- 2) TIH w/ tubing to 13600'. Spot 25 sxs balanced cement plug 13,200' to 13,600'.
- 3) TIH w/ tubing and tag cement at 13,180'. Displace hole w/ 9.8 PPG mud.
- 4) TOH w/ tbg to 11330'. Spot 35 sxs balanced cement plug 11230' to 11,330' (TOL @ 11280').
- 5) TOH w/ tbg to 10,956'. Spot 25 sxs cement. WOC. Tag at 10,698'.
- 6) TOH w/ tbg to 9,720'. Spot 25 sxs cement. WOC. Tag at 9471'.
- 7) TOH w/ tbg to 8,400'. Spot 25 sxs cement. WOC. Tag at 8180'.
- 8) TOH w/ tbg to 6516'. Spot 25 sxs cement. WOC. Tag at 6305'.
- 9) TOH w/ tbg to 5,550'. Spot 40 sxs cmt from 5,550' to 5450'. WOC.
- 10) Perf and squeeze San Andres at 4970' with 40 sxs cement plug from 4793' to 4970'.
- 11) Perf and squeeze Queen at 4000' with 40 sxs cement plug from 3813' to 4050'.
- 12) Perf and squeeze Yates at 3150' with 40 sxs cement plug from 2974' to 3150'.
- 13) Perf and squeeze top of salt at 1700' with 40 sxs cement plug 1483' to 1750'.
- 14) Perf and squeeze surface at 450' with 100 sxs cement from 0 to 500'.
- 15) Cut off casing below GL and weld on ID plate.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Steve Flynn TITLE Joint Operations Engineer DATE 6/24/2021
 Type or print name Steve Flynn E-mail address: sflynn@sundownenergy.com PHONE (214) 368-6100 ext 2114
 For State Use Only

APPROVED BY: Kerry Fortner TITLE Compliance Officer A DATE 8/24/21
 Conditions of Approval (if any):

WELL DATA SHEET

PROPOSED

LEASE: KOCHIA AAM STATE

WELL: 1

FIELD: WILDCAT PENN/DEAN, DEVONIAN

LOC: 990' FSL & 2310' FEL

SEC: 35

Unit: O T: 15S R: 36E

STATUS: ~~Converted to GWD~~ PJA

CO: LEA

API NO: 30-025-28905

TD: 14,200'

ST: NM

LEASE # LG 2252

PBD: 14,160'

FINAL PLUGGING RECORD

Spud Date: 9-21-84

Comp. Date: 1-28-85

GL: 3855'

DF:

KB:

Plug #12: 12,000-500' (100% cement)

Cag Detail:

Hole Size:

13-3/8	OD	54.5	Wt, grade	J55
csg set @	404	Wt	435	bx.
Circ?	YES	TOC @		By

Hole Size:

8-5/8	OD	32	Wt, grade	J55 & N80
csg set @	4922	Wt	2350	bx.
Circ?	YES	TOC @		By

Hole Size:

5-1/2	OD	17	Wt, grade	S95 & N80
csg set @	13800	Wt	1800	bx.
In	2	stages w/OV tool @		
Stage 1 circ?	YES	TOC		By
Stage 2 circ?		TOC	8950	By

Hole Size: 4-1/2"

4" Liner, 8.5 # & 10.46#, L-80
Cemented w/ 150 sx 50/50 POZ TF cement
Set @ 14,200' TOL @ 11,280'

TOC @ 8950' by CBL

4" Liner TOL @ 11,280'

Strawn Parts 11,499-508' & 11,678-86' (SQZD)

Morrow Parts 12,234-55' cemented behind liner

Morrow Parts 12,494-98', 12,518-18', 64-73 cemented behind liner

DV TOOL @ 12,602'

CIBP @ 13,494' for whipstock

Junk subpump TOF @ 13,558'

Devonian Parts 13,594-96'

CIBP @ 13,654 W/ 4' CMT

5-1/2" RBP @ 13,600
Devonian Parts 13,672 - 76'
TD 13,800'

Window @ 13,482'

Plug #1: 13,180'-13,600' (25% cement)

CIBP @ 13,600'

Pecker @ 13,639'

Devonian Parts @ 13,670-13,720'

PBD 14,160'

TD 14,200'

(Bullards Drilling #21344)

10/31/19.

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 34221

CONDITIONS

Operator: SUNDOWN ENERGY LP 16400 Dallas Pkwy Dallas, TX 75248	OGRID: 232611
	Action Number: 34221
	Action Type: [C-103] Sub. Plugging (C-103P)

CONDITIONS

Created By	Condition	Condition Date
kfortner	None	8/24/2021