

<b>Well Name:</b> BOX CANYON 34 BAB FEDERAL	<b>Well Location:</b> T20S / R21E / SEC 34 / NESE /	<b>County or Parish/State:</b> EDDY / NM
<b>Well Number:</b> 1	<b>Type of Well:</b> CONVENTIONAL GAS WELL	<b>Allottee or Tribe Name:</b>
<b>Lease Number:</b> NMNM37826A	<b>Unit or CA Name:</b>	<b>Unit or CA Number:</b>
<b>US Well Number:</b> 300153077900S1	<b>Well Status:</b> Gas Well Shut In	<b>Operator:</b> EOG RESOURCES INCORPORATED

Accepted for record – NMOCD gc 10/18/2021

Notice of Intent

**Sundry ID:** 2636085

<b>Type of Submission:</b> Notice of Intent	<b>Type of Action:</b> Plug and Abandonment
<b>Date Sundry Submitted:</b> 09/27/2021	<b>Time Sundry Submitted:</b> 01:18
<b>Date proposed operation will begin:</b> 10/28/2021	

**Procedure Description:** Please see attached Notice Of Intent to P&A. Thank you,

Surface Disturbance

**Is any additional surface disturbance proposed?:** No

NOI Attachments

**Procedure Description**

Box\_Canyon\_34\_BAB\_Federal\_1\_9\_27\_21\_20210927131741.pdf

Received by OCD: 10/13/2021 10:47:52 AM

Page 2 of 10

Well Name: BOX CANYON 34 BAB FEDERAL	Well Location: T20S / R21E / SEC 34 / NESE /	County or Parish/State: EDDY / NM
Well Number: 1	Type of Well: CONVENTIONAL GAS WELL	Allottee or Tribe Name:
Lease Number: NMNM37826A	Unit or CA Name:	Unit or CA Number:
US Well Number: 300153077900S1	Well Status: Gas Well Shut In	Operator: EOG RESOURCES INCORPORATED

Conditions of Approval

Specialist Review

Box\_Canyon\_34\_BAB\_Federal\_1\_Sundry\_ID\_2636085\_20211013090352.pdf

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

Operator Electronic Signature: TINA HUERTA	Signed on: SEP 27, 2021 01:17 PM
Name: EOG RESOURCES INCORPORATED	
Title: Regulatory Specialist	
Street Address: 104 SOUTH FOURTH STREET	
City: Artesia	State: NM
Phone: (575) 748-4168	
Email address: tina_huerta@eogresources.com	

Field Representative

Representative Name:		
Street Address:		
City:	State:	Zip:
Phone:		
Email address:		

BLM Point of Contact

BLM POC Name: LONG VO	BLM POC Title: Petroleum Engineer
BLM POC Phone: 5752345972	BLM POC Email Address: LVO@BLM.GOV
Disposition: Approved	Disposition Date: 10/13/2021
Signature: Long Vo	

Box Canyon 34 BAB Federal 1  
30-015-30779  
Lease # NM-37826A  
2260'FSL & 660'FEL  
Unit Letter I-34-20S-21E  
Eddy County, New Mexico

EOG Resources, Inc. plans to plug and abandon this well as follows:

1. MIRU all safety equipment as needed. NU BOP. POOH with production equipment.
2. Set a CIBP at 7406' with 25 sx Class C cement on top to 7160'. This will cover Strawn top. *WOC & TAG*
3. Set a CIBP at 5962' with 25 sx Class C cement on top to 5716'. This will cover Cisco perms and top. *Leak test CSBP*
4. Spot a 25 sx Class C cement plug from 4632'-4386'. This will cover Wolfcamp top.
5. Spot a 25 sx Class C cement plug from 3545'-3299'. This will cover Abo top.
6. Perforate at 1996'. Spot a 25 sx Class C cement plug from 1996'-1750'. WOC and tag. This will cover Glorieta top and Intermediate casing shoe.
7. Spot a 25 sx Class C cement plug from 1598'-1352'. This will cover San Andres top.
8. Perforate at 573'. Spot a ~~25~~ *50* sx Class C cement plug from 573'-~~327~~ *surface*'. WOC and tag. This will cover surface casing shoe.
9. ~~Perforate at 100'. Spot a 10 sx Class C cement plug from 100' up to surface. Back fill as needed.~~
10. Cut off wellhead and install dry hole marker. Clean location as per regulated.

Wellbore schematics attached



## Box Canyon 34 BAB Federal #1 Proposed

8th Plug

7th Plug

6th Plug

5th Plug

4th Plug

3rd Plug

2nd Plug

Cisco Perfs: 6012' - 6023'

1st Plug

Strawn Perfs: 7456' - 7510'

Atoka Perfs: 7710' - 7718'

PBTD: 6,100 MD

TD: 8,360 MD

Sec-TWN-RNG: Sec. 34-20S-21E  
 FOOTAGES: 2260'FSL & 660'FEL

API: 30-015-30779  
 GL: 4528  
 KB:

## CASING DETAIL

#	HOLE SIZE	SIZE	WGHT	GRADE	Top	Bottom	Sx Cmt	Circ/TOC	TOC Method
A	17 1/2	13 3/8	48	H-40	0	290	450	Circ	
B	12 1/4	8 5/8	24	J-55	0	1,915	1540	Circ	
C	7 7/8	5 1/2	15.5, 17	J-55	0	8,360	1355	Circ	

## FORMATION TOPS

Formation	Top	Formation	Top
San Andres	1475	Strawn	7156
Glorieta	1946	Atoka	7675
Abo	3422	Morrow	8087
Wolfcamp	4509	Chester	8253
Cisco	5894		

## TUBING DETAIL

#	Joints	Description	Length	OD	ID	Grade	Wt (lb/ft)	Top (ftKB)	Blm (ftKB)
		2-7/8" Tubing and packer						5,969	

## PLUGS

#	SX	Class	Top	Bottom	Δ	Notes	Tag
1	25	C	7160	7406	246	Strawn Top	N Y
2	25	C	5716	5962	246	Cisco Perfs & Cisco Top	N Y
3	25	C	4386	4632	246	Wolfcamp Top	N
4	25	C	3299	3545	246	Abo Top	N
5	25	C	1750	1996	246	Glorieta Top & Int. Csg. Shoe	Y
6	25	C	1352	1598	246	San Andres Top	N
7	25 50	C	3270	573	546	Surface Csg. Shoe	Y
8	10	C	0	100	100	Surface Plug	Y

## Perforation Detail

Formation	Top	Bottom	Treatment
A Atoka	7,710	7,719	Acidized w/1000g 7-1/2% IC HCL + 1000 scf/bbl N2 and BS
B Strawn	7,456	7,540	Frac w/35,000# 20/40 Optibrop Binary and 15% Methanol
			Acidized w/1000g 10% IC HCL acid + 1000 scf/bbl N2
			Acidized 7535-7540 w/1000g 10% IC HCL + 1000 scf/bbl
			Acidized 7456-7466 w/1000g 10% IC HCL + 1000 scf/bbl N2
C Cisco	6012	6028	Acidize w/1500g 15% IC HCL and BS

Prepared by: KJP



**Box Canyon 34 BAB Federal #1 Current**

[illegible]

	Formation	Top		Formation	Top
	San Andres	1475			
	Glorieta	1946			
	Abo	3422			
	Wolfcamp	4509			
	Grisco	5894			
	Strawn	7166			
	Atoka	7675			
	Morrow	8087			
	Chester	8253			

[illegible][illegible]

	Formation	Top	Bottom	Treatment	
A	Atoka	7,710	7,719	Acidized w/1000g 7-1/2% IC HCL + 1000 scf/bbl N2 and BS	
B	Strawn	7,456	7,540	Frac w/35_000# 20/40 Optiprop Binary and 15% Methanol Acidized w/1000g 10% IC HCL acid + 1000 scf/bbl N2 Acidized 7535-7540 w/1000g 10% IC HCL + 1000 scf/bbl Acidized 7456-7466 w/1000g 10% IC HCL + 1000 scf/bbl N2	
C	Cisco	6012	6028	Acidize w/1500g 15% IC HCL and BS	
D					
E					
F					
G					
H					
I					
J					
K					
L					
M					
N					
O					
P					
Q					
R					
S					
T					
U					
V					
W					
X					
Y					
Z					

Prepared by: TH

PBTD:	6,100	MD
TD:	8,360	MD

Perf A



**BUREAU OF LAND MANAGEMENT  
Carlsbad Field Office  
620 East Greene Street  
Carlsbad, New Mexico 88220  
575-234-5972**

**Permanent Abandonment of Federal Wells  
Conditions of Approval**

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within ninety (90) days from the approval date of this Notice of Intent to Abandon.

**If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.**

**The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.**

2. **Notification:** Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.

3. **Blowout Preventers:** A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. **Mud Requirement:** Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.

5. **Cement Requirement:** Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

**In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.**

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). **The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10<sup>th</sup> day, the BLM is to be contacted with justification to receive an extension for completing the cut off.**

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

7. Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**

8. Trash: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.





# United States Department of the Interior

## BUREAU OF LAND MANAGEMENT

Carlsbad Field Office  
620 E. Greene St.  
Carlsbad, New Mexico 88220-6292  
www.blm.gov/nm

In Reply Refer To: 1310

TAKE PRIDE  
IN AMERICA

### Reclamation Objectives and Procedures

**Reclamation Objective:** Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its pre-disturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines (Contact service companies, allowing plenty of time to have the riggers and power lines and poles removed prior to reclamation, don't wait till the last day and try to get them to remove infrastructure). Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you



have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos  
Supervisory Petroleum Engineering Tech  
575-234-5909 (Office), 575-361-2648 (Cell)

Arthur Arias  
Environmental Protection Specialist  
575-234-6230

Crisha Morgan  
Environmental Protection Specialist  
575-234-5987

Melissa Horn  
Environmental Protection Specialist  
575-234-5951

Kelsey Wade  
Environmental Protection Specialist  
575-234-2220

Trishia Bad Bear, Hobbs Field Station  
Natural Resource Specialist  
575-393-3612

**District I**

1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720

**District II**

811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720

**District III**

1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170

**District IV**

1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

CONDITIONS

Action 55619

**CONDITIONS**

Operator: EOG RESOURCES INC P.O. Box 2267 Midland, TX 79702	OGRID: 7377
	Action Number: 55619
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

**CONDITIONS**

Created By	Condition	Condition Date
gcordero	None	10/18/2021