

**District I**

1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720

**District II**

811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720

**District III**

1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170

**District IV**

1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

Form C-101  
August 1, 2011

Permit 304374

**APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE**

1. Operator Name and Address DEVON ENERGY PRODUCTION COMPANY, LP 333 West Sheridan Ave. Oklahoma City, OK 73102		2. OGRID Number 6137
		3. API Number 30-025-49588
4. Property Code 322866	5. Property Name CHILES 28 21 STATE COM	6. Well No. 004H

**7. Surface Location**

UL - Lot O	Section 28	Township 21S	Range 34E	Lot Idn O	Feet From 182	N/S Line S	Feet From 2455	E/W Line E	County Lea
---------------	---------------	-----------------	--------------	--------------	------------------	---------------	-------------------	---------------	---------------

**8. Proposed Bottom Hole Location**

UL - Lot C	Section 21	Township 21S	Range 34E	Lot Idn C	Feet From 20	N/S Line N	Feet From 1980	E/W Line W	County Lea
---------------	---------------	-----------------	--------------	--------------	-----------------	---------------	-------------------	---------------	---------------

**9. Pool Information**

BERRY;BONE SPRING, SOUTH	96660
--------------------------	-------

**Additional Well Information**

11. Work Type New Well	12. Well Type OIL	13. Cable/Rotary	14. Lease Type State	15. Ground Level Elevation 3713
16. Multiple N	17. Proposed Depth 21172	18. Formation Bone Spring	19. Contractor	20. Spud Date 7/6/2022
Depth to Ground water		Distance from nearest fresh water well		Distance to nearest surface water

☒ We will be using a closed-loop system in lieu of lined pits

**21. Proposed Casing and Cement Program**

Type	Hole Size	Casing Size	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	1870	1392	0
Int1	12.25	9.625	40	5628	775	0
Prod	8.75	5.5	17	21172	2533	5128

**Casing/Cement Program: Additional Comments**

--

**22. Proposed Blowout Prevention Program**

Type	Working Pressure	Test Pressure	Manufacturer
Annular	5000	5000	
Blind	5000	5000	
Double Ram	5000	5000	
Annular	5000	5000	
Blind	5000	5000	
Double Ram	5000	5000	

23. I hereby certify that the information given above is true and complete to the best of my knowledge and belief.  
I further certify I have complied with 19.15.14.9 (A) NMAC ☒ and/or 19.15.14.9 (B) NMAC ☒ if applicable.

Signature:

**OIL CONSERVATION DIVISION**

Printed Name: Electronically filed by Jeff Walla

Title: Supervisor Land

Email Address: Jeff.Walla@dmv.com

Date: 11/19/2021

Phone: 575-748-9925

Approved By: Paul F Kautz

Title: Geologist

Approved Date: 11/23/2021

Expiration Date: 11/23/2023

Conditions of Approval Attached

DISTRICT I  
1625 N. FRENCH DR., HOBBS, NM 88240  
Phone: (575) 393-6161 Fax: (575) 393-0720

DISTRICT II  
811 S. FIRST ST., ARTESIA, NM 88210  
Phone: (575) 748-1283 Fax: (575) 748-9720

DISTRICT III  
1000 RIO BRAZOS RD., AZTEC, NM 87410  
Phone: (505) 334-6178 Fax: (505) 334-6170

DISTRICT IV  
1220 S. ST. FRANCIS DR., SANTA FE, NM 87505  
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico  
Energy, Minerals & Natural Resources Department  
**OIL CONSERVATION DIVISION**  
1220 SOUTH ST. FRANCIS DR.  
Santa Fe, New Mexico 87505

Form C-102  
Revised August 1, 2011  
Submit one copy to appropriate  
District Office

☐ AMENDED REPORT

**WELL LOCATION AND ACREAGE DEDICATION PLAT**

API Number <b>30-025-49588</b>	Pool Code <b>96660</b>	Pool Name <b>BERRY; BONE SPRING, SOUTH</b>
Property Code <b>322866</b>	Property Name <b>CHILES 28-21 STATE COM</b>	Well Number <b>4H</b>
OGRID No. <b>6137</b>	Operator Name <b>DEVON ENERGY PRODUCTION COMPANY, L.P.</b>	Elevation <b>3713.3'</b>

**Surface Location**


UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
0	28	21-S	34-E		182	SOUTH	2455	EAST	LEA

**Bottom Hole Location If Different From Surface**

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
C	21	21-S	34-E		20	NORTH	1980	WEST	LEA

Dedicated Acres <b>320</b>	Joint or Infill	Consolidation Code	Order No.
-------------------------------	-----------------	--------------------	-----------

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED  
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



**OPERATOR CERTIFICATION**

I hereby certify that the information herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

*Rebecca Deal* 11/10/2021  
Signature Date

Rebecca Deal, Regulatory Analyst  
Printed Name

rebecca.deal@dvn.com  
E-mail Address

**SURVEYOR CERTIFICATION**

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

11/2021

Date of Survey

Signature & Seal of Professional Surveyor



11/09/21

Certificate No. 22404 B.L. LAMAN  
W.O. # DRAWN BY: CM

Intent ☒ As Drilled ☐

API #

Operator Name: DEVON ENERGY PRODUCTION COMPANY, LP.	Property Name: CHILES 28-21 STATE COM	Well Number 4H
---	--	-------------------

Kick Off Point (KOP)

UL	Section 28	Township 21S	Range 34E	Lot	Feet 44	From N/S FSL	Feet 1978	From E/W FWL	County LEA
Latitude 32.4426					Longitude -103.4771			NAD 83	

First Take Point (FTP)

UL N	Section 28	Township 21-S	Range 34-E	Lot	Feet 100	From N/S SOUTH	Feet 1980	From E/W WEST	County LEA
Latitude 32.442896					Longitude 103.477005			NAD 83	

Last Take Point (LTP)

UL C	Section 21	Township 21-S	Range 34-E	Lot	Feet 100	From N/S NORTH	Feet 1980	From E/W WEST	County LEA
Latitude 32.471364					Longitude 103.477026			NAD 83	

Is this well the defining well for the Horizontal Spacing Unit? Is this well an infill well? 

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API #

Operator Name: DEVON ENERGY PRODUCTION COMPANY, LP.	Property Name: CHILES 28-21 STATE COM	Well Number 3H
---	--	-------------------

KZ 06/29/2018

**CHILES 28 WELLPAD 1**

DEVON ENERGY PRODUCTION COMPANY, L.P.

IN THE SOUTHEAST QUARTER (SE/4)

SECTION 28, TOWNSHIP 21 SOUTH, RANGE 34 EAST, N.M.P.M.

LEA COUNTY, NEW MEXICO


SEC. 28, T21S-R34E  
STATE OF NEW  
MEXICO  
SW/4SEC. 28, T21S-R34E  
STATE OF NEW  
MEXICO  
SE/4**CHILES 28  
WELLPAD 1**

5.62 ACRES

244' FSL • 2253' FEL

N: 526072.56

E: 806555.64

**DESCRIPTION**

BEING A SURFACE SITE EASEMENT LYING IN THE SOUTHEAST QUARTER (SE/4) OF SECTION 28, TOWNSHIP 21 SOUTH, RANGE 34 EAST N.M.P.M., LEA COUNTY, NEW MEXICO.

BEGINNING AT THE SOUTHWEST CORNER OF SAID SITE EASEMENT, WHERE A 1" IRON PIPE W/BC FOR THE SOUTH QUARTER CORNER OF SECTION 28, TOWNSHIP 21 SOUTH, RANGE 34 EAST N.M.P.M. BEARS S 38°25' W, A DISTANCE 78.94';


THENCE N 00°28' W, A DISTANCE 338.99 FEET TO AN ANGLE POINT;  
 THENCE N 40°32' E, A DISTANCE 32.15 FEET TO THE NORTHWEST CORNER OF THIS EASEMENT;  
 THENCE N 89°47' E, A DISTANCE 194.42' FEET TO AN ANGLE POINT;  
 THENCE N 88°30' E, A DISTANCE 409.45' FEET TO AN ANGLE POINT;  
 THENCE S 88°10' E, A DISTANCE 50.06 FEET TO THE NORTHEAST CORNER OF THIS EASEMENT;  
 THENCE S 00°47' E, A DISTANCE 370.99 FEET TO THE SOUTHEAST CORNER OF THIS EASEMENT,  
 THENCE N 87°15' W, A DISTANCE 167.51' FEET TO AN ANGLE POINT;  
 THENCE S 88°50' W, A DISTANCE 509.77' FEET TO THE SOUTHWEST CORNER OF THIS EASEMENT,  
 TO THE POINT OF BEGINNING; CONTAINING 5.62 ACRES.

**GENERAL NOTES:**

1.) THE INTENT OF THIS SURVEY IS TO ACQUIRE A BUSINESS LEASE FOR THE PURPOSE OF BUILDING A WELLPAD.

2.) All bearings recited herein are based on the New Mexico State Plane Coordinate System, NAD 83, New Mexico East Zone 100N, US Survey Feet, all distances are grid.

I, B.L. Laman, New Mexico PLS No. 22404, hereby certify this survey to reflect an actual survey made on the ground under my supervision. This survey meets the minimum standards for surveying in New Mexico.



B.L. Laman  
 Horizonrow, LLC  
 Date Signed: 11-05-2021  
 P.O. Box 548, Dry Creek, La.  
 (903) 388-3045 70637  
 Employee of Horizonrow, LLC

**DIRECTIONS TO LOCATION**

FROM THE INTERSECTION OF HWY 176 AND BERRY BOOSTER ROAD, HEAD SOUTH ON BERRY BOOSTER ROAD FOR 3.8 MILES. TURN LEFT ONTO AN ACCESS ROAD FOR 0.2 OF A MILE. TURN RIGHT AND HEAD SOUTH ONTO AN ACCESS ROAD FOR 1.0 MILE. TURN LEFT AND HEAD SOUTHEAST ONTO AN ACCESS ROAD FOR 0.8 OF A MILE TO THE NORTHWEST CORNER OF THE CHILES 28 WELLPAD 1.

0 250 500

**HORIZON ROW LLC**

Drawn for:

Drawn by:  
CHRIS MAAS

Date: 11/02/2021

DEVON ENERGY PRODUCTION COMPANY, L.P.

CHILES 28 WELLPAD 1

SURVEY PLAT SHOWING  
 A WELLPAD  
 ON THE PROPERTY OF THE  
 STATE OF NEW MEXICO

SITE NUMBER:  
AA000210615


WBS NUMBER:

SCALE:  
1" = 250'

REVISIONS:

DATE OF SURVEY:  
11/1/2021

# SECTION 28, TOWNSHIP 21 SOUTH, RANGE 34 EAST, N.M.P.M. LEA COUNTY, STATE OF NEW MEXICO SITE MAP




CHILES 28-21 STATE COM 4H  
182' FSL 2455' FEL SEC. 28  
EL: 3713.3'  
N: 526008.68  
E: 806353.69

CHILES 28-21 STATE COM 5H  
182' FSL 2425' FEL SEC. 28  
EL: 3713.3'  
N: 526009.29  
E: 806383.69

*Note: All bearings recited herein are based on the New Mexico State Plane Coordinate System, NAD 83, New Mexico East Zone 3001, US Survey Feet, all distances are grid.*

DEVON ENERGY PRODUCTION COMPANY, L.P.  
CHILES 28-21 STATE COM 4H  
LOCATED 182 FT. FROM THE SOUTH LINE  
AND 2455 FT. FROM THE EAST LINE OF  
SECTION 28, TOWNSHIP 21 SOUTH,  
RANGE 34 EAST, N.M.P.M.  
LEA COUNTY, STATE OF NEW MEXICO



## DIRECTIONS TO LOCATION

FROM THE INTERSECTION OF HWY 176 AND BERRY BOOSTER ROAD, HEAD SOUTH ON BERRY BOOSTER ROAD FOR 3.8 MILES. TURN LEFT ONTO AN ACCESS ROAD FOR 0.2 OF A MILE. TURN RIGHT AND HEAD SOUTH ONTO AN ACCESS ROAD FOR 1.0 MILE. TURN LEFT AND HEAD SOUTHEAST ONTO AN ACCESS ROAD FOR 0.8 OF A MILE TO THE NORTHWEST CORNER OF THE CHILES 28 WELLPAD 1.

**HORIZON ROW LLC**

DEVON ENERGY PRODUCTION CO., L.P.


Drawn by:  
CHRIS MAAS

Date: 11/04/2021

Drawn for:



# SECTION 28, TOWNSHIP 21 SOUTH, RANGE 34 EAST, N.M.P.M. LEA COUNTY, STATE OF NEW MEXICO INTERIM SITE BUILD PLAN



CHILES 28-21 STATE COM 4H  
182' FSL 2455' FEL SEC. 28  
EL: 3713.3'  
N: 526008.68  
E: 806353.69

CHILES 28-21 STATE COM 5H  
182' FSL 2425' FEL SEC. 28  
EL: 3713.3'  
N: 526009.29  
E: 806383.69

 DENOTES INTERIM PAD RECLAMATION AREA

4.19 ± ACRES INTERIM PAD RECLAMATION AREA

1.43 ± ACRES NON-RECLAIMED AREA

5.62 ± ACRES GRADING SITE RECLAMATION AREA



DEVON ENERGY PRODUCTION COMPANY, L.P.  
CHILES 28-21 STATE COM 4H  
LOCATED 182 FT. FROM THE SOUTH LINE  
AND 2455 FT. FROM THE EAST LINE OF  
SECTION 28, TOWNSHIP 21 SOUTH,  
RANGE 34 EAST, N.M.P.M.  
LEA COUNTY, STATE OF NEW MEXICO

**HORIZON ROW LLC**

DEVON ENERGY PRODUCTION CO., L.P.

Drawn by:  
CHRIS MAAS


Date: 11/04/2021

Drawn for:





# SECTION 28 TOWNSHIP 21 SOUTH, RANGE 34 EAST, N.M.P.M. LEA COUNTY, STATE OF NEW MEXICO VICINITY MAP



DEVON ENERGY PRODUCTION COMPANY, L.P.  
CHILES 28-21 STATE COM 4H  
LOCATED 182 FT. FROM THE SOUTH LINE  
AND 2455 FT. FROM THE EAST LINE OF  
SECTION 28, TOWNSHIP 21 SOUTH,  
RANGE 34 EAST, N.M.P.M.  
LEA COUNTY, STATE OF NEW MEXICO

NOT TO SCALE

## DIRECTIONS TO LOCATION

FROM THE INTERSECTION OF HWY 176 AND BERRY BOOSTER ROAD, HEAD SOUTH ON BERRY BOOSTER ROAD FOR 3.8 MILES. TURN LEFT ONTO AN ACCESS ROAD FOR 0.2 OF A MILE. TURN RIGHT AND HEAD SOUTH ONTO AN ACCESS ROAD FOR 1.0 MILE. TURN LEFT AND HEAD SOUTHEAST ONTO AN ACCESS ROAD FOR 0.8 OF A MILE TO THE NORTHWEST CORNER OF THE CHILES 28 WELLPAD 1.

**HORIZON ROW LLC**

DEVON ENERGY PRODUCTION CO., L.P.

Drawn by:  
CHRIS MAAS


Date: 11/04/2021

Drawn for:


**devon**



SECTION 28, TOWNSHIP 21 SOUTH, RANGE 34 EAST, N.M.P.M.  
LEA COUNTY, STATE OF NEW MEXICO  
LOCATION VERIFICATION MAP



DEVON ENERGY PRODUCTION COMPANY, L.P.  
CHILES 28-21 STATE COM 4H  
LOCATED 182 FT. FROM THE SOUTH LINE  
AND 2455 FT. FROM THE EAST LINE OF  
SECTION 28, TOWNSHIP 21 SOUTH,  
RANGE 34 EAST, N.M.P.M.  
LEA COUNTY, STATE OF NEW MEXICO



**HORIZON ROW LLC**

DEVON ENERGY PRODUCTION CO., L.P.

Drawn by:  
CHRIS MAAS


Date: 11/04/2021

Drawn for:

**devon**



SECTION 28 TOWNSHIP 21 SOUTH, RANGE 34 EAST, N.M.P.M.  
LEA COUNTY, STATE OF NEW MEXICO  
AERIAL PHOTO



DEVON ENERGY PRODUCTION COMPANY, L.P.  
CHILES 28-21 STATE COM 4H  
LOCATED 182 FT. FROM THE SOUTH LINE  
AND 2455 FT. FROM THE EAST LINE OF  
SECTION 28, TOWNSHIP 21 SOUTH,  
RANGE 34 EAST, N.M.P.M.  
LEA COUNTY, STATE OF NEW MEXICO

0 2000 4000



**HORIZON ROW LLC**

Drawn for:

DEVON ENERGY PRODUCTION CO., L.P.

Drawn by:  
CHRIS MAAS

Date: 11/04/2021

**devon**



SECTION 28 TOWNSHIP 21 SOUTH, RANGE 34 EAST, N.M.P.M.  
LEA COUNTY, STATE OF NEW MEXICO  
AERIAL ACCESS ROUTE MAP



DEVON ENERGY PRODUCTION COMPANY, L.P.  
CHILES 28-21 STATE COM 4H  
LOCATED 182 FT. FROM THE SOUTH LINE  
AND 2455 FT. FROM THE EAST LINE OF  
SECTION 28, TOWNSHIP 21 SOUTH,  
RANGE 34 EAST, N.M.P.M.  
LEA COUNTY, STATE OF NEW MEXICO

NOT TO SCALE

**HORIZON ROW LLC**

DEVON ENERGY PRODUCTION CO., L.P.

Drawn by:  
CHRIS MAAS

Date: 11/04/2021

Drawn for:



**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720

**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720

**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170

**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

Form APD Comments

Permit 304374

PERMIT COMMENTS

Operator Name and Address: DEVON ENERGY PRODUCTION COMPANY, LP [6137] 333 West Sheridan Ave. Oklahoma City, OK 73102		API Number: 30-025-49588
		Well: CHILES 28 21 STATE COM #004H

Created By	Comment	Comment Date
drebecca	Please see attached C-102, Drill Plan, Directional Plan, H2S Plan & NGMP	11/19/2021

**District I**

1625 N. French Dr., Hobbs, NM 88240  
 Phone:(575) 393-6161 Fax:(575) 393-0720

**District II**

811 S. First St., Artesia, NM 88210  
 Phone:(575) 748-1283 Fax:(575) 748-9720

**District III**

1000 Rio Brazos Rd., Aztec, NM 87410  
 Phone:(505) 334-6178 Fax:(505) 334-6170

**District IV**

1220 S. St Francis Dr., Santa Fe, NM 87505  
 Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

Form APD Conditions

Permit 304374

**PERMIT CONDITIONS OF APPROVAL**

Operator Name and Address: DEVON ENERGY PRODUCTION COMPANY, LP [6137] 333 West Sheridan Ave. Oklahoma City, OK 73102	API Number: 30-025-49588
	Well: CHILES 28 21 STATE COM #004H

OCD Reviewer	Condition
pkautz	Notify OCD 24 hours prior to casing & cement
pkautz	Will require a File As Drilled C-102 and a Directional Survey with the C-104
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
pkautz	Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system
pkautz	1) SURFACE & INTERMEDIATE CASING - Cement must circulate to surface -- 2) PRODUCTION CASING - Cement must tie back into intermediate casing --
pkautz	The Operator is to notify NMOCD by sundry (Form C-103) within ten (10) days of the well being spud




Chiles 28-21 State Com 4H



**Well:** Chiles 28-21 State Com 4H  
**County:** Lea  
**Wellbore:** Permit Plan  
**Design:** Permit Plan #1

**Geodetic System:** US State Plane 1983  
**Datum:** North American Datum 1927  
**Ellipsoid:** Clarke 1866  
**Zone:** 3001 - NM East (NAD83)

MD (ft)	INC (°)	AZI (°)	TVD (ft)	NS (ft)	EW (ft)	VS (ft)	DLS (°/100ft)	Comment
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	SHL
2000.00	0.00	260.00	2000.00	0.00	0.00	0.00	0.00	Start Tangent
2500.00	10.00	260.00	2497.47	-7.56	-42.86	-3.67	2.00	Hold Tangent
6948.86	10.00	260.00	6878.74	-141.71	-803.66	-68.83	0.00	Drop to Vertical
7448.86	0.00	260.00	7376.21	-149.26	-846.52	-72.50	2.00	Hold Vertical
10349.76	0.00	359.52	10277.11	-149.26	-846.52	-72.50	0.00	KOP
11258.43	90.87	359.52	10850.00	432.34	-851.40	507.19	10.00	Landing Point
21171.51	90.87	359.52	10700.00	10343.93	-934.43	10386.05	0.00	BHL

**Key Depths**

	MD (ft)	TVD (ft)
Rustler	1845.00	1845.00
Salt	2080.01	2080.00
Base of Salt	5577.29	5528.00
Delaware	5577.29	5528.00
Cherry Canyon	6127.65	6070.00
Brushy Canyon	7083.67	7012.00
1st Bone Spring Lime	8707.66	8635.00
Bone Spring 1st	9947.66	9875.00
Bone Spring 2nd / Point of Penetrati	10557.16	10480.00
exit	21091.51	10701.22

**SHL**  
**KOP**  
**Point of Penetration**  
**Exit**  
**BHL**

MD (ft)	TVD (ft)	Lat (°)	Long (°)	Section Footages
0.00	0.00	32.4430	-103.4743	182' FSL, 2455' FEL of Sec 28 in T21S, R34E
10349.76	10277.11	32.4426	-103.4771	44' FSL, 1978' FWL of Sec 28 in T21S, R34E
10557.16	10480.00	32.4429	-103.4770	100' FSL, 1980' FWL of Sec 28 in T21S, R34E
21091.51	10701.22	32.4714	-103.4770	100' FNL, 1980' FWL of Sec 21 in T21S, R34E
21171.51	10700.00	32.4715	-103.4771	20' FNL, 1980' FWL of Sec 21 in T21S, R34E

Chiles 28-21 State Com 4H



Well: Chiles 28-21 State Com 4H  
 County: Lea  
 Wellbore: Permit Plan  
 Design: Permit Plan #1

Geodetic System: US State Plane 1983  
 Datum: North American Datum 1927  
 Ellipsoid: Clarke 1866  
 Zone: 3001 - NM East (NAD83)

MD	INC	AZI	TVD	NS	EW	VS	DLS	Comment
(ft)	(°)	(°)	(ft)	(ft)	(ft)	(ft)	(°/100ft)	
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	SHL
100.00	0.00	260.00	100.00	0.00	0.00	0.00	0.00	
200.00	0.00	260.00	200.00	0.00	0.00	0.00	0.00	
300.00	0.00	260.00	300.00	0.00	0.00	0.00	0.00	
400.00	0.00	260.00	400.00	0.00	0.00	0.00	0.00	
500.00	0.00	260.00	500.00	0.00	0.00	0.00	0.00	
600.00	0.00	260.00	600.00	0.00	0.00	0.00	0.00	
700.00	0.00	260.00	700.00	0.00	0.00	0.00	0.00	
800.00	0.00	260.00	800.00	0.00	0.00	0.00	0.00	
900.00	0.00	260.00	900.00	0.00	0.00	0.00	0.00	
1000.00	0.00	260.00	1000.00	0.00	0.00	0.00	0.00	
1100.00	0.00	260.00	1100.00	0.00	0.00	0.00	0.00	
1200.00	0.00	260.00	1200.00	0.00	0.00	0.00	0.00	
1300.00	0.00	260.00	1300.00	0.00	0.00	0.00	0.00	
1400.00	0.00	260.00	1400.00	0.00	0.00	0.00	0.00	
1500.00	0.00	260.00	1500.00	0.00	0.00	0.00	0.00	
1600.00	0.00	260.00	1600.00	0.00	0.00	0.00	0.00	
1700.00	0.00	260.00	1700.00	0.00	0.00	0.00	0.00	
1800.00	0.00	260.00	1800.00	0.00	0.00	0.00	0.00	
1845.00	0.00	260.00	1845.00	0.00	0.00	0.00	0.00	Rustler
1900.00	0.00	260.00	1900.00	0.00	0.00	0.00	0.00	
2000.00	0.00	260.00	2000.00	0.00	0.00	0.00	0.00	Start Tangent
2080.01	1.60	260.00	2080.00	-0.19	-1.10	-0.09	2.00	Salt
2100.00	2.00	260.00	2099.98	-0.30	-1.72	-0.15	2.00	
2200.00	4.00	260.00	2199.84	-1.21	-6.87	-0.59	2.00	
2300.00	6.00	260.00	2299.45	-2.73	-15.46	-1.32	2.00	
2400.00	8.00	260.00	2398.70	-4.84	-27.46	-2.35	2.00	
2500.00	10.00	260.00	2497.47	-7.56	-42.86	-3.67	2.00	Hold Tangent
2600.00	10.00	260.00	2595.95	-10.57	-59.96	-5.14	0.00	
2700.00	10.00	260.00	2694.43	-13.59	-77.06	-6.60	0.00	
2800.00	10.00	260.00	2792.91	-16.60	-94.16	-8.06	0.00	
2900.00	10.00	260.00	2891.39	-19.62	-111.27	-9.53	0.00	
3000.00	10.00	260.00	2989.87	-22.63	-128.37	-10.99	0.00	
3100.00	10.00	260.00	3088.35	-25.65	-145.47	-12.46	0.00	
3200.00	10.00	260.00	3186.83	-28.67	-162.57	-13.92	0.00	
3300.00	10.00	260.00	3285.31	-31.68	-179.67	-15.39	0.00	
3400.00	10.00	260.00	3383.79	-34.70	-196.77	-16.85	0.00	
3500.00	10.00	260.00	3482.27	-37.71	-213.87	-18.32	0.00	
3600.00	10.00	260.00	3580.75	-40.73	-230.97	-19.78	0.00	
3700.00	10.00	260.00	3679.23	-43.74	-248.07	-21.25	0.00	
3800.00	10.00	260.00	3777.72	-46.76	-265.17	-22.71	0.00	
3900.00	10.00	260.00	3876.20	-49.77	-282.28	-24.18	0.00	
4000.00	10.00	260.00	3974.68	-52.79	-299.38	-25.64	0.00	
4100.00	10.00	260.00	4073.16	-55.80	-316.48	-27.10	0.00	
4200.00	10.00	260.00	4171.64	-58.82	-333.58	-28.57	0.00	
4300.00	10.00	260.00	4270.12	-61.84	-350.68	-30.03	0.00	
4400.00	10.00	260.00	4368.60	-64.85	-367.78	-31.50	0.00	
4500.00	10.00	260.00	4467.08	-67.87	-384.88	-32.96	0.00	
4600.00	10.00	260.00	4565.56	-70.88	-401.98	-34.43	0.00	
4700.00	10.00	260.00	4664.04	-73.90	-419.08	-35.89	0.00	
4800.00	10.00	260.00	4762.52	-76.91	-436.18	-37.36	0.00	
4900.00	10.00	260.00	4861.00	-79.93	-453.28	-38.82	0.00	
5000.00	10.00	260.00	4959.48	-82.94	-470.39	-40.29	0.00	
5100.00	10.00	260.00	5057.97	-85.96	-487.49	-41.75	0.00	
5200.00	10.00	260.00	5156.45	-88.97	-504.59	-43.22	0.00	
5300.00	10.00	260.00	5254.93	-91.99	-521.69	-44.68	0.00	
5400.00	10.00	260.00	5353.41	-95.01	-538.79	-46.14	0.00	
5500.00	10.00	260.00	5451.89	-98.02	-555.89	-47.61	0.00	
5577.29	10.00	260.00	5528.00	-100.35	-569.11	-48.74	0.00	Base of Salt, Delaware
5600.00	10.00	260.00	5550.37	-101.04	-572.99	-49.07	0.00	
5700.00	10.00	260.00	5648.85	-104.05	-590.09	-50.54	0.00	
5800.00	10.00	260.00	5747.33	-107.07	-607.19	-52.00	0.00	
5900.00	10.00	260.00	5845.81	-110.08	-624.29	-53.47	0.00	
6000.00	10.00	260.00	5944.29	-113.10	-641.40	-54.93	0.00	
6100.00	10.00	260.00	6042.77	-116.11	-658.50	-56.40	0.00	
6127.65	10.00	260.00	6070.00	-116.95	-663.22	-56.80	0.00	Cherry Canyon
6200.00	10.00	260.00	6141.25	-119.13	-675.60	-57.86	0.00	
6300.00	10.00	260.00	6239.73	-122.14	-692.70	-59.33	0.00	
6400.00	10.00	260.00	6338.22	-125.16	-709.80	-60.79	0.00	
6500.00	10.00	260.00	6436.70	-128.17	-726.90	-62.25	0.00	

Chiles 28-21 State Com 4H



**Well:** Chiles 28-21 State Com 4H  
**County:** Lea  
**Wellbore:** Permit Plan  
**Design:** Permit Plan #1

**Geodetic System:** US State Plane 1983  
**Datum:** North American Datum 1927  
**Ellipsoid:** Clarke 1866  
**Zone:** 3001 - NM East (NAD83)

MD (ft)	INC (°)	AZI (°)	TVD (ft)	NS (ft)	EW (ft)	VS (ft)	DLS (°/100ft)	Comment
6600.00	10.00	260.00	6535.18	-131.19	-744.00	-63.72	0.00	
6700.00	10.00	260.00	6633.66	-134.21	-761.10	-65.18	0.00	
6800.00	10.00	260.00	6732.14	-137.22	-778.20	-66.65	0.00	
6900.00	10.00	260.00	6830.62	-140.24	-795.30	-68.11	0.00	
6948.86	10.00	260.00	6878.74	-141.71	-803.66	-68.83	0.00	Drop to Vertical
7000.00	8.98	260.00	6929.18	-143.17	-811.96	-69.54	2.00	
7083.67	7.30	260.00	7012.00	-145.23	-823.63	-70.54	2.00	Brushy Canyon
7100.00	6.98	260.00	7028.20	-145.58	-825.63	-70.71	2.00	
7200.00	4.98	260.00	7127.66	-147.39	-835.88	-71.59	2.00	
7300.00	2.98	260.00	7227.41	-148.59	-842.72	-72.17	2.00	
7400.00	0.98	260.00	7327.34	-149.19	-846.11	-72.46	2.00	
7448.86	0.00	260.00	7376.21	-149.26	-846.52	-72.50	2.00	Hold Vertical
7500.00	0.00	359.52	7427.34	-149.26	-846.52	-72.50	0.00	
7600.00	0.00	359.52	7527.34	-149.26	-846.52	-72.50	0.00	
7700.00	0.00	359.52	7627.34	-149.26	-846.52	-72.50	0.00	
7800.00	0.00	359.52	7727.34	-149.26	-846.52	-72.50	0.00	
7900.00	0.00	359.52	7827.34	-149.26	-846.52	-72.50	0.00	
8000.00	0.00	359.52	7927.34	-149.26	-846.52	-72.50	0.00	
8100.00	0.00	359.52	8027.34	-149.26	-846.52	-72.50	0.00	
8200.00	0.00	359.52	8127.34	-149.26	-846.52	-72.50	0.00	
8300.00	0.00	359.52	8227.34	-149.26	-846.52	-72.50	0.00	
8400.00	0.00	359.52	8327.34	-149.26	-846.52	-72.50	0.00	
8500.00	0.00	359.52	8427.34	-149.26	-846.52	-72.50	0.00	
8600.00	0.00	359.52	8527.34	-149.26	-846.52	-72.50	0.00	
8700.00	0.00	359.52	8627.34	-149.26	-846.52	-72.50	0.00	
8707.66	0.00	359.52	8635.00	-149.26	-846.52	-72.50	0.00	1st Bone Spring Lime
8800.00	0.00	359.52	8727.34	-149.26	-846.52	-72.50	0.00	
8900.00	0.00	359.52	8827.34	-149.26	-846.52	-72.50	0.00	
9000.00	0.00	359.52	8927.34	-149.26	-846.52	-72.50	0.00	
9100.00	0.00	359.52	9027.34	-149.26	-846.52	-72.50	0.00	
9200.00	0.00	359.52	9127.34	-149.26	-846.52	-72.50	0.00	
9300.00	0.00	359.52	9227.34	-149.26	-846.52	-72.50	0.00	
9400.00	0.00	359.52	9327.34	-149.26	-846.52	-72.50	0.00	
9500.00	0.00	359.52	9427.34	-149.26	-846.52	-72.50	0.00	
9600.00	0.00	359.52	9527.34	-149.26	-846.52	-72.50	0.00	
9700.00	0.00	359.52	9627.34	-149.26	-846.52	-72.50	0.00	
9800.00	0.00	359.52	9727.34	-149.26	-846.52	-72.50	0.00	
9900.00	0.00	359.52	9827.34	-149.26	-846.52	-72.50	0.00	
9947.66	0.00	359.52	9875.00	-149.26	-846.52	-72.50	0.00	Bone Spring 1st
10000.00	0.00	359.52	9927.34	-149.26	-846.52	-72.50	0.00	
10100.00	0.00	359.52	10027.34	-149.26	-846.52	-72.50	0.00	
10200.00	0.00	359.52	10127.34	-149.26	-846.52	-72.50	0.00	
10300.00	0.00	359.52	10227.34	-149.26	-846.52	-72.50	0.00	
10349.76	0.00	359.52	10277.11	-149.26	-846.52	-72.50	0.00	KOP
10400.00	5.02	359.52	10327.28	-147.06	-846.54	-70.30	10.00	
10500.00	15.02	359.52	10425.63	-129.68	-846.69	-52.98	10.00	
10557.16	20.74	359.52	10480.00	-112.14	-846.83	-35.49	10.00	Bone Spring 2nd / Point of Penetration
10600.00	25.02	359.52	10519.46	-95.49	-846.97	-18.89	10.00	
10700.00	35.02	359.52	10605.94	-45.52	-847.39	30.91	10.00	
10800.00	45.02	359.52	10682.42	18.71	-847.93	94.92	10.00	
10900.00	55.02	359.52	10746.58	95.24	-848.57	171.20	10.00	
11000.00	65.02	359.52	10796.48	181.75	-849.30	257.43	10.00	
11100.00	75.02	359.52	10830.60	275.61	-850.09	350.98	10.00	
11200.00	85.02	359.52	10847.91	373.97	-850.91	449.01	10.00	
11258.43	90.87	359.52	10850.00	432.34	-851.40	507.19	10.00	Landing Point
11300.00	90.87	359.52	10849.37	473.90	-851.74	548.61	0.00	
11400.00	90.87	359.52	10847.86	573.89	-852.58	648.27	0.00	
11500.00	90.87	359.52	10846.34	673.87	-853.42	747.92	0.00	
11600.00	90.87	359.52	10844.83	773.86	-854.26	847.58	0.00	
11700.00	90.87	359.52	10843.32	873.84	-855.10	947.23	0.00	
11800.00	90.87	359.52	10841.81	973.83	-855.94	1046.89	0.00	
11900.00	90.87	359.52	10840.29	1073.81	-856.77	1146.54	0.00	
12000.00	90.87	359.52	10838.78	1173.80	-857.61	1246.20	0.00	
12100.00	90.87	359.52	10837.27	1273.78	-858.45	1345.85	0.00	
12200.00	90.87	359.52	10835.75	1373.77	-859.29	1445.51	0.00	
12300.00	90.87	359.52	10834.24	1473.75	-860.13	1545.16	0.00	
12400.00	90.87	359.52	10832.73	1573.74	-860.96	1644.82	0.00	
12500.00	90.87	359.52	10831.21	1673.72	-861.80	1744.47	0.00	
12600.00	90.87	359.52	10829.70	1773.71	-862.64	1844.13	0.00	
12700.00	90.87	359.52	10828.19	1873.69	-863.48	1943.78	0.00	

Chiles 28-21 State Com 4H



Well: Chiles 28-21 State Com 4H

County: Lea

Wellbore: Permit Plan

Design: Permit Plan #1

Geodetic System: US State Plane 1983

Datum: North American Datum 1927

Ellipsoid: Clarke 1866

Zone: 3001 - NM East (NAD83)

MD (ft)	INC (°)	AZI (°)	TVD (ft)	NS (ft)	EW (ft)	VS (ft)	DLS (°/100ft)	Comment
12800.00	90.87	359.52	10826.68	1973.68	-864.32	2043.44	0.00	
12900.00	90.87	359.52	10825.16	2073.66	-865.16	2143.09	0.00	
13000.00	90.87	359.52	10823.65	2173.65	-865.99	2242.75	0.00	
13100.00	90.87	359.52	10822.14	2273.63	-866.83	2342.40	0.00	
13200.00	90.87	359.52	10820.62	2373.62	-867.67	2442.06	0.00	
13300.00	90.87	359.52	10819.11	2473.60	-868.51	2541.71	0.00	
13400.00	90.87	359.52	10817.60	2573.59	-869.35	2641.37	0.00	
13500.00	90.87	359.52	10816.08	2673.57	-870.18	2741.02	0.00	
13600.00	90.87	359.52	10814.57	2773.56	-871.02	2840.68	0.00	
13700.00	90.87	359.52	10813.06	2873.54	-871.86	2940.33	0.00	
13800.00	90.87	359.52	10811.54	2973.53	-872.70	3039.99	0.00	
13900.00	90.87	359.52	10810.03	3073.51	-873.54	3139.64	0.00	
14000.00	90.87	359.52	10808.52	3173.50	-874.38	3239.30	0.00	
14100.00	90.87	359.52	10807.01	3273.48	-875.21	3338.95	0.00	
14200.00	90.87	359.52	10805.49	3373.47	-876.05	3438.61	0.00	
14300.00	90.87	359.52	10803.98	3473.45	-876.89	3538.26	0.00	
14400.00	90.87	359.52	10802.47	3573.44	-877.73	3637.92	0.00	
14500.00	90.87	359.52	10800.95	3673.42	-878.57	3737.57	0.00	
14600.00	90.87	359.52	10799.44	3773.41	-879.40	3837.23	0.00	
14700.00	90.87	359.52	10797.93	3873.39	-880.24	3936.88	0.00	
14800.00	90.87	359.52	10796.41	3973.38	-881.08	4036.54	0.00	
14900.00	90.87	359.52	10794.90	4073.36	-881.92	4136.19	0.00	
15000.00	90.87	359.52	10793.39	4173.35	-882.76	4235.85	0.00	
15100.00	90.87	359.52	10791.88	4273.33	-883.60	4335.50	0.00	
15200.00	90.87	359.52	10790.36	4373.32	-884.43	4435.16	0.00	
15300.00	90.87	359.52	10788.85	4473.30	-885.27	4534.81	0.00	
15400.00	90.87	359.52	10787.34	4573.29	-886.11	4634.47	0.00	
15500.00	90.87	359.52	10785.82	4673.27	-886.95	4734.12	0.00	
15600.00	90.87	359.52	10784.31	4773.26	-887.79	4833.78	0.00	
15700.00	90.87	359.52	10782.80	4873.24	-888.62	4933.43	0.00	
15800.00	90.87	359.52	10781.28	4973.23	-889.46	5033.09	0.00	
15900.00	90.87	359.52	10779.77	5073.21	-890.30	5132.74	0.00	
16000.00	90.87	359.52	10778.26	5173.20	-891.14	5232.39	0.00	
16100.00	90.87	359.52	10776.75	5273.18	-891.98	5332.05	0.00	
16200.00	90.87	359.52	10775.23	5373.17	-892.82	5431.70	0.00	
16300.00	90.87	359.52	10773.72	5473.15	-893.65	5531.36	0.00	
16400.00	90.87	359.52	10772.21	5573.14	-894.49	5631.01	0.00	
16500.00	90.87	359.52	10770.69	5673.12	-895.33	5730.67	0.00	
16600.00	90.87	359.52	10769.18	5773.11	-896.17	5830.32	0.00	
16700.00	90.87	359.52	10767.67	5873.09	-897.01	5929.98	0.00	
16800.00	90.87	359.52	10766.15	5973.08	-897.84	6029.63	0.00	
16900.00	90.87	359.52	10764.64	6073.06	-898.68	6129.29	0.00	
17000.00	90.87	359.52	10763.13	6173.05	-899.52	6228.94	0.00	
17100.00	90.87	359.52	10761.62	6273.03	-900.36	6328.60	0.00	
17200.00	90.87	359.52	10760.10	6373.02	-901.20	6428.25	0.00	
17300.00	90.87	359.52	10758.59	6473.00	-902.04	6527.91	0.00	
17400.00	90.87	359.52	10757.08	6572.99	-902.87	6627.56	0.00	
17500.00	90.87	359.52	10755.56	6672.97	-903.71	6727.22	0.00	
17600.00	90.87	359.52	10754.05	6772.96	-904.55	6826.87	0.00	
17700.00	90.87	359.52	10752.54	6872.94	-905.39	6926.53	0.00	
17800.00	90.87	359.52	10751.02	6972.93	-906.23	7026.18	0.00	
17900.00	90.87	359.52	10749.51	7072.91	-907.06	7125.84	0.00	
18000.00	90.87	359.52	10748.00	7172.90	-907.90	7225.49	0.00	
18100.00	90.87	359.52	10746.49	7272.88	-908.74	7325.15	0.00	
18200.00	90.87	359.52	10744.97	7372.87	-909.58	7424.80	0.00	
18300.00	90.87	359.52	10743.46	7472.85	-910.42	7524.46	0.00	
18400.00	90.87	359.52	10741.95	7572.84	-911.26	7624.11	0.00	
18500.00	90.87	359.52	10740.43	7672.82	-912.09	7723.77	0.00	
18600.00	90.87	359.52	10738.92	7772.81	-912.93	7823.42	0.00	
18700.00	90.87	359.52	10737.41	7872.79	-913.77	7923.08	0.00	
18800.00	90.87	359.52	10735.89	7972.78	-914.61	8022.73	0.00	
18900.00	90.87	359.52	10734.38	8072.76	-915.45	8122.39	0.00	
19000.00	90.87	359.52	10732.87	8172.75	-916.28	8222.04	0.00	
19100.00	90.87	359.52	10731.35	8272.73	-917.12	8321.70	0.00	
19200.00	90.87	359.52	10729.84	8372.72	-917.96	8421.35	0.00	
19300.00	90.87	359.52	10728.33	8472.71	-918.80	8521.01	0.00	
19400.00	90.87	359.52	10726.82	8572.69	-919.64	8620.66	0.00	
19500.00	90.87	359.52	10725.30	8672.68	-920.48	8720.32	0.00	
19600.00	90.87	359.52	10723.79	8772.66	-921.31	8819.97	0.00	
19700.00	90.87	359.52	10722.28	8872.65	-922.15	8919.63	0.00	



Chiles 28-21 State Com 4H



**Well:** Chiles 28-21 State Com 4H  
**County:** Lea  
**Wellbore:** Permit Plan  
**Design:** Permit Plan #1

**Geodetic System:** US State Plane 1983  
**Datum:** North American Datum 1927  
**Ellipsoid:** Clarke 1866  
**Zone:** 3001 - NM East (NAD83)

MD	INC	AZI	TVD	NS	EW	VS	DLS	Comment
(ft)	(°)	(°)	(ft)	(ft)	(ft)	(ft)	(°/100ft)	
19800.00	90.87	359.52	10720.76	8972.63	-922.99	9019.28	0.00	
19900.00	90.87	359.52	10719.25	9072.62	-923.83	9118.94	0.00	
20000.00	90.87	359.52	10717.74	9172.60	-924.67	9218.59	0.00	
20100.00	90.87	359.52	10716.22	9272.59	-925.50	9318.25	0.00	
20200.00	90.87	359.52	10714.71	9372.57	-926.34	9417.90	0.00	
20300.00	90.87	359.52	10713.20	9472.56	-927.18	9517.56	0.00	
20400.00	90.87	359.52	10711.69	9572.54	-928.02	9617.21	0.00	
20500.00	90.87	359.52	10710.17	9672.53	-928.86	9716.87	0.00	
20600.00	90.87	359.52	10708.66	9772.51	-929.70	9816.52	0.00	
20700.00	90.87	359.52	10707.15	9872.50	-930.53	9916.18	0.00	
20800.00	90.87	359.52	10705.63	9972.48	-931.37	10015.83	0.00	
20900.00	90.87	359.52	10704.12	10072.47	-932.21	10115.49	0.00	
21000.00	90.87	359.52	10702.61	10172.45	-933.05	10215.14	0.00	
21091.51	90.87	359.52	10701.22	10263.94	-933.82	10306.33	0.00	exit
21100.00	90.87	359.52	10701.09	10272.44	-933.89	10314.80	0.00	
21171.51	90.87	359.52	10700.00	10343.93	-934.43	10386.05	0.00	BHL

Chiles 28-21 State Com 4H

**Well:** Chiles 28-21 State Com 4H  
**County:** Lea  
**Wellbore:** Permit Plan  
**Design:** Permit Plan #1

**Geodetic System:** US State Plane 1983  
**Datum:** North American Datum 1927  
**Ellipsoid:** Clarke 1866  
**Zone:** 3001 - NM East (NAD83)

MD	INC	AZI	TVD	NS	EW	VS	DLS	Comment
(ft)	(°)	(°)	(ft)	(ft)	(ft)	(ft)	(°/100ft)	



**Devon Energy Center  
333 West Sheridan Avenue  
Oklahoma City, Oklahoma 73102-5015**

# **Hydrogen Sulfide (H<sub>2</sub>S) Contingency Plan**

**For**



**Chiles 28-21 State Com 4H**

**Sec-28 T-21S R-34E  
182 FSL & 2455' FEL  
LAT. = 32.443133 N (NAD83)  
LONG = 103.474266 W**

**Lea County NM**

## Chiles 28-21 State Com 4H

This is an open drilling site. H<sub>2</sub>S monitoring equipment and emergency response equipment will be used within 500' of zones known to contain H<sub>2</sub>S, including warning signs, wind indicators and H<sub>2</sub>S monitor.



Assumed 100 ppm **ROE = 3000'** (Radius of Exposure)  
100 ppm H<sub>2</sub>S concentration shall trigger activation of this plan.

### Escape

Crews shall escape upwind of escaping gas in the event of an emergency release of gas. Escape can be facilitated from the location entrance road. Crews should then block the entrance to the location from the lease road so as not to allow anyone traversing into a hazardous area. The blockade should be at a safe distance outside of the ROE. There are no homes or buildings in or near the ROE.

**Assumed 100 ppm ROE = 3000'**



## 100 ppm H<sub>2</sub>S concentration shall trigger activation of this plan.

### Emergency Procedures

In the event of a release of gas containing H<sub>2</sub>S, the first responder(s) must

- Isolate the area and prevent entry by other persons into the 100 ppm ROE.
- Evacuate any public places encompassed by the 100 ppm ROE.
- Be equipped with H<sub>2</sub>S monitors and air packs in order to control the release.
- Use the “buddy system” to ensure no injuries occur during the response
- Take precautions to avoid personal injury during this operation.
- Contact operator and/or local officials to aid in operation. See list of phone numbers attached.
- Have received training in the
  - Detection of H<sub>2</sub>S, and
  - Measures for protection against the gas,
  - Equipment used for protection and emergency response.

### **Ignition of Gas Source**

Should control of the well be considered lost and ignition considered, take care to protect against exposure to Sulfur Dioxide (SO<sub>2</sub>). Intentional ignition must be coordinated with the NMOCD and local officials. Additionally the NM State Police may become involved. NM State Police shall be the Incident Command on scene of any major release. Take care to protect downwind whenever there is an ignition of the gas

### **Characteristics of H<sub>2</sub>S and SO<sub>2</sub>**

<b>Common Name</b>	<b>Chemical Formula</b>	<b>Specific Gravity</b>	<b>Threshold Limit</b>	<b>Hazardous Limit</b>	<b>Lethal Concentration</b>
<b>Hydrogen Sulfide</b>	H <sub>2</sub> S	1.189 Air = 1	10 ppm	100 ppm/hr	600 ppm
<b>Sulfur Dioxide</b>	SO <sub>2</sub>	2.21 Air = 1	2 ppm	N/A	1000 ppm

### **Contacting Authorities**

Devon Energy Corp. personnel must liaison with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available. The following call list of essential and potential responders has been prepared for use during a release. Devon Energy Corp. Company response must be in coordination with the State of New Mexico's 'Hazardous Materials Emergency Response Plan' (HMER)

## Hydrogen Sulfide Drilling Operation Plan

### I. HYDROGEN SULFIDE (H<sub>2</sub>S) TRAINING

All personnel, whether regularly assigned, contracted, or employed on an unscheduled basis, will receive training from a qualified instructor in the following areas prior to commencing drilling operations on this well:

1. The hazards and characteristics of hydrogen sulfide (H<sub>2</sub>S)
2. The proper use and maintenance of personal protective equipment and life support systems.
3. The proper use of H<sub>2</sub>S detectors, alarms, warning systems, briefing areas, evacuation procedures, and prevailing winds.
4. The proper techniques for first aid and rescue procedures.

In addition, supervisory personnel will be trained in the following areas:

1. The effects of H<sub>2</sub>S metal components. If high tensile tubulars are to be used, personnel will be trained in their special maintenance requirements.
2. Corrective action and shut-in procedures when drilling or reworking a well and blowout prevention and well control procedures.
3. The contents and requirements of the H<sub>2</sub>S Drilling Operations Plan.

There will be weekly H<sub>2</sub>S and well control drills for all personnel in each crew.

### II. HYDROGEN SULFIDE TRAINING

Note: All H<sub>2</sub>S safety equipment and systems will be installed, tested, and operational when drilling reaches a depth of 500 feet above, or three days prior to penetrating the first zone containing or reasonably expected to contain H<sub>2</sub>S.

## **1. Well Control Equipment**

- A. Flare line
- B. Choke manifold – Remotely Operated
- C. Blind rams and pipe rams to accommodate all pipe sizes with properly sized closing unit
- D. Auxiliary equipment may include if applicable: annular preventer and rotating head.
- E. Mud/Gas Separator

## **2. Protective equipment for essential personnel:**

30-minute SCBA units located at briefing areas, as indicated on well site diagram, with escape units available in the top doghouse. As it may be difficult to communicate audibly while wearing these units, hand signals shall be utilized.

Fire extinguishers are located at various locations around the rig. First Aid supplies are located in the top doghouse and the rig manger's office.

## **3. H<sub>2</sub>S detection and monitoring equipment:**

Portable H<sub>2</sub>S monitors positioned on location for best coverage and response. These units have warning lights which activate when H<sub>2</sub>S levels reach 10 ppm and audible sirens which activate at 15 ppm. Sensor locations:

- Bell nipple
- Possum Belly/Shale shaker
- Rig floor
- Choke manifold
- Cellar

**4. Visual warning systems:**

- A. Wind direction indicators as shown on well site diagram
- B. Caution/Danger signs shall be posted on roads providing direct access to locations. Signs will be painted a high visibility yellow with black lettering of sufficient size to be reasonable distance from the immediate location. Bilingual signs will be used when appropriate.

**5. Mud program:**

The mud program has been designed to minimize the volume of H<sub>2</sub>S circulated to surface. Proper mud weight, safe drilling practices and the use of H<sub>2</sub>S scavengers will minimize hazards when penetrating H<sub>2</sub>S bearing zones.

**6. Metallurgy:**

All drill strings, casings, tubing, wellhead, blowout preventer, drilling spool, kill lines, choke manifold lines, and valves shall be H<sub>2</sub>S trim.

All elastomers used for packing and seals shall be H<sub>2</sub>S trim.

**7. Communication:**

- a. Company personnel have/use cellular telephones in the field.
- b. Land line (telephone) communications at Office

**8. Well testing:**

- a. Drill stem testing will be performed with a minimum number of personnel in the immediate vicinity, which are necessary to safety and adequately conduct the test. The drill stem testing will be conducted during daylight hours and formation fluids will not be flowed to the surface. All drill-stem-testing operations conducted in an H<sub>2</sub>S environment will use the closed chamber method of testing.
- b. There will be no drill stem testing.




<b><u>Devon Energy Corp. Company Call List</u></b>			
<b>Employee/Company Contact Representative</b>	<b>Position</b>	<b>Phone Number</b>	<b>After Hours Number</b>
Jonathan Fisher (North)	Drilling Manager	832-967-7912	
Jason Hildebrand (South)	Drilling Manager	405-552-6514	
Rich Downey	Drilling VP	405-228-2415	
Josh Harvey	EHS Manger	405-228-2440	918-500-5536
Laura Wright	EHS Supervisor	405-552-5334	832-969-8145
Robert Glover	EHS Professional	575-703-5712	575-703-5712
Lane Frank	Lead EHS	580-579-7052	580-579-7052
Rickey Porter	Lead EHS	903-720-8315	903-720-8315
Brock Vise	Lead EHS	918-413-3291	918-413-3291
<b><u>Agency Call List</u></b>			
<b><u>Lea County (575)</u></b>	<b>Hobbs</b>		
	Lea County Communication Authority		397-9265
	State Police		885-3138
	City Police		397-9265
	Sheriff's Office		396-3611
	<b>Ambulance</b>		<b>911</b>
	Fire Department		397-9308
	LEPC (Local Emergency Planning Committee)		393-2870
	NMOCD		393-6161
	US Bureau of Land Management (Hobbs Office Closed)		393-0002
<b><u>Eddy County (575)</u></b>	<b>Carlsbad</b>		
	State Police		885-3137
	City Police		885-2111
	Sheriff's Office		887-7551
	<b>Ambulance</b>		<b>911</b>
	Fire Department		885-3125
	LEPC (Local Emergency Planning Committee)		887-3798
	US Bureau of Land Management (Carlsbad)		(575)-706-1920
			(575)-234-5909
	NM Emergency Response Commission (Santa Fe)		(505) 476-9600
	24 HR		(505) 827-9126
	National Emergency Response Center		(800) 424-8802
	National Pollution Control Center: Direct		(703) 872-6000
	For Oil Spills		(800) 280-7118
	<b>Emergency Services</b>		
	Wild Well Control		(281) 784-4700
	Cudd Pressure Control	(915) 699-0139	(915) 563-3356
	Halliburton		(575) 746-2757
	B. J. Services		(575) 746-3569

<b>Give GPS position:</b>	Native Air – Emergency Helicopter – Hobbs	(575) 347-9836
	For Air Ambulance - <b>Eddy County</b> Dispatch	(575)-616-7155
	For Air Ambulance - <b>Lea County</b> (LCCA)	(575)-397-9265
	Poison Control (24/7)	(800) 222-1222
	Oil & Gas Pipeline 24 Hour Service	(800) 364-4366
	NOAA – Website - <a href="http://www.nhc.noaa.gov">www.nhc.noaa.gov</a>	
	National Pollution Control Center	202-795-6958
	NPCC – Oil Spills	800-280-7118
	BNSF Railroad Resource Operations	800-832-5452
	NM OSHA – Santa Fe	505-222-9595
	NM OSHA (Reporting)	877-610-6742 505-476-8700

Prepared in conjunction with  
Dave Small



# Devon Energy - Well Pad Rig Location Layout Safety Equipment Location



State of New Mexico  
Energy, Minerals and Natural Resources Department

Submit Electronically  
Via E-permitting

Oil Conservation Division  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

## NATURAL GAS MANAGEMENT PLAN

This Natural Gas Management Plan must be submitted with each Application for Permit to Drill (APD) for a new or recompleted well.

### Section 1 – Plan Description

Effective May 25, 2021

**I. Operator:** Devon Energy Production Company, L.P. **OGRID:** 6137 **Date:** 11 / 10 / 2021

**II. Type:** ☒ Original ☐ Amendment due to ☐ 19.15.27.9.D(6)(a) NMAC ☐ 19.15.27.9.D(6)(b) NMAC ☐ Other.

If Other, please describe: \_\_\_\_\_

**III. Well(s):** Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	ULSTR	Footages	Anticipated Oil BBL/D	Anticipated Gas MCF/D	Anticipated Produced Water BBL/D
See Attached						

**IV. Central Delivery Point Name:** Chiles 28 Wellpad 1 [See 19.15.27.9(D)(1) NMAC]

**V. Anticipated Schedule:** Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	Spud Date	TD Reached Date	Completion Commencement Date	Initial Flow Back Date	First Production Date
See Attached						

**VI. Separation Equipment:** ☒ Attach a complete description of how Operator will size separation equipment to optimize gas capture.

**VII. Operational Practices:** ☒ Attach a complete description of the actions Operator will take to comply with the requirements of Subsection A through F of 19.15.27.8 NMAC.

**VIII. Best Management Practices:** ☒ Attach a complete description of Operator's best management practices to minimize venting during active and planned maintenance.

## **Section 2 – Enhanced Plan**

### **EFFECTIVE APRIL 1, 2022**

Beginning April 1, 2022, an operator that is not in compliance with its statewide natural gas capture requirement for the applicable reporting area must complete this section.

☒ Operator certifies that it is not required to complete this section because Operator is in compliance with its statewide natural gas capture requirement for the applicable reporting area.

#### **IX. Anticipated Natural Gas Production:**

Well	API	Anticipated Average Natural Gas Rate MCF/D	Anticipated Volume of Natural Gas for the First Year MCF

#### **X. Natural Gas Gathering System (NGGS):**

Operator	System	ULSTR of Tie-in	Anticipated Gathering Start Date	Available Maximum Daily Capacity of System Segment Tie-in

**XI. Map.** ☐ Attach an accurate and legible map depicting the location of the well(s), the anticipated pipeline route(s) connecting the production operations to the existing or planned interconnect of the natural gas gathering system(s), and the maximum daily capacity of the segment or portion of the natural gas gathering system(s) to which the well(s) will be connected.

**XII. Line Capacity.** The natural gas gathering system ☐ will ☐ will not have capacity to gather 100% of the anticipated natural gas production volume from the well prior to the date of first production.

**XIII. Line Pressure.** Operator ☐ does ☐ does not anticipate that its existing well(s) connected to the same segment, or portion, of the natural gas gathering system(s) described above will continue to meet anticipated increases in line pressure caused by the new well(s).

☐ Attach Operator's plan to manage production in response to the increased line pressure.

**XIV. Confidentiality:** ☐ Operator asserts confidentiality pursuant to Section 71-2-8 NMSA 1978 for the information provided in Section 2 as provided in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and attaches a full description of the specific information for which confidentiality is asserted and the basis for such assertion.



### **Section 3 - Certifications**

**Effective May 25, 2021**

Operator certifies that, after reasonable inquiry and based on the available information at the time of submittal:

☒ Operator will be able to connect the well(s) to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system; or

☐ Operator will not be able to connect to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system.

***If Operator checks this box, Operator will select one of the following:***

**Well Shut-In.** ☐ Operator will shut-in and not produce the well until it submits the certification required by Paragraph (4) of Subsection D of 19.15.27.9 NMAC; or

**Venting and Flaring Plan.** ☐ Operator has attached a venting and flaring plan that evaluates and selects one or more of the potential alternative beneficial uses for the natural gas until a natural gas gathering system is available, including:

- (a) power generation on lease;
- (b) power generation for grid;
- (c) compression on lease;
- (d) liquids removal on lease;
- (e) reinjection for underground storage;
- (f) reinjection for temporary storage;
- (g) reinjection for enhanced oil recovery;
- (h) fuel cell production; and
- (i) other alternative beneficial uses approved by the division.

### **Section 4 - Notices**

1. If, at any time after Operator submits this Natural Gas Management Plan and before the well is spud:


(a) Operator becomes aware that the natural gas gathering system it planned to connect the well(s) to has become unavailable or will not have capacity to transport one hundred percent of the production from the well(s), no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised venting and flaring plan containing the information specified in Paragraph (5) of Subsection D of 19.15.27.9 NMAC; or

(b) Operator becomes aware that it has, cumulatively for the year, become out of compliance with its baseline natural gas capture rate or natural gas capture requirement, no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised Natural Gas Management Plan for each well it plans to spud during the next 90 days containing the information specified in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and shall file an update for each Natural Gas Management Plan until Operator is back in compliance with its baseline natural gas capture rate or natural gas capture requirement.

2. OCD may deny or conditionally approve an APD if Operator does not make a certification, fails to submit an adequate venting and flaring plan which includes alternative beneficial uses for the anticipated volume of natural gas produced, or if OCD determines that Operator will not have adequate natural gas takeaway capacity at the time a well will be spud.



I certify that, after reasonable inquiry, the statements in and attached to this Natural Gas Management Plan are true and correct to the best of my knowledge and acknowledge that a false statement may be subject to civil and criminal penalties under the Oil and Gas Act.

Signature:	
Printed Name:	Lindsey N. Miles
Title:	Land Manager
E-mail Address:	
Date:	
Phone:	
<b>OIL CONSERVATION DIVISION</b> (Only applicable when submitted as a standalone form)	
Approved By:	
Title:	
Approval Date:	
Conditions of Approval:	

Chiles 28 Wellpad 1									
Well Name	API	ULSTR	N/S Footage	Call	E/W Footage	Call	Anticipated Oil BBL/D	Anticipated Gas MCF/D	Anticipated Produced Water BBL/D
Chiles 28-21 State Com 4H		28-21S-34E	180	FSL	2455	FEL	(+/-) 836mcf/d	(+/-)1075bopd	(+/-)2043bwpd
Chiles 28-21 State Com 5H		28-21S-34E	180	FSL	2425	FEL	(+/-) 836mcf/d	(+/-)1075bopd	(+/-)2043bwpd

Well Name	API	Spud Date	TD Reached Date	Completion Commencement Date	Initial Flow Back Date	First Production Date
Chiles 28-21 State Com 4H		7/6/2022	8/5/2022	12/3/2022	12/3/2022	12/3/2022
Chiles 28-21 State Com 5H		7/10/2022	8/9/2022	12/7/2022	12/7/2022	12/7/2022

\*All dates and volumes are approximate and subject to change



## VI. Separation Equipment

Devon Energy Production Company, L.P. utilizes a "stage separation" process in which oil and gas separation is carried out through a series of separators operating at successively reduced pressures. Hydrocarbon liquids are produced into a high-pressure inlet separator, then carried through one or more lower pressure separation vessels before entering the storage tanks. The purpose of this separation process is to attain maximum recovery of liquid hydrocarbons from the fluids and allow maximum capture of produced gas into the sales pipeline. Devon utilizes a series of Low-Pressure Compression units to capture gas off the staged separation and send it to the sales pipeline. This process minimizes the amount of flash gas that enters the end-stage storage tanks that is subsequently vented or flared.



## VII. Operational Practices

Devon Energy Production Company, L. P. will employ best management practices and control technologies to maximize the recovery and minimize waste of natural gas through venting and flaring.

- During drilling operations, Devon will utilize flares and/or combustors to capture and control natural gas, where technically feasible. If flaring is deemed technically in-feasible, Devon will employ best management practices to minimize or reduce venting to the extent possible.
- During completions operations, Devon will utilize Green Completion methods to capture gas produced during well completions that is otherwise vented or flared. If capture is technically in-feasible, flares and/or combustors will be used to capture and control flow back fluids entering into frac tanks during initial flowback. Upon indication of first measurable hydrocarbon volumes, Devon will turn operations to onsite separation vessels and flow to the gathering pipeline.
- During production operations, Devon will take every practical effort to minimize waste of natural gas through venting and flaring by:
  - Designing and constructing facilities in a manner consistent to achieve maximum capture and control of hydrocarbon liquids & produced gas
  - Utilizing a closed-loop capture system to collect and route produced gas to sales line via low pressure compression, or to a flare/combustor
  - Flaring in lieu of venting, where technically feasible
  - Utilizing auto-ignitors or continuous pilots, with thermocouples connected to Scada, to quickly detect and resolve issues related to malfunctioning flares/combustors
  - Employ the use of automatic tank gauging to minimize storage tank venting during loading events
  - Installing air-driven or electric-driven pneumatics & combustion engines, where technically feasible to minimize venting to the atmosphere
  - Confirm equipment is properly maintained and repaired through a preventative maintenance and repair program to ensure equipment meets all manufacturer specifications
  - Conduct and document AVO inspections on the frequency set forth in Part 27 to detect and repair any onsite leaks as quickly and efficiently as is feasible



#### VIII. Best Management Practices during Maintenance

Devon Energy Production Company, L.P. will utilize best management practices to minimize venting during active and planned maintenance activities. Devon is operating under guidance that production facilities permitted under NOI permits have no provisions to allow high pressure flaring and high pressure flaring is only allowed in disruption scenarios so long as the duration is less than eight hours. When technically feasible, flaring during maintenance activities will be utilized in lieu of venting to the atmosphere. Devon will work with third-party operators during scheduled maintenance of downstream pipeline or processing plants to address those events ahead of time to minimize venting. Actions considered include identifying alternative capture approaches or planning to temporarily reduce production or shut in the well to address these circumstances.

## Chiles 28-21 State Com 4H

**1. Geologic Formations**

TVD of target	10701	Pilot hole depth	N/A
MD at TD:	21172	Deepest expected fresh water	

**Basin**

Formation	Depth (TVD) from KB	Water/Mineral Bearing/Target Zone?	Hazards*
Rustler	1845		
Salt	2080		
Base of Salt	5528		
Delaware	5528		
Cherry Canyon	6070		
Brushy Canyon	7012		
1st Bone Spring Lime	8635		
Bone Spring 1st	9875		
Bone Spring 2nd	10480		

\*H<sub>2</sub>S, water flows, loss of circulation, abnormal pressures, etc.



## Chiles 28-21 State Com 4H

**2. Casing Program**

Hole Size	Csg. Size	Wt (PPF)	Grade	Conn	Casing Interval		Casing Interval	
					From (MD)	To (MD)	From (TVD)	To (TVD)
17 1/2	13 3/8	48	H40	BTC	0	1870	0	1870
12 1/4	9 5/8	40	J-55	BTC	0	5628	0	5628
8 3/4	5 1/2	17	P110	BTC	0	21172	0	10701

- All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 IILB.1.h Must have table for contingency casing.

## Chiles 28-21 State Com 4H

**3. Cementing Program (3-String Primary Design)**

Casing	# Sks	TOC	Wt. (lb/gal)	Yld (ft <sup>3</sup> /sack)	Slurry Description
Surface	1392	Surf	13.2	1.4	Lead: Class C Cement + additives
Int 1	621	Surf	9.0	3.3	Lead: Class C Cement + additives
	154	500' above shoe	13.2	1.4	Tail: Class H / C + additives
Int 1 Intermediate Squeeze	As Needed	Surf	9.0	3.3	Squeeze Lead: Class C Cement + additives
	621	Surf	9.0	3.3	Lead: Class C Cement + additives
	154	500' above shoe	13.2	1.4	Tail: Class H / C + additives
Production	445	500' tieback	9.0	3.3	Lead: Class H / C + additives
	2088	KOP	13.2	1.4	Tail: Class H / C + additives

If a DV tool is ran the depth(s) will be adjusted based on hole conditions and cement volumes will be adjusted proportionally. Slurry weights will be adjusted based on estimated fracture gradient of the formation. DV tool will be set a minimum of 50 feet below previous casing and a minimum of 200 feet above current shoe. If cement is not returned to surface during the primary cement job on the surface casing string, a planned top job will be conducted immediately after completion of the primary job.

Casing String	% Excess
Surface	50%
Intermediate	30%
Production	10%

## Chiles 28-21 State Com 4H

**4. Pressure Control Equipment (Three String Design)**

BOP installed and tested before drilling which hole?	Size?	Min. Required WP	Type	✓	Tested to:
Int 1	13-58"	5M	Annular	X	50% of rated working pressure
			Blind Ram	X	5M
			Pipe Ram		
			Double Ram	X	
			Other*		
Production	13-5/8"	5M	Annular	X	50% of rated working pressure
			Blind Ram	X	5M
			Pipe Ram		
			Double Ram	X	
			Other*		
			Annular (5M)		
			Blind Ram		
			Pipe Ram		
			Double Ram		
			Other*		

## Chiles 28-21 State Com 4H

**5. Mud Program (Three String Design)**

Section	Type	Weight (ppg)
Surface	FW Gel	8.5-9
Intermediate	Brine	10-10.5
Production	WBM	8.5-9

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	PVT/Pason/Visual Monitoring
---	-----------------------------

**6. Logging and Testing Procedures**

Logging, Coring and Testing	
X	Will run GR/CNL from TD to surface (horizontal well - vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
	No logs are planned based on well control or offset log information.
	Drill stem test? If yes, explain.
	Coring? If yes, explain.

Additional logs planned		Interval
	Resistivity	
	Density	
X	CBL	Production casing
X	Mud log	KOP to TD
	PEX	

**7. Drilling Conditions**

Condition	Specify what type and where?
BH pressure at deepest TVD	5008
Abnormal temperature	No

Mitigation measure for abnormal conditions. Describe. Lost circulation material/sweeps/mud scavengers.

Hydrogen Sulfide (H<sub>2</sub>S) monitors will be installed prior to drilling out the surface shoe. If H<sub>2</sub>S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered measured values and formations will be provided to the BLM.

N	H <sub>2</sub> S is present
Y	H <sub>2</sub> S plan attached.

## Chiles 28-21 State Com 4H

**8. Other facets of operation**

Is this a walking operation? Potentially

- 1 If operator elects, drilling rig will batch drill the surface holes and run/cement surface casing; walking the rig to next wells on the pad.
- 2 The drilling rig will then batch drill the intermediate sections and run/cement intermediate casing; the wellbore will be isolated with a blind flange and pressure gauge installed for monitoring the well before walking to the next well.
- 3 The drilling rig will then batch drill the production hole sections on the wells with OBM, run/cement production casing, and install TA caps or tubing heads for completions.

NOTE: During batch operations the drilling rig will be moved from well to well however, it will not be removed from the pad until all wells have production casing run/cemented.

Will be pre-setting casing? Potentially

- 1 Spudder rig will move in and batch drill surface hole.
  - a. Rig will utilize fresh water based mud to drill surface hole to TD. Solids control will be handled entirely on a closed loop basis.
- 2 After drilling the surface hole section, the spudder rig will run casing and cement following all of the applicable rules and regulations (OnShore Order 2, all COAs and NMOCD regulations).
- 3 The wellhead will be installed and tested once the surface casing is cut off and the WOC time has been reached.
- 4 A blind flange with the same pressure rating as the wellhead will be installed to seal the wellbore. Pressure will be monitored with a pressure gauge installed on the wellhead.
- 5 Spudder rig operations is expected to take 4-5 days per well on a multi-well pad.
- 6 The NMOCD will be contacted and notified 24 hours prior to commencing spudder rig operations.
- 7 Drilling operations will be performed with drilling rig. At that time an approved BOP stack will be nipped up and tested on the wellhead before drilling operations commences on each well.
  - a. The NMOCD will be contacted / notified 24 hours before the drilling rig moves back on to the pad with the pre-set surface casing.

Attachments

X Directional Plan  
           Other, describe