For State Use Only:

APPROVED BY:

Paul F Kautz

Form C-103 State of New Mexico 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 **Energy, Minerals and Natural Resources** Permit 309932 **District II** WELL APLNIIMBER 811 S. First St., Artesia, NM 88210 Oil Conservation Division 30-025-48658 Phone:(575) 748-1283 Fax:(575) 748-9720 **District III** 5. Indicate Type of Lease 1220 S. St Francis Dr. 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 6 State Oil & Gas Lease No. District IV **Santa Fe, NM 87505** 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS APOLLO STATE COM (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: 8. Well Number 173H 2. Name of Operator 9. OGRID Number TAP ROCK OPERATING, LLC 372043 3. Address of Operator 10. Pool name or Wildcat 523 Park Point Drive, Suite 200, Golden, CO 80401 4. Well Location Unit Letter O : 873 feet from the S line and feet 1755 from the E Township 33E NMPM 24S Range County Lea 11. Elevation (Show whether DR, KB, BT, GR, etc.) 3542 GR Pit or Below-grade Tank Application or Closure ___ Distance from nearest fresh water well__ __ Depth to Groundwater___ _ Distance from nearest surface water Pit Type mil Below-Grade Tank: Volume_ bbls; Construction Material Pit Liner Thickness: 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON ALTER CASING REMEDIAL WORK TEMPORARILY ABANDON CHANGE OF PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON CASING/CEMENT JOB PULL OR ALTER CASING MULTIPLE COMPL X Other: Other: Drilling/Cement 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. See attached description of work for intermediate and production casing See Attached 1/15/2022 Spudded well. **Casing and Cement Program** Date String Csg Weight Grade Yield Open Size Size lb/ft TOC Held Drop Hole 01/15/22 Surf FreshWater 17.5 13.375 54.5 J55 0 1308 1125 1.32 С 1500 0 Ν 02/19/22 Int1 Brine 12.25 9.625 40 J55 0 5332 1045 1.33 С 1500 0 Ν 02/27/22 OilBasedMud 20 P110 19749 Prod 8.75 5.5 3987 1979 1.63 С Ν I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines \square , a general permit \square or an (attached) alternative OCD-approved plan \square SIGNATURE TITLE DATE Electronically Signed Regulatory Manager 3/1/2022 Type or print name Christian Combs E-mail address ccombs@taprk.com Telephone No. 720-360-4028

Geologist

DATE

3/2/2022 8:12:13 AM

TITLE

Apollo State Com 173H – Intermediate and Production

2/18/2022: Test BOPS. Drill 12.25 intermediate hole to 5346 ft.

2/19/2022: Run 9.625 inch 40.00 lb J-55 intermediate casing to 5332 ft. Pump 20 bbls chem wash, 20 bbls vis water, followed by 712 sks of 10.5 ppg lead cmt, 333 sks of 14.8 ppg tail cmt. Drop plug and displace with 402 bbls of briner. 212 bbls cement to surface. EST TOC at 0 ft. Pressure test casing to 1500 for 30 minutes, good test.

2/20/2022: Drill 8.75 inch production hole to 9060 ft then switch to 6.75 inch to 19757 ft

2/27/2022: Run 5.5 inch 20 lb P-110 production casing to 19749 ft MD. Pump 20 bbls chem wash, 20 bbls vis water, then 337 sks of 10.5 ppg lead and 1642 sks of 13.2 ppg tail cmt. Drop plug and displace with 20 bbls sugar water, 426 bbls brine. 0 bbls returned to surface. Est TOC at 3987 ft.

Intermediate Casing Details: Casing ran: 2/19/2022, Fluid Type Brine, Hole 12.25 inch to 5346 ft, Csg Size 9.625 inch, Weight 40lbs, Grade J-55, Est TOC 0 ft, Depth set 5332 ft, Cement 1045 sks, Yield 3.60 lead/1.33 tail, Class C, Pressure Held 1500 psi, Pres Drop 0.

Production Casing details: Casing Date: 2/27/2022, Fluid Type Oil Based Mud, Hole 8.75 inch hole to 9060 ft then switch to 6.75 inch to 19757 ft, Csg Size, 5.5 inch, Weight 20 lbs, Grade P-110, Depth set 19749 ft, EST TOC 3987 ft, Cement 1979 sacks, yield 3.35 lead/1.63 tail, Class C.

2/25/2022: TD Reached at 19757 ft MD, 9578 ft TVD. Plug Back Measured depth at 19726 ft MD, 9580 ft TVD. Rig Release on 2/28/2022 at 01:00.