Received by OCD: 3/9/2022 9:06:18 AM

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Sundry Print Report of 13

Well Name: EAGLE 34 C FEDERAL

Well Location: T17S / R27E / SEC 34 /

NENW /

County or Parish/State: EDDY /

NM

Well Number: 51

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMLC064050A

Unit or CA Name:

Unit or CA Number:

US Well Number: 300153327200S2

Well Status: Producing Oil Well

Operator: REDWOOD OPERATING LLC

Accepted for record – NMOCD gc 3/14/2022

## Notice of Intent

Sundry ID: 2657241

Type of Submission: Notice of Intent

Date Sundry Submitted: 02/15/2022

Date proposed operation will begin: 06/09/2022

Type of Action: Plug and Abandonment

Time Sundry Submitted: 02:33

Procedure Description: 1. Set 5 1/2" CIBP @ 2871'. Spot 25 sx cmt @ 2871-2671'. WOC & Tag 2. Set 5 1/2" CIBP @ 1833'. Circ hole w/ MLF. Pressure test csg. Spot 65 sx cmt @ 1833-1216'. (SA, GRBG) 3. Spot 25 sx cmt @ 957-757'. (Queen) 4. Spot 50 sx cmt @ 486' to surface. (8 5/8 Shoe & 7 Rivers) 5. Cut off well head, verify cmt @ surface, weld on Dry Hole Marker.

\* No Changes\*

### Surface Disturbance

Is any additional surface disturbance proposed?: No

### **NOI Attachments**

### **Procedure Description**

Redwood\_Eagle\_34C\_Federal\_51\_Plugged\_WBD\_20220215143242.pdf

Redwood\_Eagle\_34C\_Federal\_51\_Current\_WBD\_20220215143234.pdf

Redwood\_Eagle\_34C\_Federal\_51\_NOI\_20220215143105.pdf

Released to Imaging: 3/16/2022 11:41:18 AM

Received by OCDE 38(2034 COEESEA)

Well Location: T17S / R27E / SEC 34 /

NENW /

County or Parish/State: EDD Page 2 of 13

NM

Well Number: 51

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMLC064050A

Unit or CA Name:

Unit or CA Number:

US Well Number: 300153327200S2

Well Status: Producing Oil Well

Operator: REDWOOD OPERATING LLC

# **Conditions of Approval**

## **Specialist Review**

Eagle\_34C\_Federal\_51\_Sundry\_ID\_2657241\_P\_A\_20220306110949.pdf

## **Operator Certification**

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

Operator Electronic Signature: ABIGAIL ANDERSON

Signed on: FEB 15, 2022 02:32 PM

Name: REDWOOD OPERATING LLC

Title: Regulatory

Street Address: PO BOX 13077

City: ODESSA

State: TX

Phone: (432) 580-7161

Email address: ABBYM@BCMANDASSOCIATES.COM

# **Field Representative**

Representative Name: Cole Ponce

Street Address: PO Box 1370

City: Artesia

State: NM

**Zip:** 88211

Phone: (575)748-1288

Email address: ColePonce@mec.com

### **BLM Point of Contact**

BLM POC Name: LONG VO

**BLM POC Phone:** 5752345972

Disposition: Approved

BLM POC Title: Petroleum Engineer

BLM POC Email Address: LVO@BLM.GOV

Disposition Date: 03/06/2022

# Plug Abandonment NOI Proposed

High Cove

OPERATOR NAME: Redwood Operating, LLc

LEASE NO.: NMLC064050A

WELL NAME & NO.: Eagle 34C Federal #51

US WELL NUMBER: 30-015-33272-00-X1

LOCATION: T17S/R27E/ Sec 34

COUNTY: Eddy County, NM

- 1. Set 5 1/2" CIBP @ 2871'. Spot 25 sx cmt @ 2871-2671'. WOC & Tag
- 2. Set 5 1/2" CIBP @ 1833'. Circ hole w/ MLF. Pressure test csg. Spot 25 sx cmt @ 1833-1216'. (SA, GRBG)
- 3. Spot 25 sx cmt @ 957-757'. (Queen)
- 4. Spot 50 sx cmt @ 486' to surface. (8 5/8 Shoe & 7 Rivers)
- 5. Cut off well head, verify cmt @ surface, weld on Dry Hole Marker.

Sundry ID 2657692

Plug Type	Тор	Bottom	Length	Tag	Sacks	Notes
Surface Plug	0.00	486.00	486.00	Tag/Verify		
				If solid		
				base no		
				need to		
				Tag		
				(CIBP		
				present		
				and/or		
				Mechanic		
				al Integrity		
				Test), If		
		atherina ke		Perf &		
				Sqz then		
				Tag, Leak		
				Test all		
				CIBP if no		
				Open		Burney Parkers
Fresh Water @ 350	296.50	400.00	103.50	Perforatio		10011
						Spot from 486' to
					E0.00	surface. Verify at
Shoe Plug	381.64			Tag/Verify	50.00	Surface.
San Andres @ 1566	1500.34	1616.00	115.66	If solid	4	
				If solid base no		
	18 10 15			need to		
				Tag		
				(CIBP		Section 1
				present		
				and/or		
				Mechanic		
				al Integrit	And the second s	
				Test), If	,	
				Perf &		
				Sqz then		
				Tag, Leal		
				Test all		Set CIBP at 1833'.
				CIBP if no		Spot from 1833' to
				Open		1216', Leak Test
CIBP Plug	1798.0	0 1833.0	35.0	0 Perforation	65.0	O CIBP.
Perforations Plug (If No CIBP)	1833.0	the property of the particular and the second		0 Tag/Verif		

				If solid		
Table 1				base no		
		Tanada Ba		need to		
				Tag		
Library				(CIBP		in a second
				present		
				and/or		
			18	Mechanic		
				al Integrity		
			:	Test), If		
				Perf &		
			. *	Sgz then		
				Tag, Leak		
				Test all		Set CIBP at 2871'.
				CIBP if no		Spot from 2871' to
				Open		2671'. WOC and
CIBP Plug	2836.00	2871.00	35.00	Perforatio	25.00	
				If solid		149.
				base no		
				need to		
				Tag		
				(CIBP		- 4
				present		
				and/or		
				Mechanic		
				al Integrity		
				Test), If	-0.4	
				Perf &		
				Sqz then		
				Tag, Leak		
				Test all		
				CIBP if no		
Glorieta @ 2920	2040.00	2070.00	400.00	Open		
Perforations Plug (If No CIBP)	2840.80 2871.00	2970.00 3249.00		Perforatio		Nath
Shoe Plug	3429.85	3565.00		Tag/Verify Tag/Verify		Not Necessary
Cito i itag	0423.00	3300.00	130.15	rag/verily		Not Necessary

No more than 2000' is to be allowed be	tween plugs in open hole, and no more than 3000' between plugs
in cased hole.	
Class H >7500'	
Class C<7500'	
Fluid used to mix the cement in R111P penetrated, and in suitable proportions	shall be saturated with the salts common to the section s, but not more than 3% calcium chloride by weight of cement will
be considered the desired mixture whe	never possible.
Critical, High, Medium, Secretary: Top	of salt to surface if no salt take the deepest fresh water.
R111P: 50' from bottom of salt to surfa	

Class C: 1.32 ft^3/sx	
Class H: 1.06 ft^3/sx	

Onshore Order 2.III.G Drilling Abandonment Requirements: "All formations bearing usable-quality water, oil, gas, or geothermal resources, and/or a prospectively valuable deposit of minerals shall be protected.

Cave Karst/Potash Cement	High Top o	of Salt to surface	
Shoe @	436.00		
Shoe @	3515.00		
Perforatons Top @	1883.00	Perforations Bottom @ Perforations	2447.00
Perforatons Top @	2921.00	Bottom @	3199.00
		CIBP @	1833.00
		CIBP @	2871.

0

Cmt Sx 455

Depth Hole 436 12 1/4 0

897

7 7/8

3,515

Redwood O	Redwood Operating, LLC		PROPOSED	Description O.D. Grade Weight	0.D.	Grade	Weight
Author:	Abby @ BCM				0.11		
Well Name	Eagle 34 C Fed	Well No.	#51	Surface Csg 8 5/8 J55	8/6 8	155	7.4#
Field/Pool	Redlake; Gb-SA-GL-Yeso	API#:	30-015-33272	7	2.2	1	2.0
County	Eddy	Location:	Sec 34, T17S, R27E	Floa Csg 9 1/2 Jaa	2/1 0	222	30°
State /10	New Mexico	7.0 X	990 FNL & 1650 FWL	hormonius and a second	-	documental	Antonios becomb casages.
Spud Date	2/16/2005	GL:	3537				

Formation	Тор
7 Rivers	300
Queen	206
Grbg	1266
San Andres	1566
Glorieta	2920
Yeso	2982

12   13   14   15   15   15   15   15   15   15
---

Release

T0C	0	0 0	300 907 1266 1566	2982							
Cmt Sx	455	897 Formation	7 Rivers Queen Grbg San Andres	Glorieta Yeso					32.7952576 -104.2695923		
Hole		7.7/8		0 >-							
Depth	436	3,515									
Weight Depth	24#	15.5#									
Grade	155	355									
0.D.		5 1/2									
Description	11	Prod Csg				-					
			7	436						ro.	
	#51	30-015-33272 Sec 34, T17S, R27E 390 FNL & 1650 FWL 3537		CSG @ 43						CSG @ 3,515 77/8	
CURRENT	*	30-015-33272 Sec 34, T17S, R27E 990 FNL & 1650 FWL 3537		8 5/8 24# Hole Size:				1883-2447	Perfs @ 2921-3199 2 7/8 tbg @ 3237'		
	Well No.	API #: Location: GL:			4			Perfs @	Perfs @ 2 7/8 tbg		
Redwood Operating 11.C	Abby @ BCM Eagle 34 C Fed	Rediake; Gb-SA-GL-Yeso Eddy New Mexico 2/16/2005								1	@ 3515
- In-		Field/Pool County State Spud Date	] 2 11:41:18 A	M	4					TDP8 @	@ C

## BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

## Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10<sup>th</sup> day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.



# United States Department of the Interior

### BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

### Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of
  Operations must include adequate measures for stabilization and reclamation of disturbed lands.
  Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD
  process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation.

equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Petroleum Engineering Tech 575-234-5909 (Office), 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Crisha Morgan Environmental Protection Specialist 575-234-5987

Kelsey Wade Environmental Protection Specialist 575-234-2220

Trishia Bad Bear, Hobbs Field Station Natural Resource Specialist 575-393-3612

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division** 1220 S. St Francis Dr. **Santa Fe, NM 87505** 

CONDITIONS

Action 88601

### **CONDITIONS**

Operator:	OGRID:
Redwood Operating LLC	330211
PO Box 1370	Action Number:
Artesia, NM 88210	88601
	Action Type:
	[C-103] NOI Plug & Abandon (C-103F)

#### CONDITIONS

Created By		Condition Date
gcordero	None	3/14/2022