

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Sundry Print Reports
08/06/2021

Well Name: LOST TANK 4 FEDERAL Well Location: T22S / R31E / SEC 4 / County or Parish/State: EDDY /

SWNE / 32.422817 / -103.778576

Well Number: 22 Type of Well: CONVENTIONAL GAS Allottee or Tribe Name:

WELL

Lease Number: NMNM0417696 Unit or CA Name: Unit or CA Number:

US Well Number: 3001540774 Well Status: Gas Well Shut In Operator: OXY USA

INCORPORATED

Notice of Intent

Type of Submission: Notice of Intent

Type of Action Plug and Abandonment

Date Sundry Submitted: 07/23/2021 Time Sundry Submitted: 06:10

Date proposed operation will begin: 01/22/2022

Procedure Description: Please see attached the planned procedure and current/proposed wellbore diagrams.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

Lost_Tank_4_Fed_022_WBDs_Procedure_20210723060803.pdf

Conditions of Approval

Specialist Review

Lost_Tank_4_Federal_22_Sundry_ID_2509375_P_A_20210731155258.pdf

weived by OCD: 3/22/2022 9:08:40 AM Well Location: T22S / R31E / SEC 4 / County or Parish/State: EDDY / OCD / County / Co

SWNE / 32.422817 / -103.778576

Well Number: 22 Type of Well: CONVENTIONAL GAS Allottee or Tribe Name:

WELL

Lease Number: NMNM0417696 Unit or CA Name: Unit or CA Number:

US Well Number: 3001540774 Well Status: Gas Well Shut In Operator: OXY USA

INCORPORATED

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

Operator Electronic Signature: RONI MATHEW Signed on: JUL 23, 2021 06:08 AM

Name: OXY USA INCORPORATED

Title: REGULATORY SPECIALIST

Street Address: 5 Greenway Plaza, Suite 110

City: Houston State: TX

Phone: (713) 215-7827

Email address: RONI_MATHEW@OXY.COM

Field Representative

Representative Name: CASEY BITNER
Street Address: 6001 DEAUVILLE BLVD.

City: MIDLAND State: TX Zip: 79710

Phone: (432)699-3081

Email address: CASEY_BITNER@OXY.COM

BLM Point of Contact

BLM POC Name: LONG VO BLM POC Title: Petroleum Engineer

BLM POC Phone: 5752345972 BLM POC Email Address: LVO@BLM.GOV

Disposition: Approved **Disposition Date:** 07/31/2021

Signature: Long Vo

Page 2 of 2

Proposed PxA Procedure

TD-12908'M 12337'V

PBTD-12766'M 12179'V

Perfs-12502-12678'

- 13-3/8" 48.0# csg @ 715' w/ 830sx, 17-1/2" hole, TOC-Surf-Circ
- 9-5/8" 40.0# csg @ 4181', DVT @ 1121' w/ 2580sx, 12-1/4" hole, TOC-Surf-Circ
- Sidetrack @ 4196' w/ 750sx, 8-3/4" hole
- 7" 29.0# csg @ 11815', DVT @ 7228' w/ 1420sx, 8-3/4" hole, TOC-Surf-Circ
- 4-1/2" 15.1# csg @ 12854' w/ 310sx, 6-1/8" hole, TOC-8861'-Calc
- 1. POOH w/ equipment and tubing
- 2. RIH & SET CIBP @ 12452', DUMP BAIL 35' CL H CMT. TAG lenk test es BP
- 3. Spot 60sx CL H CMT 11865-11163'. TAG
- 4. PERF & SQZ 26sx CL H CMT 8082-7962'. TAG 4. PERF & SQZ 265x CL H CMT 8082-7962'. TAG
 5. PERF & SQZ 1705x CL H CMT 7278-6322'. TAG
 6. PERF & SQZ 1705x CL H CMT 7278-6322'. TAG

30 SX (IN/OA) WOC

6. PERF & SQZ 190sx CL C CMT 5193-4113'. TAG 175 SX (IN/OUT) WOC

7. PERF & SQZ 205sx CL C CMT 1171-SURF. VERIFY @ SURF.

10# MLF between plugs - Above ground steel tanks will be utilized

Fishing Work Performed

8/14/2014 RIH w/ packer attempt to set @ 12529' but did not set correctly.

8/15/2014-8/18/2014 RIH and attempted to pump out packer, but was unsuccessful.

8/22/2014-10/14/2014 Continue to work on fishing stuck packer.

10/17/2014 RIH & tagged existing stuck packer @ 12527'. Decision to set new packer approx. 5' on top of existing stuck packer @ 12522', but was unable to set properly. Attempted to release packer, but was unsuccessful, POOH.

5/20/2015-5/23/2015 RU WSU and successfully fished 'unset' stuck packer that was set @ approx 12522', POOH.

5/24/2015-6/4/2015 Continued to fish existing stuck packer set @ approx. 12527' and was able to push packer down to 12566'.

 $6/10/2015 \,$ RIH w/ 2-3/8" tubing and packer set @ 12450', RD $6/12/2015 \,$

 $5/24/2107\,$ RIH w/ perf guns and perf'd tubing w/ 6 shots @ 10235'. Perf gun stuck

5/25/2017 Pulled 4K into tools several times and pulled free. Pulled tools to surface and found all tools.

6/5/2017 Tagged up @ 10205'. Set down on pump to set packoff.

10/10/2017 MIRU wireline w/ required equipment. RIH tag @ 10234' pull up to 10145 to perf tubing but gun would not fire.

10/11/2017 Attempt to unset packer w/ but unsuccessful.

10/13/2017 RIH tag jetpackoff @ 10204' (was hard to latch onto). Tag 2nd packoff @ 10216' but could not latch onto. Try to unjay off packer but unsuccessful.

10/16/2017 Worked tubing to come off at tool. Used constant torque @ 800 lbs & pulled up 80 to85k on tubing then lowered hard to get off tool,

but unsuccussful. Worked tubing to release packer. Used constant torque @ 1200 lbs but unsuccessful.

leif & Sqz @ 3899 - 3760' 25 SX (In/out) woc & TAK (B. SaH@ 3849')

Roni Mathew 5/3/2021

Proposed Wellbore

LOST TANK 4 FEDERAL #022

30-015-40774-0000 Eddy

17-1/2" hole @ 715' 13-3/8" csg @ 715' w/ 830sx-TOC-Surf-Circ


12-1/4" hole @ 4189' 9-5/8" csg @ 4181' w/ 2580sx-TOC-Surf-Circ DVT @ 1121'

8-3/4" hole @ 9987' Lost BHA @ 4582-7523' 150sx cmt @ 7575-6675' 600sx cmt @ 4582-3890' Sidetrack @ 4196'

8-3/4" hole @ 11825' 7" csg @ 11815' DVT @ 7228', POST @ 4264 w/ 1420sx-TOC-Surf-Circ

6-1/8" hole @ 12908' 4-1/2" csg @ 12854' w/ 310sx-TOC-8861', Calc

TD-12908' PBTD-12766'



RIIIf, Prairie Chicken

Roni Mathew 5/3/2021

Current Wellbore

LOST TANK 4 FEDERAL #022

30-015-40774-0000 Eddy

17-1/2" hole @ 715' 13-3/8" csg @ 715' w/ 830sx-TOC-Surf-Circ


12-1/4" hole @ 4189' 9-5/8" csg @ 4181' w/ 2580sx-TOC-Surf-Circ DVT @ 1121'

8-3/4" hole @ 9987' Lost BHA @ 4582-7523' 150sx cmt @ 7575-6675' 600sx cmt @ 4582-3890' Sidetrack @ 4196'

8-3/4" hole @ 11825' 7" csg @ 11815' DVT @ 7228', POST @ 4264 w/ 1420sx-TOC-Surf-Circ

6-1/8" hole @ 12908' 4-1/2" csg @ 12854' w/ 310sx-TOC-8861', Calc

TD-12908' PBTD-12766'



BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval (LPC Habitat)

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Below Ground Level Cap (Lesser Prairie-Chicken Habitat): All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off. Upon the plugging and subsequent abandonment of wells that are located in lesser prairie-chicken habitat, the casings shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be covered with a metal plate at least ¼ inch thick and welded in place. A weep hole shall be left in the plate and/or casing.

NMOCD also requires the operator to notify NMOCD when this type of dry hole marker is used. This can be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a below ground cap was installed as required in the COA's from the BLM.

- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

<u>Timing Limitation Stipulation/ Condition of Approval for Lesser Prairie-Chicken:</u>
From March 1st through June 15th annually, abandonment activities will be allowed except between the hours from 3:00 am and 9:00 am. Normal vehicle use on existing roads will not be restricted

Received by OCD: 3,



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration. including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines (Contact service companies, allowing plenty of time to have the risers and power lines and poles removed prior to reclamation, don't wait till the last day and try to get them to remove infrastructure). Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to

- The Application for Permit to Drill or Reenter (APD, Form 3160-3). Surface Use Plan of Operations and reclamation of disturbed Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you

have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5. Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Supervisory Petroleum Engineering Tech 575-234-5909 (Office), 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Crisha Morgan Environmental Protection Specialist

Melissa Horn Environmental Protection Specialist 575-234-5951

Kelsey Wade Environmental Protection Specialist 575-234-2220

Trishia Bad Bear, Hobbs Field Station Natural Resource Specialist 575-393-3612

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 91936

CONDITIONS

Operator:	OGRID:
OXY USA INC	16696
P.O. Box 4294	Action Number:
Houston, TX 772104294	91936
	Action Type:
	[C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By		Condition Date
gcordero	None	3/23/2022