

Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-015-10414
5. Indicate Type of Lease
STATE [X] FEE [ ]
6. State Oil & Gas Lease No.
VA-636
7. Lease Name or Unit Agreement Name
Archimedes SWD
8. Well Number
1
9. OGRID Number
7377
10. Pool name or Wildcat
SWD; Devonian

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)
1. Type of Well: Oil Well [ ] Gas Well [ ] Other SWD [ ]
2. Name of Operator
EOG Resources, Inc.
3. Address of Operator
104 South Fourth Street, Artesia, NM 88210
4. Well Location
Unit Letter J : 1650 feet from the South line and 1980 feet from the East line
Section 18 Township 21S Range 24E NMPM Eddy County
11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3838'GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK [ ] PLUG AND ABANDON [X]
TEMPORARILY ABANDON [ ] CHANGE PLANS [ ]
PULL OR ALTER CASING [ ] MULTIPLE COMPL [ ]
DOWNHOLE COMMINGLE [ ]
CLOSED-LOOP SYSTEM [ ]
OTHER: [ ]
SUBSEQUENT REPORT OF:
REMEDIAL WORK [ ] ALTERING CASING [ ]
COMMENCE DRILLING OPNS. [ ] P AND A [ ]
CASING/CEMENT JOB [ ]
OTHER: [ ]
Notify OCD 24 hrs. prior to any work done

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

AMENDED

Run CBL to surface after removing 4 1/2" casing

EOG Resources, Inc. plans to plug and abandon this well as follows:

Bubble test casing and again after removing casing

- 1. MIRU all safety equipment as needed. NU BOP. POOH with production equipment.
2. Set a CIBP at 10,425'. Pressure test. Spot 25 sx Class "H" cement on top of CIBP to 10,087'. WOC and tag. This will cover Devonian perms.
3. Spot a 25 sx Class "H" cement plug from 9290'-8952'. This will cover Morrow top. 25 sx cmt 9979' - 9629'- T of Chester
4. Spot a 25 sx Class "H" cement plug from 7593'-7255'. This will cover Cisco Canyon top. 25 sx cmt 8785' - 8365'- T of Atoka & Strawn
5. Spot a 25 sx Class "C" cement plug from 6615'-6237'. This will cover Wolfcamp top.
6. Pull and remove 4-1/2" casing down to liner hanger. Proceed with plugging operations.
7. Spot a 30 sx Class "C" cement plug from 5542'-5363'. This is a spacer requirement and will cover casing split.
8. Spot a 25 sx Class "C" cement plug from 3025'-2876'. This will cover Bone Spring top.
9. Spot a 25 sx Class "C" cement plug from 2365'-2216'. This will cover Glorieta top.
10. Perforate at 1500'. Attempt injection rate. Spot a 25 sx Class "C" cement plug from 1500'-1351'. WOC and tag. This will cover casing shoe.
11. Perforate at 480'. Attempt injection rate. Spot 90 sx Class "C" cement from 480' and circulate up to surface. Verify cement at surface. Back fill as needed.
12. Cut off wellhead and install dry hole marker. Clean location as per regulated.

Wellbore schematics attached

Spud Date: [ ]

Rig Release Date: [ ]

\*\*\*\*SEE ATTACHED COA's\*\*\*\*

Must be plugged by 4/11/2023

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Specialist DATE April 7, 2022

Type or print name Tina Huerta E-mail address: tina\_huerta@eogresources.com PHONE: 575-748-4168

For State Use Only

APPROVED BY: [Signature] TITLE Staff Manager DATE 4/11/2022

Conditions of Approval (if any):

Archimedes SWD 1 Current		Sec-TWN-RNG: 18-21S-24E Surface 1650' FSL & 1980' FEL	API: 30-015-10414 KB: 3838'																																																																						
<b>COMMENTS</b>  Existing Circ. Holes at 1970' TOC at 2086'  Casing Splice at 5492'  Top of liner at 5995' TOC in 4.5" ~6000' Sqz'd hole in csg at 6700' TOC at 6730' by temp survey  Existing Cisco Canyon Perfs: 7550' - 8069'  Existing Atoka Perfs: 9090' - 9086' DV tool at 9220' Existing Morrow Perfs: 9521' - 9599'  Existing Devonian Perfs: 10475' - 10487'	A																																																																								
	B																																																																								
	C																																																																								
	D																																																																								
	PBTD: 10,923 MD TD: 11,000 MD																																																																								
	<b>CASING DETAIL</b> <table border="1"> <thead> <tr> <th>#</th> <th>Hole Size</th> <th>Csg. Size</th> <th>Wt.</th> <th>Grade</th> <th>Top</th> <th>Bottom</th> <th>Sx Cmt</th> <th>TOC</th> <th>TOC by</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>17 1/2</td> <td>13 3/8</td> <td>48</td> <td>-</td> <td>0</td> <td>375</td> <td>430</td> <td>Surface</td> <td>Circ.</td> </tr> <tr> <td>B</td> <td>12 1/4</td> <td>9 5/8</td> <td>36/40</td> <td>-</td> <td>0</td> <td>3205</td> <td>1450</td> <td>Surface</td> <td>1"</td> </tr> <tr> <td>C</td> <td>8 3/4</td> <td>7</td> <td>23/26</td> <td>N-80</td> <td>0</td> <td>9755</td> <td>see below</td> <td>6730</td> <td>TS</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Before Re-Entry</td> <td>Stage I 500</td> <td></td> <td colspan="2">Below DV tool</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>After Re-Entry</td> <td>5458</td> <td>400</td> <td>Surface *after remediation</td> <td>1"</td> </tr> <tr> <td>D</td> <td>6 1/8</td> <td>4 1/2</td> <td>11.6</td> <td>P-110</td> <td>5995</td> <td>11000</td> <td>350</td> <td>6000</td> <td>Circ.</td> </tr> </tbody> </table>			#	Hole Size	Csg. Size	Wt.	Grade	Top	Bottom	Sx Cmt	TOC	TOC by	A	17 1/2	13 3/8	48	-	0	375	430	Surface	Circ.	B	12 1/4	9 5/8	36/40	-	0	3205	1450	Surface	1"	C	8 3/4	7	23/26	N-80	0	9755	see below	6730	TS						Before Re-Entry	Stage I 500		Below DV tool							After Re-Entry	5458	400	Surface *after remediation	1"	D	6 1/8	4 1/2	11.6	P-110	5995	11000	350	6000	Circ.
	#	Hole Size	Csg. Size	Wt.	Grade	Top	Bottom	Sx Cmt	TOC	TOC by																																																															
	A	17 1/2	13 3/8	48	-	0	375	430	Surface	Circ.																																																															
	B	12 1/4	9 5/8	36/40	-	0	3205	1450	Surface	1"																																																															
	C	8 3/4	7	23/26	N-80	0	9755	see below	6730	TS																																																															
					Before Re-Entry	Stage I 500		Below DV tool																																																																	
					After Re-Entry	5458	400	Surface *after remediation	1"																																																																
D	6 1/8	4 1/2	11.6	P-110	5995	11000	350	6000	Circ.																																																																
<b>FORMATION TOPS</b> <table border="1"> <thead> <tr> <th>Formation</th> <th>Top (MD)</th> <th>Formation</th> <th>Top (MD)</th> <th>Formation</th> <th>Top (MD)</th> </tr> </thead> <tbody> <tr> <td>Glorieta</td> <td>2,315</td> <td>Mississippian</td> <td>9,974</td> <td></td> <td></td> </tr> <tr> <td>Bone Spring</td> <td>2,975</td> <td>Woodford Sh.</td> <td>10,340</td> <td></td> <td></td> </tr> <tr> <td>Wolfcamp</td> <td>6,565</td> <td>Devonian</td> <td>10,408</td> <td></td> <td></td> </tr> <tr> <td>Cisco Canyon</td> <td>7,543</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Strawn</td> <td>8,420</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Atoka</td> <td>8,735</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Morrow</td> <td>9,240</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Chester</td> <td>9,929</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>			Formation	Top (MD)	Formation	Top (MD)	Formation	Top (MD)	Glorieta	2,315	Mississippian	9,974			Bone Spring	2,975	Woodford Sh.	10,340			Wolfcamp	6,565	Devonian	10,408			Cisco Canyon	7,543					Strawn	8,420					Atoka	8,735					Morrow	9,240					Chester	9,929																					
Formation	Top (MD)	Formation	Top (MD)	Formation	Top (MD)																																																																				
Glorieta	2,315	Mississippian	9,974																																																																						
Bone Spring	2,975	Woodford Sh.	10,340																																																																						
Wolfcamp	6,565	Devonian	10,408																																																																						
Cisco Canyon	7,543																																																																								
Strawn	8,420																																																																								
Atoka	8,735																																																																								
Morrow	9,240																																																																								
Chester	9,929																																																																								
<b>TUBING DETAIL</b> 5,995' of 4.5" 11.6# N-80 tubing stung into 4.5" liner hanger. Remove for P&A.																																																																									
<b>ROD DETAIL</b> No rods.																																																																									
<b>PERFORATION DETAIL</b> <table border="1"> <thead> <tr> <th>Formation</th> <th>Top</th> <th>Bottom</th> <th>Perfd Csg String</th> </tr> </thead> <tbody> <tr> <td>Morrow</td> <td>9,521</td> <td>9,599</td> <td>7"</td> </tr> <tr> <td>Atoka</td> <td>9,090</td> <td>9,086</td> <td>7"</td> </tr> <tr> <td>Sqz'd Cisco Canyon</td> <td>7,550</td> <td>8,069</td> <td>7"</td> </tr> <tr> <td>Devonian</td> <td>10,475</td> <td>10,647</td> <td>4.5"</td> </tr> </tbody> </table>			Formation	Top	Bottom	Perfd Csg String	Morrow	9,521	9,599	7"	Atoka	9,090	9,086	7"	Sqz'd Cisco Canyon	7,550	8,069	7"	Devonian	10,475	10,647	4.5"																																																			
Formation	Top	Bottom	Perfd Csg String																																																																						
Morrow	9,521	9,599	7"																																																																						
Atoka	9,090	9,086	7"																																																																						
Sqz'd Cisco Canyon	7,550	8,069	7"																																																																						
Devonian	10,475	10,647	4.5"																																																																						
<b>ADDITIONAL DETAIL</b> Cut & pulled 7" csg at 5495', well fully P&A'd on May 2, 1964. Well re-entered July 3, 1997. Milled plugs at surface [7'-28'], int. csg. shoe [3102' - 3358'], plug #3 [3765' - 3902'] & tagged stub at 5492'. RIH with 8 3/8" OD [7 3/4" ID] x 4' long skirt with 7" slip collar, 1 joint, float collar and 7" 23# casing & slipped over stub. 4.5" Liner set at 5995' - 10998' & cemented w/ 350 sx.																																																																									
KJP 3/17/2022																																																																									

Archimedes SWD #1 Proposed		Sec-TWN-RNG: 18-21S-24E Surface 1650' FSL & 1980' FEL	API: 30-015-10414 KB: 3838'																																																																																																																																																																																																																																						
<p><b>COMMENTS</b></p> <p>Plug 9: Perf @ 480, 0-480. Verify @ surface. Surface csg shoe + Surface plug</p> <p>Existing Circ. Holes at 1970' TOC at 2086'</p> <p>Plug 8: 1351' - 1500'. Int. Csg. Shoe</p> <p>Plug 7: 2216' - 2365'. Glorieta top</p> <p>Plug 6: 2876' - 3025'. Bone Spring top</p> <p>Plug 5: 5363' - 5542'. Spacer &amp; Csg. Splice</p> <p>Casing Splice at 5492'</p> <p>Top of liner at 5995' TOC in 4.5" ~6000'</p> <p>Sqz'd hole in csg at 6700'</p> <p>Plug 4: 6237' - 6615'. Wolfcamp top. TOC at 6730' by temp survey</p> <p>Plug 3: 7255' - 7593'. Cisco Canyon top. Existing Cisco Canyon Perfs: 7550' - 8069'</p> <p>Existing Atoka Perfs: 9090' - 9086'</p> <p>DV tool at 9220'</p> <p>Plug 2: 8652' - 9290'. Morrow top. Existing Morrow Perfs: 9521' - 9599'</p> <p>Plug 1: CIBP @ 10425, 10087' - 10425'. WOC &amp; tag. Devonian Perfs. Existing Devonian Perfs: 10475' - 10487'</p>		<p><b>CASING DETAIL</b></p> <table border="1"> <thead> <tr> <th>#</th> <th>Hole Size</th> <th>Csg. Size</th> <th>Wt.</th> <th>Grade</th> <th>Top</th> <th>Bottom</th> <th>Sx Crnt</th> <th>TOC</th> <th>TOC by</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>17 1/2</td> <td>13 3/8</td> <td>48</td> <td>-</td> <td>0</td> <td>375</td> <td>430</td> <td>Surface</td> <td>Circ.</td> </tr> <tr> <td>B</td> <td>12 1/4</td> <td>9 5/8</td> <td>36/40</td> <td>-</td> <td>0</td> <td>3205</td> <td>1450</td> <td>Surface</td> <td>1"</td> </tr> <tr> <td>C</td> <td>8 3/4</td> <td>7</td> <td>23/26</td> <td>N-80</td> <td>0</td> <td>9755</td> <td>see below</td> <td>6730</td> <td>TS</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Before Re-Entry</td> <td>Stage I 100</td> <td></td> <td>Below DV tool</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Stage II 500</td> <td></td> <td>Above DV tool</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>After Re-Entry</td> <td>5458</td> <td>400</td> <td>Surface "after remediation"</td> <td>1"</td> </tr> <tr> <td>D</td> <td>6 1/8</td> <td>4 1/2</td> <td>11.6</td> <td>P-110</td> <td>5995</td> <td>11000</td> <td>350</td> <td>6000</td> <td>Circ.</td> </tr> </tbody> </table> <p><b>FORMATION TOPS</b></p> <table border="1"> <thead> <tr> <th>Formation</th> <th>Top (MD)</th> <th>Formation</th> <th>Top (MD)</th> <th>Formation</th> <th>Top (MD)</th> </tr> </thead> <tbody> <tr> <td>Glorieta</td> <td>2,315</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Bone Spring</td> <td>2,975</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Wolfcamp</td> <td>6,565</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Cisco Canyon</td> <td>7,543</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Atoka</td> <td>8,735</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Morrow</td> <td>9,240</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table> <p><b>PLUGS</b></p> <table border="1"> <thead> <tr> <th>#</th> <th>SX</th> <th>Class</th> <th>Top</th> <th>Bottom</th> <th>Δ</th> <th>Notes</th> <th>Tag</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>25</td> <td>H</td> <td>10087</td> <td>10425</td> <td>338</td> <td>CIBP at 10425'. Pressure test. Spot 25 sx. WOC &amp; Tag. Devonian Perfs</td> <td>Y</td> </tr> <tr> <td>2</td> <td>25</td> <td>H</td> <td>8952</td> <td>9290</td> <td>338</td> <td>Spot 25 sx at 9290'. Morrow top</td> <td>N</td> </tr> <tr> <td>3</td> <td>25</td> <td>H</td> <td>7255</td> <td>7593</td> <td>338</td> <td>Spot 25 sx at 7593'. Cisco Canyon top</td> <td>N</td> </tr> <tr> <td>4</td> <td>25</td> <td>C</td> <td>6237</td> <td>6615</td> <td>378</td> <td>Spot 25 sx at 6615'. Wolfcamp top</td> <td>N</td> </tr> <tr> <td>5</td> <td>NA</td> <td>NA</td> <td>NA</td> <td>NA</td> <td>NA</td> <td>Pull and Remove 4-1/2" casing down to liner hanger</td> <td>NA</td> </tr> <tr> <td>6</td> <td>30</td> <td>C</td> <td>5363</td> <td>5542</td> <td>179</td> <td>Spot 30 sx at 5542'. Spacer requirement &amp; casing splice.</td> <td>N</td> </tr> <tr> <td>7</td> <td>25</td> <td>C</td> <td>2876</td> <td>3025</td> <td>149</td> <td>Spot 25 sx at 3025'. Bone Spring top</td> <td>N</td> </tr> <tr> <td>8</td> <td>25</td> <td>C</td> <td>2216</td> <td>2365</td> <td>149</td> <td>Spot 25 sx at 2365'. Glorieta top</td> <td>N</td> </tr> <tr> <td>9</td> <td>25</td> <td>C</td> <td>1351</td> <td>1500</td> <td>149</td> <td>Perf at 1500'. Attempt Inj. Spot 25 sx. WOC &amp; tag. Int. Csg. Shoe</td> <td>Y</td> </tr> <tr> <td>10</td> <td>90</td> <td>C</td> <td>0</td> <td>480</td> <td>480</td> <td>Perf at 480'. Attempt Inj. Spot 90 sx. Verify @ surface. Sur Csg. Shoe + Surface plug</td> <td>Y</td> </tr> </tbody> </table> <p><b>PERFORATION DETAIL</b></p> <table border="1"> <thead> <tr> <th>Formation</th> <th>Top</th> <th>Bottom</th> <th>Perf'd Csg String</th> </tr> </thead> <tbody> <tr> <td>Morrow</td> <td>9,521</td> <td>9,599</td> <td>7"</td> </tr> <tr> <td>Atoka</td> <td>9,090</td> <td>9,086</td> <td>7"</td> </tr> <tr> <td>Sqz'd Cisco Canyon</td> <td>7,550</td> <td>8,069</td> <td>7"</td> </tr> <tr> <td>Devonian</td> <td>10,475</td> <td>10,647</td> <td>4.5"</td> </tr> </tbody> </table> <p><b>ADDITIONAL DETAIL</b></p> <p>Cut &amp; pulled 7" csg at 5495', well fully P&amp;A'd on May 2, 1964. Well re-entered July 3, 1997. Milled plugs at surface [7'-28'], int. csg. shoe [3102' - 3358'], plug #3 [3765' - 3902'] &amp; tagged stub at 5492'. RIH with 8 3/8" OD [7 3/4" ID] x 4' long skirt with 7" slip collar, 1 joint, float collar and 7" 23# casing &amp; slipped over stub. 4.5" Liner set at 5995' - 10998' &amp; cemented w/ 350 sx.</p>		#	Hole Size	Csg. Size	Wt.	Grade	Top	Bottom	Sx Crnt	TOC	TOC by	A	17 1/2	13 3/8	48	-	0	375	430	Surface	Circ.	B	12 1/4	9 5/8	36/40	-	0	3205	1450	Surface	1"	C	8 3/4	7	23/26	N-80	0	9755	see below	6730	TS						Before Re-Entry	Stage I 100		Below DV tool								Stage II 500		Above DV tool							After Re-Entry	5458	400	Surface "after remediation"	1"	D	6 1/8	4 1/2	11.6	P-110	5995	11000	350	6000	Circ.	Formation	Top (MD)	Formation	Top (MD)	Formation	Top (MD)	Glorieta	2,315					Bone Spring	2,975					Wolfcamp	6,565					Cisco Canyon	7,543					Atoka	8,735					Morrow	9,240					#	SX	Class	Top	Bottom	Δ	Notes	Tag	1	25	H	10087	10425	338	CIBP at 10425'. Pressure test. Spot 25 sx. WOC & Tag. Devonian Perfs	Y	2	25	H	8952	9290	338	Spot 25 sx at 9290'. Morrow top	N	3	25	H	7255	7593	338	Spot 25 sx at 7593'. Cisco Canyon top	N	4	25	C	6237	6615	378	Spot 25 sx at 6615'. Wolfcamp top	N	5	NA	NA	NA	NA	NA	Pull and Remove 4-1/2" casing down to liner hanger	NA	6	30	C	5363	5542	179	Spot 30 sx at 5542'. Spacer requirement & casing splice.	N	7	25	C	2876	3025	149	Spot 25 sx at 3025'. Bone Spring top	N	8	25	C	2216	2365	149	Spot 25 sx at 2365'. Glorieta top	N	9	25	C	1351	1500	149	Perf at 1500'. Attempt Inj. Spot 25 sx. WOC & tag. Int. Csg. Shoe	Y	10	90	C	0	480	480	Perf at 480'. Attempt Inj. Spot 90 sx. Verify @ surface. Sur Csg. Shoe + Surface plug	Y	Formation	Top	Bottom	Perf'd Csg String	Morrow	9,521	9,599	7"	Atoka	9,090	9,086	7"	Sqz'd Cisco Canyon	7,550	8,069	7"	Devonian	10,475	10,647	4.5"
#	Hole Size	Csg. Size	Wt.	Grade	Top	Bottom	Sx Crnt	TOC	TOC by																																																																																																																																																																																																																																
A	17 1/2	13 3/8	48	-	0	375	430	Surface	Circ.																																																																																																																																																																																																																																
B	12 1/4	9 5/8	36/40	-	0	3205	1450	Surface	1"																																																																																																																																																																																																																																
C	8 3/4	7	23/26	N-80	0	9755	see below	6730	TS																																																																																																																																																																																																																																
					Before Re-Entry	Stage I 100		Below DV tool																																																																																																																																																																																																																																	
						Stage II 500		Above DV tool																																																																																																																																																																																																																																	
					After Re-Entry	5458	400	Surface "after remediation"	1"																																																																																																																																																																																																																																
D	6 1/8	4 1/2	11.6	P-110	5995	11000	350	6000	Circ.																																																																																																																																																																																																																																
Formation	Top (MD)	Formation	Top (MD)	Formation	Top (MD)																																																																																																																																																																																																																																				
Glorieta	2,315																																																																																																																																																																																																																																								
Bone Spring	2,975																																																																																																																																																																																																																																								
Wolfcamp	6,565																																																																																																																																																																																																																																								
Cisco Canyon	7,543																																																																																																																																																																																																																																								
Atoka	8,735																																																																																																																																																																																																																																								
Morrow	9,240																																																																																																																																																																																																																																								
#	SX	Class	Top	Bottom	Δ	Notes	Tag																																																																																																																																																																																																																																		
1	25	H	10087	10425	338	CIBP at 10425'. Pressure test. Spot 25 sx. WOC & Tag. Devonian Perfs	Y																																																																																																																																																																																																																																		
2	25	H	8952	9290	338	Spot 25 sx at 9290'. Morrow top	N																																																																																																																																																																																																																																		
3	25	H	7255	7593	338	Spot 25 sx at 7593'. Cisco Canyon top	N																																																																																																																																																																																																																																		
4	25	C	6237	6615	378	Spot 25 sx at 6615'. Wolfcamp top	N																																																																																																																																																																																																																																		
5	NA	NA	NA	NA	NA	Pull and Remove 4-1/2" casing down to liner hanger	NA																																																																																																																																																																																																																																		
6	30	C	5363	5542	179	Spot 30 sx at 5542'. Spacer requirement & casing splice.	N																																																																																																																																																																																																																																		
7	25	C	2876	3025	149	Spot 25 sx at 3025'. Bone Spring top	N																																																																																																																																																																																																																																		
8	25	C	2216	2365	149	Spot 25 sx at 2365'. Glorieta top	N																																																																																																																																																																																																																																		
9	25	C	1351	1500	149	Perf at 1500'. Attempt Inj. Spot 25 sx. WOC & tag. Int. Csg. Shoe	Y																																																																																																																																																																																																																																		
10	90	C	0	480	480	Perf at 480'. Attempt Inj. Spot 90 sx. Verify @ surface. Sur Csg. Shoe + Surface plug	Y																																																																																																																																																																																																																																		
Formation	Top	Bottom	Perf'd Csg String																																																																																																																																																																																																																																						
Morrow	9,521	9,599	7"																																																																																																																																																																																																																																						
Atoka	9,090	9,086	7"																																																																																																																																																																																																																																						
Sqz'd Cisco Canyon	7,550	8,069	7"																																																																																																																																																																																																																																						
Devonian	10,475	10,647	4.5"																																																																																																																																																																																																																																						
<p>PBTD: 10,923 MD TD: 11,000 MD</p>		KJP 3/17/2022																																																																																																																																																																																																																																							

## CONDITIONS FOR PLUGGING AND ABANDONMENT

### OCD - Southern District

The following is a guide or checklist in preparation of a plugging program, this is not all inclusive and care must be exercised in establishing special plugging programs in unique and unusual cases, **Notify NMOCD District Office II at (575)-748-1283 at least 24 hours before beginning work. After MIRU rig will remain on well until it is plugged to surface. OCD is to be notified before rig down. Company representative will be on location during plugging procedures.**

1. A notice of intent to plug and abandon a wellbore is required to be approved before plugging operations are conducted. A cement evaluation tool is required in order to ensure isolation of producing formations, protection of water and correlative rights. A cement bond log or other accepted cement evaluation tool is to be provided to the division for evaluation if one has not been previously run or if the well did not have cement circulated to surface during the original casing cementing job or subsequent cementing jobs. Insure all bradenheads have been exposed, identified and valves are operational prior to rig up.
2. Closed loop system is to be used for entire plugging operation. Upon completion, contents of steel pits are to be hauled to a permitted disposal location.
3. Trucking companies being used to haul oilfield waste fluids to a disposal – commercial or private – shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator as well as the contractor, to verify that this permit is in place prior to performing work. Drivers shall be able to produce a copy upon request of an NMOCD Field inspector.
4. Filing a subsequent C-103 will serve as notification that the well has been plugged.
5. A final C-103 shall be filed (and a site inspection by NMOCD Inspector to determine if the location is satisfactorily cleaned, all equipment, electric poles and trash has been removed to Meet NMOCD standards) before bonding can be released.
6. If work has not begun within 1 Year of the approval of this procedure, an extension request must be file stating the reason the well has not been plugged.
7. Squeeze pressures are not to exceed 500 psi, unless approval is given by NMOCD.
8. Produced water **will not** be used during any part of the plugging operation.
9. Mud laden fluids must be placed between all cement plugs mixed at 25 sacks per 100 bbls of water.
10. All cement plugs will be a minimum of 100' in length or a minimum of 25 sacks of cement, whichever is greater. 50' of calculated cement excess required for inside casing plugs and 100% calculated cement excess required on outside casing plugs.
11. Class 'C' cement will be used above 7500 feet.
12. Class 'H' cement will be used below 7500 feet.
13. A cement plug is required to be set 50' above and 50' below, casing stubs, DV tools, attempted casing cut offs, cement tops outside casing, salt sections and anywhere the casing is perforated, these plugs require a 4 hour WOC and then will be tagged
14. All Casing Shoes Will Be Perforated 50' below shoe depth and Attempted to be Squeezed, cement needs to be 50' above and 50' Below Casing Shoe inside the Production Casing.

16. When setting the top out cement plug in production, intermediate and surface casing, wellbores should remain full at least 30 minutes after plugs are set
17. A CIBP is to be set within 100' of production perforations, capped with 100' of cement, WOC 4 hours and tag.
18. A CIBP with 35' of cement may be used in lieu of the 100' plug if set with a bailer. This plug will be placed within 100' of the top perforation, (WOC 4 hrs and tag).
19. No more than 3000' is allowed between cement plugs in cased hole and 2000' in open hole.
20. Some of the Formations to be isolated with cement plugs are: These plugs to be set to isolate formation tops
  - A) Fusselman
  - B) Devonian
  - C) Morrow
  - D) Wolfcamp
  - E) Bone Springs
  - F) Delaware
  - G) Any salt sections
  - H) Abo
  - I) Glorieta
  - J) Yates.

K) Potash---(In the R-111-P Area (Page 3 & 4), a solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts that are common to the section penetrated and in suitable proportions, not more than 3% calcium chloride (by weight of cement) will be considered the desired mixture whenever possible, WOC 4 hours and tag, this plug will be 50' below the bottom and 50' above the top of the Formation.
21. If cement does not exist behind casing strings at recommended formation depths, the casing can be cut and pulled with plugs set at recommended depths. If casing is not pulled, perforations will be shot and cement squeezed behind casing, WOC and tagged. These plugs will be set 50' below formation bottom to 50' above formation top inside the casing

#### DRY HOLE MARKER REQUIREMENTS

The operator shall mark the exact location of the plugged and abandoned well with a steel marker not less than four inches in diameter, 3' below ground level with a plate of at least ¼" welded to the top of the casing and the dry hole marker welded on the plate with the following information welded on the dry hole marker:

1. Operator name
  2. Lease and Well Number
  3. API Number
  4. Unit Letter
  5. Quarter Section (feet from the North, South, East or West)
  6. Section, Township and Range
  7. Plugging Date
  8. County
- (SPECIAL CASES)-----AGRICULTURE OR PRARIE CHICKEN BREEDING AREAS

In these areas, a below ground marker is required with all pertinent information mentioned above on a plate, set 3' below ground level, a picture of the plate will be supplied to NMOCD for record, the exact location of the marker (longitude and latitude by GPS) will be provided to NMOCD (We typically require a current survey to verify the GPS)

#### SITE REMEDIATION DUE WITHIN ONE YEAR OF WELL PLUGGING COMPLETION

## R-111-P Area

### T 18S – R 30E

Sec 10 Unit P. Sec 11 Unit M,N. Sec 13 Unit L,M,N. Sec 14 Unit C -P. Sec 15 Unit A G,H,I,J,K,N,O,P. Sec 22 Unit All except for M. Sec 23, Sec 24 Unit C,D,E,L, Sec 26 Unit A-G, Sec 27 Unit A,B,C

### T 19S – R 29E

Sec 11 Unit P. Sec 12 Unit H-P. Sec 13. Sec 14 Unit A,B,F-P. Sec 15 Unit P. Sec 22 Unit A,B,C,F,G,H,I,J K,N,O,P. Sec 23. Sec 24. Sec 25 Unit D. Sec 26 Unit A- F. Sec 27 Unit A,B,C,F,G,H.

### T 19S – R 30E

Sec 2 Unit K,L,M,N. Sec 3 Unit I,L,M,N,O,P. Sec 4 Unit C,D,E,F,G,I-P. Sec 5 Unit A,B,C,E-P. Sec 6 Unit I,O,P. Sec 7 – Sec 10. Sec 11 Unit D, G—P. Sec 12 Unit A,B,E-P. Sec 13 Unit A-O. Sec 14-Sec 18. Sec 19 Unit A-L, P. Sec 20 – Sec 23. Sec 24 Unit C,D,E,F,L,M,N. Sec 25 Unit D. Sec 26 Unit A-G, I-P. Sec 27, Sec 28, Sec 29 Unit A,B,C,D,F,G,H,I,J,O,P. Sec 32 Unit A,B,G,H,I,J,N,O,P. Sec 33. Sec 34. Sec 35. Sec 36 Unit D,E,F,I-P.

### T 19S – R 31E

Sec 7 Unit C,D,E,F,L. Sec 18 Unit C,D,E,F,G,K,L. Sec 31 Unit M. Sec 34 Unit P. Sec 35 Unit M,N,O. Sec 36 Unit O,P.

### T 20S – R 29E

Sec 1 Unit H,I,P. Sec 13 Unit E,L,M,N. Sec 14 Unit B-P. Sec 15 Unit A,H,I,J,N,O,P. Sec 22 Unit A,B,C,F,G,H,I,J,O,P. Sec 23. Sec 24 Unit C,D,E,F,G,J-P. Sec 25 Unit A-O. Sec 26. Sec 27 Unit A,B,G,H,I,J,O,P. Sec 34 Unit A,B,G,H. Sec 35 Unit A-H. Sec 36 Unit B-G.

### T 20S – R 30E

Sec 1 – Sec 4. Sec 5 Unit A,B,C,E-P. Sec 6 Unit E,G-P. Sec 7 Unit A-H,I,J,O,P. Sec 8 – 17. Sec 18 Unit A,B,G,H,I,J,O,P. Sec 19 Unit A,B,G,H,I,J,O,P. Sec 20 – 29. Sec 30 Unit A-L,N,O,P. Sec 31 Unit A,B,G,H,I,P. Sec 32 – Sec 36.

### T 20S – R 31E

Sec 1 Unit A,B,C,E-P. Sec 2. Sec 3 Unit A,B,G,H,I,J,O,P. Sec 6 Unit D,E,F,J-P. Sec 7. Sec 8 Unit E-P. Sec 9 Unit E,F,J-P. Sec 10 Unit A,B,G-P. Sec 11 – Sec 36.

### T 21S – R 29E

Sec 1 – Sec 3. Sec 4 Unit L1 – L16,I,J,K,O,P. Sec 5 Unit L1. Sec 10 Unit A,B,H,P. Sec 11 – Sec 14. Sec 15 Unit A,H,I. Sec 23 Unit A,B. Sec 24 Unit A,B,C,D,F,G,H,I,J,O,P. Sec 25 Unit A,O,P. Sec 35 Unit G,H,I,J,K,N,O,P. Sec 36 A,B,C,F – P.

### T 21S – R 30E

Sec 1 – Sec 36

### T 21S – R 31E

Sec 1 – Sec 36

### T 22S – R 28E

Sec 36 Unit A,H,I,P.

**T 22S – R 29E**

Sec 1. Sec2. Sec 3 Unit I,J,N,O,P. Sec 9 Unit G – P. Sec 10 – Sec 16. Sec 19 Unit H,I,J. Sec 20 – Sec 28. Sec 29 Unit A,B,C,D,G,H,I,J,O,P. Sec 30 Unit A. Section 31 Unit C – P. Sec 32 – Sec 36

**T 22S – R 30E**

Sec 1 – Sec 36

**T 22S – R 31E**

Sec 1 – Sec 11. Sec 12 Unit B,C,D,E,F,L. Sec 13 Unit E,F,K,L,M,N. Sec 14 – Sec 23. Sec 24 Unit C,D,E,F,K,L,M,N. Sec 25 Unit A,B,C,D. Sec 26 Unit A,BC,D,G,H. Sec 27 – Sec 34.

**T 23S – R 28E**

Sec 1 Unit A

**T 23S – R 29E**

Sec 1 – Sec 5. Sec 6 Unit A – I, N,O,P. Sec 7 Unit A,B,C,G,H,I,P. Sec 8 Unit A – L, N,O,P. Sec 9 – Sec 16. Sec 17 Unit A,B,G,H,I,P. Sec 21 – Sec 23. Sec 24 Unit A – N. Sec 25 Unit D,E,L. Sec 26. Sec 27. Sec 28 Unit A – J, N,O,P. Sec 33 Unit A,B,C. Sec 34 Unit A,B,C,D,F,G,H. Sec 35. Sec 36 Unit B,C,D,E,F,G,K,L.

**T 23S – R 30E**

Sec 1 – Sec 18. Sec 19 Unit A – I,N,O,P. Sec 20, Sec 21. Sec 22 Unit A – N, P. Sec 23, Sec 24, Sec 25. Sec 26 Unit A,B,F-P. Sec 27 Unit C,D,E,I,N,O,P. Sec 28 Unit A – H, K,L,M,N. Sec 29 Unit A – J, O,P. Sec 30 Unit A,B. Sec 32 A,B. Sec 33 Unit C,D,H,I,O,P. Sec 34, Sec 35, Sec 36.

**T 23S – R 31E**

Sec 2 Unit D,E,J,O. Sec 3 – Sec 7. Sec 8 Unit A – G, K – N. Sec 9 Unit A,B,C,D. Sec 10 Unit D,P. Sec 11 Unit G,H,I,J,M,N,O,P. Sec 12 Unit E,L,K,M,N. Sec 13 Unit C,D,E,F,G,J,K,L,M,N,O. Sec 14. Sec 15 Unit A,B,E – P. Sec 16 Unit I, K – P. Sec 17 Unit B,C,D,E, I – P. Sec 18 – Sec 23. Sec 24 Unit B – G, K,L,M,N. Sec 25 Unit B – G, J,K,L. Sec 26 – Sec 34. Sec 35 Unit C,D,E.

**T 24S – R 29E**

Sec 2 Unit A, B, C, D. Sec 3 Unit A

**T 24S – R 30E**

Sec 1 Unit A – H, J – N. Sec 2, Sec 3. Sec 4 Unit A,B,F – K, M,N,O,P. Sec 9 Unit A – L. Sec 10 Unit A – L, O,P. Sec 11. Sec 12 Unit D,E,L. Sec 14 Unit B – G. Sec 15 Unit A,B,G,H.

**T 24S – R 31E**

Sec 3 Unit B – G, J – O. Sec 4. Sec 5 Unit A – L, P. Sec 6 Unit A – L. Sec 9 Unit A – J, O,P. Sec 10 Unit B – G, K – N. Sec 35 Unit E – P. Sec 36 Unit E,K,L,M,N.

**T 25S – R 31E**

Sec 1 Unit C,D,E,F. Sec 2 Unit A – H.

**District I**  
 1625 N. French Dr., Hobbs, NM 88240  
 Phone:(575) 393-6161 Fax:(575) 393-0720

**District II**  
 811 S. First St., Artesia, NM 88210  
 Phone:(575) 748-1283 Fax:(575) 748-9720

**District III**  
 1000 Rio Brazos Rd., Aztec, NM 87410  
 Phone:(505) 334-6178 Fax:(505) 334-6170

**District IV**  
 1220 S. St Francis Dr., Santa Fe, NM 87505  
 Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

CONDITIONS  
 Action 96755

**CONDITIONS**

Operator: EOG RESOURCES INC P.O. Box 2267 Midland, TX 79702	OGRID: 7377
	Action Number: 96755
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

**CONDITIONS**

Created By	Condition	Condition Date
gcordero	None	4/11/2022