

Office
 District I – (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II – (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III – (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV – (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM
 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised July 18, 2013

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

| |
|--|
| WELL API NO. 30-025-05423 |
| 5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> |
| 6. State Oil & Gas Lease No. |
| 7. Lease Name or Unit Agreement Name Lovington San Andres Unit |
| 8. Well Number 38 |
| 9. OGRID Number 241333 |
| 10. Pool name or Wildcat San Andrew |
| 4. Well Location Unit Letter <u>F</u> : <u>1650</u> feet from the <u>North</u> line and <u>1980</u> feet from the <u>West</u> line Section <u>6</u> Township <u>17 S</u> Range <u>37E</u> NMPM County <u>Lea</u> |
| 11. Elevation (Show whether DR, RKB, RT, GR, etc.) |

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other Injector

2. Name of Operator
Chevron Midcontinent, L.P.

3. Address of Operator
6301 Deauville Blvd Midland, Texas 79706

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

| NOTICE OF INTENTION TO: | SUBSEQUENT REPORT OF: |
|--|--|
| PERFORM REMEDIAL WORK <input type="checkbox"/> | REMEDIAL WORK <input type="checkbox"/> |
| PLUG AND ABANDON <input checked="" type="checkbox"/> | ALTERING CASING <input type="checkbox"/> |
| TEMPORARILY ABANDON <input type="checkbox"/> | COMMENCE DRILLING OPNS. <input type="checkbox"/> |
| CHANGE PLANS <input type="checkbox"/> | P AND A <input type="checkbox"/> |
| PULL OR ALTER CASING <input type="checkbox"/> | CASING/CEMENT JOB <input type="checkbox"/> |
| MULTIPLE COMPL <input type="checkbox"/> | |
| DOWNHOLE COMMINGLE <input type="checkbox"/> | |
| CLOSED-LOOP SYSTEM <input type="checkbox"/> | |
| OTHER: <input type="checkbox"/> | OTHER: <input type="checkbox"/> |

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Please see attached procedure for well abandonment details.

4" diameter 4' tall Above Ground Marker

SEE ATTACHED CONDITIONS
OF APPROVAL

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Hayes Thibodeaux TITLE Engineer DATE 5/23/2022

Type or print name Hayes Thibodeaux E-mail address: Hayes.Thibodeaux@chevron.com PHONE: 281-726-9683

For State Use Only

APPROVED BY: Kerry Fortner TITLE Compliance Officer A DATE 5/25/22

Conditions of Approval (if any): 575-263-6633

Plugging Plan – Lovington San Andres Unit #38

API: 30-025-05423

Note:

- Injector well with internally lined plastic tubing
- Loc-set packer at 4511'

Proposed procedure – Lay down rig + CTU

1. Move in Axis 34 Lay Down rig package
2. N/U BOPE and pressure test same to 250 psi low for 5 minutes / 2500 psi high for 10 minutes.
3. Pull 2-3/8" IPC tubing w/ on/off tool
4. Gauge ring run will be required unless the packer is removed from the wellbore
5. RIH with CIBP and set at proposed depth in C-103 (4511')
6. Pressure test mech. barrier + casing to 500 psi for 15 minutes. Document results in WellView.
7. Conduct bubble tests on all annuli. If bubble test fails, communicate to coiled tubing WSR for planning purposes.
8. Rig down Axis 34 lay down rig

Proposed procedure - Coiled Tubing Unit

9. R/U coiled tubing P&A package
10. N/U BOPE and pressure test same to 250 psi low for 5 minutes / 2500 psi high for 10 minutes.
11. RIH with coiled tubing to tag existing mechanical barrier in wellbore
12. Spot 43 sacks Class C cement from 4511' to 4242'.
13. Spot 25 sacks Class C cement from 3900' to 3745'.
14. Spot 25 sacks Class C cement from 3000' to 2845'.
15. Spot 37 sacks Class C cement from 2120' to 1884'.
16. Conduct bubble test on 7" x 9-5/8", 9-5/8" x 13"
 - a. If bubble test fails, consider running CBL to confirm TOC (calculated at 970') and identify depth to perforate OR cut/pull casing
17. Perforate 7" and 9-5/8" strings with deep penetrating charges from 360'. Establish circulation to surface in both annuli if possible. Conduct bubble test and ensure it's passing prior to bringing cement to surface.
18. If bubble test fails, consider transitioning directly to casing cutting & pulling. Discuss forward plan with NMOCD engineer for approval.
 - a. Cut casing will require a stub plug 50' inside of cut casing extending 50' above the cut portion at a minimum. WOC, tag, pressure test barrier. Proceed with approved C-103 if passing bubble test is achieved.
19. Circulate 214 sacks Class C cement from 360' to 0' in all strings
20. Confirm cement returns at surface
21. Rig down move off location

Wellbore Diagram

Created: 04/24/19 By: _____
 Updated: _____ By: _____
 Lease: Lovington San Andres Unit
 Field: Lovington
 Surf. Loc.: 1650 FNL & 1980 FWL
 Bot. Loc.: _____
 County: Lea St.: NM
 Status: _____

Well #: 38 St. Lse: _____
 API: 30-025-05423
 Unit Ltr.: F Section: 6
 TSHP/Rng: 17S-37E
 Unit Ltr.: _____ Section: _____
 TSHP/Rng: _____
 Directions: Lovington, NM
 Chevno: FA6550

Surface Casing

Size: 13"
 Wt., Grd.: 40#
 Depth: 310'
 Sxs Cmt: 250
 Circulate: Yes
 TOC: Surface
 Hole Size: 15"

KB: 3,819
 DF: _____
 GL: _____
 Ini. Spud: 08/05/39
 Ini. Comp.: 09/08/39


Intermediate Casing

Size: 9-5/8"
 Wt., Grd.: 36#
 Depth: 2950'
 Sxs Cmt: 350
 Circulate: _____
 TOC: 700 calc est TOC
 Hole Size: 10-3/4"

Production Casing

Size: 7"
 Wt., Grd.: 24#
 Depth: 4590'
 Sxs Cmt: 300
 Circulate: No
 TOC: 970 calc est TOC
 Hole Size: 8-1/4"

| | |
|--------------|-------|
| Rustler | 1,984 |
| Salt | 2,120 |
| Seven Rivers | 3,278 |
| Queen | 3,900 |
| Grayburg | 4,342 |
| San Andres | 4,609 |
| TD | 4,945 |



2-3/8" IPC Inj Tbg w/ on/off tool

Set Loc-set PKR @ 4511'

Open Hole: 4590' - 4945'

PBTD(est.): _____
 TD: 4,945
 Deepened: _____

Proposed Wellbore Diagram

| | | | | | | | |
|-------------|----------------------------------|------|-----------------------------|-------------|-----------------------------|----------|-----------------------------|
| Created: | <u>04/24/19</u> | By: | <u> </u> | Well #: | <u>38</u> | St. Lse: | <u> </u> |
| Updated: | <u> </u> | By: | <u> </u> | API | <u>30-025-05423</u> | | |
| Lease: | <u>Lovington San Andres Unit</u> | | | Unit Ltr.: | <u>F</u> | Section: | <u>6</u> |
| Field: | <u>Lovington</u> | | | TSHP/Rng: | <u>17S-37E</u> | | |
| Surf. Loc.: | <u>1650 FNL & 1980 FWL</u> | | | Unit Ltr.: | <u> </u> | Section: | <u> </u> |
| Bot. Loc.: | <u> </u> | | | TSHP/Rng: | <u> </u> | | |
| County: | <u>Lea</u> | St.: | <u>NM</u> | Directions: | <u>Lovington, NM</u> | | |
| Status: | <u> </u> | | | Chevno: | <u>FA6550</u> | | |

Surface Casing

Size: 13"
 Wt., Grd.: 40#
 Depth: 310'
 Sxs Cmt: 250
 Circulate: Yes
 TOC: Surface
 Hole Size: 15"

Perf at 360'
 Circ to SURF
 in all strings

Isolate 13" shoe
 Cmt from 360' to Surface

KB: 3,819

DF:

GL:

Ini. Spud: 08/05/39

Ini. Comp.: 09/08/39

Intermediate Casing

Size: 9-5/8"
 Wt., Grd.: 36#
 Depth: 2950'
 Sxs Cmt: 350
 Circulate:
 TOC: 700 est calc TOC
 Hole Size: 10-3/4"

Isolate Salt, Rustler
 Cmt from 2120' to 1884'

Production Casing

Size: 7"
 Wt., Grd.: 24#
 Depth: 4590'
 Sxs Cmt: 300
 Circulate: No
 TOC: 970 est calc TOC
 Hole Size: 8-1/4"

Isolate 9-5/8" shoe
 Cmt from 3000' to 2845'

| | |
|--------------|-------|
| Rustler | 1,984 |
| Salt | 2,120 |
| Seven Rivers | 3,278 |
| Queen | 3,900 |
| Grayburg | 4,342 |
| San Andres | 4,609 |
| TD | 4,945 |

Isolate Queen
 Cmt from 3900' to 3745'

Isolate San Andres, Graysburg
 Barrier #1: CIBP set at +/- 4511'
 Cmt from 4511' to 4242'
 (100' above formation top)

Open Hole: 4590' - 4945'

PBTD(est.):
 TD: 4,945

Deepened: _____

106.74419
213.48837
320.23256
426.97674
533.72093
640.46512
747.2093
853.95349
960.69767
1067.4419
1174.186
1280.9302
1387.6744
1494.4186
1601.1628
1707.907
1814.6512
1921.3953
2028.1395
2134.8837
2241.6279
2348.3721
2455.1163
2561.8605
2668.6047
2775.3488
2882.093
2988.8372
3095.5814
3202.3256
3309.0698
3415.814
3522.5581
3629.3023
3736.0465
3842.7907
3949.5349
4056.2791
4163.0233
4269.7674
4376.5116
4483.2558
4590

**CONDITIONS OF APPROVAL
FOR PLUGGING AND ABANDONMENT
OCD - Southern District**

The following is a guide or checklist in preparation of a plugging program, this is not all inclusive and care must be exercised in establishing special plugging programs in unique and unusual cases, Notify NMOCD District Office I (Hobbs) at (575)-263-6633 at least 24 hours before beginning work. After MIRU rig will remain on well until it is plugged to surface. OCD is to be notified before rig down.

Company representative will be on location during plugging procedures.

1. A notice of intent to plug and abandon a wellbore is required to be approved before plugging operations are conducted. A cement evaluation tool is required in order to ensure isolation of producing formations, protection of water and correlative rights. A cement bond log or other accepted cement evaluation tool is to be provided to the division for evaluation if one has not been previously run or if the well did not have cement circulated to surface during the original casing cementing job or subsequent cementing jobs. Insure all bradenheads have been exposed, identified and valves are operational prior to rig up.
2. Closed loop system is to be used for entire plugging operation. Upon completion, contents of steel pits are to be hauled to a permitted disposal location.
3. Trucking companies being used to haul oilfield waste fluids to a disposal - commercial or private- shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator as well as the contractor, to verify that this permit is in place prior to performing work. Drivers shall be able to produce a copy upon request of an NMOCD Field inspector.
4. Filing a subsequent C-103 will serve as notification that the well has been plugged.
5. A final C-103 shall be filed (and a site inspection by NMOCD Inspector to determine if the location is satisfactorily cleaned, all equipment, electric poles and trash has been removed to Meet NMOCD standards) before bonding can be released.
6. If work has not begun within 1 Year of the approval of this procedure, an extension request must be file stating the reason the well has not been plugged.
7. Squeeze pressures are not to exceed 500 psi, unless approval is given by NMOCD.
8. Produced water will not be used during any part of the plugging operation.
9. Mud laden fluids must be placed between all cement plugs mixed at 25 sacks per 100 bbls of water.
10. All cement plugs will be a minimum of 100' in length or a minimum of 25 sacks of cement, whichever is greater. 50' of calculated cement excess required for inside casing plugs and 100% calculated cement excess required on outside casing plugs.
11. Class 'C' cement will be used above 7500 feet.
12. Class 'H' cement will be used below 7500 feet.
13. A cement plug is required to be set 50' above and 50' below, casing stubs, DV tools, attempted casing cut offs, cement tops outside casing, salt sections and anywhere the casing is perforated, these plugs require a 4 hour WOC and then will be tagged
14. All Casing Shoes Will Be Perforated 50' below shoe depth and Attempted to be Squeezed, cement needs to be 50' above and 50' Below Casing Shoe inside the Production Casing.
16. When setting the top out cement plug in production, intermediate and surface casing, wellbores should remain full at least 30 minutes after plugs are set
17. A CIBP is to be set within 100' of production perforations, capped with 100' of cement, WOC 4 hours and tag.
18. A CIBP with 35' of cement may be used in lieu of the 100' plug if set with a bailer. This plug will be placed within 100' of the top perforation, (WOC 4 hrs and tag).

19. No more than 3000' is allowed between cement plugs in cased hole and 2000' in open hole.
20. Some of the Formations to be isolated with cement plugs are: These plugs to be set to isolate formation tops
- A) Fusselman
 - B) Devonian
 - C) Morrow
 - D) Wolfcamp
 - E) Bone Springs
 - F) Delaware
 - G) Any salt sections
 - H) Abo
 - I) Glorieta
 - J) Yates.
 - K) Potash---(In the R-111-P Area (Potash Mine Area),
A solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts that are common to the section penetrated and in suitable proportions, not more than 3% calcium chloride (by weight of cement) will be considered the desired mixture whenever possible, WOC 4 hours and tag, this plug will be 50' below the bottom and 50' above the top of the Formation.
21. If cement does not exist behind casing strings at recommended formation depths, the casing can be cut and pulled with plugs set at recommended depths. If casing is not pulled, perforations will be shot and cement squeezed behind casing, WOC and tagged. These plugs will be set 50' below formation bottom to 50' above formation top inside the casing.

DRY HOLE MARKER REQUIREMENTS

The operator shall mark the exact location of the plugged and abandoned well with a steel marker not less than four inches in diameter, 3' below ground level with a plate of at least ¼" welded to the top of the casing and the dry hole marker welded on the plate with the following information welded on the dry hole marker:

1. Operator name
2. Lease and Well Number
3. API Number
4. Unit letter
5. Quarter Section (feet from the North, South, East or West)
6. Section, Township and Range
7. Plugging Date
8. County

SPECIAL CASES -----AGRICULTURE OR PRARIE CHICKEN BREEDING AREAS

In these areas, a below ground marker is required with all pertinent information mentioned above on a plate, set 3' below ground level, a picture of the plate will be supplied to NMOCD for record, the exact location of the marker (longitude and latitude by GPS) will be provided to NMOCD (We typically require a current survey to verify the GPS)

SITE REMEDIATION DUE WITHIN ONE YEAR OF WELL PLUGGING COMPLETION

Plugging Plan – Lovington San Andres Unit #38

API: 30-025-05423

Note:

- Injector well with internally lined plastic tubing
- Loc-set packer at 4511'

Proposed procedure – Lay down rig + CTU

1. Move in Axis 34 Lay Down rig package
2. N/U BOPE and pressure test same to 250 psi low for 5 minutes / 2500 psi high for 10 minutes.
3. Pull 2-3/8" IPC tubing w/ on/off tool
4. Gauge ring run will be required unless the packer is removed from the wellbore
5. RIH with CIBP and set at proposed depth in C-103 (4511')
6. Pressure test mech. barrier + casing to 500 psi for 15 minutes. Document results in WellView.
7. Conduct bubble tests on all annuli. If bubble test fails, communicate to coiled tubing WSR for planning purposes.
8. Rig down Axis 34 lay down rig

Proposed procedure - Coiled Tubing Unit

9. R/U coiled tubing P&A package
10. N/U BOPE and pressure test same to 250 psi low for 5 minutes / 2500 psi high for 10 minutes.
11. RIH with coiled tubing to tag existing mechanical barrier in wellbore
12. Spot 43 sacks Class C cement from 4511' to 4242'.
13. Spot 25 sacks Class C cement from 3900' to 3745'.
14. Spot 25 sacks Class C cement from 3000' to 2845'.
15. Spot 37 sacks Class C cement from 2120' to 1884'.
16. Conduct bubble test on 7" x 9-5/8", 9-5/8" x 13"
 - a. If bubble test fails, consider running CBL to confirm TOC (calculated at 970') and identify depth to perforate OR cut/pull casing
17. Perforate 7" and 9-5/8" strings with deep penetrating charges from 360'. Establish circulation to surface in both annuli if possible. Conduct bubble test and ensure it's passing prior to bringing cement to surface.
18. If bubble test fails, consider transitioning directly to casing cutting & pulling. Discuss forward plan with NMOCD engineer for approval.
 - a. Cut casing will require a stub plug 50' inside of cut casing extending 50' above the cut portion at a minimum. WOC, tag, pressure test barrier. Proceed with approved C-103 if passing bubble test is achieved.
19. Circulate 214 sacks Class C cement from 360' to 0' in all strings
20. Confirm cement returns at surface
21. Rig down move off location

Wellbore Diagram

Created: 04/24/19 By: _____
 Updated: _____ By: _____
 Lease: Lovington San Andres Unit
 Field: Lovington
 Surf. Loc.: 1650 FNL & 1980 FWL
 Bot. Loc.: _____
 County: Lea St.: NM
 Status: _____

Well #: 38 St. Lse: _____
 API: 30-025-05423
 Unit Ltr.: F Section: 6
 TSHP/Rng: 17S-37E
 Unit Ltr.: _____ Section: _____
 TSHP/Rng: _____
 Directions: Lovington, NM
 Chevno: FA6550

Surface Casing

Size: 13"
 Wt., Grd.: 40#
 Depth: 310'
 Sxs Cmt: 250
 Circulate: Yes
 TOC: Surface
 Hole Size: 15"

KB: 3,819
 DF: _____
 GL: _____
 Ini. Spud: 08/05/39
 Ini. Comp.: 09/08/39


Intermediate Casing

Size: 9-5/8"
 Wt., Grd.: 36#
 Depth: 2950'
 Sxs Cmt: 350
 Circulate: _____
 TOC: 700 calc est TOC
 Hole Size: 10-3/4"

Production Casing

Size: 7"
 Wt., Grd.: 24#
 Depth: 4590'
 Sxs Cmt: 300
 Circulate: No
 TOC: 970 calc est TOC
 Hole Size: 8-1/4"

| | |
|--------------|-------|
| Rustler | 1,984 |
| Salt | 2,120 |
| Seven Rivers | 3,278 |
| Queen | 3,900 |
| Grayburg | 4,342 |
| San Andres | 4,609 |
| TD | 4,945 |



2-3/8" IPC Inj Tbg w/ on/off tool

Set Loc-set PKR @ 4511'

Open Hole: 4590' - 4945'

PBTD(est.): _____
 TD: 4,945
 Deepened: _____

Proposed Wellbore Diagram

| | | | | | | | |
|-------------|----------------------------------|------|-----------------------------|-------------|-----------------------------|----------|-----------------------------|
| Created: | <u>04/24/19</u> | By: | <u> </u> | Well #: | <u>38</u> | St. Lse: | <u> </u> |
| Updated: | <u> </u> | By: | <u> </u> | API | <u>30-025-05423</u> | | |
| Lease: | <u>Lovington San Andres Unit</u> | | | Unit Ltr.: | <u>F</u> | Section: | <u>6</u> |
| Field: | <u>Lovington</u> | | | TSHP/Rng: | <u>17S-37E</u> | | |
| Surf. Loc.: | <u>1650 FNL & 1980 FWL</u> | | | Unit Ltr.: | <u> </u> | Section: | <u> </u> |
| Bot. Loc.: | <u> </u> | | | TSHP/Rng: | <u> </u> | | |
| County: | <u>Lea</u> | St.: | <u>NM</u> | Directions: | <u>Lovington, NM</u> | | |
| Status: | <u> </u> | | | Chevno: | <u>FA6550</u> | | |

Surface Casing

Size: 13"
 Wt., Grd.: 40#
 Depth: 310'
 Sxs Cmt: 250
 Circulate: Yes
 TOC: Surface
 Hole Size: 15"

Perf at 360'
 Circ to SURF
 in all strings

Isolate 13" shoe
 Cmt from 360' to Surface

KB: 3,819

DF:

GL:

Ini. Spud: 08/05/39

Ini. Comp.: 09/08/39

Intermediate Casing

Size: 9-5/8"
 Wt., Grd.: 36#
 Depth: 2950'
 Sxs Cmt: 350
 Circulate:
 TOC: 700 est calc TOC
 Hole Size: 10-3/4"

Isolate Salt, Rustler
 Cmt from 2120' to 1884'

Production Casing

Size: 7"
 Wt., Grd.: 24#
 Depth: 4590'
 Sxs Cmt: 300
 Circulate: No
 TOC: 970 est calc TOC
 Hole Size: 8-1/4"

Isolate 9-5/8" shoe
 Cmt from 3000' to 2845'

| | |
|--------------|-------|
| Rustler | 1,984 |
| Salt | 2,120 |
| Seven Rivers | 3,278 |
| Queen | 3,900 |
| Grayburg | 4,342 |
| San Andres | 4,609 |
| TD | 4,945 |

Isolate Queen
 Cmt from 3900' to 3745'

Isolate San Andres, Graysburg
 Barrier #1: CIBP set at +/- 4511'
 Cmt from 4511' to 4242'
 (100' above formation top)

Open Hole: 4590' - 4945'

PBTD(est.):
 TD: 4,945

Deepened: _____

106.74419
213.48837
320.23256
426.97674
533.72093
640.46512
747.2093
853.95349
960.69767
1067.4419
1174.186
1280.9302
1387.6744
1494.4186
1601.1628
1707.907
1814.6512
1921.3953
2028.1395
2134.8837
2241.6279
2348.3721
2455.1163
2561.8605
2668.6047
2775.3488
2882.093
2988.8372
3095.5814
3202.3256
3309.0698
3415.814
3522.5581
3629.3023
3736.0465
3842.7907
3949.5349
4056.2791
4163.0233
4269.7674
4376.5116
4483.2558
4590

District I

1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

COMMENTS

Action 109441

COMMENTS

| | |
|--|---|
| Operator: CHEVRON U S A INC 6301 Deauville Blvd Midland, TX 79706 | OGRID: 4323 |
| | Action Number: 109441 |
| | Action Type: [C-103] NOI Plug & Abandon (C-103F) |

COMMENTS

| Created By | Comment | Comment Date |
|------------|---------------|--------------|
| plmartinez | DATA ENTRY PM | 5/26/2022 |

District I

1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 109441

CONDITIONS

| | |
|--|---|
| Operator: CHEVRON U S A INC 6301 Deauville Blvd Midland, TX 79706 | OGRID: 4323 |
| | Action Number: 109441 |
| | Action Type: [C-103] NOI Plug & Abandon (C-103F) |

CONDITIONS

| Created By | Condition | Condition Date |
|------------|------------------|----------------|
| kfortner | See attached COA | 5/25/2022 |