For State Use Only:

APPROVED BY:

Patricia L Martinez

Form C-103 State of New Mexico 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 **Energy, Minerals and Natural Resources** Permit 324413 **District II** WELL APLNIIMBER 811 S. First St., Artesia, NM 88210 Oil Conservation Division Phone:(575) 748-1283 Fax:(575) 748-9720 30-025-48770 **District III** 5. Indicate Type of Lease 1220 S. St Francis Dr. 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 6 State Oil & Gas Lease No. District IV **Santa Fe, NM 87505** 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS PROMETHEUS STATE COM (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: 8. Well Number 183H 2. Name of Operator 9. OGRID Number TAP ROCK OPERATING, LLC 372043 3. Address of Operator 10. Pool name or Wildcat 523 Park Point Drive, Suite 200, Golden, CO 80401 4. Well Location . <u>U</u> : <u>828</u> Unit Letter O feet from the S line and feet 2435 from the E __ Township 33E NMPM 24S Range County Lea 11. Elevation (Show whether DR, KB, BT, GR, etc.) 3556 GR Pit or Below-grade Tank Application or Closure __ Depth to Groundwater___ ___ Distance from nearest fresh water well__ _ Distance from nearest surface water Pit Type mil Below-Grade Tank: Volume_ bbls; Construction Material Pit Liner Thickness: 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON ALTER CASING REMEDIAL WORK TEMPORARILY ABANDON CHANGE OF PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON CASING/CEMENT JOB PULL OR ALTER CASING MULTIPLE COMPL X Other: Other: Drilling/Cement 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. See attached description of work for intermediate and production casing See Attached 5/30/2022 Spudded well. **Casing and Cement Program** Date String Csg Weight Grade Yield Open Size Size lb/ft TOC Held Drop Hole 05/31/22 Surf FreshWater 17.5 13.375 54.5 J55 0 1297 975 1.34 С 1500 0 Ν 06/17/22 Int1 Brine 12.25 9.625 40 J55 0 5328 1110 1.33 С 1500 0 Ν 06/26/22 OilBasedMud 20 P110 Prod 6.75 5.5 1750 20338 2150 1.53 С Ν I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines \square , a general permit \square or an (attached) alternative OCD-approved plan \square SIGNATURE TITLE DATE Electronically Signed Regulatory Manager 8/31/2022 Type or print name **Christian Combs** E-mail address ccombs@taprk.com Telephone No. 720-360-4028

TITLE

DATE

9/1/2022 1:15:43 PM

Prometheus State Com 183H Intermediate and Production

6/16/2022: Test BOPS. Drill 12.25 intermediate hole to 5342 ft.

6/17/2022: Run 9.625 inch 40 lb J-55 intermediate casing to 5328 ft. Pump 20 bbls vis water, followed by 780 sks of 11.3 ppg lead cmt, 330 sks of 14.8 ppg tail cmt. Drop plug and displace with 400 bbls of fresh water. 87 bbls cement to surface. EST TOC at 0 ft. Pressure test casing to 1500 for 30 minutes, good test.

6/18/2022: Drill 8.75 inch production hole to 9503 ft then switch to 6.75 in hole to 20346 ft.

6/26/2022: Run 5.5 inch 20 lb P-110 production casing to 20338 ft MD. Pump 40 bbls fresh water, then 290 sks of 10.5 lead cmt, 1860 sks of 13.2 ppg tail cmt. Drop plug and displace with 20 bbls sugar water, 430 bbls brine. 0 bbls returned to surface. Est TOC at 1750 ft.

Intermediate Casing Details: Casing ran: 6/17/2022, Fluid Type Brine, Hole 12.25 inch to 5342 ft, Csg Size 9.625 inch, Weight 40 lbs, Grade J-55, Est TOC 0 ft, Depth set 5328 ft, Cement 1110 sks, Yield 2.69 lead/1.33 tail, Class C, Pressure Held 1500 psi, Pres Drop 0.

Production Casing details: Casing Date: 6/26/2022, Fluid Type Oil Based Mud, Hole 8.75 inch to 9503, 6.75 inch to 20346 ft, Csg Size, 5.5 inch, Weight 20 lbs, Grade P-110, Depth set 20338 ft, EST TOC 1750 ft, Cement 2150 sacks, yield 4.13 lead/1.53 tail, Class C.

6/25/2022: TD Reached at 20346 ft MD, 9948 ft TVD. Plug Back Measured depth at 20315 ft MD, 9951 ft TVD. Rig Release on 6/27/2022 at 08:30.