

U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Well Name: DEPTH CC 6-7 FEDERAL COM	Well Location: T23S / R29E / SEC 31 / SESE / 32.2542733 / -104.0184877	County or Parish/State: EDDY / NM
Well Number: 44H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM117551, NMNM13996	Unit or CA Name:	Unit or CA Number:
US Well Number: 3001546779	Well Status: Approved Application for Permit to Drill	Operator: OXY USA INCORPORATED

Notice of Intent

Sundry ID: 2387889

Type of Submission: Notice of Intent

Type of Action: Other

Date Sundry Submitted: 05/19/2021

Time Sundry Submitted: 09:55

Date proposed operation will begin: 08/01/2021

Procedure Description: OXY USA Inc. respectfully requests to amend the casing, cement, mud, BOP programs on the subject well approved APD. Also note the offline cementing variance, CBL variance, BOP break testing language, updated wellhead diagram, and the skid order in the revised drill plan attachments. 1/13/2022 - Drill Plan/BOPE Revised

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

- DepthCC6_7FederalCom44H_DrillPlanAMEND_20220113104717.pdf
- DepthCC6_7FederalCom44H_DQW_20210519095500.pdf
- DepthCC6_7FederalCom44H_SFTORQ_20210519095448.pdf
- DepthCC6_7FederalCom44H_BOP_20210519095436.pdf
- DepthCC6_7FederalCom44H_BOPBreakSKID_20210519095422.pdf

Well Name: DEPTH CC 6-7 FEDERAL COM

Well Location: T23S / R29E / SEC 31 / SESE / 32.2542733 / -104.0184877

County or Parish/State: EDDY / NM

Well Number: 44H

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM117551, NMNM13996

Unit or CA Name:

Unit or CA Number:

US Well Number: 3001546779

Well Status: Approved Application for Permit to Drill

Operator: OXY USA INCORPORATED

Conditions of Approval

Additional

Depth_CC_6___Federal_Com_44H_DrillingCOA_Sundry_2387889_20220606122143.pdf

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: LESLIE REEVES

Signed on: JAN 13, 2022 10:48 AM

Name: OXY USA INCORPORATED

Title: Advisor Regulatory

Street Address: 5 GREENWAY PLAZA, SUITE 110

City: HOUSTON

State: TX

Phone: (713) 497-2492

Email address: LESLIE_REEVES@OXY.COM

Field

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: CODY LAYTON

BLM POC Title: Assistant Field Manager Lands & Minerals

BLM POC Phone: 5752345959

BLM POC Email Address: clayton@blm.gov

Disposition: Approved

Disposition Date: 06/09/2022

Signature: Chris Walls

PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

OPERATOR'S NAME:	OXY USA INCORPORATED
LEASE NO.:	NMNM
LOCATION:	Section 6, T.24 S., R.29 E., NMPM
COUNTY:	Eddy County, New Mexico

WELL NAME & NO.:	Depth CC 6-7 Federal Com 44H
SURFACE HOLE FOOTAGE:	25'/S & 1004'/E
BOTTOM HOLE FOOTAGE:	20'/S & 940'/E

COA

H2S	<input type="radio"/> Yes	<input checked="" type="radio"/> No	
Potash	<input checked="" type="radio"/> None	<input type="radio"/> Secretary	<input type="radio"/> R-111-P
Cave/Karst Potential	<input type="radio"/> Low	<input checked="" type="radio"/> Medium	<input type="radio"/> High
Cave/Karst Potential	<input type="radio"/> Critical		
Variance	<input type="radio"/> None	<input checked="" type="radio"/> Flex Hose	<input type="radio"/> Other
Wellhead	<input type="radio"/> Conventional	<input type="radio"/> Multibowl	<input checked="" type="radio"/> Both
Other	<input type="checkbox"/> 4 String Area	<input type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP
Other	<input checked="" type="checkbox"/> Fluid Filled	<input checked="" type="checkbox"/> Cement Squeeze	<input type="checkbox"/> Pilot Hole
Special Requirements	<input type="checkbox"/> Water Disposal	<input checked="" type="checkbox"/> COM	<input type="checkbox"/> Unit

A. CASING

Casing Design:

3. The minimum required fill of cement behind the **5-1/2 X 5** inch production casing is:

Option 1 (Single Stage):

- Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification.

Option 2:

Operator has proposed a DV tool, the depth may be adjusted as long as the cement is changed proportionally. The DV tool may be cancelled if cement circulates to surface on the first stage.

- a. First stage to DV tool: Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.

b. Second stage above DV tool:

- Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification.

B. SPECIAL REQUIREMENT (S)

Communitization Agreement

- The operator will submit a Communitization Agreement to the Santa Fe Office, 301 Dinosaur Trail Santa Fe, New Mexico 87508, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.
- If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.
- In addition, the well sign shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.

Offline Cementing

Contact the BLM prior to the commencement of any offline cementing procedure

BOPE Break Testing Variance (Note: For 5M BOPE or less)

- BOPE Break Testing is ONLY permitted for 5M BOPE or less.
- BOPE Break Testing is NOT permitted to drilling the production hole section.
- While in transfer between wells, the BOPE shall be secured by the hydraulic carrier or cradle.
- Any well control event while drilling require notification to the BLM Petroleum Engineer prior to the commencement of any BOPE Break Testing operations.
- A full BOPE test is required prior to drilling the first deep intermediate hole section. If any subsequent hole interval is deeper than the first, a full BOPE test will be required.
- The BLM is to be contacted (**575-361-2822 Eddy County**) 4 hours prior to BOPE tests.
- As a minimum, a full BOPE test shall be performed at 21-day intervals.

Oxy USA Inc. - Depth CC 6_7 Federal Com 44H Drill Plan

1. Geologic Formations

TVD of Target (ft):	10922	Pilot Hole Depth (ft):	
Total Measured Depth (ft):	21728	Deepest Expected Fresh Water (ft):	123

Delaware Basin

Formation	MD-RKB (ft)	TVD-RKB (ft)	Expected Fluids
Rustler	123	123	
Salado	540	540	Salt
Castile	1312	1312	Salt
Delaware	2789	2789	Oil/Gas/Brine
Bell Canyon	2823	2823	Oil/Gas/Brine
Cherry Canyon	3702	3702	Oil/Gas/Brine
Brushy Canyon	4931	4931	Losses
Bone Spring	6513	6513	Oil/Gas
Bone Spring 1st	7521	7513	Oil/Gas
Bone Spring 2nd	8302	8282	Oil/Gas
Bone Spring 3rd	9418	9381	Oil/Gas
Wolfcamp	9786	9746	Oil/Gas
Penn			Oil/Gas
Strawn			Oil/Gas

*H2S, water flows, loss of circulation, abnormal pressures, etc.

2. Casing Program

Section	Hole Size (in)	MD		TVD		Csg. OD (in)	Csg. Wt. (ppf)	Grade	Conn.
		From (ft)	To (ft)	From (ft)	To (ft)				
Surface	14.75	0	480	0	480	10.75	45.5	J-55	BTC
Intermediate	9.875	0	10320	0	10278	7.625	26.4	L-80 HC	BTC
Production	6.75	0	10870	0	10650	5.5	26	P-110 CYHP	TORQ SFW
Production	6.75	10870	21728	10650	10922	5	21.4	P-110 CYHP	TORQ DQW

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h

*Oxy requests the option to run production casing with DQX, TORQ DQW, Wedge 425, Wedge 461, and/or Wedge 441 connections to accommodate hole conditions or drilling operations.

<i>All Casing SF Values will meet or exceed those below</i>			
SF Collapse	SF Burst	Body SF Tension	Joint SF Tension
1.125	1.2	1.4	1.4

Annular Clearance Variance Request

As per the agreement reached in the Oxy/BLM face-to-face meeting on Feb 22, 2018, Oxy requests permission to allow deviation from the 0.422" annular clearance requirement from Onshore Order #2 under the following conditions:

1. Annular clearance to meet or exceed 0.422" between intermediate casing ID and production casing coupling only on the first 500' overlap between both casings.
2. Annular clearance less than 0.422" is acceptable for the curve and lateral portions of the production open hole section.

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Does casing meet API specifications? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	Y
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the intermediate pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Capitan Reef	
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	
SOPA	
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
R-111-P	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	
High Cave/Karst	
Is well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Critical Cave/Karst	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

3. Cementing Program

Section	Stage	Slurry:	Capacities	ft ³ /ft	Excess:	From	To	Sacks	Volume (ft ³)	Placement
Surface	1	Surface - Tail	OH x Csg	0.5563	100%	480	-	402	534	Circulate
Int.	1	Intermediate 1S - Tail	OH x Csg	0.2148	5%	10,320	5,181	702	1159	Circulate
Int.	2	Intermediate 2S - Tail BH	OH x Csg	0.2148	25%	5,181	480	657	1262	Bradenhead
Int.	2	Intermediate 2S - Tail BH	Csg x Csg	0.2338	0%	480	-	58	112	Bradenhead
Prod.	1	Production - Tail	OH x Csg2	0.2812	20%	21,728	10,870	2655	3664	Circulate
Prod.	1	Production - Tail	OH x Csg1	0.2526	20%	10,870	10,320	121	167	Circulate
Prod.	1	Production - Tail	Csg x Csg	0.0999	0%	10,320	9,820	36	50	Circulate

Description	Density (lb/gal)	Yield (ft ³ /sk)	Water (gal/sk)	500psi Time (hh:mm)	Cmt. Class	Accelerator	Retarder	Dispersant	Salt
Surface - Tail	14.8	1.33	6.365	5:26	C	x			
Intermediate 1S - Tail	13.2	1.65	8.64	11:54	H	x	x	x	x
Intermediate 2S - Tail BH	12.9	1.92	10.41	23:10	C	x			
Production - Tail	13.2	1.38	6.686	3:39	H		x	x	x

Offline Cementing

Oxy requests a variance to cement the 9.625" and/or 7.625" intermediate casing strings offline in accordance to the approved variance, EC Tran 461365.

The summarized operational sequence will be as follows:

Run casing as per normal operations. While running casing, conduct negative pressure test and confirm integrity of the float equipment (float collar and shoe).

Land casing.

Fill pipe with kill weight fluid, and confirm well is static.

If well Oxy requests a variance to cement the 9.625" and/or 7.625" intermediate casing strings offline in accordance to the approved variance, EC Tran 461365.

The summarized operational sequence will be as follows:

1. Run casing as per normal operations. While running casing, conduct negative pressure test and confirm integrity of the float equipment (float collar and shoe).
2. Land casing.
3. Fill pipe with kill weight fluid, and confirm well is static.
 - a. If well is not static notify BLM and kill well.
 - b. Once well is static notify BLM with intent to proceed with nipple down and offline cementing.
4. Set and pressure test annular packoff.
5. After confirmation of both annular barriers and internal barriers, nipple down BOP and install cap flange. If any barrier fails to test, the BOP stack will not be nipped down until after the cement job is completed.
6. Skid rig to next well on pad.
7. Confirm well is static before removing cap flange.
8. If well is not static notify BLM and kill well prior to cementing or nipping up for further remediation.
9. Install offline cement tool.
10. Rig up cement equipment.
 - a. Notify BLM prior to cement job.
11. Perform cement job.
12. Confirm well is static and floats are holding after cement job.
13. Remove cement equipment, offline cement tools and install night cap with pressure gauge for monitoring.

Oxy requests permission to adjust the CBL requirement after bradenhead cement jobs, on 7-5/8" intermediate casings, as per the agreement reached in the OXY/BLM meeting on September 5, 2019.

Three string wells:

- CBL will be required on one well per pad
- If the pumped volume of cement is less than permitted in the APD, BLM will be notified and a CBL may be run
- Echometer will be used after bradenhead cement job to determine TOC before pumping top-out cement

4. Pressure Control Equipment

BOP installed and tested before drilling which hole?	Size?	Min. Required WP	Type	✓	Tested to:	Deepest TVD Depth (ft) per Section:
9.875" Hole	13-5/8"	5M	Annular	✓	70% of working pressure	10278
		5M	Blind Ram	✓	250 psi / 5000 psi	
			Pipe Ram			
			Double Ram	✓		
			Other*			
6.75" Hole	13-5/8"	5M	Annular	✓	100% of working pressure	10922
		10M	Blind Ram	✓	250 psi / 10000 psi	
			Pipe Ram			
			Double Ram	✓		
			Other*			

*Specify if additional ram is utilized

BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold.

	Formation integrity test will be performed per Onshore Order #2.
	On Exploratory wells or on that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.i.
	A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold. See attached for specs and hydrostatic test chart.
Y	Are anchors required by manufacturer?
	A multibowl or a unionized multibowl wellhead system will be employed. The wellhead and connection to the BOPE will meet all API 6A requirements. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested. We will test the flange connection of the wellhead with a test port that is directly in the flange. We are proposing that we will run the wellhead through the rotary prior to cementing surface casing as discussed with the BLM on October 8, 2015. See attached schematics.

BOP Break Testing Request

Oxy requests permission to adjust the BOP break testing requirements as per the agreement reached in the OXY/BLM meeting on September 5, 2019.

BOP break test under the following conditions:

- After a full BOP test is conducted
- When skidding to drill an intermediate section where ICP is set into the third Bone Spring or shallower.

If the kill line is broken prior to skid, two tests will be performed.

- 1) Wellhead flange, co-flex hose, kill line connections and upper pipe rams
- 2) Wellhead flange, HCR valve, check valve, upper pipe rams

If the kill line is not broken prior to skid, only one test will be performed.

- 1) Wellhead flange, co-flex hose, check valve, upper pipe rams

5. Mud Program

Section	Depth - MD		Depth - TVD		Type	Weight (ppg)	Viscosity	Water Loss
	From (ft)	To (ft)	From (ft)	To (ft)				
Surface	0	480	0	480	Water-Based Mud	8.6 - 8.8	40-60	N/C
Intermediate	480	10320	480	10278	Saturated Brine-Based or Oil-Based Mud	8.0 - 10.0	35-45	N/C
Production	10320	21728	10278	10922	Water-Based or Oil-Based Mud	9.5 - 13	38-50	N/C

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times. The following is a general list of products: Barite, Bentonite, Gypsum, Lime, Soda Ash, Caustic Soda, Nut Plug, Cedar Fiber, Cotton Seed Hulls, Drilling Paper, Salt Water Clay, CACL2. Oxy will use a closed mud system.

What will be used to monitor the loss or gain of fluid?	PVT/MD Totco/Visual Monitoring
---------------------------------------------------------	--------------------------------

6. Logging and Testing Procedures

Logging, Coring and Testing.	
Yes	Will run GR from TD to surface (horizontal well – vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
No	Logs are planned based on well control or offset log information.
No	Drill stem test? If yes, explain
No	Coring? If yes, explain

Additional logs planned		Interval
No	Resistivity	
No	Density	
No	CBL	
Yes	Mud log	Bone Spring – TD
No	PEX	

7. Drilling Conditions

Condition	Specify what type and where?
BH Pressure at deepest TVD	7384 psi
Abnormal Temperature	No
BH Temperature at deepest TVD	168°F

Pump high viscosity sweeps as needed for hole cleaning. The mud system will be monitored visually/manually as well as with an electronic PVT. The necessary mud products for additional weight and fluid loss control will be on location at all times. Appropriately weighted mud will be used to isolate potential gas, oil, and water zones until such time as casing can be cemented into place for zonal

Hydrogen Sulfide (H2S) monitors will be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered, measured values and formations will be provided to the BLM.	
N	H2S is present
Y	H2S Plan attached

8. Other facets of operation

	Yes/No
Will the well be drilled with a walking/skidding operation? If yes, describe. We plan to drill the 2 well pad in batch by section: all surface sections, intermediate sections and production sections. The wellhead will be secured with a night cap whenever the rig is not over the well.	Yes
Will more than one drilling rig be used for drilling operations? If yes, describe. Oxy requests the option to contract a Surface Rig to drill, set surface casing, and cement for this well. If the timing between rigs is such that Oxy would not be able to preset surface, the Primary Rig will MIRU and drill the well in its entirety per the APD. Please see the attached document for information on the spudder rig.	Yes

Total Estimated Cuttings Volume: 1539 bbls

Attachments

- Directional Plan
- H2S Contingency Plan
- Flex III Attachments
- Spudder Rig Attachment
- Premium Connection Specs

9. Company Personnel

Name	Title	Office Phone	Mobile Phone
Garrett Granier	Drilling Engineer	713-513-6633	832-265-0581
Filip Krneta	Drilling Engineer Supervisor	713-350-4751	832-244-4980
Simon Benavides	Drilling Superintendent	713-522-8652	281-684-6897
Diego Tellez	Drilling Manager	713-350-4602	713-303-4932

TUBULAR PARAMETERS

Nominal OD, (inch)	5.000
Wall Thickness, (inch)	0.437
Pipe Grade	P110 CYHP
Coupling	Regular
Coupling Grade	P110 CYHP
Drift	Standard

CONNECTION PARAMETERS



Connection OD (inch)	5.800
Connection ID, (inch)	4.126
Make-Up Loss, (inch)	4.284
Connection Critical Area, (sq inch)	8.106
Yield Strength in Tension, (klbs)	783
Yield Strength in Compression, (klbs)	783
Tension Efficiency	100%
Compression Efficiency	100%
Min. Internal Yield Pressure, (psi)	19 120
Collapse Pressure, (psi)	19 860
Uniaxial Bending (deg/100ft)	114.7

MAKE-UP TORQUES

Minimum Make-Up Torque, (ft-lb)	13 000
Optimum Make-Up Torque, (ft-lb)	14 500
Maximum Make-Up Torque, (ft-lb)	16 000
Operating Torque, (ft-lb)	32 000
Yield Torque, (ft-lb)	40 000

PIPE BODY PROPERTIES

PE Weight, (lbs/ft)	21.32
Nominal Weight, (lbs/ft)	21.40
Nominal ID, (inch)	4.126
Drift Diameter, (inch)	4.001
Nominal Pipe Body Area, (sq inch)	6.264
Yield Strength in Tension, (klbs)	783
Min. Internal Yield Pressure, (psi)	19 120
Collapse Pressure, (psi)	19 860
Minimum Yield Strength, (psi)	125 000
Minimum Tensile Strength, (psi)	135 000



NOTE: The content of this Technical Data Sheet is for general information only and does not guarantee performance or imply fitness for a particular purpose, which only a competent drilling professional can determine considering the specific installation and operation parameters. This information supersedes all prior versions for this connection. Information that is printed or downloaded is no longer controlled by TMK and might not be the latest information. Anyone using the information herein does so at their own risk. To verify that you have the latest technical information, please contact PAO "TMK" Technical Sales in Russia (Tel: +7 (495) 775-76-00, Email: techsales@tmk-group.com) and TMK IPSCO in North America (Tel: +1 (281)949-1044, Email: techsales@tmk-ipSCO.com).

Print date: 08/21/2019 02:11

TUBULAR PARAMETERS

Nominal OD, (inch)	5.500
Wall Thickness, (inch)	0.476
Pipe Grade	P110 CYHP
Coupling	Regular
Coupling Grade	P110 CYHP
Drift	Standard

CONNECTION PARAMETERS



Connection OD (inch)	5.858
Connection ID, (inch)	4.504
Make-Up Loss, (inch)	5.660
Connection Critical Area, (sq inch)	6.906
Yield Strength in Tension, (klbs)	845
Yield Strength in Compression, (klbs)	845
Tension Efficiency	90%
Compression Efficiency	90%
Min. Internal Yield Pressure, (psi)	18 930
Collapse Pressure, (psi)	20 420
Uniaxial Bending (deg/100ft)	93.8

MAKE-UP TORQUES

Minimum Make-Up Torque, (ft-lb)	17 500
Optimum Make-Up Torque, (ft-lb)	25 000
Maximum Make-Up Torque, (ft-lb)	27 500
Operating Torque, (ft-lb)	39 000
Yield Torque, (ft-lb)	48 000

PIPE BODY PROPERTIES


PE Weight, (lbs/ft)	25.56
Nominal Weight, (lbs/ft)	26.00
Nominal ID, (inch)	4.548
Drift Diameter, (inch)	4.423
Nominal Pipe Body Area, (sq inch)	7.513
Yield Strength in Tension, (klbs)	939
Min. Internal Yield Pressure, (psi)	18 930
Collapse Pressure, (psi)	20 420
Minimum Yield Strength, (psi)	125 000
Minimum Tensile Strength, (psi)	135 000



NOTE: The content of this Technical Data Sheet is for general information only and does not guarantee performance or imply fitness for a particular purpose, which only a competent drilling professional can determine considering the specific installation and operation parameters. This information supersedes all prior versions for this connection. Information that is printed or downloaded is no longer controlled by TMK and might not be the latest information. Anyone using the information herein does so at their own risk. To verify that you have the latest technical information, please contact PAO "TMK" Technical Sales in Russia (Tel: +7 (495) 775-76-00, Email: techsales@tmk-group.com) and TMK IPSCO in North America (Tel: +1 (281)949-1044, Email: techsales@tmk-ipsco.com).

Print date: 10/14/2019 22:14


5/10M BOP Stack






13-5/8" 10M MN-DS Wellhead System Slips

Ground Level



NOTE: All dimensions on this drawing are estimated measurements determined by master quote and may vary by components used in the field.



NOTE: All dimensions on this drawing are estimated measurements determined by master quote and may vary by components used in the field.

2017-192-01 Rev02

Oxy USA Inc. – Depth 41H/42H/43H/44H, Radius 51H/52H Break Test Sundry

Oxy requests permission to Break Test, as per the agreement reached in the OXY/BLM meeting on September 5, 2019.

API #	Well Name
30-015-46777	Depth CC 6 7 Federal Com 41H
30-015-46780	Depth CC 6 7 Federal Com 42H
30-015-46781	Depth CC 6 7 Federal Com 43H
30-015-46779	Depth CC 6 7 Federal Com 44H
30-015-46825	Radius CC 6 7 Federal Com 51H
30-015-46826	Radius CC 6 7 Federal Com 51H

BOP break test under the following conditions:

- After a full BOP test is conducted
- When skidding to drill an intermediate section where ICP is set into the third Bone Spring or shallower.
- When skidding to drill a production section that does not penetrate into the third Bone Spring or deeper.

If the kill line is broken prior to skid, two tests will be performed.

1. Wellhead flange, co-flex hose, kill line connections and upper pipe rams
2. Wellhead flange, HCR valve, check valve, upper pipe rams

If the kill line is not broken prior to skid, only one test will be performed.

1. Wellhead flange, co-flex hose, check valve, upper pipe rams

Depth 43H/44H	
PRIMARY SKID ORDER	
Step	Operation
1	RU on Depth 43H
2	Full BOP Test
3	Drill 9-7/8" Deep Intermediate on Depth 43H
4	Skid to Depth 44H
5	Full BOP Test
6	Drill 9-7/8" Deep Intermediate and 6-3/4" Curve/Lateral on Depth 44H
7	Skid to Depth 43H
8	Full BOP Test
9	Drill 6-3/4" Curve/Lateral on Depth 43H
10	Rig Down on Depth 43H
	NOTE: No opportunity to Break Test per Variance Rules

Oxy USA Inc. – Depth 41H/42H/43H/44H, Radius 51H/52H Break Test Sundry

Depth 41H/42H, Radius 51H/52H	
PRIMARY SKID ORDER	
Step	Operation
1	RU on Radius 52H
2	Full BOP Test
3	Drill 9-7/8" Deep Intermediate on Radius 52H
4	Skid to Depth 42H
5	Full BOP Test
6	Drill 9-7/8" Deep Intermediate on Depth 42H
7	Skid to Radius 51H
8	Full BOP Test
9	Drill 9-7/8" Deep Intermediate on Radius 51H
10	Skid to Depth 41H
11	Full BOP Test
12	Drill 9-7/8" Deep Intermediate and 6-3/4" Pilot on Depth 41H
13	Plugback Pilot Hole/Full BOP Test (if needed)
14	Sidetrack/Drill 6-3/4" Curve/Lateral on Depth 41H
15	Skid to Radius 51H
16	Full BOP Test
17	Drill 6-3/4" Curve/Lateral on Radius 51H
18	Skid to Depth 42H
19	Full BOP Test
20	Drill 6-3/4" Curve/Lateral on Depth 42H
21	Skid to Radius 52H
22	Full BOP Test
23	Drill 6-3/4" Curve/Lateral on Radius 52H
24	Rig Down on Radius 52H
	NOTE: No opportunity to Break Test per Variance Rules

District I
 1625 N. French Dr., Hobbs, NM 88240
 Phone:(575) 393-6161 Fax:(575) 393-0720

District II
 811 S. First St., Artesia, NM 88210
 Phone:(575) 748-1283 Fax:(575) 748-9720

District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV
 1220 S. St Francis Dr., Santa Fe, NM 87505
 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

COMMENTS

Action 115688

COMMENTS

Operator: OXY USA INC P.O. Box 4294 Houston, TX 772104294	OGRID: 16696
	Action Number: 115688
	Action Type: [C-103] NOI Change of Plans (C-103A)

COMMENTS

Created By	Comment	Comment Date
jagarcia	Approved, John Garcia, Petroleum Engineer	9/6/2022

District I
 1625 N. French Dr., Hobbs, NM 88240
 Phone:(575) 393-6161 Fax:(575) 393-0720

District II
 811 S. First St., Artesia, NM 88210
 Phone:(575) 748-1283 Fax:(575) 748-9720

District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV
 1220 S. St Francis Dr., Santa Fe, NM 87505
 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 115688

CONDITIONS

Operator: OXY USA INC P.O. Box 4294 Houston, TX 772104294	OGRID: 16696
	Action Number: 115688
	Action Type: [C-103] NOI Change of Plans (C-103A)

CONDITIONS

Created By	Condition	Condition Date
jagarcia	CBL will be required if cement does not come to surface on the surface or intermediate casing strings	9/6/2022